

NAME

ubuntu-build – command-line interface to Launchpad build operations

SYNOPSIS

ubuntu-build <srcpackage> <release> <operation>

DESCRIPTION

ubuntu-build provides a command line interface to the Launchpad build operations.

OPERATIONS

Listed below are the available operations for **ubuntu-build**:

status Outputs the build status of the package on Launchpad on all architectures.

retry Requests that the package has another attempt at rebuilding from source. This will only work if the package has *Failed to build* on Launchpad.

rescore Requests that the package's build priority be raised in the build queue. Only members of the Launchpad build administrators may issue this operation, and it may only be performed on packages which *Need building*.

OPTIONS

Listed below are the command line options for **ubuntu-build**:

-h or --help

Display a help message and exit.

Retry and rescore options:

These options may only be used with the 'retry' and 'rescore' operations.

-a ARCHITECTURE, --arch=ARCHITECTURE Rebuild or rescore a specific architecture. Valid architectures include: amd64, sparc, powerpc, i386, armel, armhf, arm64, ia64, lpia, hppa, ppc64el, s390x.

Batch processing:

These options and parameter ordering is only available in **--batch** mode. Usage: **ubuntu-build --batch** [options] <package>...

--batch Enable batch mode

--series=SERIES Selects the Ubuntu series to operate on (default: current development series)

--retry Retry builds (give-back).

--rescore=PRIORITY Rescore builds to <priority>.

--arch2=ARCHITECTURE Affect only 'architecture' (can be used several times). Valid architectures are: amd64, sparc, powerpc, i386, armel, armhf, arm64, ia64, lpia, hppa.

AUTHORS

ubuntu-build was written by Martin Pitt <martin.pitt@canonical.com>, and this manual page was written by Jonathan Patrick Davies <jpds@ubuntu.com>.

Both are released under the terms of the GNU General Public License, version 3 or (at your option) any later version.