#### **NAME**

add-apt-repository - Adds a repository into the /etc/apt/sources.list or /etc/apt/sources.list.d or removes an existing one

#### **SYNOPSIS**

add-apt-repository [OPTIONS] REPOSITORY

### **DESCRIPTION**

**add-apt-repository** is a script which adds an external APT repository to either /etc/apt/sources.list or a file in /etc/apt/sources.list.d/ or removes an already existing repository.

The options supported by add-apt-repository are:

- -h, --help Show help message and exit
- -m, --massive-debug Print a lot of debug information to the command line
- -r, --remove Remove the specified repository
- -y, --yes Assume yes to all queries
- **-u, --update** After adding the repository, update the package cache with packages from this repository (avoids need to apt-get update)
- -k, --keyserver Use a custom keyserver URL instead of the default
- -s, --enable-source Allow downloading of the source packages from the repository

### REPOSITORY STRING

In the first form, REPOSITORY will just be appended to /etc/apt/sources.list.

In the second form, ppa:\user>/\pa-name> will be expanded to the full deb line of the PPA and added into a new file in the /etc/apt/sources.list.d/ directory. The GPG public key of the newly added PPA will also be downloaded and added to apt's keyring.

In the third form, the given distribution component will be enabled for all sources.

# **SEE ALSO**

sources.list(5) apt-get(8)

## **COPYRIGHT**

On Debian systems, the complete text of the GNU General Public License can be found in /usr/share/common-licenses.