## **NAME**

Net::DNS::RR::SMIMEA - DNS SMIMEA resource record

### **SYNOPSIS**

```
use Net::DNS;
$rr = new Net::DNS::RR('name SMIMEA usage selector matchingtype certificate')
```

### DESCRIPTION

Net::DNS::RR::SMIMEA(3pm)

The SMIMEA DNS resource record (RR) is used to associate an end entity certificate or public key with the associated email address, thus forming a "SMIMEA certificate association". The semantics of how the SMIMEA RR is interpreted are described in RFC6698.

## **METHODS**

The available methods are those inherited from the base class augmented by the type-specific methods defined in this package.

Use of undocumented package features or direct access to internal data structures is discouraged and could result in program termination or other unpredictable behaviour.

#### usage

```
$usage = $rr->usage;
$rr->usage( $usage );
```

8-bit integer value which specifies the provided association that will be used to match the certificate.

## selector

```
$selector = $rr->selector;
$rr->selector( $selector );
```

8-bit integer value which specifies which part of the certificate presented by the server will be matched against the association data.

## matchingtype

```
$matchingtype = $rr->matchingtype;
$rr->matchingtype( $matchingtype );
```

8-bit integer value which specifies how the certificate association is presented.

## certificate

cert

```
$cert = $rr->cert;
$rr->cert($cert);
```

Hexadecimal representation of the certificate data.

## certbin

```
$certbin = $rr->certbin;
$rr->certbin( $certbin );
```

Binary representation of the certificate data.

# babble

```
print $rr->babble;
```

The **babble**() method returns the 'BubbleBabble' representation of the digest if the Digest::BubbleBabble package is available, otherwise an empty string is returned.

BubbleBabble represents a message digest as a string of plausible words, to make the digest easier to verify. The "words" are not necessarily real words, but they look more like words than a string of hex characters.

The 'BubbleBabble' string is appended as a comment when the string method is called.

# COPYRIGHT

Copyright (c)2016 Dick Franks.

All rights reserved.

Package template (c)2009,2012 O.M.Kolkman and R.W.Franks.

# **LICENSE**

Permission to use, copy, modify, and distribute this software and its documentation for any purpose and without fee is hereby granted, provided that the above copyright notice appear in all copies and that both that copyright notice and this permission notice appear in supporting documentation, and that the name of the author not be used in advertising or publicity pertaining to distribution of the software without specific prior written permission.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

## **SEE ALSO**

perl, Net::DNS, Net::DNS::RR, RFC8162, RFC6698