

NAME

uuidparse – a utility to parse unique identifiers

SYNOPSIS

uuidparse [options] *uuid*

DESCRIPTION

This command will parse unique identifier inputs from either command line arguments or standard input. The inputs are white-space separated.

OUTPUT**Variants**

NCS	Network Computing System identifier. These were the original UUIDs.
DCE	The Open Software Foundation's (OSF) Distributed Computing Environment UUIDs.
Microsoft	Microsoft Windows platform globally unique identifier (GUID).
other	Unknown variant. Usually invalid input data.

Types

nil	Special type for zero in type file.
time-based	The DCE time based.
DCE	The DCE time and MAC Address.
name-based	RFC 4122 md5sum hash.
random	RFC 4122 random.
sha1-based	RFC 4122 sha-1 hash.
unknown	Unknown type. Usually invalid input data.

OPTIONS**-J, --json**

Use JSON output format.

-n, --noheadings

Do not print a header line.

-o, --output

Specify which output columns to print. Use **--help** to get a list of all supported columns.

-r, --raw

Use the raw output format.

-V, --version

Display version information and exit.

-h, --help

Display help text and exit.

AUTHORS

Sami Kerola <kerolasa@iki.fi>

SEE ALSO

uuidgen(1), **libuuid**(3), RFC 4122 <<https://tools.ietf.org/html/rfc4122>>

AVAILABILITY

The example command is part of the util-linux package and is available from Linux Kernel Archive <<https://www.kernel.org/pub/linux/utils/util-linux/>>.