

NAME

combine_lang_model – generate starter traineddata

SYNOPSIS

combine_lang_model --input_unicharset *filename* --script_dir *dirname* --output_dir *rootdir* --lang *lang* [--lang_is_rtl] [pass_through_recoder] [--words file --puncs file --numbers file]

DESCRIPTION

combine_lang_model(1) generates a starter traineddata file that can be used to train an LSTM-based neural network model. It takes as input a unicharset and an optional set of wordlists. It eliminates the need to run set_unicharset_properties(1), wordlist2dawg(1), some non-existent binary to generate the recoder (unicode compressor), and finally combine_tessdata(1).

OPTIONS

- lang *lang*
The language to use. Tesseract uses 3-character ISO 639-2 language codes. (See LANGUAGES)
- script_dir *PATH*
Directory name for input script unicharsets. It should point to the location of langdata (github repo) directory. (type:string default:)
- input_unicharset *FILE*
Unicharset to complete and use in encoding. It can be a hand-created file with incomplete fields. Its basic and script properties will be set before it is used. (type:string default:)
- lang_is_rtl *BOOL*
True if language being processed is written right-to-left (eg Arabic/Hebrew). (type:bool default:false)
- pass_through_recoder *BOOL*
If true, the recoder is a simple pass-through of the unicharset. Otherwise, potentially a compression of it by encoding Hangul in Jamos, decomposing multi-unicode symbols into sequences of unicodes, and encoding Han using the data in the radical_table_data, which must be the content of the file: langdata/radical-stroke.txt. (type:bool default:false)
- version_str *STRING*
An arbitrary version label to add to traineddata file (type:string default:)
- words *FILE*
(Optional) File listing words to use for the system dictionary (type:string default:)
- numbers *FILE*
(Optional) File listing number patterns (type:string default:)
- puncs *FILE*
(Optional) File listing punctuation patterns. The words/puncs/numbers lists may be all empty. If any are non-empty then puncs must be non-empty. (type:string default:)
- output_dir *PATH*
Root directory for output files. Output files will be written to <output_dir>/<lang>/<lang>.* (type:string default:)

HISTORY

combine_lang_model(1) was first made available for tesseract4.00.00alpha.

RESOURCES

Main web site: <https://github.com/tesseract-ocr> Information on training tesseract LSTM:
<https://github.com/tesseract-ocr/tesseract/wiki/TrainingTesseract-4.00>

SEE ALSO

tesseract(1)

COPYING

Copyright (C) 2012 Google, Inc. Licensed under the Apache License, Version 2.0

AUTHOR

The Tesseract OCR engine was written by Ray Smith and his research groups at Hewlett Packard (1985–1995) and Google (2006–present).