

NAME

w3m – a text based web browser and pager

SYNOPSIS

w3m [OPTION]... [*file* | *URL*]...

DESCRIPTION

w3m is a text based browser which can display local or remote web pages as well as other documents. It is able to process HTML tables and frames but it ignores JavaScript and Cascading Style Sheets. *w3m* can also serve as a pager for text files named as arguments or passed on standard input, and as a general purpose directory browser.

w3m organizes its content in buffers or tabs, allowing easy navigation between them. With the *w3m-img* extension installed, *w3m* can display inline graphics in web pages. And whenever *w3m*'s HTML rendering capabilities do not meet your needs, the target URL can be handed over to a graphical browser with a single command.

For help with runtime options, press “H” while running *w3m*.

ARGUMENTS

When given one or more command line arguments, *w3m* will handle targets according to content type. For web, *w3m* gets this information from HTTP headers; for relative or absolute file system paths, it relies on filenames.

With no argument, *w3m* expects data from standard input and assumes “text/plain” unless another MIME type is given by the user.

If provided with no target and no fallback target (see for instance option **-v** below), *w3m* will exit with usage information.

OPTIONS

Command line options are introduced with a single “-” character and may take an argument.

General options

- B** with no other target defined, use the bookmark page for startup
- M** monochrome display
- no-mouse**
deactivate mouse support
- num** display each line's number
- N** distribute multiple command line arguments to tabs. By default, a stack of buffers is used
- ppc** *num*
width of *num* pixels per character. Range of 4.0 to 32.0, default 8.0. Larger values will make tables narrower. (Implementation not verified)
- ppl** *num*
height of *num* pixels per line. Range of 4.0 to 64.0. (Implementation not verified)
- title, -title=TERM**
use the buffer name as terminal title string. With specified TERM, this sets the title configuration style accordingly
- v** with no other target defined, welcome users with a built-in page
- W** toggle wrapping mode in searches
- X** do not initialize/deinitialize the terminal

+num go to line *num*; only effective for *num* larger than the number of lines in the terminal

Browser options

-cols *num*

with stdout as destination; HTML is rendered to lines of *num* characters

-cookie, -no-cookie

use stored cookies and accept new ones, or do neither

-F render frames

-graph, -no-graph

use or do not use graphic characters for drawing HTML table and frame borders

-header *string*

append *string* to the HTTP(S) request. Expected to match the header syntax `Variable: Value`

-m Render the body of Usenet messages according to the header “Content-type”

-no-proxy

do not use proxy

-post *file*

use POST method to upload data defined in *file*. The syntax to be used is `var1=value1 [&var2=value2] . . .`

-4 IPv4 only. Corresponds to `dns_order=4` in configuration files

-6 IPv6 only. Corresponds to `dns_order=6` in configuration files

Text pager options

-l *num* number of lines preserved internally when receiving plain text from stdin (default 10,000)

-r use caret notation to display special escape characters (such as ANSI escapes or nroff-style backspaces for bold and underlined characters) instead of processing them

-s squeeze multiple blank lines into one

-t *num* set tab width to *num* columns. No effect on stdout

Data type/encoding options

-I *charset*

user defined character encoding of input data

-O *charset*

user defined character encoding of output data

-T *type*

explicit characterization of input data by MIME type

Options for data output, followed by immediate exit

-dump dump rendered page into stdout. Set implicitly when output is directed to a file or pipe

-dump_source

dump the page’s source code into stdout

-dump_head

dump response of a HEAD request for a URL into stdout

-dump_both

dump HEAD, and source code for a URL into stdout

-dump_extra

dump HEAD, source code, and extra information for a URL into stdout

-help show a summary of compiled-in features and command line options

-show-option

show all available configuration options

-versionshow the version of *w3m***Options for overriding default settings and resources****-bookmark *file***use *file* instead of the default bookmark.html file**-config *file***use *file* instead of the default configuration file**-debug**

DO NOT USE

-o *option=value*modify one configuration item with an explicitly given value; without *option=value*, equivalent to**-show-option****-reqlog**log headers of HTTP communication in file `~/.w3m/request.log`**EXAMPLES****Pager-like usage**

Combine snippets of HTML code and preview the page

```
$ cat header.html footer.html | w3m -T text/html
```

Compare two files using tabs

```
$ w3m -N config.old config
```

Browser-like usage

Display web content in monochrome terminal

```
$ w3m -M http://w3m.sourceforge.net
```

Display embedded graphics

```
$ w3m -o auto_image=TRUE http://w3m.sourceforge.net
```

Display content from Usenet

```
$ w3m -m nntp://news.aioe.org/comp.os.linux.networking
```

Upload data for a URL using the POST method

```
$ w3m -post - http://example.com/form.php <<<'a=0&b=1'
```

Filter-like usage

Convert an HTML file to plain text with a defined line length

```
$ w3m -cols 40 foo.html > foo.txt
```

Output the bookmarks page as text with an appended list of links

```
$ w3m -B -o display_link_number=1 > out.txt
```

Conversion of file format and character encoding

```
$ w3m -T text/html -I EUC-JP -O UTF-8 < foo.html > foo.txt
```

Start with no input

Welcome users with a built-in page

```
$ w3m -v
```

ENVIRONMENT*w3m* recognises the environment variable `WWW_HOME` as defining a fallback target for use if it is invoked without one.**FILES**

`~/.w3m/bookmark.html`
default bookmark file

`~/.w3m/config`
user defined configuration file; overrides `/etc/w3m/config`

`~/.w3m/cookie`
cookie jar; written on exit, read on launch

`~/.w3m/history`
browser history - visited files and URLs

`~/.w3m/keymap`
user defined key bindings; overrides default key bindings

`~/.w3m/mailcap`
external viewer configuration file

`~/.w3m/menu`
user defined menu; overrides default menu

`~/.w3m/mime.types`
MIME types file

`~/.w3m/mouse`
user defined mouse settings

`~/.w3m/passwd`
password and username file

`~/.w3m/pre_form`
contains predefined values to fill recurrent HTML forms

SEE ALSO

README and example files are to be found in the doc directory of your *w3m* installation. Recent information about *w3m* may be found on the project's web pages at <http://w3m.sourceforge.net>

ACKNOWLEDGMENTS

w3m has incorporated code from several sources. Users have contributed patches and suggestions over time.

AUTHOR

Akinori ITO (aito@fw.ipsj.or.jp)