

**NAME**

fpclassify, isfinite, isnormal, isnan, isinf – floating-point classification macros

**SYNOPSIS**

```
#include <math.h>
```

```
int fpclassify(x);
```

```
int isfinite(x);
```

```
int isnormal(x);
```

```
int isnan(x);
```

```
int isinf(x);
```

Link with `-lm`.

Feature Test Macro Requirements for glibc (see **feature\_test\_macros(7)**):

**fpclassify()**, **isfinite()**, **isnormal()**:

```
_ISOC99_SOURCE || _POSIX_C_SOURCE >= 200112L
```

**isnan()**:

```
_ISOC99_SOURCE || _POSIX_C_SOURCE >= 200112L
```

```
|| _XOPEN_SOURCE
```

```
|| /* Since glibc 2.19: */ _DEFAULT_SOURCE
```

```
|| /* Glibc versions <= 2.19: */ _BSD_SOURCE || _SVID_SOURCE
```

**isinf()**:

```
_ISOC99_SOURCE || _POSIX_C_SOURCE >= 200112L
```

```
|| /* Since glibc 2.19: */ _DEFAULT_SOURCE
```

```
|| /* Glibc versions <= 2.19: */ _BSD_SOURCE || _SVID_SOURCE
```

**DESCRIPTION**

Floating point numbers can have special values, such as infinite or NaN. With the macro **fpclassify(*x*)** you can find out what type *x* is. The macro takes any floating-point expression as argument. The result is one of the following values:

**FP\_NAN** *x* is "Not a Number".

**FP\_INFINITE** *x* is either positive infinity or negative infinity.

**FP\_ZERO** *x* is zero.

**FP\_SUBNORMAL**

*x* is too small to be represented in normalized format.

**FP\_NORMAL** if nothing of the above is correct then it must be a normal floating-point number.

The other macros provide a short answer to some standard questions.

**isfinite(*x*)** returns a nonzero value if  
(fpclassify(*x*) != FP\_NAN && fpclassify(*x*) != FP\_INFINITE)

**isnormal(*x*)** returns a nonzero value if (fpclassify(*x*) == FP\_NORMAL)

**isnan(*x*)** returns a nonzero value if (fpclassify(*x*) == FP\_NAN)

**isinf(*x*)** returns 1 if *x* is positive infinity, and -1 if *x* is negative infinity.

**ATTRIBUTES**

For an explanation of the terms used in this section, see **attributes(7)**.

Interface	Attribute	Value
<b>fpclassify()</b> , <b>isfinite()</b> , <b>isnormal()</b> , <b>isnan()</b> , <b>isinf()</b>	Thread safety	MT-Safe

**CONFORMING TO**

POSIX.1-2001, POSIX.1-2008, C99.

For **isinf()**, the standards merely say that the return value is nonzero if and only if the argument has an infinite value.

**NOTES**

In glibc 2.01 and earlier, **isinf()** returns a nonzero value (actually: 1) if  $x$  is positive infinity or negative infinity. (This is all that C99 requires.)

**SEE ALSO**

**finite(3)**, **INFINITY(3)**, **isgreater(3)**, **signbit(3)**

**COLOPHON**

This page is part of release 5.02 of the Linux *man-pages* project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.