

## NAME

**bitesize** – Add **bitesize** tag to bugs and add a comment.

## SYNOPSIS

**bitesize** *<bug number>*

**bitesize** **--help**

## DESCRIPTION

**bitesize** adds a bitesize tag to the bug, if it's not there yet. It also adds a comment to the bug indicating that you are willing to help with fixing it. It checks for permission to operate on a given bug first, then perform required tasks on Launchpad.

## OPTIONS

Listed below are the command line options for **bitesize**:

**-h, --help**

Display a help message and exit.

**-I INSTANCE, --linstance=INSTANCE**

Use the specified instance of Launchpad (e.g. "staging"), instead of the default of "production".

**--no-conf**

Do not read any configuration files, or configuration from environment variables.

## ENVIRONMENT

All of the **CONFIGURATION VARIABLES** below are also supported as environment variables. Variables in the environment take precedence to those in configuration files.

## CONFIGURATION VARIABLES

The following variables can be set in the environment or in **ubuntu-dev-tools(5)** configuration files. In each case, the script-specific variable takes precedence over the package-wide variable.

**BITESIZE\_LPINSTANCE, UBUNTUTOOLS\_LPINSTANCE**

The default value for **--linstance**.

## SEE ALSO

**ubuntu-dev-tools(5)**

## AUTHORS

**bitesize** and this manual page were written by Daniel Holbach <daniel.holbach@canonical.com>.

Both are released under the terms of the GNU General Public License, version 3.