

NAME

`exp10`, `exp10f`, `exp10l` – base-10 exponential function

SYNOPSIS

```
#define _GNU_SOURCE      /* See feature_test_macros(7) */
#include <math.h>
```

```
double exp10(double x);
float exp10f(float x);
long double exp10l(long double x);
```

Link with `-lm`.

DESCRIPTION

These functions return the value of 10 raised to the power of x .

RETURN VALUE

On success, these functions return the base-10 exponential value of x .

For various special cases, including the handling of infinity and NaN, as well as overflows and underflows, see **exp(3)**.

ERRORS

See **math_error(7)** for information on how to determine whether an error has occurred when calling these functions.

For a discussion of the errors that can occur for these functions, see **exp(3)**.

VERSIONS

These functions first appeared in glibc in version 2.1.

ATTRIBUTES

For an explanation of the terms used in this section, see **attributes(7)**.

Interface	Attribute	Value
exp10() , exp10f() , exp10l()	Thread safety	MT-Safe

CONFORMING TO

These functions are GNU extensions.

BUGS

Prior to version 2.19, the glibc implementation of these functions did not set *errno* to **ERANGE** when an underflow error occurred.

SEE ALSO

cbrt(3), **exp(3)**, **exp2(3)**, **log10(3)**, **sqrt(3)**

COLOPHON

This page is part of release 5.02 of the Linux *man-pages* project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.