

NAME

update-initramfs – generate an initramfs image

SYNOPSIS

update-initramfs {**-c**|**-d**|**-u**} [**-k** *version*] [**-v**] [**-b** *directory*]

update-initramfs -h

DESCRIPTION

The **update-initramfs** script manages your initramfs images on your local box. It keeps track of the existing initramfs archives in /boot. There are three modes of operation create, update or delete. You must at least specify one of those modes.

The initramfs is a gzipped cpio archive. At boot time, the kernel unpacks that archive into RAM disk, mounts and uses it as initial root file system. All finding of the root device happens in this early userspace.

OPTIONS

-k *version*

Set the specific kernel version for whom the initramfs will be generated. For example the output of `uname -r` for your currently running kernel. This argument is optional for update. The default is the latest kernel version.

The use of "all" for the *version* string specifies **update-initramfs** to execute the chosen action for all kernel versions, that are already known to **update-initramfs**.

-c This mode creates a new initramfs.

-u This mode updates an existing initramfs.

-d This mode removes an existing initramfs.

-v This option increases the amount of information you are given during the chosen action.

-b *directory*

Set an different bootdir for the image creation.

-h, --help

Print a short help page describing the available options in **update-initramfs**.

EXAMPLES

Update the initramfs of the newest kernel:

update-initramfs -u

Create the initramfs for a specific kernel:

update-initramfs -c -k 2.6.18-1-686

FILES

/etc/initramfs-tools/update-initramfs.conf

AUTHOR

The initramfs-tools are written by Maximilian Attems <maks@debian.org>, Jeff Bailey <jbailey@raspberrypi.com> and numerous others.

SEE ALSO

initramfs.conf(5), *initramfs-tools*(7), *mkinitramfs*(8), *lsinitramfs*(8).