

NAME

pam_motd – Display the motd file

SYNOPSIS

pam_motd.so [motd=/path/filename]

DESCRIPTION

pam_motd is a PAM module that can be used to display arbitrary motd (message of the day) files after a successful login. By default the /etc/motd file is shown. The message size is limited to 64KB.

OPTIONS

motd=/path/filename

The /path/filename file is displayed as message of the day.

motd_dir=/path/dirname.d

The /path/dirname.d directory is scanned and each file contained inside of it is displayed.

noupdate

Don't run the scripts in /etc/update-motd.d to refresh the motd file.

When no options are given, the default is to display both /etc/motd and the contents of /etc/motd.d. Specifying either option (or both) will disable this default behavior.

MODULE TYPES PROVIDED

Only the **session** module type is provided.

RETURN VALUES

PAM_IGNORE

This is the only return value of this module.

EXAMPLES

The suggested usage for /etc/pam.d/login is:

```
session optional pam_motd.so
```

To use a motd file from a different location:

```
session optional pam_motd.so motd=/elsewhere/motd
```

To use a motd file from elsewhere, along with a corresponding .d directory:

```
session optional pam_motd.so motd=/elsewhere/motd motd_dir=/elsewhere/motd.d
```

SEE ALSO

motd(5), **pam.conf(5)**, **pam.d(5)**, **pam(7)**, **update-motd(5)**

AUTHOR

pam_motd was written by Ben Collins <bcollins@debian.org>.

The **motd_dir=** option was added by Allison Karlitskaya <allison.karlitskaya@redhat.com>.