

NAME

git-ls-tree – List the contents of a tree object

SYNOPSIS

```
git ls-tree [-d] [-r] [-t] [-l] [-z]
            [--name-only] [--name-status] [--full-name] [--full-tree] [--abbrev[=<n>]]
            <tree-ish> [<path>...]
```

DESCRIPTION

Lists the contents of a given tree object, like what `/bin/ls -a` does in the current working directory. Note that:

- the behaviour is slightly different from that of `/bin/ls` in that the `<path>` denotes just a list of patterns to match, e.g. so specifying directory name (without `-r`) will behave differently, and order of the arguments does not matter.
- the behaviour is similar to that of `/bin/ls` in that the `<path>` is taken as relative to the current working directory. E.g. when you are in a directory *sub* that has a directory *dir*, you can run `git ls-tree -r HEAD dir` to list the contents of the tree (that is *sub/dir* in **HEAD**). You don't want to give a tree that is not at the root level (e.g. `git ls-tree -r HEAD:sub dir`) in this case, as that would result in asking for *sub/sub/dir* in the **HEAD** commit. However, the current working directory can be ignored by passing `--full-tree` option.

OPTIONS

`<tree-ish>`
Id of a tree-ish.

`-d`
Show only the named tree entry itself, not its children.

`-r`
Recurse into sub-trees.

`-t`
Show tree entries even when going to recurse them. Has no effect if `-r` was not passed. `-d` implies `-t`.

`-l, --long`
Show object size of blob (file) entries.

`-z`
\0 line termination on output and do not quote filenames. See OUTPUT FORMAT below for more information.

`--name-only, --name-status`
List only filenames (instead of the "long" output), one per line.

`--abbrev[=<n>]`
Instead of showing the full 40-byte hexadecimal object lines, show only a partial prefix. Non default number of digits can be specified with `--abbrev=<n>`.

`--full-name`
Instead of showing the path names relative to the current working directory, show the full path names.

`--full-tree`
Do not limit the listing to the current working directory. Implies `--full-name`.

`[<path>...]`
When paths are given, show them (note that this isn't really raw pathnames, but rather a list of patterns to match). Otherwise implicitly uses the root level of the tree as the sole path argument.

OUTPUT FORMAT

```
<mode> SP <type> SP <object> TAB <file>
```

This output format is compatible with what **--index-info --stdin** of *git update-index* expects.

When the **-l** option is used, format changes to

<mode> SP <type> SP <object> SP <object size> TAB <file>

Object size identified by <object> is given in bytes, and right-justified with minimum width of 7 characters. Object size is given only for blobs (file) entries; for other entries – character is used in place of size.

Without the **-z** option, pathnames with "unusual" characters are quoted as explained for the configuration variable **core.quotePath** (see **git-config(1)**). Using **-z** the filename is output verbatim and the line is terminated by a NUL byte.

GIT

Part of the **git(1)** suite