## **NAME**

icuinfo - Shows some basic info about the current ICU

## **SYNOPSIS**

```
icuinfo [ -h, -?, --help ] [ -V, --version ] [ -c, --copyright ] [ -i, --icudatadir \mathit{directory} ] [ -v, --verbose ] [ -L, --list-plugins ] [ -m, --milisecond-time ] [ -K, --cleanup ]
```

# DESCRIPTION

icuinfo prints basic information about the current version of ICU.

## **OPTIONS**

## -h, -?, --help

Print help about usage and exit.

### -V, --version

Print the version of **icuinfo** and exit.

## -c, --copyright

Embeds the standard ICU copyright into the output-file.

#### -v, --verbose

Display extra informative messages during execution.

## -i, --icudatadir directory

Look for any necessary ICU data files in *directory*. For example, the file **pnames.icu** must be located when ICU's data is not built as a shared library. The default ICU data directory is specified by the environment variable ICU\_DATA. Most configurations of ICU do not require this argument.

## -L, --list-plugins

If specified, list and diagnose issues with ICU plugins.

## -K, --cleanup

Attempt to unload plugins before exiting.

## -m, --milisecond-time

Print the current UTC time in milliseconds.

## **COPYRIGHT**

Copyright (C) 2010 International Business Machines Corporation and others