

NAME

pthread_attr_setaffinity_np, pthread_attr_getaffinity_np – set/get CPU affinity attribute in thread attributes object

SYNOPSIS

```
#define _GNU_SOURCE      /* See feature_test_macros(7) */
#include <pthread.h>

int pthread_attr_setaffinity_np(pthread_attr_t *attr,
                                size_t cpusetsize, const cpu_set_t *cpuset);
int pthread_attr_getaffinity_np(const pthread_attr_t *attr,
                                size_t cpusetsize, cpu_set_t *cpuset);
```

Compile and link with `-pthread`.

DESCRIPTION

The **pthread_attr_setaffinity_np()** function sets the CPU affinity mask attribute of the thread attributes object referred to by *attr* to the value specified in *cpuset*. This attribute determines the CPU affinity mask of a thread created using the thread attributes object *attr*.

The **pthread_attr_getaffinity_np()** function returns the CPU affinity mask attribute of the thread attributes object referred to by *attr* in the buffer pointed to by *cpuset*.

The argument *cpusetsize* is the length (in bytes) of the buffer pointed to by *cpuset*. Typically, this argument would be specified as `sizeof(cpu_set_t)`.

For more details on CPU affinity masks, see **sched_setaffinity(2)**. For a description of a set of macros that can be used to manipulate and inspect CPU sets, see **CPU_SET(3)**.

RETURN VALUE

On success, these functions return 0; on error, they return a nonzero error number.

ERRORS**EINVAL**

(**pthread_attr_setaffinity_np()**) *cpuset* specified a CPU that was outside the set supported by the kernel. (The kernel configuration option **CONFIG_NR_CPUS** defines the range of the set supported by the kernel data type used to represent CPU sets.)

EINVAL

(**pthread_attr_getaffinity_np()**) A CPU in the affinity mask of the thread attributes object referred to by *attr* lies outside the range specified by *cpusetsize* (i.e., *cpuset/cpusetsize* is too small).

ENOMEM

(**pthread_attr_setaffinity_np()**) Could not allocate memory.

VERSIONS

These functions are provided by glibc since version 2.3.4.

ATTRIBUTES

For an explanation of the terms used in this section, see **attributes(7)**.

Interface	Attribute	Value
pthread_attr_setaffinity_np() , pthread_attr_getaffinity_np()	Thread safety	MT-Safe

CONFORMING TO

These functions are nonstandard GNU extensions; hence the suffix "_np" (nonportable) in the names.

NOTES

In glibc 2.3.3 only, versions of these functions were provided that did not have a *cpusetsize* argument. Instead the CPU set size given to the underlying system calls was always `sizeof(cpu_set_t)`.

SEE ALSO

sched_setaffinity(2), pthread_attr_init(3), pthread_setaffinity_np(3), cpuset(7), pthreads(7)

COLOPHON

This page is part of release 5.02 of the Linux *man-pages* project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.