

NAME

dh_autotools-dev_updateconfig – update config.sub and config.guess

SYNOPSIS

dh_autotools-dev_updateconfig [*debhelper options*]

DESCRIPTION

Deprecated: dh_autotools-dev_updateconfig and dh_autotools-dev_restoreconfig are deprecated and replaced by *dh_update_autotools_config*(1) and *dh_clean*(1) from debhelper. Please replace all uses of dh_autotools-dev_updateconfig with dh_update_autotools_config and then remove any use of dh_autotools-dev_restoreconfig.

dh_autotools-dev_updateconfig replaces all occurrences of **config.sub** and **config.guess** in the source tree by the up-to-date versions found in the autotools-dev package. The original files are backed up under the names **config.sub.dh-orig** and **config.guess.dh-orig**.

EXAMPLES

dh_autotools-dev_updateconfig is usually called indirectly in a rules file via the dh command.

```
%:
    dh $@ --with autotools_dev
```

It can also be directly called at the start of the build (or configure) rule.

```
build:
    dh_autotools-dev_updateconfig
    ./configure
    $ (MAKE)
```

SEE ALSO

debhelper(7), *dh*(1).

This program is meant to be used together with debhelper.

AUTHOR

Fabian Greffrath <fabian+debian@greffrath.com>