

**NAME**

HTML::Template::FAQ – Frequently Asked Questions about HTML::Template

**SYNOPSIS**

In the interest of greater understanding I've started a FAQ section of the perldocs. Please look in here before you send me email.

**FREQUENTLY ASKED QUESTIONS****Is there a place to go to discuss HTML::Template and/or get help?**

There's a mailing-list for discussing HTML::Template at `html-template-users@lists.sourceforge.net`. Join at:

```
http://lists.sourceforge.net/lists/listinfo/html-template-users
```

If you just want to get email when new releases are available you can join the announcements mailing-list here:

```
http://lists.sourceforge.net/lists/listinfo/html-template-announce
```

**Is there a searchable archive for the mailing-list?**

Yes, you can find an archive of the SourceForge list here:

```
http://dir.gmane.org/gmane.comp.lang.perl.modules.html-template
```

**I want support for <TMPL\_XXX>! How about it?**

Maybe. I definitely encourage people to discuss their ideas for HTML::Template on the mailing list. Please be ready to explain to me how the new tag fits in with HTML::Template's mission to provide a fast, lightweight system for using HTML templates.

NOTE: Offering to program said addition and provide it in the form of a patch to the most recent version of HTML::Template will definitely have a softening effect on potential opponents!

**I found a bug, can you fix it?**

That depends. Did you send me the VERSION of HTML::Template, a test script and a test template? If so, then almost certainly.

If you're feeling really adventurous, HTML::Template is publicly available on GitHub (<https://github.com/mpeters/html-template>). Please feel free to fork it and send me a pull request with any changes you have.

**<TMPL\_VAR>s from the main template aren't working inside a <TMPL\_LOOP>! Why?**

This is the intended behavior. <TMPL\_LOOP> introduces a separate scope for <TMPL\_VAR>s much like a subroutine call in Perl introduces a separate scope for my variables.

If you want your <TMPL\_VAR>s to be global you can set the `global_vars` option when you call `new()`. See above for documentation of the `global_vars new()` option.

**How can I pre-load my templates using cache-mode and mod\_perl?**

Add something like this to your startup.pl:

```
use HTML::Template;
use File::Find;

print STDERR "Pre-loading HTML Templates...\n";
find(
    sub {
        return unless /\.tmpl$/;
        HTML::Template->new(
            filename => "$File::Find::dir/$_",
            cache    => 1,
        );
    },
    '/path/to/templates',
```

```
        '/another/path/to/templates/'
    );
```

Note that you'll need to modify the `return unless` line to specify the extension you use for your template files – I use `.tmpl`, as you can see. You'll also need to specify the path to your template files.

One potential problem: the `/path/to/templates/` must be **EXACTLY** the same path you use when you call `HTML::Template->new()`. Otherwise the cache won't know they're the same file and will load a new copy – instead getting a speed increase, you'll double your memory usage. To find out if this is happening set `cache_debug = 1` in your application code and look for "CACHE MISS" messages in the logs.

#### What characters are allowed in TMPL\_\* names?

Numbers, letters, '.', '/', '+', '-' and '\_'.

#### How can I execute a program from inside my template?

Short answer: you can't. Longer answer: you shouldn't since this violates the fundamental concept behind HTML::Template – that design and code should be separate.

But, inevitably some people still want to do it. If that describes you then you should take a look at HTML::Template::Expr. Using HTML::Template::Expr it should be easy to write a `run_program()` function. Then you can do awful stuff like:

```
<tmpl_var expr="run_program('foo.pl') ">
```

Just, please, don't tell me about it. I'm feeling guilty enough just for writing HTML::Template::Expr in the first place.

#### What's the best way to create a <select> form element using HTML::Template?

There is much disagreement on this issue. My personal preference is to use CGI.pm's excellent `popup_menu()` and `scrolling_list()` functions to fill in a single `<tmpl_var select_foo>` variable.

To some people this smacks of mixing HTML and code in a way that they hoped HTML::Template would help them avoid. To them I'd say that HTML is a violation of the principle of separating design from programming. There's no clear separation between the programmatic elements of the `<form>` tags and the layout of the `<form>` tags. You'll have to draw the line somewhere – clearly the designer can't be entirely in charge of form creation.

It's a balancing act and you have to weigh the pros and cons on each side. It is certainly possible to produce a `<select>` element entirely inside the template. What you end up with is a rat's nest of loops and conditionals. Alternately you can give up a certain amount of flexibility in return for vastly simplifying your templates. I generally choose the latter.

Another option is to investigate HTML::FillInForm which some have reported success using to solve this problem.