

NAME

chroot – run command or interactive shell with special root directory

SYNOPSIS

chroot [*OPTION*] *NEWROOT* [*COMMAND* [*ARG*]...]
chroot *OPTION*

DESCRIPTION

Run *COMMAND* with root directory set to *NEWROOT*.

--groups=*G_LIST*
specify supplementary groups as *g1,g2,...,gN*

--userspec=*USER:GROUP*
specify user and group (ID or name) to use

--skip-chdir
do not change working directory to '/'

--help display this help and exit

--version
output version information and exit

If no command is given, run *"\$SHELL" -i* (default: *'/bin/sh -i'*).

AUTHOR

Written by Roland McGrath.

REPORTING BUGS

GNU coreutils online help: <<https://www.gnu.org/software/coreutils/>>

Report chroot translation bugs to <<https://translationproject.org/team/>>

COPYRIGHT

Copyright © 2018 Free Software Foundation, Inc. License GPLv3+: GNU GPL version 3 or later
<<https://gnu.org/licenses/gpl.html>>.

This is free software: you are free to change and redistribute it. There is NO WARRANTY, to the extent permitted by law.

SEE ALSO

chroot(2)

Full documentation at: <<https://www.gnu.org/software/coreutils/chroot>>
or available locally via: info '(coreutils) chroot invocation'