

**NAME**

gnome-disk-image-mounter – Attach and mount disk images

**SYNOPSIS**

**gnome-disk-image-mounter** [**--writable**] [*URI*...]

**DESCRIPTION**

**gnome-disk-image-mounter** can be used to set up disk images. Both regular files and *GVfs* URIs (such as `smb://filer/media/file.iso`) can be used in the *URI* parameter. If no *URIs* are given and a window server is running, a graphical file chooser will be presented.

Note that **gnome-disk-image-mounter** will not mount filesystems or unlock encrypted volumes in the disk image – this responsibility is left to the automounter in GNOME Shell to ensure that the same interactions happen as if the disk image was a regular physical device or disc.

By default the disk images are attached read-only, use the option **--writable** to change this.

**RETURN VALUE**

**gnome-disk-image-mounter** returns 0 on success and non-zero on failure.

**AUTHOR**

Written by David Zeuthen <zeuthen@gmail.com> with a lot of help from many others.

**BUGS**

Please send bug reports to either the distribution bug tracker or the upstream bug tracker at

[https://bugzilla.gnome.org/enter\\_bug.cgi?product=gnome-disk-utility](https://bugzilla.gnome.org/enter_bug.cgi?product=gnome-disk-utility).

**SEE ALSO**

**gnome-shell**(1), **gnome-disks**(1), **udisks**(8), **losetup**(8)