

NAME

`migrate-pubring-from-classic-gpg` – Migrate a public keyring from "classic" to "modern" GnuPG

SYNOPSIS

`migrate-pubring-from-classic-gpg` [`GPGHOMEDIR` | `--default`]

DESCRIPTION

`migrate-pubring-from-classic-gpg` migrates the public keyring in GnuPG home directory `GPGHOMEDIR` from the "classic" keyring format to the "modern" keybox format using GnuPG versions 2.1 or 2.2.

Specifying `--default` selects the standard GnuPG home directory (looking at `$GNUPGHOME` first, and falling back to `~/.gnupg` if unset).

OPTIONS

`-h`, `--help`, `--usage` Output a short usage information.

DIAGNOSTICS

The program sends quite a bit of text (perhaps too much) to `stderr`.

During a migration, the tool backs up several pieces of data in a timestamped subdirectory of the `GPGHOMEDIR`.

ENVIRONMENT VARIABLES

GNUPGHOME Selects the GnuPG home directory when set and `--default` is given.

GPG The name of the `gpg` executable (defaults to `gpg`).

SEE ALSO

`gpg(1)`

AUTHOR

Copyright (C) 2016 Daniel Kahn Gillmor for the Debian project. Please report bugs via the Debian BTS.