

**NAME**

`telldir` – return current location in directory stream

**SYNOPSIS**

```
#include <dirent.h>
```

```
long telldir(DIR *dirp);
```

Feature Test Macro Requirements for glibc (see **feature\_test\_macros(7)**):

```
telldir():
_XOPEN_SOURCE
  || /* Glibc since 2.19: */ _DEFAULT_SOURCE
  || /* Glibc versions <= 2.19: */ _BSD_SOURCE || _SVID_SOURCE
```

**DESCRIPTION**

The **telldir**() function returns the current location associated with the directory stream *dirp*.

**RETURN VALUE**

On success, the **telldir**() function returns the current location in the directory stream. On error, `-1` is returned, and *errno* is set appropriately.

**ERRORS****EBADF**

Invalid directory stream descriptor *dirp*.

**ATTRIBUTES**

For an explanation of the terms used in this section, see **attributes(7)**.

Interface	Attribute	Value
<b>telldir</b> ()	Thread safety	MT-Safe

**CONFORMING TO**

POSIX.1-2001, POSIX.1-2008, 4.3BSD.

**NOTES**

In glibc up to version 2.1.1, the return type of **telldir**() was *off\_t*. POSIX.1-2001 specifies *long*, and this is the type used since glibc 2.1.2.

In early filesystems, the value returned by **telldir**() was a simple file offset within a directory. Modern filesystems use tree or hash structures, rather than flat tables, to represent directories. On such filesystems, the value returned by **telldir**() (and used internally by **readdir**(3)) is a "cookie" that is used by the implementation to derive a position within a directory. Application programs should treat this strictly as an opaque value, making *no* assumptions about its contents.

**SEE ALSO**

**closedir**(3), **opendir**(3), **readdir**(3), **rewinddir**(3), **scandir**(3), **seekdir**(3)

**COLOPHON**

This page is part of release 5.02 of the Linux *man-pages* project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.