

NAME

`ibv_query_qp` – get the attributes of a queue pair (QP)

SYNOPSIS

```
#include <infiniband/verbs.h>
```

```
int ibv_query_qp(struct ibv_qp *qp, struct ibv_qp_attr *attr,
                int attr_mask,
                struct ibv_qp_init_attr *init_attr);
```

DESCRIPTION

ibv_query_qp() gets the attributes specified in *attr_mask* for the QP *qp* and returns them through the pointers *attr* and *init_attr*. The argument *attr* is an `ibv_qp_attr` struct, as defined in `<infiniband/verbs.h>`.

```
struct ibv_qp_attr {
    enum ibv_qp_state    qp_state;        /* Current QP state */
    enum ibv_qp_state    cur_qp_state;    /* Current QP state - irrelevant for ibv_query_qp */
    enum ibv_mtu         path_mtu;        /* Path MTU (valid only for RC/UC QPs) */
    enum ibv_mig_state    path_mig_state; /* Path migration state (valid if HCA supports APM) */
    uint32_t             qkey;            /* Q_Key of the QP (valid only for UD QPs) */
    uint32_t             rq_psn;          /* PSN for receive queue (valid only for RC/UC QPs) */
    uint32_t             sq_psn;          /* PSN for send queue (valid only for RC/UC QPs) */
    uint32_t             dest_qp_num;     /* Destination QP number (valid only for RC/UC QPs) */
    int                  qp_access_flags; /* Mask of enabled remote access operations (valid only for RC/UC QPs) */
    struct ibv_qp_cap     cap;             /* QP capabilities */
    struct ibv_ah_attr     ah_attr;        /* Primary path address vector (valid only for RC/UC QPs) */
    struct ibv_ah_attr     alt_ah_attr;    /* Alternate path address vector (valid only for RC/UC QPs) */
    uint16_t              pkey_index;      /* Primary P_Key index */
    uint16_t              alt_pkey_index;  /* Alternate P_Key index */
    uint8_t               en_sqd_async_notify; /* Enable SQD.drained async notification - irrelevant for ibv_query_qp */
    uint8_t               sq_draining;     /* Is the QP draining? (Valid only if qp_state is SQD) */
    uint8_t               max_rd_atomic;   /* Number of outstanding RDMA reads & atomic operations on RDMA read */
    uint8_t               max_dest_rd_atomic; /* Number of responder resources for handling incoming RDMA read */
    uint8_t               min_rnr_timer;   /* Minimum RNR NAK timer (valid only for RC QPs) */
    uint8_t               port_num;        /* Primary port number */
    uint8_t               timeout;         /* Local ack timeout for primary path (valid only for RC QPs) */
    uint8_t               retry_cnt;       /* Retry count (valid only for RC QPs) */
    uint8_t               rnr_retry;      /* RNR retry (valid only for RC QPs) */
    uint8_t               alt_port_num;    /* Alternate port number */
    uint8_t               alt_timeout;     /* Local ack timeout for alternate path (valid only for RC QPs) */
};
```

For details on struct `ibv_qp_cap` see the description of **ibv_create_qp()**. For details on struct `ibv_ah_attr` see the description of **ibv_create_ah()**.

RETURN VALUE

ibv_query_qp() returns 0 on success, or the value of `errno` on failure (which indicates the failure reason).

NOTES

The argument *attr_mask* is a hint that specifies the minimum list of attributes to retrieve. Some RDMA devices may return extra attributes not requested, for example if the value can be returned cheaply. This has the same form as in **ibv_modify_qp()**.

Attribute values are valid if they have been set using **ibv_modify_qp()**. The exact list of valid attributes depends on the QP state.

Multiple calls to **ibv_query_qp()** may yield some differences in the values returned for the following attributes: `qp_state`, `path_mig_state`, `sq_draining`, `ah_attr` (if APM is enabled).

SEE ALSO

ibv_create_qp(3), ibv_destroy_qp(3), ibv_modify_qp(3), ibv_create_ah(3)

AUTHORS

Dotan Barak <dotanba@gmail.com>