

NAME

getpw – reconstruct password line entry

SYNOPSIS

```
#define _GNU_SOURCE      /* See feature_test_macros(7) */
#include <sys/types.h>
#include <pwd.h>

int getpw(uid_t uid, char *buf);
```

DESCRIPTION

The **getpw()** function reconstructs the password line entry for the given user ID *uid* in the buffer *buf*. The returned buffer contains a line of format

name:passwd:uid:gid:gecos:dir:shell

The *passwd* structure is defined in *<pwd.h>* as follows:

```
struct passwd {
    char    *pw_name;          /* username */
    char    *pw_passwd;        /* user password */
    uid_t   pw_uid;            /* user ID */
    gid_t   pw_gid;            /* group ID */
    char    *pw_gecos;         /* user information */
    char    *pw_dir;           /* home directory */
    char    *pw_shell;         /* shell program */
};
```

For more information about the fields of this structure, see **passwd(5)**.

RETURN VALUE

The **getpw()** function returns 0 on success; on error, it returns **-1**, and *errno* is set to indicate the error.

If *uid* is not found in the password database, **getpw()** returns **-1**, sets *errno* to 0, and leaves *buf* unchanged.

ERRORS**0 or ENOENT**

No user corresponding to *uid*.

EINVAL

buf is NULL.

ENOMEM

Insufficient memory to allocate *passwd* structure.

FILES

/etc/passwd
password database file

ATTRIBUTES

For an explanation of the terms used in this section, see **attributes(7)**.

Interface	Attribute	Value
getpw()	Thread safety	MT-Safe locale

CONFORMING TO

SVr2.

BUGS

The **getpw()** function is dangerous as it may overflow the provided buffer *buf*. It is obsoleted by **getpwuid(3)**.

SEE ALSO

endpwent(3), fgetpwent(3), getpwent(3), getpwnam(3), getpwuid(3), putpwent(3), setpwent(3), passwd(5)

COLOPHON

This page is part of release 5.02 of the Linux *man-pages* project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.