

NAME

`readlink`, `readlinkat` – read value of a symbolic link

SYNOPSIS

```
#include <unistd.h>
```

```
ssize_t readlink(const char *pathname, char *buf, size_t bufsiz);
```

```
#include <fcntl.h>      /* Definition of AT_* constants */
```

```
#include <unistd.h>
```

```
ssize_t readlinkat(int dirfd, const char *pathname,
                   char *buf, size_t bufsiz);
```

Feature Test Macro Requirements for glibc (see **feature_test_macros(7)**):

readlink():

```
_XOPEN_SOURCE >= 500 || _POSIX_C_SOURCE >= 200112L
|| /* Glibc versions <= 2.19: */ _BSD_SOURCE
```

readlinkat():

Since glibc 2.10:

```
_POSIX_C_SOURCE >= 200809L
```

Before glibc 2.10:

```
_ATFILE_SOURCE
```

DESCRIPTION

readlink() places the contents of the symbolic link *pathname* in the buffer *buf*, which has size *bufsiz*. **readlink()** does not append a null byte to *buf*. It will (silently) truncate the contents (to a length of *bufsiz* characters), in case the buffer is too small to hold all of the contents.

readlinkat()

The **readlinkat()** system call operates in exactly the same way as **readlink()**, except for the differences described here.

If the *pathname* given in *pathname* is relative, then it is interpreted relative to the directory referred to by the file descriptor *dirfd* (rather than relative to the current working directory of the calling process, as is done by **readlink()** for a relative *pathname*).

If *pathname* is relative and *dirfd* is the special value **AT_FDCWD**, then *pathname* is interpreted relative to the current working directory of the calling process (like **readlink()**).

If *pathname* is absolute, then *dirfd* is ignored.

Since Linux 2.6.39, *pathname* can be an empty string, in which case the call operates on the symbolic link referred to by *dirfd* (which should have been obtained using **open(2)** with the **O_PATH** and **O_NOFOLLOW** flags).

See **openat(2)** for an explanation of the need for **readlinkat()**.

RETURN VALUE

On success, these calls return the number of bytes placed in *buf*. (If the returned value equals *bufsiz*, then truncation may have occurred.) On error, `-1` is returned and *errno* is set to indicate the error.

ERRORS**EACCES**

Search permission is denied for a component of the path prefix. (See also **path_resolution(7)**.)

EFAULT

buf extends outside the process's allocated address space.

EINVAL

bufsiz is not positive.

EINVAL

The named file (i.e., the final filename component of *pathname*) is not a symbolic link.

EIO

An I/O error occurred while reading from the filesystem.

ELOOP

Too many symbolic links were encountered in translating the *pathname*.

ENAMETOOLONG

A *pathname*, or a component of a *pathname*, was too long.

ENOENT

The named file does not exist.

ENOMEM

Insufficient kernel memory was available.

ENOTDIR

A component of the path prefix is not a directory.

The following additional errors can occur for **readlinkat()**:

EBADF

dirfd is not a valid file descriptor.

ENOTDIR

pathname is relative and *dirfd* is a file descriptor referring to a file other than a directory.

VERSIONS

readlinkat() was added to Linux in kernel 2.6.16; library support was added to glibc in version 2.4.

CONFORMING TO

readlink(): 4.4BSD (**readlink()** first appeared in 4.2BSD), POSIX.1-2001, POSIX.1-2008.

readlinkat(): POSIX.1-2008.

NOTES

In versions of glibc up to and including glibc 2.4, the return type of **readlink()** was declared as *int*. Nowadays, the return type is declared as *ssize_t*, as (newly) required in POSIX.1-2001.

Using a statically sized buffer might not provide enough room for the symbolic link contents. The required size for the buffer can be obtained from the *stat.st_size* value returned by a call to **lstat(2)** on the link. However, the number of bytes written by **readlink()** and **readlinkat()** should be checked to make sure that the size of the symbolic link did not increase between the calls. Dynamically allocating the buffer for **readlink()** and **readlinkat()** also addresses a common portability problem when using *PATH_MAX* for the buffer size, as this constant is not guaranteed to be defined per POSIX if the system does not have such limit.

Glibc notes

On older kernels where **readlinkat()** is unavailable, the glibc wrapper function falls back to the use of **readlink()**. When *pathname* is a relative *pathname*, glibc constructs a *pathname* based on the symbolic link in */proc/self/fd* that corresponds to the *dirfd* argument.

EXAMPLE

The following program allocates the buffer needed by **readlink()** dynamically from the information provided by **lstat(2)**, falling back to a buffer of size **PATH_MAX** in cases where **lstat(2)** reports a size of zero.

```
#include <sys/types.h>
#include <sys/stat.h>
#include <limits.h>
#include <stdio.h>
#include <stdlib.h>
#include <unistd.h>

int
main(int argc, char *argv[])
```

```
{
    struct stat sb;
    char *buf;
    ssize_t nbytes, bufsiz;

    if (argc != 2) {
        fprintf(stderr, "Usage: %s <pathname>\n", argv[0]);
        exit(EXIT_FAILURE);
    }

    if (lstat(argv[1], &sb) == -1) {
        perror("lstat");
        exit(EXIT_FAILURE);
    }

    /* Add one to the link size, so that we can determine whether
       the buffer returned by readlink() was truncated. */

    bufsiz = sb.st_size + 1;

    /* Some magic symlinks under (for example) /proc and /sys
       report 'st_size' as zero. In that case, take PATH_MAX as
       a "good enough" estimate. */

    if (sb.st_size == 0)
        bufsiz = PATH_MAX;

    buf = malloc(bufsiz);
    if (buf == NULL) {
        perror("malloc");
        exit(EXIT_FAILURE);
    }

    nbytes = readlink(argv[1], buf, bufsiz);
    if (nbytes == -1) {
        perror("readlink");
        exit(EXIT_FAILURE);
    }

    printf("%s' points to '%.*s'\n", argv[1], (int) nbytes, buf);

    /* If the return value was equal to the buffer size, then the
       the link target was larger than expected (perhaps because the
       target was changed between the call to lstat() and the call to
       readlink()). Warn the user that the returned target may have
       been truncated. */

    if (nbytes == bufsiz)
        printf("(Returned buffer may have been truncated)\n");

    free(buf);
    exit(EXIT_SUCCESS);
}
```

SEE ALSO

readlink(1), lstat(2), stat(2), symlink(2), realpath(3), path_resolution(7), symlink(7)

COLOPHON

This page is part of release 5.02 of the Linux *man-pages* project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.