

Name

mmd - make an MSDOS subdirectory

Note of warning

This manpage has been automatically generated from mtools's texinfo documentation, and may not be entirely accurate or complete. See the end of this man page for details.

Description

The mmd command is used to make an MS-DOS subdirectory. Its syntax is:

```
mmd [-D clash_option] msdosdirectory [ msdosdirectories... ]
```

Mmd makes a new directory on an MS-DOS file system. An error occurs if the directory already exists.

See Also

Mtools' texinfo doc

Viewing the texi doc

This manpage has been automatically generated from mtools's texinfo documentation. However, this process is only approximative, and some items, such as crossreferences, footnotes and indices are lost in this translation process. Indeed, these items have no appropriate representation in the manpage format. Moreover, not all information has been translated into the manpage version. Thus I strongly advise you to use the original texinfo doc. See the end of this manpage for instructions how to view the texinfo doc.

* To generate a printable copy from the texinfo doc, run the following commands:

```
./configure; make dvi; dvips mtools.dvi
```

* To generate a html copy, run:

```
./configure; make html
```

A premade html can be found at '<http://www.gnu.org/software/mtools/manual/mtools.html>'

* To generate an info copy (browsable using emacs' info mode), run:

```
./configure; make info
```

The texinfo doc looks most pretty when printed or as html. Indeed, in the info version certain examples are difficult to read due to the quoting conventions used in info.