

NAME

reverse-depends – List the reverse-dependencies (or build-dependencies) of a package

SYNOPSIS

reverse-depends [*options*] *package*

DESCRIPTION

List reverse-dependencies (or build-dependencies) of *package*. If the package name is prefixed with **src:** then the reverse-dependencies of all the binary packages that the specified source package builds will be listed.

OPTIONS

-r *RELEASE*, **--release=***RELEASE*

Query dependencies in *RELEASE*. Default: current development release.

-R, **--without-recommends**

Only consider Depends relationships, not Recommends.

-s, **--with-suggests**

Also consider Suggests relationships.

-b, **--build-depends**

Query build dependencies. Synonym for **--arch=source**.

-a *ARCH*, **--arch=***ARCH*

Query dependencies in *ARCH*. Besides valid architecture names, the special values **any** and **source** may be used. **any** displays all reverse dependencies, the union across all architecture. **source** displays build dependencies. Default: **any**.

-c *COMPONENT*, **--component=***COMPONENT*

Only consider reverse-dependencies in *COMPONENT*. Can be specified multiple times. Default: all components.

-l, **--list**

Display a simple, machine-readable list.

-u *URL*, **--service-url=***URL*

Reverse Dependencies web-service *URL*. Default: UbuntuWire's service at <http://qa.ubuntuwire.org/rdepends/>.

-h, **--help**

Display a help message and exit

EXAMPLES

All reverse dependencies of source package bash:

reverse-depends src:bash

AUTHORS

reverse-depends and this manpage were written by Stefano Rivera <stefanor@ubuntu.com>.

Both are released under the terms of the ISC License.