**NAME**
>       ip-ntable - neighbour table configuration

**SYNOPSIS**
>       **ip** [ *OPTIONS* ] **ntable**  { *COMMAND* | **help** }

>       **ip ntable change name** *NAME* [ **dev** *DEV* ] [ **thresh1** *VAL* ] [ **thresh2** *VAL* ] [ **thresh3** *VAL* ] [ **gc_int**
>              *MSEC* ] [ **base_reachable** *MSEC* ] [ **retrans** *MSEC* ] [ **gc_stale** *MSEC* ] [ **de-**
>              **lay_probe** *MSEC* ] [ **queue** *LEN* ] [ **app_probs** *VAL* ] [ **ucast_probes** *VAL* ] [
>              **mcast_probes** *VAL* ] [ **anycast_delay** *MSEC* ] [ **proxy_delay** *MSEC* ] [ **proxy_queue**
>              *LEN* ] [ **locktime** *MSEC* ]

>       **ip ntable show** [ **dev** *DEV* ] [ **name** *NAME* ]

**DESCRIPTION**
>       *ip ntable* controls the parameters for the neighbour tables.

>    **ip ntable show - list the ip neighbour tables**
>       This commands displays neighbour table parameters and statistics.

>       **dev** *DEV*
>              only list the table attached to this device.

>       **name** *NAME*
>              only lists the table with the given name.

>    **ip ntable change - modify table parameter**
>       This command allows modifying table parameters such as timers and queue lengths.

>       **name** *NAME*
>              the name of the table to modify.

>       **dev** *DEV*
>              the name of the device to modify the table values.

**EXAMPLES**
>       ip ntable show dev eth0
>           Shows the neighbour table (IPv4 ARP and IPv6 ndisc) parameters on device eth0.

>       ip ntable change name arp_cache queue 8 dev eth0
>           Changes the number of packets queued while address is being resolved from the default value (3) to 8
>           packets.

**SEE ALSO**
>       **ip**(8)

**AUTHOR**
>       Manpage by Stephen Hemminger