

NAME

`xkbprint` – print an XKB keyboard description

SYNOPSIS

xkbprint [options] source [output_file]

DESCRIPTION

The *xkbprint* command generates a printable or encapsulated PostScript description of the XKB keyboard description specified by *source*. The *source* can be any compiled keymap (.xkm) file that includes a geometry description or an X display specification. If an *output_file* is specified, *xkbprint* writes to it. If no output file is specified, *xkbprint* creates replaces the extension of the source file with *.ps* or *.eps* depending on the requested format. If the source is a non-local X display (e.g.:0), *xkbprint* appends the appropriate prefix to the display specification, replacing the colon with a dash. For a local display, *xkprint* uses *server-n* where *n* is the number of the display.

OPTIONS

-?, -help

Prints a usage message.

-color Print using the colors specified in the geometry file; by default, *xkbprint* prints a black-and-white image of the keyboard.

-dfmts Attempt to compute default names for any missing components, such as keys.

-diffs Show symbols only where they are explicitly bound.

-eps Generate an encapsulated PostScript file.

-fit Fit the keyboard image on the page (default).

-full Print the keyboard at full size.

-grid *res*

Print a grid with *res*mm resolution over the keyboard.

-if *fontName*

Specifies an internal PostScript type 1 font to dump to the specified output file or to *fontName.pfa*, if no output file is specified. No keyboard description is printed if an internal font is dumped.

-label *type*

Specifies the labels to be printed on keys; legal types are: *none, name, code, symbols*.

-lc *<locale>*

Specifies a locale in which KeySyms should be resolved.

-level1 Generate level 1 PostScript.

-level2 Generate level 2 PostScript.

-lg *group*

Print symbols in keyboard groups starting from *group*.

-ll *level* Print symbols starting from shift level *level*.

-mono Generate black-and-white image of keyboard (default).

-n *num* Print *num* copies.

-nkg *num*

Print the symbols in *num* keyboard groups.

-npk *num*

Number of keyboard images to print on each page; for EPS files, this specifies the total number of keyboard images to print.

-o *file* Write output to *file*.

-R*directory*

Use *directory* as the root directory; all path names are interpreted relative to *directory*.

-pict *which*

Controls use of pictographs instead of keysym names where available. *which* can be any of *all*, *none*, or *common*(default).

-synch Forces synchronization for X requests.

-version Print out the program version and exit.

-w *level* Sets warning level (0 for no warning, 10 for all warnings).

SEE ALSO

X(7), xkbcomp(1)

COPYRIGHT

Copyright 1995, Silicon Graphics Computer Systems Copyright 1995, 1998 The Open Group
See X(7) for a full statement of rights and permissions.

AUTHOR

Erik Fortune, Silicon Graphics