NAME

git-instaweb - Instantly browse your working repository in gitweb

SYNOPSIS

DESCRIPTION

A simple script to set up **gitweb** and a web server for browsing the local repository.

OPTIONS

```
-l, --local
```

Only bind the web server to the local IP (127.0.0.1).

-d, --httpd

The HTTP daemon command—line that will be executed. Command—line options may be specified here, and the configuration file will be added at the end of the command—line. Currently apache2, lighttpd, mongoose, plackup and webrick are supported. (Default: lighttpd)

-m, --module-path

The module path (only needed if httpd is Apache). (Default: /usr/lib/apache2/modules)

-p, --port

The port number to bind the httpd to. (Default: 1234)

-b, --browser

The web browser that should be used to view the gitweb page. This will be passed to the *git* web--browse helper script along with the URL of the gitweb instance. See **git-web--browse**(1) for more information about this. If the script fails, the URL will be printed to stdout.

start, --start

Start the httpd instance and exit. Regenerate configuration files as necessary for spawning a new instance.

```
stop, --stop
```

Stop the httpd instance and exit. This does not generate any of the configuration files for spawning a new instance, nor does it close the browser.

```
restart, --restart
```

Restart the httpd instance and exit. Regenerate configuration files as necessary for spawning a new instance.

CONFIGURATION

You may specify configuration in your .git/config

```
[instaweb]

local = true

httpd = apache2 -f

port = 4321

browser = konqueror

modulePath = /usr/lib/apache2/modules
```

If the configuration variable **instaweb.browser** is not set, **web.browser** will be used instead if it is defined. See **git-web--browse**(1) for more information about this.

SEE ALSO

gitweb(1)

GIT

Part of the **git**(1) suite