

NAME

import-bug-from-debian – Import bugs from Debian’s BTS, and file them against Ubuntu in LP.

SYNOPSIS

import-bug-from-debian [*options*] *bug*...

import-bug-from-debian -h

DESCRIPTION

import-bug-from-debian clones bugs from Debian’s BTS into Launchpad. Each *bug* listed on the command line has its initial report re-filed against the same source package in Ubuntu. The Ubuntu bug is linked back to its Debian counterpart.

Each *bug* may be provided either as a bug number or URL.

OPTIONS

-b, --browserless

Don’t open the bug in a browser at the end.

-h, --help

Display a help message and exit.

-l INSTANCE, --linstance=INSTANCE

Use the specified instance of Launchpad (e.g. "staging"), instead of the default of "production".

-p PACKAGE, --package=PACKAGE

Launchpad package to file bug against, if not the same source package name as Debian. Useful for importing removal bugs filed against **ftp.debian.org**.

--no-conf

Do not read any configuration files, or configuration from environment variables.

ENVIRONMENT

All of the **CONFIGURATION VARIABLES** below are also supported as environment variables. Variables in the environment take precedence to those in configuration files.

CONFIGURATION VARIABLES

The following variables can be set in the environment or in **ubuntu-dev-tools(5)** configuration files. In each case, the script-specific variable takes precedence over the package-wide variable.

IMPORT_BUG_FROM_DEBIAN_LPINSTANCE, UBUNTUTOOLS_LPINSTANCE

The default value for **--linstance**.

SEE ALSO

ubuntu-dev-tools(5)

AUTHORS

import-bug-from-debian was written by James Westby <james.westby@ubuntu.com>, and this manual page was written by Stefano Rivera <stefanor@ubuntu.com>.

Both are released under the terms of the GNU General Public License, version 2.