

NAME

jinfo – Generates configuration information. This command is experimental and unsupported.

SYNOPSIS

jinfo [*option*] *pid*

jinfo [*option*] *executable core*

jinfo [*option*] [*server-id*] *remote-hostname-or-IP*

option The command-line options. See Options.

pid The process ID for which the configuration information is to be printed. The process must be a Java process. To get a list of Java processes running on a machine, use the **jps(1)** command.

executable

The Java executable from which the core dump was produced.

core The core file for which the configuration information is to be printed.

remote-hostname-or-IP

The remote debug server **hostname** or **IP** address. See **jsadebugd(1)**.

server-id

An optional unique ID to use when multiple debug servers are running on the same remote host.

DESCRIPTION

The **jinfo** command prints Java configuration information for a specified Java process or core file or a remote debug server. The configuration information includes Java system properties and Java Virtual Machine (JVM) command-line flags. If the specified process is running on a 64-bit JVM, then you might need to specify the **-J-d64** option, for example: **jinfo-J-d64 -sysprops pid**.

This utility is unsupported and might not be available in future releases of the JDK. In Windows Systems where **dbgeng.dll** is not present, Debugging Tools For Windows must be installed to have these tools working. The **PATH** environment variable should contain the location of the **jvm.dll** that is used by the target process or the location from which the crash dump file was produced. For example, **set PATH=%JDK_HOME%\jre\bin\client;%PATH%** .

OPTIONS

no-option

Prints both command-line flags and system property name-value pairs.

-flag *name*

Prints the name and value of the specified command-line flag.

-flag [+|-]*name*

enables or disables the specified Boolean command-line flag.

-flag *name*=*value*

Sets the specified command-line flag to the specified value.

-flags

Prints command-line flags passed to the JVM.

-sysprops

Prints Java system properties as name-value pairs.

-h

Prints a help message.

-help

Prints a help message.

SEE ALSO

- [jps\(1\)](#)
- [jsadebugd\(1\)](#)

