

Quicksort

Shusen Wang

Quicksort: 3 Steps

1. Selecting a pivot.
2. Partition.
3. Recursion.

Step 1: Selecting Pivot

Step 1: Selecting Pivot

8	1	4	9	0	6	5	2	7	3
---	---	---	---	---	---	---	---	---	---

- Select one element from the array as the pivot.
- The pivot should be close to the median.

Step 1: Selecting Pivot


8	1	4	9	0	6	5	2	7	3
left					center				right

Pick it as pivot!

- Select one element from the array as the pivot.
- The pivot should be close to the median. (Why?)
- Heuristic:


`pivot = median(left, center, right)`

Step 1: Selecting Pivot



- Select one element from the array as the pivot.
- The pivot should be close to the median. (Why?)
- Heuristic:
$$\text{pivot} = \text{median}(\text{left}, \text{center}, \text{right})$$
- Put the pivot at the end.

Step 1: Selecting Pivot



- Select one element from the array as the pivot.
- The pivot should be close to the median. (Why?)
- Heuristic:
$$\text{pivot} = \text{median}(\text{left}, \text{center}, \text{right})$$
- Put the pivot at the end.


Step 2: Partition

Step 2: Partition


8	1	4	9	0	3	5	2	7	6
---	---	---	---	---	---	---	---	---	---

- Partition the first $n - 1$ elements to 2 groups.
- Group 1: $\{x \mid x \leq 6\}$.
- Group 2: $\{x \mid x \geq 6\}$.


Step 2: Partition




Step 2: Partition




Step 2: Partition



Step 2: Partition



Step 2: Partition



Step 2: Partition

2	1	4	9	0	3	5	8	7	6
---	---	---	---	---	---	---	---	---	---

Greater than 6?

No!

Step 2: Partition

2	1	4	9	0	3	5	8	7	6
---	---	---	---	---	---	---	---	---	---

Greater than 6?

No!


Step 2: Partition

2	1	4	9	0	3	5	8	7	6
---	---	---	---	---	---	---	---	---	---


Greater than 6?

Yes!


Step 2: Partition



Step 2: Partition



Step 2: Partition



Step 2: Partition

2	1	4	5	0	3	9	8	7	6
---	---	---	---	---	---	---	---	---	---



Greater than 6?

No!

Step 2: Partition

2	1	4	5	0	3	9	8	7	6
---	---	---	---	---	---	---	---	---	---

Greater than 6?

No!


Step 2: Partition

2	1	4	5	0	3	9	8	7	6
---	---	---	---	---	---	---	---	---	---



Stop when the two pointers are equal!

Step 2: Partition



Step 2: Partition

2	1	4	5	0	3	6	8	7	9
---	---	---	---	---	---	---	---	---	---

↑
pivot

Step 2: Partition

2	1	4	5	0	3	6	8	7	9
---	---	---	---	---	---	---	---	---	---

Group 1: $\{x \mid x \leq 6\}$.


Group 2: $\{x \mid x \geq 6\}$.

```
int partition(int arr[], int left, int right) {  
    int ptr1 = left;  
    int ptr2 = right-1;  
    int pivot = arr[right];  
    while (true) {  
        while (arr[ptr1] < pivot) ptr1++;  
        while (ptr2 > 0 && arr[ptr2] > pivot) ptr2--;  
        if (ptr1 < ptr2)  
            swap(arr, ptr1, ptr2);  
        else  
            break;  
    }  
    return ptr1;  
}
```


```

int partition(int arr[], int left, int right) {
    int ptr1 = left;
    int ptr2 = right-1;
    int pivot = arr[right];
    while (true) {
        while (arr[ptr1] < pivot) ptr1++;
        while (ptr2 > 0 && arr[ptr2] > pivot) ptr2--;
        if (ptr1 < ptr2)
            swap(arr, ptr1, ptr2);
        else
            break;
    }
    return ptr1;
}


```




```
int partition(int arr[], int left, int right) {  
    int ptr1 = left;  
    int ptr2 = right-1;  
    ➡ int pivot = arr[right];  
    while (true) {  
        while (arr[ptr1] < pivot) ptr1++;  
        while (ptr2 > 0 && arr[ptr2] > pivot) ptr2--;  
        if (ptr1 < ptr2)  
            swap(arr, ptr1, ptr2);  
        break;  
    }  
    return ptr1;  
}
```




```
int partition(int arr[], int left, int right) {  
    int ptr1 = left;  
    int ptr2 = right-1;  
    int pivot = arr[right];  
    while (true) {  
        ➡ while (arr[ptr1] < pivot) ptr1++;  
        ➡ while (ptr2 > 0 && arr[ptr2] > pivot) ptr2--;  
        if (ptr1 < ptr2)  
            swap(arr, ptr1, ptr2);  
        else  
            break;  
    }  
    return ptr1;  
}
```

```
int partition(int arr[], int left, int right) {  
    int ptr1 = left;  
    int ptr2 = right-1;  
    int pivot = arr[right];  
    while (true) {  
        while (arr[ptr1] < pivot) ptr1++;  
        while (ptr2 > 0 && arr[ptr2] > pivot) ptr2--;  
         if (ptr1 < ptr2)  
            swap(arr, ptr1, ptr2);  
        else  
            break;  
    }  
    return ptr1;  
}
```

```
int partition(int arr[], int left, int right) {  
    int ptr1 = left;  
    int ptr2 = right-1;  
    int pivot = arr[right];  
    while (true) {  
        while (arr[ptr1] < pivot) ptr1++;  
        while (ptr2 > 0 && arr[ptr2] > pivot) ptr2--;  
        if (ptr1 < ptr2)  
            swap(arr, ptr1, ptr2);  
         else  
            break;  
    }  
    return ptr1;  
}
```



```
int partition(int arr[], int left, int right) {  
    int ptr1 = left;  
    int ptr2 = right-1;  
    int pivot = arr[right];  
    while (true) {  
        while (arr[ptr1] < pivot) ptr1++;  
        while (ptr2 > 0 && arr[ptr2] > pivot) ptr2--;  
        if (ptr1 < ptr2)  
            swap(arr, ptr1, ptr2);  
        else  
            break;  
    }  
     return ptr1;  
}
```

Step 3: Recursion

Step 3: Recursion

2	1	4	5	0	3	6	8	7	9
---	---	---	---	---	---	---	---	---	---

Group 1: $\{x \mid x \leq 6\}$.

Group 2: $\{x \mid x \geq 6\}$.

Step 3: Recursion

2	1	4	5	0	3	6	8	7	9
---	---	---	---	---	---	---	---	---	---

Group 1: $\{x \mid x \leq 6\}$.

Group 2: $\{x \mid x \geq 6\}$.

- **Recursion:**

- Quicksort(Group 1).
- Quicksort(Group 2).

Step 3: Recursion

2	1	4	5	0	3	6	8	7	9
---	---	---	---	---	---	---	---	---	---

Group 1: $\{x \mid x \leq 6\}$.

Group 2: $\{x \mid x \geq 6\}$.

- **Recursion:**

- Quicksort(Group 1).
- Quicksort(Group 2).

- **Cut-Off:**

- If array is small (e.g., $n < 10$), Quicksort is not quick.
- In this case, use insertion sort instead.

```
void quickSort(int arr[], int left, int right) {  
    if (left+10 > right) { // for short array  
        insertsort(arr, left, right);  
    }  
    else { // for long array  
        int p = selectpivot(arr, left, right); // pivot position  
        swap(arr, p, right-1); //put pivot in the end  
        int i = partition(arr, left, right);  
        swap(arr, i, right-1); // restore pivot  
        // recursively sort the two sub-arrays  
        quicksort(arr, left, i - 1);  
        quicksort(arr, i + 1, right);  
    }  
}
```



```
void quickSort(int arr[], int left, int right) {  
    if (left+10 > right) { // for short array  
        insertsort(arr, left, right);  
    }  
    else { // for long array  
        int p = selectpivot(arr, left, right); // pivot position  
        swap(arr, p, right-1); //put pivot in the end  
        int i = partition(arr, left, right);  
        swap(arr, i, right-1); // restore pivot  
        // recursively sort the two sub-arrays  
        quicksort(arr, left, i - 1);  
        quicksort(arr, i + 1, right);  
    }  
}
```

```
void quickSort(int arr[], int left, int right) {  
    if (left+10 > right) { // for short array  
        insertsort(arr, left, right);  
    }  
    else { // for long array  
        int p = selectpivot(arr, left, right); // pivot position  
        swap(arr, p, right-1); //put pivot in the end  
        int i = partition(arr, left, right);  
        swap(arr, i, right-1); // restore pivot  
        // recursively sort the two sub-arrays  
        quicksort(arr, left, i - 1);  
        quicksort(arr, i + 1, right);  
    }  
}
```



```
void quickSort(int arr[], int left, int right) {  
    if (left+10 > right) { // for short array  
        insertsort(arr, left, right);  
    }  
    else { // for long array  
        ➡ int p = selectpivot(arr, left, right); // pivot position  
        ➡ swap(arr, p, right-1); // put pivot in the end  
        int i = partition(arr, left, right);  
        swap(arr, i, right-1); // restore pivot  
        // recursively sort the two sub-arrays  
        quicksort(arr, left, i - 1);  
        quicksort(arr, i + 1, right);  
    }  
}
```

```
void quickSort(int arr[], int left, int right) {  
    if (left+10 > right) { // for short array  
        insertsort(arr, left, right);  
    }  
    else { // for long array  
        int p = selectpivot(arr, left, right); // pivot position  
        swap(arr, p, right-1); //put pivot in the end  
        ➡ int i = partition(arr, left, right);  
        ➡ swap(arr, i, right-1); // restore pivot  
        // recursively sort the two sub-arrays  
        quicksort(arr, left, i - 1);  
        quicksort(arr, i + 1, right);  
    }  
}
```

```
void quickSort(int arr[], int left, int right) {  
    if (left+10 > right) { // for short array  
        insertsort(arr, left, right);  
    }  
    else { // for long array  
        int p = selectpivot(arr, left, right); // pivot position  
        swap(arr, p, right-1); //put pivot in the end  
        int i = partition(arr, left, right);  
        swap(arr, i, right-1); // restore pivot  
        // recursively sort the two sub-arrays  
         quicksort(arr, left, i - 1);  
         quicksort(arr, i + 1, right);  
    }  
}
```

Time Complexity

Best-Case Time Complexity

Suppose pivot is the median (best-case).


- $T(n)$: Time complexity of sorting size- n array.
- Sizes of the two subarrays are both $\frac{n}{2}$.
- Time complexity:

$$T(n) = 2 T(n/2) + c n.$$

- $\rightarrow T(n) = O(n \log n)$.

Worst-Case Time Complexity


Pivot can be the second largest (worst-case).



- Group 1 has $n - 2$ elements.
- Group 2 has only one element.

Worst-Case Time Complexity

Pivot can be the second largest (worst-case).



- Time complexity:

$$T(n) = T(n - 2) + T(1) + cn.$$

- $\rightarrow T(n) = O(n^2)$.

Time Complexity: Comparisons

- **Best case:**

- Sizes of the two subarrays are both $n/2$.
- Time complexity: $O(n \log n)$.

- **Worst case:**

- Size of Group 1: $n - 2$
- Size of Group 2: 1.
- Time complexity: $O(n^2)$.

This is why we hope **pivot** is close to the **median**!

Time Complexity: Comparisons

- **Average case:**

- Assume the data is randomly shuffled.
- All the elements are equally likely to be the pivot.
- Expected time complexity: $O(n \log n)$.
- Algorithm is non-random; data is random.

Time Complexity: Comparisons

- **Average case:**

- Assume the data is randomly shuffled.
- All the elements are equally likely to be the pivot.
- Expected time complexity: $O(n \log n)$.
- Algorithm is non-random; data is random.

- **Random pivot:**

- The position of the pivot is random.
- Expected time complexity: $O(n \log n)$.
- Algorithm is random; data is non-random.

Thank You!

Best-Case Time Complexity

Suppose pivot is the median (best-case).

$$\bullet \frac{T(n)}{n} = \frac{T(n/2)}{n/2} + c.$$

$$\bullet \frac{T(n/2)}{n/2} = \frac{T(n/4)}{n/4} + c.$$

$$\bullet \frac{T(n/4)}{n/4} = \frac{T(n/8)}{n/8} + c.$$

\vdots

$$\bullet \frac{T(2)}{2} = \frac{T(1)}{1} + c.$$

$$\frac{T(n)}{n} = \frac{T(n/2)}{n/2} + c$$

$$= \frac{T(n/4)}{n/4} + 2c$$

$$= \frac{T(n/8)}{n/8} + 3c$$

$$= \dots$$

$$= \frac{T(1)}{1} + c \log_2 n$$

Worst-Case Time Complexity

Pivot can be the second largest (worst-case).

- $T(n) = T(n - 2) + cn.$
- $T(n - 2) = T(n - 4) + c(n - 2).$
- $T(n - 4) = T(n - 6) + c(n - 4).$
- \vdots
- $T(4) = T(2) + 4c.$
- $T(2) = 2c.$
- Thus $T(n) = c \cdot [2c + 4c + \cdots + (n - 4) + (n - 2) + n]$
 $= O(n^2)$