NATIONAL HYDRO-AX®

Owatonna, Minnesota 55060

300 SERIES

MODEL 311
PRIME MOVER

OPTIONAL attachments

SOLD AND SERVICED BY

TIMBER-MAT
S.A. au Capital de 2.495.000 F
R.C. 70 B 42 SIREN 697080422 00010
60700 FLEURINES
PONT-Ste-MAXENCE
Tél. : 454.10.22 (6 lignes)

NATIONAL HYDRO-AX, INC.
P.O. BOX 568 • OWATONNA, MINNESOTA 55060 • 507-451-8654

/79

SPECIFICATIONS

300 SERIES

MODEL 311 PRIME MOVER / OPTIONAL attachments

STANDARD EQUIPMENT

All-wheel drive, Hydrostatic Propel transmission, Transfer case, Orbit powered articulated steering, Diesel engine, Dry type air cleaner, Electric starting, 42 amp alternator, Hand throttle, Double pump drive with manual clutch disconnect, Exhaust muffler, Gauges; ammeter, engine oil pressure, water temperature, hydrostatic oil temperature. Hydrostatic oil cooler with fan. Roll over protective structure with roof, Chromed cylinder shafts, Adjustable upholstered seat with belt. Hydraulic pump and valve to supply oil to attachment. Windshield wiper, spark arrestor. Impact resistant lexon windows, hourmeter.

WEIGHT (LESS ATTACHMENTS WITH 18.4 TIRES)

Total . . . . . 13,250 Lbs. (6010 kg)
On front axle . . . . . 3,250 (1475 kg)
On rear axle . . . . . 10,000 Lbs. (4536 kg)

DIMENSIONS (LESS ATTACHMENTS WITH 18.4 TIRES)

Height overall . . . . . 8′ - 10″ (2692 mm)
Width overall . . . . . 8′ - 0″ (2438 mm)
Length overall . . . . . 17′ - 2″ (5232 mm)
Wheel base . . . . . 8′ - 0″ (2438 mm)
Ground clearance . . . . . 17″ (432 mm)
Turning radius (outside Tire) . . . . . 15′ - 0″ (4572 mm)

ENGINE

Make . . . . . GMC diesel
Model . . . . . 3-53 N
Horsepower . . . . . 91 intermittant
R.P.M.(High idle) 2800
Bore and stroke . . . . . 3.875 x 4.50″ (98 x 114 mm)
Number of cylinders 3
Electrical system . . . . . 12 V
Fuel tank capacity . . . . . 40 Gal. (151 l)

POWER TRAIN

Hydrostatic transmission . . . . Variable displacement pump
Variable displacement motor
Transfer case . . . . . Fixed ratio

AXLES

Planetary . . . . . NO-SPIN differential in front and rear axles

WHEEL AND TIRES (INTERCHANGEABLE)

Wheels . . . . . 16 x 26 with reinforced flanges
Tires . . . . . 18.4 x 26 - 10 ply logger type
(OPTIONAL)
Tires . . . . . 23.1 x 26 - 10 PR Logger type

TRAVEL SPEEDS - FWD. & REV. (Approx.)

Infinetly variable . . . . . 0 - 6 mph. (9.7 km/h)
(with 18.4 Tires)

BRAKES - SERVICE

Type . . . . . hydraulic disc
Size disc . . . . . 14″ Dia (355.6 mm)
Location . . . . . Rear drive shaft at transfer case

BRAKES - EMERGENCY AND PARKING

Type . . . . . Mechanical expanding shoe
Location . . . . . front drive shaft at transfer case

STEERING

Articulate . . . . . Orbital power on demand (2250 PSI)
(158 kg/cm²)

HYDROSTATIC PUMP

Propel transmission . . . . . Variable displacement pump
40 GPM (151 l) at full displacement
6000 PSI (422 kg/cm²) relief setting

HYDRAULIC TANDEM GEAR PUMP

Auxiliary Section 25 GPM (94 l) - 2250 PSI (158 kg/cm²)
Attachment Section 53 GPM (201 l) - 2500 PSI (176kg/cm²)

HYDRAULIC CYLINDERS	BORE	STROKE
Lift Cylinders (2)	3.00″ (76 mm)	24″ (610 mm)
Steering Cylinders (2)	3.00″ (76 mm)	12″ (305 mm)
Tilt Cylinders (2)	3.00″ (76 mm)	31½ (800 mm)

WINCH (OPTIONAL)

Type . . . . . Hydraulic
F.P.M. 25
Line pull . . . . . 15,000 Lbs. (6804 kg) Bare Drum
Cable . . . . . 9/16 (14.3 mm) x 200′ (61 m)Max.

OPTIONAL EQUIPMENT

Cab enclosure, Defroster, Cab sound insulation, Light package, Directional signals, Tachometer with Hourmeter, Heater, Back-up alarm, Horn, Quick Tach Frame, Fire extinguisher, First aid kit. Heavy duty double caliper brake system, Winch and fairlead, wire mesh cab enclosure, machine protection package.

OPTIONAL ATTACHMENTS

CUTTER HEAD

Width overall . . . . . 7′ - 8″ (2337 mm)
Blades . . . . . Free swinging, mounted to rotate
Blade RPM . . . . . control in cab (1100 max rpm)
Drive . . . . . fixed displacement pump
fixed displacement motor

DEELIMBER HEAD

Overall Width . . . . . 8′ - 0″ (2438 mm)
Drum Length . . . . . 6′ - 0″ (1829 mm)
Drum RPM 350
Effective flail Dia (Chain Tip To Tip) . . . . . 5′ - 6″ (1676 mm)
Effective Chain Spacing . . . . . 8″ (203 mm)
Alloy Delimbing Chains 8
Drive System . . . . . fixed displacement pump
fixed displacement motor

FELLERBUNCHER HEAD . . . . . (max. size) 15″ (381 mm)

DIRECTIONAL SHEAR . . . . . (max. size) 30″ (762 mm)

National Hydro-Ax reserves the right to change specifications without notice to follow its policy of constantly striving to manufacture a better product.