

Binder-1

1. Lifetime of Binder Objects The use of multiple reference counters and object dependencies introduces complex object lifetime management logic in Binder. When doing vulnerability research, it is helpful to understand the lifetime of every object in Binder as many past vulnerabilities have exploited flaws hidden within them. To highlight the complexity, let's look at some properties of the binder_node object: Has 4 different reference counters Can be in multiple linked lists owned by other objects,	
such as a binder_proc and a workqueue One or more associated binder_ref objects hold a pointer to it One or more associated binder_buffer objects hold a pointer to it	
These properties also result in multiple code paths with different conditions t	
3	
4. still confusing	9
5. who all create these objects and when these created	
6. why binder maintain these doubly linkedlist	3
object represents a client in Binder. It is the first object to be allocated when a process opens the Binder device node. Note: In contrast to the userspace Binder, a process	
can act as a server or a client of a service. Throughout this article, we will generally refer to the process that interacts with the Binder device as the client and the Binder device itself as the server. It contains the following fields that determine its lifetime: threads is the root node of a red-black tree that contains all binder_threads it owns. is dead determines whether the client is dead. t	_
8. Binder Concurrency Model Binder is designed to facilitate remote procedure calls (RPC) between clients. A client initiates communication by sending commands	5
prefixed with BC_*. These commands are accompanied by relevant data specific to the command. Then, the client waits for a response prefixed with BR_* from Binder. In the beginning, a single-threaded client initiates a RPC by send a BC_TRANSACTION command to Binder. Then, Binder forwards the command as a BR_TRANSACTION response to the recipient client. To return the RPC result, the recipient client sends a BC_REPLY command along with the result data back to Binder. Finally, Binder	
forwards it back to the client as a BR_REPLY response, completing the RPC process	
9	1
transaction until it has replied to the current one	3
11	
12. Multithreaded Client Binder has support for multithreaded clients, enabling them to simultaneously process multiple RPCs in separate threads. Therefore, Binder maintains a list of threads (binder_thread) owned by a client (binder_proc). When a client process spawns a new thread, the child thread inherits the previously opened Binder file descriptor. This file descriptor is associated with the same client binder_proc as the parent thread. int binder_fd = open("/dev/binder", O_RDWR O_CLOEXEC); pid_t pid = fork(); // spawns a new thread if (pid == -1) { // fork failed return 1; } else if (pid > 0) { // child thread starts here ret = io	7
13	
14. Register as a Looper Before a child thread can retrieve an incoming transaction from the main workqueue, it must first register itself as a looper. This is achieved by sending the BC_ENTER_LOOPER or BC_REGISTER_LOOPER command to Binder upon spawning. Subsequently, when the child thread performs a read operation (BINDER_WRITE_READ ioctl), Binder retrieves the next transaction from the main workqueue and passes it to the child thread for processing. The overall multithreaded client is not required to respond to every transaction in a FIFO order. However, each thread must still adhere to the FIFO order when replying to its own workqueue32	2
15	4
16. A client thread can invoke the BINDER_THREAD_EXIT ioctl to exit early. Then, Binder cleans up all pending work in the thread's workqueue and notifies the client that initiates the transaction with the BR_DEAD_REPLY response	
18. Request a New Looper When Binder cannot find a thread with an empty workqueue, it sends a BR_SPAWN_LOOPER response to the latest thread that is performing a read operation. This response requests the client to spawn a new thread to handle more future workloads. Spawning a new thread is not mandatory for the client.	
However, if it does, the new thread must register itself as a looper (BC_REGISTER_LOOPER) after spawn	0
Binder will not request any additional thread (BR_SPAWN_LOOPER)	2
20. Asynchronous Transaction Binder supports one-way or asynchronous transactions, which does not require the recipient client to reply to. To initiate an asynchronous transaction, the sender sets the TF_ONE_WAY flag in the binder_transaction->flags field. The recipient client will receive regular transactions and asynchronous transactions together in a FIFO order. However, Binder manages asynchronous transactions by queuing them in a dedicated asynchronous workqueue associated with each port (binder_node->async_todo). To read the next asynchronous transaction from a port's asynchronous workqueue (binder_node->async_todo), the receiving client	
must first free the current one assigned in it using the BC_FREE_BUFFER command. After all, asynchron	3
represented as a doubly linked list with only the head pointer (struct list_head) being stored. There are three types of workqueue in Binder: Main client workqueue (binder_proc->todo): Stores all work items assigned to a client Individual client thread workqueue (binder_thread->todo): Stores work items assigned to a specific client	
thread. Individual binder_node asynchronous workqueue (binder_node->async_todo): Stores only a list of work items that relate to asynchronous transactions (BINDER_WORK_TRANSACTION). Each work item is defined by a struct binder_work that can be added to a workqueue. The	5
22. Category Container Work Type Enum Transaction binder_transaction BINDER_WORK_TRANSACTION Transaction status update None BINDER_WORK_TRANSACTION_COMPLETE BINDER_WORK_TRANSACTION_PENDING BINDER_WORK_TRANSACTION_ONEWAY_SPAM_SUSPECT Binder node update	ر
binder_node BINDER_WORK_NODE Death notifications binder_ref_death BINDER_WORK_DEAD_BINDER_BINDER_WORK_DEAD_BINDER_AND_CLEAR	
BINDER_WORK_CLEAR_DEATH_NOTIFICATION this is the table Error binder_error BINDER_WORK_RETURN_ERROR	8
23. Transaction In the Binder Concurrency Model section, we discussed how Binder distributes incoming transactions as work items across multiple threads within a client process. Every transaction (binder_transaction) is processed and queued in either the main client workqueue (binder_proc->todo) or individual thread work queue	
(binder_thread->todo). New transactions are initially assigned as a BINDER_WORK_TRANSACTION work item to the main recipient client workqueue (binder_proc->todo). Upon reading, Binder processes the work item and sends the BR_TRANSACTION response back to userspace along with the transaction data. On the other hand, reply	
transactions are specifically assigned to the workqueue of the client thread (binder_thread->todo) tha	9
24. Binder Node The BINDER_WORK_NODE work item provides updates to the client about the presence or absence of strong or weak references of a binder_node. Depending on who initiated the operation, Binder assigns the binder_node->work as a BINDER_WORK_NODE work item to either the main client workqueue or a client	
thread workqueue. For example, if a client sends a BINDER_TYPE_BINDER to another client, which results in the creation of a binder_ref and an increase in the strong reference of the binder_node, Binder then assigns the work item to the workqueue of the client thread that sends it. Meanwhile, if another client acquires a strong	
reference on its binder_ref, leading to an increase in the strong reference of the binder_node owned by anothe	1
25. Binder Buffer Allocator Initialization Binder implements a memory allocator to store incoming transaction data, which we will call the binder buffer allocator. Every client binder_proc owns a binder buffer allocator binder_alloc which allocates memory for incoming transaction data. During initialization, a client must create a memory map for the Binder device file descriptor as follows: #define BINDER_VM_SIZE 4 * 1024 * 1024 int binder_fd = open("/dev/binder", O_RDWR O_CLOEXEC); void *map =	
mmap(nullptr, BINDER_VM_SIZE, PROT_READ, MAP_PRIVATE, binder_fd, 0); The mmap syscall will call binder_mmap to reserve a virtual memory area and map it to the userspace. Binder defers the allocation of physical backing pages to store incoming transa	4



26. confusing explain in simple words	56
corruptions and even code execution in the kernel as demonstrated in the CVE-2020-0041 and CVE-2023-20938 writeups. As a result, Binder only allows users to create a	
read-only memory map (PROT_READ) and prevents them from modifying its access permission later	5/
allocator starts with a single binder_buffer, which takes up the whole buffer space and is labeled as unused	
allocates a binder_buffer object to own a chunk of memory in the memory map and assign it to the binder_transaction	60
allocates a binder_buffer object to own a chunk of memory in the memory map and assign it to the binder_transaction	61
31. confused with the offset here explain in simple	
copies the data into it. The target client receives the transaction and reads the data from the memory map	
33. explain the image in detail.	. 67
34. Free a Buffer To free a transaction and its data, a client sends a BC_FREE_BUFFER message with the start address of the transaction data. Binder then frees the	
binder_transaction and sets the free field of the binder_buffer. If adjacent memory is also freed, the binder buffer allocator merges the two binder_buffer into one	. 69
annotate the interface with @SensitiveData to explicitly set the TF_CLEAR_BUF flag in all outgoing transactions. This prevents sensitive data in the transaction from remaining in memory after free. For example, the IKeyMintOperation.aidl AIDL interface used by Keymint i	71
36. Binder Transaction Stacks As we discussed in Binder Concurrency Model, a single-threaded client cannot retrieve the next incoming transaction until it has responded to the current one. On the caller side, a single-threaded client cannot initiate a new RPC (BC_TRANSACTION) until it receives a reply (BR_REPLY) to the previou	
RPC. To maintain these orders, Binder tracks every incoming and outgoing transaction between two different threads on a transaction stack. The purpose of transaction	
stacks is different from the Binder Workqueues whose purpose is to support concurrency among multiple threads in a client. Note: Every transaction is only associated with one sender thread and one receiver thread during its lifetime, regardless of whether t	72
37. A Chain Request with Multiple Clients It is common to have multiple clients working with each other to serve a RPC request. The diagram below shows an example of	
a RPC originating from A that involves multiple single-threaded clients	75
38. It is a chain of transactions in the following order: A -> B -> C -> D -> B Binder allows a client to handle multiple pending transactions at the same time. For example, client B has two pending transactions at one point, one coming from A and another coming from D. However, the client can only respond with BR_REPLY to those	
pending transactions in the last-in-first-out (LIFO) order. In addition, when one of the clients in the chain dies, Binder ensures proper error handling by delivering errors back to every involved client in the correct order	
39. Two Stack Layouts Binder puts every transaction on two different stacks, which we will call the chain transaction stack and the thread transaction stack. Let's have an	
overview of the functions each stack serves: Chain transaction stack The order of transactions of a chain request. Binder traverses it to clean up the chain request when one of the clients exits early. Thread transaction stack The order of transactions that is sent or received by a client Binder traverses it to clean up and release transactions, which a client participated in before exit. Binder implements these two stacks as two linked lists with the following fields in binder_transaction: struct	
binder_transaction { struct binder_transaction *from_parent; struct bi	79
40. Chain Transaction Stack'from_parent'Tracks **caller-to-callee** path across clientsThread Transaction Stack'to_parent'Tracks **per-thread transactions**Reply Cleanup'to_parent'Pop when **replying**explain in simple words	
41. to_parentconfusing	
42. Chain Transaction Stack The chain transaction stack tracks the order of transactions in a chain, which originates from the first request. Let's reuse the example abovin volving four transactions among A, B, C and D. Before B responds D, the chain transaction stack will look as follows:	
43. Binder can traverse the chain transaction stack, by following the from_parent field of any transaction, to find the previous transaction and the first transaction in the	
chain. Suppose client B exits before responding to the last transaction sent by D. During cleanup, Binder traverses the chain transaction stack starting from the top transaction on B's transaction_stack to look for its previous client in the chain. Then, it sends a BR_DEAD_REPLY to notify the client that there is a failed reply. In our case, Binder sends BR_DEAD_REPLY to D, which is the previous client before B in the chain. A -> B -> C -> D -> B Binder calls binder send failed reply to traverse the chain	,
transaction stack and sends an error_code (e.g BR_DEAD_REPLY) to t	
thread transaction stack of each client will look as follows:	90
45. Binder utilizes the from parent and to parent fields along with from and to traverse the thread transaction stack of each client thread. By checking if from or to thread points to the target client thread, it follows either the from parent or to parent field to the next transaction in the stack. For example, starting from B's	1
transaction_stack, Binder checks whether the from or to_thread points to B and follows either the from_parent or to_parent to the next transaction. The first transaction from the top has to_thread pointing to B, so Binder follows to_parent to the next transaction. The second transaction has from pointing to B, so Binder follows the	
from_parent to the next transaction. When a client thread exits, Binder must	
46. Still confusing	
you might have noticed based on the information provided above Binder kernel module is a very complex target for analysis. In order to fully understand semantics of the exposed Binder kernel API to the user-space code via ioctls one would need to study the implementation of libbinder – library which sits on top of the Binder kernel module and provides a higher-level Binder IPC interface to the Android Framework. The libbinder itself consists of multiple files written in C++ & Rust and might be	
challenging to comprehend for the audience with no prior knowledge in this area. Thu.	97





1. Lifetime of Binder Objects

The use of multiple reference counters and object dependencies introduces complex object lifetime management logic in Binder. When doing vulnerability research, it is helpful to understand the lifetime of every object in Binder as many past vulnerabilities have exploited flaws hidden within them.

To highlight the complexity, let's look at some properties of the binder_node object:

Has 4 different reference counters

Can be in multiple linked lists owned by other objects, such as a binder_proc and a workqueue

One or more associated binder_ref objects hold a pointer to it

One or more associated binder_buffer objects hold a pointer to it

These properties also result in multiple code paths with different conditions to free a binder_node.

Here is a simplified diagram to show dependencies between every data structure in Binder:

You're right — Binder's lifetime management is intricate, and understanding it is essential, especially when auditing for vulnerabilities. Let's break it down based on your mention of the binder node object and its relationships with other structures.

Core Concept: Reference Counting in Binder

The Binder kernel driver uses multiple reference counting mechanisms to track the ownership and lifetime of objects. This is important to:

- Avoid use-after-free
- Ensure memory is released when no longer needed
- · Prevent leaks from circular references

Let's start by examining the key structure: binder_node.

binder_node Overview

A binder_node represents a Binder object (an exported binder service or object) from a process. It can be either:

- A local node: represents an object in the current process.
- A remote node: used by other processes to refer to the local object.

ii binder_node Reference Counts

A binder_node typically maintains four different types of reference counters:

Ref Counter	Description	
internal_strong_refs	Count of strong refs from the local process.	
local_weak_refs	Weak refs (do not keep node alive) from the local process.	
ptr_refs	External references to this node, like from other processes (via binder_ref).	
tmp_refs	Temporary references during transactions or work queues to prevent premature freeing.	

ℰ Relationships

binder_ref

- A binder_ref is created in a remote process when it holds a reference to a binder_node in another process.
- Maintains its own strong/weak reference counts.
- Keeps the binder_node alive.
- When the last strong/weak ref is dropped, it may cause binder_node to be freed.

binder_proc



- Each process using Binder has a binder_proc.
- Holds references to all binder_node and binder_ref objects it knows about.
- Contains lists like nodes, refs_by_desc, etc.

binder_buffer

- Used during IPC transactions.
- Temporarily references binder_node if an object is passed over IPC.
- When the buffer is freed (after transaction completes), the tmp_refs to binder_node are decremented.

Workqueue

- binder_work objects (e.g. transactions, death notifications) may point to binder_node.
- Work items hold temporary references to nodes until they are processed.

Complexity in Freeing binder_node

A binder node can only be safely freed when:

- All binder_ref objects referencing it are gone.
- No binder_buffer points to it.
- It's removed from the binder_proc's list.
- It's not part of any pending work in the queue.
- All reference counters (strong, weak, tmp) drop to 0.

This results in multiple freeing code paths, which historically have led to:

- Use-after-free vulnerabilities when temp refs were mishandled.
- Double-free bugs from incorrect ownership assumptions.
- Leaks when a reference cycle wasn't broken properly.

📊 Simplified Binder Lifetime Dependency Diagram

Here's a textual representation (you can visualize or draw this later):

Tips for Vulnerability Research

When auditing Binder:

- Trace all code paths that affect the reference counts.
- Check for imbalanced inc/dec of refs (esp. tmp_refs).
- Look for missing checks before accessing freed binder_node.
- Inspect transaction and death notification flows often complex.

Would you like a visual diagram (SVG or image form) of the Binder object relationships? I can generate one.





2. explain all in simple words

Absolutely. Let's break everything down in very simple words so it's easy to understand, even if you're new to Binder or kernel development.

What is Binder?

Binder is how Android processes talk to each other (IPC = Inter-Process Communication). For example:

- App A wants to call a function in App B or a system service.
- Binder makes this happen safely and quickly.

🧱 Main Building Blocks

Here are the key parts (like Lego blocks) that Binder uses:

1. binder_node

- Think of this like a real object in memory (like a service or function that can be called).
- This lives in the server process (e.g., system service).
- Other apps can talk to it using a special ID.

2. binder_ref

- Think of this like a remote handle or shortcut.
- A client app doesn't hold the object directly it holds a reference to binder_node.
- It's like having someone's phone number but not the person themselves.

3. binder_proc

- Every app or process that uses Binder gets a binder_proc.
- It stores all the nodes, refs, and transactions related to that process.

4. binder_buffer

- Used to send and receive data (like function arguments).
- Think of this as a temporary message container.

5. workqueue / binder_work

- Like a to-do list inside the Binder driver.
- Contains work like "send this message" or "notify death".

🔁 Reference Counting (Important)

To manage memory safely, Binder counts how many people are using each object. This is called reference counting.

Let's take **binder_node** — it has 4 counters:

Ref Counter	In Simple Words	
strong ref	I'm using this object, don't delete it."	
weak ref	"I might use this object later, but it's okay to delete."	
ptr ref	"Someone else is holding a shortcut to this object."	
temp ref	"I need this object for a short time, like during a message."	

✓ When can a binder_node be deleted?

Only when:

- 1. No one is using it (strong + weak refs are 0).
- 2. No other process has a reference to it (ptr ref is 0).
- 3. It's not part of a transaction or buffer (temp ref is 0).
- 4. It's not in anyone's to-do list (workqueue).

Basically:

"Delete the object only when everyone forgets about it, and no work is left to do with it."

Why is this complex?

Because:

- Many different parts can hold the object at the same time.
- · References go up and down in many places.
- If you forget to increase or decrease the ref count at the right time:
 - It may get deleted too early (1 crash, use-after-free).
 - It may never be deleted (1 memory leak).

For Bug Hunting (Security Researchers):

Many Binder vulnerabilities happened because:

- The kernel **freed** the object while someone else was still using it.
- Or the kernel **didn't free** the object, causing memory leaks.
- Or it **freed it twice**, leading to kernel crashes or root exploits.

🔣 Summary Table

Object	What it is	Who owns or uses it?
binder_node	The actual object being called (service)	Owned by server process
binder_ref	A reference to that object	Held by client process
binder_proc	The Binder state for each app/process	Kernel-managed, one per process
binder_buffer	Message data for a transaction	Used temporarily during calls
binder_work	Pending tasks to do	Held by the kernel's work queue

Think of it Like a Library

- binder_node: The book in the library.
- binder_ref: A bookmark someone else uses to find the book.
- binder_proc: The library card system for each person.
- binder_buffer: The notepad you use while reading the book.
- workqueue: The library assistant's task list.

Let me know if you want a picture to help visualize this — I can generate one for you!



3. Dploaded image

Thanks for sharing the diagram! Let's walk through this step-by-step in simple words to understand what it shows.

🔁 Diagram Meaning

This is a Binder object lifetime/dependency diagram.

Each box is a data structure used by the **Binder kernel driver**, and each arrow means:

"This object holds a reference to that object"

(i.e., it points to it or depends on it).

🧱 Components Explained Simply

1. binder_ref

- This is a remote reference to a service.
- Lives in the **client** process.
- Points to a binder_node in the server.
- \rightarrow Points to \rightarrow binder_node

2. binder_node

- Represents a real Binder object (like a service).
- Lives in the server process.
- Can be shared across multiple clients via binder_ref.
- → Points to → binder_proc (the process that owns it)

3. binder_proc

- Represents a single **process** that's using Binder.
- Has lists of all nodes, refs, threads, etc.
- ightharpoonup Points to ightharpoonup binder_thread (threads doing Binder work)

4. binder_thread

- Represents a thread in a process that handles Binder messages.
- Gets work like transactions and replies.
- \rightarrow Points to \rightarrow binder_transaction

5. binder_transaction

- A single **Binder call** or message (like calling a function).
- Holds data and target information.
- \rightarrow **Points to** \rightarrow **binder_buffer** (for the actual data)

6. binder buffer

• Contains the data being sent (like function arguments or return values).

- Is temporary used during a call.
- → May also point back to → binder_node (if the message carries a Binder object)

Circular and Multiple References

- Notice how binder_proc, binder_ref, and binder_buffer can point back to earlier objects like binder_node.
- This is why reference counting is **complex** these objects can keep each other alive.

In Summary (Real-World Analogy)

Imagine this is a messaging system:

Structure	Analogy
binder_ref	A remote contact in your phone
binder_node	The actual person (service)
binder_proc	A person's phone
binder_thread	A person using the phone
binder_transaction	A single conversation/call
binder_buffer	The message content

📏 Why This Matters (Bug Hunting)

If a binder_node is still being used (like inside a buffer or ref), and it gets freed early:

- It can cause a **use-after-free** bug.
- Or if it's **never freed**, you get a **memory leak**.

That's why tracking these arrows (references) is critical for:

- Security researchers
- Kernel developers
- Android OEMs

Let me know if you want a color-coded version or explanation with memory layout!



4. still confusing

No worries — let's **simplify it even more** like a story with real-life characters. Forget technical terms for a moment.

零 Imagine a Company Office

Let's say:

- A company is Android OS.
- Different employees are Android apps and services.
- They talk to each other using messages (Binder IPC).

Now let's look at the characters in this diagram:

1. binder_proc = An Employee

This is a person (or app) working in the company. Every employee has:

- A list of people they know (binder_ref)
- A list of their work (binder thread)

-2. binder_ref = A Contact Card

Each employee keeps a contact card of someone they want to call.

This is a **reference** to someone else in the company.

It points to the **real person** (binder_node).

3. binder_node = The Real Person (Service)

This is the actual person (or service) in the company that other people are trying to call or use.

Example:

• Your contact card (binder_ref) points to John (binder_node), who works in IT.

4. binder_thread = The Employee's Brain

This is how the employee **processes work**.

Like a person's brain handling incoming calls or tasks.

5. binder_transaction = A Work Task or Message

This is a message or a task that says:

"Hey, call John in IT and ask him to reset your password."

This message is handled by the employee's brain (binder_thread).

6. binder_buffer = The Actual Message Content

This is the paper or email that carries the task details like:

"Please reset password for user123"

It's **temporary**, used only while the task is happening.

What the Arrows Mean

Each arrow in the diagram means:

"I know about this person" or "I depend on this thing"

Example:

- binder_ref → binder_node: The contact card points to John.
- $binder_transaction \rightarrow binder_buffer$: The task contains the message paper.
- $binder_buffer \rightarrow binder_node$: The message mentions John again.

💥 Why This Is Complicated

Because:

- Many people can know John (multiple binder_refs → binder_node)
- Messages might still mention John even if the sender is gone.
- If you delete John too early, but someone still has his name in a task → Boom! Crash (bug)

That's why Binder tracks who knows who, and when it's safe to remove or free someone.

Summary in One Line

Binder is like an office full of employees (apps), contact cards (refs), people (nodes), tasks (transactions), and memos (buffers) — and Android must manage when it's safe to throw things away without breaking anything.

Would you like me to redraw this diagram in that analogy (with people/icons) so it's visual too?



5. who all create these objects and when these created

Great question! Let's go one by one and explain **who creates each Binder object**, and **when** it gets created in the Android system — in **very simple terms**.

- f 1. binder_proc
- Created by: Binder driver (kernel)
- When: When any app or system service opens /dev/binder
 - As soon as a process (like an app or system service) wants to use Binder IPC, it opens /dev/binder or /dev/vndbinder.
 - The Binder driver creates a new binder_proc for this process.
- Think of it as the Binder profile for that process.
- 2. binder_ref
- Created by: Binder driver, on behalf of a client process
- When: When a client receives or uses a remote Binder object
 - A client process gets a reference to a remote object from the server.
 - The Binder driver creates a binder_ref in the client's binder_proc.
- Think of it as the contact card the client uses to talk to a service.
- **3.** binder_node
- Created by: Binder driver, on behalf of a server process
- When: When a server process registers an object to be shared
 - When a system service (like MediaServer) shares a Binder object (e.g. via BnInterface), the driver creates a binder_node.
 - This represents the **real object** that lives in the server process.
- Think of it as the actual service person others want to talk to.
- 4. binder_thread
- Created by: Binder driver, for the process's Binder thread
- When: When a thread in the process registers itself with Binder (via BC_ENTER_LOOPER or BC_REGISTER_LOOPER)
 - When a thread starts calling binder_poll/ioctl to wait for Binder messages, the driver creates a binder_thread.
- Think of it as the worker inside the process who processes Binder messages.
- **5.** binder transaction
- Created by: Binder driver
- **When: When a process sends a Binder call**
 - When a client makes a Binder call to a remote object, the Binder driver creates a binder_transaction to track the message.

Think of it as a message envelope that carries what to do and who it's for.

- 🦰 6. binder_buffer
- Created by: Binder driver
- When: As part of a binder_transaction
 - During a transaction, the actual data (arguments, reply, etc.) is stored in a buffer.
 - This buffer is placed in a shared memory pool in the **target process**.
- Think of it as the sheet of paper inside the envelope (holds message content).

Recap: Who Creates What and When?

Binder Object	Created by	When it's created
binder_proc	Kernel Binder	When process opens /dev/binder
binder_ref	Kernel Binder	When client gets reference to a remote object
binder_node	Kernel Binder	When server shares a Binder object
binder_thread	Kernel Binder	When a thread registers as a looper
binder_transaction	Kernel Binder	When a Binder call (transaction) is made
binder_buffer	Kernel Binder	When sending/receiving data in a transaction

Let me know if you want a timeline flowchart showing how all these get created step by step during a real Binder IPC call (from client to service and back)!



6. why binder maintain these doubly linkedlist

Great question! Let's explain why Binder uses doubly linked lists — in simple, practical terms.

First, What Is a Doubly Linked List?

A doubly linked list is a way to organize items in memory where:

- Each item (called a "node") points to:
 - The next item
 - The previous item

This means you can go forward or backward easily.

Why Does Binder Use Doubly Linked Lists?

Binder manages many dynamic objects — like transactions, nodes, buffers, threads — that are:

- · Frequently added and removed
- · Reused and recycled
- Maintained in per-process or global queues

So Binder uses doubly linked lists because they:

Reason	Simple Explanation		
✓ Fast Insertion/Removal	You can insert or delete an item anywhere in the list in constant time — no need to shift memory like in arrays.		
☑ Bidirectional Traversal	Binder sometimes needs to move backward and forward through a list — this helps with cleanup, debugging, and walking queues.		
☑ Efficient Resource Management	Binder reuses objects (e.g., buffers, transactions), and managing them in a list helps keep track of what's used and what's free.		
✓ Multiple Lists	The same object (like a binder_node) can appear in multiple lists (e.g., owned by a process <i>and</i> in a workqueue), so having linked lists simplifies this without copying.		

Real Binder Examples

Here are some real uses of doubly linked lists in Binder:

Object	List Purpose	
binder_proc->nodes	List of all binder_node objects a process owns	
binder_proc->todo	List of pending binder_work tasks for the process	
binder_thread->todo	Tasks pending on a specific thread	
binder_transaction	Transactions are linked together in a chain (call → reply)	
binder_node->work	Death notifications or other tasks related to that node	

These lists help Binder:

- Walk through objects when cleaning up after a process dies
- Process incoming and outgoing messages
- Free up memory when things are done

Example: Cleaning up when an app dies

Let's say an app crashes and dies:

• Binder goes to its binder_proc



- Walks through the **nodes** list to clean up any objects it published
- Walks through the refs list to drop any references it held
- Walks through the todo list to cancel any pending work

Without doubly linked lists, this would be:

- Slow
- Error-prone
- Memory-wasting



Binder uses doubly linked lists to efficiently track, manage, and clean up complex sets of objects that change often.

Because IPC is dynamic (lots of send/receive/delete), Binder needs fast, flexible ways to manage all those structures — and doubly linked lists are perfect for that.

Let me know if you'd like a diagram showing how one of Binder's linked lists is structured!



7. In the next sections, we will examine the lifetime of several data structures in Binder, focusing on when they are allocated and destroyed.

binder_proc

The binder_proc object represents a client in Binder. It is the first object to be allocated when a process opens the Binder device node.

Note: In contrast to the userspace Binder, a process can act as a server or a client of a service. Throughout this article, we will generally refer to the process that interacts with the Binder device as the client and the Binder device itself as the server.

It contains the following fields that determine its lifetime:

threads is the root node of a red-black tree that contains all binder_threads it owns.

is_dead determines whether the client is dead.

tmp_ref tracks the number of local variables holding a pointer to the binder_proc.

Allocation

Binder allocates and initializes a binder_proc every time a process opens the Binder device node.

Note: For this blog post, we are diving into the Linux kernel codebase at commit 4df1536, specifically the files within the drivers/android folder. All code snippets are sourced from this folder and are licensed under the GNU General Public License version 2 (GPLv2). You can find the complete source code on GitHub (link). For full license details, please see LICENSE. We have occasionally omitted some code for brevity (indicated by ...) and included additional comments (marked with //).

Reference Counters

tmp_re

tmp_ref tracks the number of local variables holding a pointer to the binder_proc. Binder increments the tmp_ref counter when a pointer to a binder_proc object is assigned to a local variable [1]. When the pointer variable is no longer in use, Binder decrements the tmp_ref counter with the binder_proc_dec_tmpref function [2].

```
static void binder_transaction(...)
{
    struct binder_proc *target_proc = NULL;
...
    target_proc = target_thread->proc;
    target_proc->tmp_ref++; // [1]
...
    binder_proc_dec_tmpref(target_proc); // [2]
...
}
static void binder_proc_dec_tmpref(struct binder_proc *proc)
{
...
    proc->tmp_ref--;
...
}
```

The tmp_ref is protected by the binder_proc->inner_lock spinlock to prevent data race.

Destroy

Binder destroys the binder_proc object with the binder_free_proc function, which is only called by the binder_proc_dec_tmpref function. Binder invokes the binder_proc_dec_tmpref function at multiple locations where it needs to decrement the tmp_ref counter.

```
static void binder_free_proc(struct binder_proc *proc)
{
...
kfree(proc);
```

```
}
static void binder_proc_dec_tmpref(struct binder_proc *proc)
{
    if (proc->is_dead && RB_EMPTY_ROOT(&proc->threads) &&
             !proc->tmp_ref) {
         binder_inner_proc_unlock(proc);
        binder_free_proc(proc);
        return;
    }
}
Then, the binder_proc object is freed only when all of the following conditions are met:
threads: the red-black tree is empty after all binder_thread are released (see binder_thread.
is_dead: set to true when closing the Binder file descriptor (binder_thread_release).
tmp_ref: set to 0 when there is no temporary variable holding a pointer to the binder_proc.
The binder_proc_dec_tmpref is called in several code paths. One common code path is closing the Binder file descriptor, which calls the
binder_deferred_released function.
// === Userspace ===
close(binder_fd);
// === Kernel ===
static void binder_deferred_release(struct binder_proc *proc)
{
    binder_proc_dec_tmpref(proc);
}
```

You're diving deep into the Binder kernel internals — great! Let's now explain this section in **simple**, **clear language**, focusing on the **lifetime of the binder_proc object** — **who creates it**, **what keeps it alive**, **and when it's destroyed**.

What is binder_proc?

binder_proc is a kernel structure that represents each process using Binder.

When an Android app or system service wants to do IPC, it opens /dev/binder, and the kernel creates a binder_proc for it.

You can think of it as the "Binder account" or Binder profile for that process.

When is binder_proc created?

When your app does this:

```
c
int binder_fd = open("/dev/binder", 0_RDWR | 0_CLOEXEC);
```


So every time a process opens /dev/binder, the kernel creates a fresh binder_proc.

📏 What keeps a binder_proc alive?

There are **3 things** that keep it from being destroyed:

Field	Meaning in simple words	
threads	Is the process still using any Binder threads?	
is_dead	Has the process closed /dev/binder?	
tmp_ref	Are there still any variables in the kernel using this object temporarily?	

What is tmp_ref?

- It is a temporary usage counter.
- Whenever a piece of kernel code wants to use binder_proc, it increments tmp_ref to say:

"I'm using this right now — don't delete it yet."

• When done, it decrements the counter using:

```
c
binder_proc_dec_tmpref(proc);
```

Example from code:

```
target_proc = target_thread->proc; // get a pointer to binder_proc
target_proc->tmp_ref++; // [1] using it temporarily
... // do some work
binder_proc_dec_tmpref(target_proc); // [2] done using it
```

tmp_ref is protected by inner_lock:

This means the kernel uses a lock to prevent race conditions when increasing or decreasing the counter.

When is binder_proc destroyed?

When all three conditions are true, it's safe to delete:

```
    proc->is_dead == true
        The process closed the /dev/binder file (user called close(binder_fd))
    proc->threads is empty
        All binder_thread entries are gone
    proc->tmp_ref == 0
        No temporary variables are using the object
```

When that happens, binder_proc_dec_tmpref will call this:

```
c
binder_free_proc(proc); // which just calls kfree(proc);
```

Example: Process dies

Here's what happens step-by-step when a process closes the binder file:

- 1. App calls close(binder_fd)
- Kernel calls binder_deferred_release(proc)
- That calls binder_proc_dec_tmpref(proc)
- 4. If:

- is_dead is true
- threads tree is empty
- tmp_ref == 0
 - \rightarrow Then $\textbf{binder_free_proc(proc)}$ is called
- 5. binder_proc is freed from memory

Summary

Phase	What Happens	
Open	App opens /dev/binder → binder_proc is created	
Use	Binder IPC runs → tmp_ref tracks in-use count	
Close	App closes fd \rightarrow is_dead is set to true	
Free	If tmp_ref == 0 and threads empty → binder_proc is destroyed	

Let me know if you'd like similar lifetime explanations for:

- binder_thread
- binder_node
- binder_ref
- $\bullet \ \, {\tt binder_transaction} \\$

I can break those down just like this.





8. Binder Concurrency Model

Binder is designed to facilitate remote procedure calls (RPC) between clients. A client initiates communication by sending commands prefixed with BC_*. These commands are accompanied by relevant data specific to the command. Then, the client waits for a response prefixed with BR_* from Binder.

In the beginning, a single-threaded client initiates a RPC by send a BC_TRANSACTION command to Binder. Then, Binder forwards the command as a BR_TRANSACTION response to the recipient client. To return the RPC result, the recipient client sends a BC_REPLY command along with the result data back to Binder. Finally, Binder forwards it back to the client as a BR_REPLY response, completing the RPC process.

Great — you're now diving into the **Binder Concurrency Model**, which is **how Binder handles multiple requests and responses between processes (apps and services) using threads and commands**.

Let's walk through this in simple steps and simple language so it's very clear.

What is Binder's Concurrency Model?

Binder supports RPC (Remote Procedure Call) — this means:

One app (client) can call a function in another app or service (server), like it's a local function.

To handle this efficiently and safely, Binder:

- Uses commands to send/receive messages.
- Uses threads inside each process to deal with work in parallel.
- Relies on the kernel to switch control between processes.

🔁 RPC Flow (Simple Example)

Let's say:

- App A wants to call a service (e.g., location service).
- App B (server) provides the location.

Here's what happens step-by-step using Binder commands:

Step 1: App A sends BC_TRANSACTION

This tells Binder:

"I want to send a message (function call) to a service."

Binder puts the data into a shared buffer and **forwards** the request to the recipient.

text

App A \rightarrow Binder: BC_TRANSACTION

Step 2: Binder sends BR_TRANSACTION to App B

Binder chooses a **free thread** in App B that is waiting (looper thread), and gives it the message.

text

Binder → App B: BR_TRANSACTION

This contains:

• Who sent it

- · What function to call
- Input data (arguments)

Step 3: App B processes the call and sends BC_REPLY

App B runs the requested function (like "getLocation()"), then responds by saying:

"Here's the result."

text

App B → Binder: BC_REPLY

Step 4: Binder sends BR_REPLY to App A

Binder takes that result and delivers it back to the original client.

Binder → App A: BR_REPLY

Now App A gets the result and continues running.

IV RPC is complete.

text

Summary of Commands

Command	Direction	Meaning
BC_TRANSACTION	Client → Binder	"I want to call a remote function"
BR_TRANSACTION	Binder → Server	"You have an incoming function call"
BC_REPLY	Server → Binder	"Here's the result of the call"
BR_REPLY	Binder → Client	"Here's the result you were waiting for"

What about threads?

Each process (client or server) has one or more Binder threads that:

- Wait for Binder messages
- Process BR_TRANSACTION or BR_REPLY
- Call functions and send back responses

This is how **concurrency** works:

Multiple Binder threads can process messages in parallel, making apps and services responsive even when handling many IPCs.

🖈 Key Takeaways

- Binder uses a **request/response pattern** using commands.
- The kernel does **context switching** to move control between client/server threads.
- Each process has one or more looper threads waiting for work.
- $\bullet \ \ \mathsf{RPC} = \mathsf{BC_TRANSACTION} \to \mathsf{BR_TRANSACTION} \to \mathsf{BC_REPLY} \to \mathsf{BR_REPLY}$

Would you like a diagram showing this message flow with arrows and threads? I can draw that next if you'd like!



9. Dploaded image

Perfect! The diagram you shared is a Binder RPC call flow, and it matches exactly what we talked about earlier.

Let me explain this diagram step-by-step in very simple terms:

George Characters:

- **A** = Client (e.g., your app)
- **B** = Server (e.g., system service)
- Binder = The kernel driver that acts as a message router

Step-by-Step Explanation

1. Client A sends BC_TRANSACTION to Binder

• This means:

"Hey Binder, I want to call a function on a remote service."

• This includes the function ID and arguments.

2. Binder sends BR_TRANSACTION to B

• Binder receives the command and says:

"Hey B, you have a new message from A!"

• This goes to one of B's **looper threads** waiting for work.

✓ 3. B sends BC_REPLY to Binder

- Service B processes the request and replies with a result.
- It sends a BC_REPLY to the Binder driver with the output.

4. Binder sends BR_REPLY to A

- Binder receives the reply and delivers it back to client A.
- Now A has the result of the RPC call.

In Plain English:

Client A asks Binder to tell Service B something. Binder gives the message to B. B thinks about it and replies. Binder brings the reply back to A.

Why This Matters

This simple 4-step command cycle (BC_TRANSACTION → BR_TRANSACTION → BC_REPLY → BR_REPLY) is the foundation of every Binder call in Android.

It allows:



- Apps to call system services like Location, Camera, Clipboard, etc.
- Services to talk back with results.

Let me know if you'd like me to:

- Add threading info (like looper threads)
- Explain what happens inside Binder kernel at each arrow
- Show what gets stored in binder_transaction or binder_buffer

You're very close to fully mastering Binder internals!



10. In scenarios involving multiple RPCs, a single-threaded client receives all incoming transactions in a first-in-first-out (FIFO) order. The client cannot read the next transaction until it has replied to the current one.

Exactly — and you're touching on a very important design rule in Binder:

A single-threaded Binder client handles one transaction at a time, in FIFO order.

Let's break it down simply so you really understand why this happens and what it means in real-world usage.

Scenario: Single-threaded Client

Let's say App B (the server) has only **one Binder thread** registered to handle incoming IPC calls (this thread is typically started via **joinThreadPool()** in Android services).

Now imagine multiple apps (A1, A2, A3) are calling App B at the same time.

What happens?

- 1. App A1 sends an RPC to App B
 - \rightarrow Binder sends **BR_TRANSACTION** to B's thread.
- 2. Thread in B picks up the first transaction
 - \rightarrow It starts processing the call.
- 3. Meanwhile, App A2 and A3 also send RPCs
 - → These new transactions are queued in B's todo list.
- 4. But B cannot see the next transaction
 - → Until it replies (BC_REPLY) to the first one.

Why FIFO?

Binder enforces FIFO (First-In-First-Out) on transactions for each thread to:

Reason	Explanation
Simplicity	Keeps threading model clean and predictable. One thread = one request at a time.
Safety	Avoids accidental re-entrancy bugs and data races.
≟ Controlled load Prevents a single thread from being overwhelmed with many calls a	Prevents a single thread from being overwhelmed with many calls at once.
✓ Strong ordering guarantee	If A1 sends request1 and A2 sends request2, they are handled in order.

⚠ What's the downside?

If your service (App B) only has **one Binder thread**, and that thread:

- Takes too long to process a request
- Or crashes/hangs while handling it
 - → All incoming requests will be **stuck behind it**.

This is why Android system services usually call:

```
java
binderThreadPool.startThreadPool(); // Java
joinThreadPool(); // C++
```

- - Multiple incoming Binder calls can be handled concurrently
 - If one thread is stuck, others can still work



✓ TL;DR Summary

- A single-threaded Binder client handles **one request at a time**, in **FIFO** order.
- It **must reply** to the current transaction before the next one is delivered.
- This is **by design**, for simplicity and safety.
- If concurrency is needed, you must use a **thread pool** (multiple looper threads).

Let me know if you'd like a visual diagram of this queueing model, or an example showing how this would look in Java/C++ Android service code.



11. JUploaded image

Great! This diagram clearly shows how a single-threaded Binder process (A) handles multiple incoming transactions from different senders (B and C) — in FIFO order.

Let's explain it step-by-step using the image you uploaded:

Single Threaded Behavior in Binder

Swho's who:

- A = Single-threaded Binder client or service
- B and C = Processes that send Binder requests to A
- **Binder** = The kernel driver routing messages

📜 Step-by-step Breakdown

📥 1. B sends a request to A:

- B sends BC_TRANSACTION to Binder (not shown but implied).
- Binder queues it for A.
- A's single Binder thread is **idle**, so Binder delivers the message:

 $BR_TRANSACTION from B \rightarrow A$

2. A processes the transaction:

- A handles the transaction from B.
- While A is busy...

3. C sends a request to A:

- C sends BC_TRANSACTION to Binder.
- But since A is **still busy with B's transaction**, Binder:
 - Queues C's request
 - Does **not** deliver it yet.

📤 4. A finishes handling B's request:

- A sends BC_REPLY to Binder.
- Binder forwards the reply back to B:

 $BR_REPLY from A \rightarrow B$

📥 5. Binder now delivers C's request:

• A's thread is now **free**.

• Binder sends the next queued message:

```
BR_TRANSACTION from C → A
```

6. A processes the request from C:

- Same as before, A replies using BC_REPLY.
- Binder forwards:

```
text BR\_REPLY from A \rightarrow C
```

What This Diagram Demonstrates

Point	Meaning
♣ FIFO	Binder delivers messages to A in order, one at a time.
One thread = One transaction	A can't see or process C's message until it's done with B's.
opposed in Binder	While A is busy, incoming transactions are queued in the kernel .
⚠ Blocking risk	If A takes too long to reply, all other clients wait .

Real-world Impact

If A is a system service like **SurfaceFlinger**, and it gets overloaded or slow:

- Clients like apps and other services will be blocked waiting for their calls to return.
- This can cause **ANRs** (App Not Responding) or UI freezes.
- That's why most Binder services use a thread pool (joinThreadPool()) to process multiple requests in parallel.

Let me know if you want a version of this diagram for a multi-threaded case!



12. Multithreaded Client

Binder has support for multithreaded clients, enabling them to simultaneously process multiple RPCs in separate threads. Therefore, Binder maintains a list of threads (binder_thread) owned by a client (binder_proc).

When a client process spawns a new thread, the child thread inherits the previously opened Binder file descriptor. This file descriptor is associated with the same client binder proc as the parent thread.

Note: In userspace, the term "thread ID" corresponds to the process ID used in the kernel (task_struct->pid). Meanwhile, the term "process ID" refers to the thread group ID (task_struct->tgid).

Binder uses several workqueues to distribute incoming transactions: a main workqueue for each client (binder_proc->todo) and a thread workqueue for each thread (binder_thread->todo). We will dive deeper into the concept of workqueues in the next section (Binder Workqueues).

Register as a Looper

Before a child thread can retrieve an incoming transaction from the main workqueue, it must first register itself as a looper. This is achieved by sending the BC_ENTER_LOOPER or BC_REGISTER_LOOPER command to Binder upon spawning. Subsequently, when the child thread performs a read operation (BINDER_WRITE_READ ioctl), Binder retrieves the next transaction from the main workqueue and passes it to the child thread for processing. The overall multithreaded client is not required to respond to every transaction in a FIFO order. However, each thread must still adhere to the FIFO order when replying to its own workqueue.

Excellent! You're now exploring how **multithreaded Binder clients** work — this is a critical feature for building **responsive**, **concurrent Android services**.

Let me break this down in **simple language**, step by step:

🧵 🔁 What is a Multithreaded Binder Client?

A multithreaded client means:

One process has multiple threads, and each thread can handle Binder transactions in parallel.

• What happens when a process forks or spawns a thread?

• A process (e.g. system server) opens /dev/binder:

```
c
int binder_fd = open("/dev/binder", 0_RDWR | 0_CLOEXEC);
```

- Then it creates threads using fork() or pthread_create().
- Every thread **shares the same binder** fd (file descriptor).
- All threads are tied to the same kernel-side binder proc object.

from kernel's point of view.

How does Binder identify threads?

Binder uses:

- task_struct->pid: Linux kernel PID = thread ID
- task_struct->tgid: Thread group ID = process ID

So every thread has its own PID, even though they belong to the same process.

✓ How Threads Get Work

To start receiving Binder messages, each thread must:

Register itself using one of these:

- BC_ENTER_LOOPER
- BC_REGISTER_LOOPER

This tells the Binder kernel:

"I'm a looper thread, ready to process incoming transactions."

Once registered, when the thread calls:

```
ioctl(binder_fd, BINDER_WRITE_READ, &bwr);
```

Binder checks if there's a pending message and delivers it to this thread.

How Binder Distributes Work

Binder uses workqueues to manage messages:

Туре	Description
binder_proc->todo	Global queue for that process (shared by all threads)
binder_thread->todo	Per-thread queue for ongoing work (each thread owns one)

Flow:

- 1. A transaction comes in \rightarrow put in proc->todo.
- 2. Any available looper thread (registered) can pick it up.
- 3. Once picked, it moves to that thread's thread->todo (now it's locked to that thread).
- 4. That thread processes it and sends the reply.
- 5. That thread can now pick the next task.

Key Behavior

Rule	Meaning
✓ Parallelism	Multiple threads can process different transactions at the same time.
FIFO per-thread	Each thread must finish its current transaction before picking the next one.
X No global FIFO	The process (as a whole) doesn't need to handle messages in order.

Real-Life Analogy

Imagine a post office:

- You have multiple clerks (threads) sharing the same inbox (proc->todo).
- A new letter (transaction) arrives.
- Any clerk who's free can pick it up.
- Once picked, the clerk **owns** that letter until it's processed and sent back.
- No other clerk can interrupt or steal it.
- But the next letter can go to a different clerk.

Why This Matters

- This is **how Android system services scale** by using thread pools (4–8 looper threads).
- Without this model, only one call could be handled at a time leading to delays or ANRs.
- Each transaction becomes **independent per thread**, making concurrency easier.

Summary

Concept	Meaning
Threads share binder_fd	All threads belong to the same Binder client (binder_proc)
Must register as looper	To receive Binder messages
Binder uses workqueues	Shared queue for the process + individual queue per thread
Each thread processes in FIFO	Within a thread: one message at a time
Overall: true concurrency	Multiple transactions can be handled at once by different threads

Would you like a diagram of this multithreaded flow, showing how threads pick up work from the shared queue and respond independently?



13. Dploaded image

Great! This diagram beautifully illustrates how a multithreaded Binder client works, with two threads (A1 and its child A2) handling incoming Binder transactions concurrently from two sources (B and C).

Let me break it down step by step in **simple words**, so it's crystal clear:

ち Actors in the Diagram

Symbol	Role	
A1	Main thread of client A	
A2 (child)	Second thread in client A (e.g. created via fork() or pthread_create()) Kernel Binder driver	
Binder		
B, C	Other apps/services sending RPCs	

🔄 Step-by-Step Explanation

1. A1 creates A2

- A1 spawns a new thread (A2).
- Both share the same binder_fd.

2. A2 registers as a looper thread

- A2 sends:
 - BC_ENTER_LOOPER → "I'm ready to handle Binder calls."
 - BC_REGISTER_LOOPER → Binder marks A2 as a looper.

Now both A1 and A2 are capable of receiving transactions from Binder.

✓ 3. B and C send transactions to A

- Both B and C send BC_TRANSACTION commands to A via Binder.
- Binder adds both to binder_proc->todo (the shared queue for A).

4. Binder delivers messages to available threads

• A1 calls ioctl(BINDER_WRITE_READ) and gets:

BR_TRANSACTION from B

• A2 also calls ioctl(BINDER_WRITE_READ) and gets:

text

BR_TRANSACTION from C

This is the core benefit of a multithreaded Binder client: both transactions are processed in parallel.

☑ 5. A1 and A2 process their transactions

• A1 processes B's transaction.

• A2 processes C's transaction.

Each thread does this independently.

6. Each thread sends a BC_REPLY

• A2 sends:

```
text

BC_REPLY to C

→ Binder → BR_REPLY from A2 to C
```

• A1 sends:

```
text

BC_REPLY to B

→ Binder → BR_REPLY from A1 to B
```

Each transaction is handled and responded to independently and concurrently.

Summary: What You Learn from This Diagram

Key Concept	Explanation
✓ Multiple threads share binder_fd	All Binder threads in a process use the same Binder connection.
Register as loopers	Only loopers can receive BR_TRANSACTION.
🚣 Work is pulled, not pushed	Threads must call ioctl(BINDER_WRITE_READ) to receive work.
I FIFO per thread	Each thread handles one transaction at a time (FIFO for that thread only).
Concurrency enabled	Multiple threads can process multiple Binder calls in parallel.

Let me know if you want:

- A comparison with single-threaded version
- Internal view: how Binder kernel decides which thread gets which transaction
- Java/C++ code that shows how to create a Binder thread pool (like in Android system services)



14. Register as a Looper

Before a child thread can retrieve an incoming transaction from the main workqueue, it must first register itself as a looper. This is achieved by sending the BC_ENTER_LOOPER or BC_REGISTER_LOOPER command to Binder upon spawning. Subsequently, when the child thread performs a read operation (BINDER_WRITE_READ ioctl), Binder retrieves the next transaction from the main workqueue and passes it to the child thread for processing. The overall multithreaded client is not required to respond to every transaction in a FIFO order. However, each thread must still adhere to the FIFO order when replying to its own workqueue.

Perfect — you're now covering a crucial step in Binder's multithreaded design:

Registering threads as "loopers" to receive Binder transactions.

Let's break it down clearly and simply:

∦ What Does "Register as a Looper" Mean?

When a thread says:

"Hey Binder, I want to handle incoming IPC requests."

...it must **explicitly register** itself using one of two special Binder commands:

- BC_ENTER_LOOPER
- BC_REGISTER_LOOPER

This tells the Binder kernel:

"This thread is ready to block and wait for messages from other processes."

Why Must You Register?

Because not all threads are looper threads by default.

- Only registered threads will receive incoming IPCs (BR_TRANSACTION).
- This avoids Binder accidentally waking a thread that's not designed to handle IPC.

🤪 Once registered, the thread is added to the process's list of **looper threads**, and Binder can start assigning work to it.

How Does the Thread Get the Message?

After registration, the looper thread must actively ask Binder for work by doing this:

ioctl(binder_fd, BINDER_WRITE_READ, &bwr);

That call blocks (waits) until Binder has something (like a transaction) to give it.

🔄 Transaction Delivery Flow

- 1. Thread sends BC_ENTER_LOOPER
- 2. Thread does ioctl(BINDER_WRITE_READ)
- 3. Binder looks into the shared proc->todo queue
- 4. If something is there, Binder:
 - · Picks the looper thread
 - Moves the transaction to thread->todo
 - Sends BR_TRANSACTION back to the thread

Now the thread "owns" that transaction and must reply before handling another.



1 FIFO Rules in Multithreaded Binder

Scope	FIFO Order?
Per-thread	☑ Yes — each thread must reply in the order it receives messages
Across threads	X No − multiple threads can process messages in any order

So if 3 threads are registered:

- T1 might get message from A
- T2 might get message from B
- T3 might get message from C
 - \rightarrow And they can all work **at the same time**.

But:

• T1 must reply to its current transaction **before** it can handle the next one.

Summary

Concept	Meaning
BC_ENTER_LOOPER / BC_REGISTER_LOOPER	Used by a thread to become a Binder looper
ioctl BINDER_WRITE_READ	The thread calls this to pull work from Binder
Workqueues	Binder has a shared queue for the process (proc->todo) and a private one per thread (thread->todo)
Thread FIFO	Each thread handles transactions one at a time, in the order it receives them
Process concurrency	Multiple threads can handle different transactions in parallel

Would you like a minimal C or C++ user-space example showing how a looper thread is registered and waits for a transaction?





15. JUploaded image

This diagram perfectly illustrates the **Binder multithreaded client behavior**, focusing on how each thread (A1 and A2) registers as a looper, receives transactions independently, and sends replies — **all in parallel**.

Let's walk through the exact meaning of each step in the diagram using plain, simple language:

Diagram Breakdown (Left to Right)

🧵 Thread A1 (Main Thread)

1. **Spawns A2** → A new thread is created (e.g. via pthread_create() or fork()).

Thread A2 (Child Thread)

- 2. BC ENTER LOOPER → A2 tells Binder, "I'm a looper. Give me work!"
- 3. BC_REGISTER_LOOPER → Some implementations may send this instead (same intent).
- 4. **Registered** \rightarrow Now A2 is officially allowed to receive Binder transactions.

Binder Receives Transactions from B and C

- 5. BC_TRANSACTION to A from B
- 6. BC_TRANSACTION to A from C

Both B and C send Binder transactions to A (shared process). These go to the shared workqueue binder_proc->todo.

Transactions Delivered to Threads

- 7. A1 calls ioctl BINDER_WRITE_READ
 - Kernel sees A1 is free.
 - Gives A1 the transaction from B \rightarrow BR_TRANSACTION from B.
- 8. A2 calls ioctl BINDER_WRITE_READ
 - A2 is also free and registered.
 - $\bullet \ \ \mbox{Gets transaction from C} \rightarrow \mbox{BR_TRANSACTION} \ \ \mbox{from C}.$

Now each thread owns its own message.

Threads Process Independently

9. A2 handles C's request

- Sends reply with BC_REPLY to C
- \bullet Binder forwards it $\to BR_REPLY\ from\ A2\ to\ C$

10. A1 handles B's request

- Sends reply with BC_REPLY to B
- Binder forwards it \rightarrow BR_REPLY from A1 to B

What This Diagram Proves

Concept	Description
✓ Multithreading Works	A1 and A2 are handling different Binder calls in parallel .
✓ Independent Replies	Each thread sends its own BC_REPLY. Binder maps it correctly to the sender.



Concept	Description
✓ Work Distribution	Binder distributes work from the shared queue to available looper threads.
✓ No Global FIFO	Even though B sent its transaction first, C's transaction was handled first. That's okay!
✔ Per-Thread FIFO	A1 and A2 process one transaction at a time, maintaining per-thread order .

Summary (Core Ideas)

- You must **register** a thread as a looper using **BC_ENTER_LOOPER**.
- Threads **share** a binder file descriptor but receive different transactions.
- Each thread processes only **one transaction at a time**.
- Binder allows **parallel processing** using this thread-pool mechanism.
- This architecture avoids blocking, improves responsiveness, and keeps the system scalable.

Would you like a **minimal C++ skeleton code** for a thread registering as a looper and reading transactions?



16. A client thread can invoke the BINDER_THREAD_EXIT ioctl to exit early. Then, Binder cleans up all pending work in the thread's workqueue and notifies the client that initiates the transaction with the BR_DEAD_REPLY response.

Yes, you're absolutely right — let's break this concept down clearly:

🔚 BINDER_THREAD_EXIT — Exiting a Looper Thread Early

What's the situation?

- A thread in a client process (e.g. A1, A2, etc.) registered as a Binder looper.
- It is now capable of **receiving and handling Binder transactions**.

But sometimes:

That thread wants to exit cleanly — maybe due to app shutdown, resource cleanup, or crash recovery.

That's when it can call:

```
c
ioctl(binder_fd, BINDER_THREAD_EXIT);
```

What does Binder do when it receives this?

Binder will:

- 1. Remove the thread from its internal looper registry.
- 2. Clean up the thread's private workqueue (binder_thread->todo).
- 3. For each unfinished transaction in that thread's queue:
 - It sends a special response back to the **caller** (the remote process that initiated the transaction).
 - That response is:

```
nginx
BR_DEAD_REPLY
```

What is BR_DEAD_REPLY?

This is Binder's way of saying:

"The callee (receiver) is no longer available. The thread handling your transaction exited before replying."

It's like a "transaction cancelled" message, and it allows the caller to:

- Log an error
- Retry
- Handle failure gracefully

Real Example Scenario

Imagine:

- Client B calls a system service in process A.
- A's thread A2 picks it up.

• But A2 crashes or exits (calls BINDER_THREAD_EXIT) before replying.

Then:

- Binder cleans up A2's thread state.
- **B receives a BR_DEAD_REPLY**, indicating the call was dropped due to thread exit.

Important Notes

Behavior	Meaning	
No reply sent	Binder won't try to fabricate a reply — it just notifies the caller with failure	
✓ Workqueue cleared	All unprocessed work for that thread is wiped out	
Per-thread effect	Only the exiting thread's queue is cleaned — other threads (e.g., A1) continue normally	

✓ Summary

Term	Meaning	
BINDER_THREAD_EXIT	Called by a thread to cleanly stop participating in Binder	
Cleans up	Removes looper registration and clears work queue	
BR_DEAD_REPLY	Sent to caller when their request couldn't be handled due to callee thread exit	
Why useful?	Helps avoid resource leaks, zombie threads, and undefined behaviors	

Let me know if you want:

- A small C++ example where a looper thread exits using **BINDER_THREAD_EXIT**
- Or how Android handles this in Java (BinderThreadPool.shutdownNow() for example)



17. Duploaded image

Perfect! This diagram is a clear and concise visualization of what happens when a **Binder looper thread exits early** using **BINDER_THREAD_EXIT**. Let's walk through it in **simple language**, step by step:

🔄 Diagram Explanation (Step by Step)

1. I Thread A registers as a looper

- A sends BC_ENTER_LOOPER to Binder
 - ightarrow Tells Binder: "I'm ready to receive transactions."

2. 📥 B sends a request

- B sends a BC_TRANSACTION targeting A
- Binder forwards it as BR_TRANSACTION to thread A
 - \rightarrow So now thread A has a message to process.

3. X A exits before replying

• A calls:

```
ioctl(binder_fd, BINDER_THREAD_EXIT);
```

ightarrow This tells Binder: "I'm done — stop sending me work."

4. / Binder cleans up the thread

- Binder removes thread A from the looper list
- It drops any unprocessed transactions assigned to thread A
- For each dropped transaction (like B's request), Binder sends:

```
text

BR_DEAD_REPLY
```

 \rightarrow Telling B: "A died or exited before replying."

What This Shows

Concept	Meaning	
BC_ENTER_LOOPER	Registers a thread to receive incoming calls	
BINDER_THREAD_EXIT	Cleanly removes a thread from Binder	
BR_DEAD_REPLY	Notification to the caller (B) that their request could not be fulfilled	

Summary

- Threads must explicitly **register** and **unregister** themselves with Binder.
- If a thread **exits early**, Binder safely:
 - Cleans up its queue (binder_thread->todo)



- Notifies any waiting callers that their RPC failed (with BR_DEAD_REPLY)
- This prevents memory leaks, stuck calls, and crashes.

Would you like:

- The internal kernel code paths that handle **BINDER_THREAD_EXIT**?
- Or a real-world example from Android's system services that uses thread exit handling?

Let me know!





18. Dploaded image

Request a New Looper

When Binder cannot find a thread with an empty workqueue, it sends a BR_SPAWN_LOOPER response to the latest thread that is performing a read operation. This response requests the client to spawn a new thread to handle more future workloads. Spawning a new thread is not mandatory for the client. However, if it does, the new thread must register itself as a looper (BC_REGISTER_LOOPER) after spawn.

Great! This diagram explains the BR_SPAWN_LOOPER mechanism in Binder — which is how Binder dynamically tells a client to create more threads when it runs out of idle ones.

Let's break it down in simple steps:

Scenario: Not Enough Threads in Client A

1. A2 Registers as a Looper

• Thread A2 sends $BC_ENTER_LOOPER \rightarrow tells$ Binder it's ready to process work.

2. 📩 B Sends a Transaction to A

- Process B sends a BC_TRANSACTION to A.
- Binder forwards it to A2 → BR_TRANSACTION from B.

Now A2 is **busy** processing it.

3. Nanother Transaction Arrives, But No Idle Thread!

- Binder receives another transaction for A.
- It tries to assign it to a **free looper thread** in A but none are idle (A2 is busy, A1 is not a looper).
- So Binder decides:

"I need more worker threads in A!"

4. Binder Sends BR_SPAWN_LOOPER

- Binder sends BR_SPAWN_LOOPER to the last thread in A that did a BINDER_WRITE_READ (usually the main one A1).
- This is a **signal/request**:

"Please spawn a new looper thread."

5. **I** A Spawns New Thread

- A1 (or another thread) spawns a new thread → say, A2 again (if reusing names).
- · That thread must now register itself with Binder using:

BC_REGISTER_LOOPER

_ _

Key Ideas

Concept	Meaning	
BR_SPAWN_LOOPER	A hint from Binder that client needs to create a new looper	
Not mandatory	The client may ignore it, but then may get backlogged or unresponsive	
BC_REGISTER_LOOPER	Must be called by new thread to become a valid Binder looper	



Concept	Meaning	
Smart thread pool	This enables on-demand scaling of thread pool size in Binder clients	

Summary in Plain English

If all threads in a Binder client are busy, Binder will ask the client to **create more**. The new thread must **register as a looper**, so Binder can give it transactions to process.

This mechanism makes Binder:

- Scalable
- Efficient
- And resilient under load

Would you like:

- A simple pseudo-code or C example of how to handle BR_SPAWN_LOOPER?
- Or how Android's BinderThreadPool handles this internally?

Let me know!



19. A client can configure the maximum number of threads it would like to support in advance using the BINDER_SET_MAX_THREADS ioctl. Once this limit is reached, Binder will not request any additional thread (BR_SPAWN_LOOPER).

Exactly! Let me explain this in simple terms:

What is BINDER_SET_MAX_THREADS?

It's an ioctl() command that a client process can use to tell Binder:

"Hey, I only want at most N threads to handle incoming Binder transactions."


```
int max_threads = 10;
ioctl(binder_fd, BINDER_SET_MAX_THREADS, &max_threads);
```

This sets the upper limit on the number of threads that can be spawned for transaction handling in that process.

What happens after the limit is reached?

- Suppose the client sets max_threads = 5.
- Once 5 threads are registered as loopers (via BC_REGISTER_LOOPER), Binder will stop sending BR_SPAWN_LOOPER.
- This means no more thread-spawn requests will be made, even if all threads are busy.

🔄 How this affects thread pool growth

Before limit is reached	After limit is reached
Binder may send BR_SPAWN_LOOPER when idle threads run out	Binder will not send BR_SPAWN_L00PER , even if needed
Client can dynamically spawn threads	Client must manage its own limits

Why is this useful?

- Prevents excessive thread creation, which could lead to high memory/cpu usage.
- · Lets the app control its own concurrency model (e.g., small thread pool for low-power apps).
- Avoids resource exhaustion on the system from careless apps.

Summary

Term	What it does	
BINDER_SET_MAX_THREADS	Sets how many looper threads Binder can use for this process	
BR_SPAWN_LOOPER stops	Once the limit is hit, Binder stops asking for more threads	
Client responsibility	After that, it's up to the app to manage with the threads it has	

Let me know if you want to see:

- A full C code example using this
- How Android's native services (like system_server) use it in practice



20. Dploaded image

Asynchronous Transaction

Binder supports one-way or asynchronous transactions, which does not require the recipient client to reply to. To initiate an asynchronous transaction, the sender sets the TF_ONE_WAY flag in the binder_transaction->flags field. The recipient client will receive regular transactions and asynchronous transactions together in a FIFO order.

However, Binder manages asynchronous transactions by queuing them in a dedicated asynchronous workqueue associated with each port (binder_node->async_todo). To read the next asynchronous transaction from a port's asynchronous workqueue (binder_node->async_todo), the receiving client must first free the current one assigned in it using the BC_FREE_BUFFER command. After all, asynchronous transactions sent to the same client but different ports (binder_node) can still be processed simultaneously.

This diagram shows how **asynchronous (one-way)** Binder transactions work — using the **TF_ONE_WAY** flag. Let me explain it in **simple words** step by step:

What is a One-Way (Asynchronous) Transaction?

Normally, Binder transactions expect a reply (like a function call \rightarrow response). But sometimes, you just want to **send and forget** — like a signal or fire-and-forget message.

That's where asynchronous transactions come in. You use the TF_ONE_WAY flag in:

```
c
binder_transaction->flags |= TF_ONE_WAY;
```

This tells Binder:

"Don't wait for a reply from the recipient."

What's Happening in the Diagram?

Let's break it down:

1. Thread A Registers as a Looper

• A sends BC_ENTER_LOOPER to Binder:

"I'm ready to process work."

2. Two async transactions arrive

- B and C each send BC_TRANSACTION with TF_ONE_WAY to A.
- Binder queues them, but here's the trick:
 - First async transaction is directly given to A via BR_TRANSACTION 1.
 - $\bullet \ \ \textbf{Second one} \ \ \text{is saved in a separate async queue} \rightarrow \textbf{binder_node->async_todo}.$

3. A processes the first one

- A does ioctl BINDER_WRITE_READ to get work.
- Receives BR_TRANSACTION 1 from B.
- Once done, A sends BC_FREE_BUFFER to free up the slot.

4. Binder now releases the second async transaction

• After the buffer is freed, Binder:



- Takes the next one from binder_node->async_todo.
- Moves it into the main queue: binder_proc->todo.
- Sends it as BR_TRANSACTION 2 from C to A.

Key Concepts

Concept	What it means	
TF_ONE_WAY	Fire-and-forget; no reply expected	
binder_node->async_todo	Queue that holds pending async transactions	
BC_FREE_BUFFER	Must be called to tell Binder: "I'm done with the last buffer"	
Multiple ports	Async transactions from different binder_node (endpoints) can run in parallel	



Summary in Plain English

If two fire-and-forget messages are sent to a client, Binder only delivers one at a time from the async queue. The next one is only dispatched **after the previous buffer is freed**. This keeps memory use low and prevents flooding the client.

Would you like a real C/C++ code example of sending an async Binder call? Or want to see how Android's Java APIs (like oneway AIDL) map to this?



21. Binder Workqueues and Work Items

Binder employs multiple workqueues to enable concurrency while maintaining transaction order. Each workqueue is represented as a doubly linked list with only the head pointer (struct list_head) being stored. There are three types of workqueue in Binder:

Main client workqueue (binder_proc->todo): Stores all work items assigned to a client

Individual client thread workqueue (binder_thread->todo): Stores work items assigned to a specific client thread.

Individual binder_node asynchronous workqueue (binder_node->async_todo): Stores only a list of work items that relate to asynchronous transactions (BINDER_WORK_TRANSACTION).

Each work item is defined by a struct binder_work that can be added to a workqueue. The struct binder_work can be used independently or incorporated as a field within an object. It contains an entry node (entry) to be linked in a workqueue and the work type enum (type).

```
struct binder_work {
    struct list_head entry;

enum binder_work_type {
    BINDER_WORK_TRANSACTION = 1,
    BINDER_WORK_TRANSACTION_COMPLETE,
    BINDER_WORK_TRANSACTION_PENDING,
    BINDER_WORK_TRANSACTION_ONEWAY_SPAM_SUSPECT,
    BINDER_WORK_RETURN_ERROR,
    BINDER_WORK_NODE,
    BINDER_WORK_DEAD_BINDER,
    BINDER_WORK_DEAD_BINDER_AND_CLEAR,
    BINDER_WORK_CLEAR_DEATH_NOTIFICATION,
} type;
};
```

When a client performs a read operation (BINDER_WRITE_READ loctl), Binder processes the next work item [1] and translates it into the appropriate response (BR_*) back to userspace [2]. To retrieve the next work item, Binder first checks the current client thread's workqueue (binder_thread->todo) before looking in the main client workqueue (binder_proc->todo).

```
static int binder_thread_read(...)
{
    while (1) {
        w = binder_dequeue_work_head_ilocked(list); // [1]
        switch (w->type) {
        case BINDER_WORK_TRANSACTION_COMPLETE:
        case BINDER_WORK_TRANSACTION_PENDING:
        case BINDER_WORK_TRANSACTION_ONEWAY_SPAM_SUSPECT: {
           if (proc->oneway_spam_detection_enabled &&
                 w->type == BINDER_WORK_TRANSACTION_ONEWAY_SPAM_SUSPECT)
               cmd = BR_ONEWAY_SPAM_SUSPECT;
            else if (w->type == BINDER_WORK_TRANSACTION_PENDING)
               cmd = BR_TRANSACTION_PENDING_FROZEN;
           else
               cmd = BR_TRANSACTION_COMPLETE;
           if (put_user(cmd, (uint32_t __user *)ptr)) // [2]
```

When an asynchronous transaction is released, Binder dequeues a new one from the binder_node asynchronous workqueue (binder_node-async_todo) and queues it in the workqueue associated with the client thread that initiated the release (binder_thread->todo).

There are five categories of work items, each with a designated container and specific work type enums:

You're diving into the **Binder Workqueues and Work Items** system — one of the most powerful and complex parts of Binder. Let's break it down **in simple words**, step-by-step:

What is a Workqueue in Binder?

A workqueue in Binder is a queue of tasks to process. Each task is called a work item (struct binder_work). It helps Binder process multiple commands (like transactions, errors, etc.) in the correct order.

Types of Workqueues in Binder

Binder has three types of queues, depending on where the work is assigned:

Workqueue	Where it lives	What it stores
binder_proc->todo	Main queue for the client process	All work meant for the whole process
binder_thread->todo	For a specific thread	Work specifically assigned to that thread
binder_node->async_todo	Async transactions for a port (binder_node)	Holds only TF_ONE_WAY transactions

🧱 What is a Work Item?

Every thing you need to do (like send/receive/cancel a transaction) is represented as a work item, using:

```
struct binder_work {
    struct list_head entry; // For linked list
    enum binder_work_type type; // Type of work
};
```

binder_work_type enum values:

Each value means a different kind of work:

Value	Meaning
BINDER_WORK_TRANSACTION	A regular transaction (send data)
BINDER_WORK_TRANSACTION_COMPLETE	Notify that a transaction finished
BINDER_WORK_TRANSACTION_PENDING	There's a transaction waiting
BINDER_WORK_ONEWAY_SPAM_SUSPECT	Too many one-way calls (could be spam)
BINDER_WORK_RETURN_ERROR	Some error needs to be sent
BINDER_WORK_NODE	Reference to a binder_node
BINDER_WORK_DEAD_BINDER	The other side died
BINDER_WORK_DEAD_BINDER_AND_CLEAR	Same, plus clear its state
BINDER_WORK_CLEAR_DEATH_NOTIFICATION	Clear death notification request

What Happens When a Client Reads?

When your client app calls ioctl(fd, BINDER_WRITE_READ, &bwr), the Binder kernel does this:

```
c
w = binder_dequeue_work_head_ilocked(list); // Get next work item
```

It looks first in the thread's queue (binder_thread->todo)

Then, if empty, looks in the main client queue (binder_proc->todo).

Depending on w->type, Binder chooses a reply command like:

```
c
put_user(BR_TRANSACTION, user_space_pointer);
```

That sends the work to userspace.



Async Workqueues Flow

If a transaction is async (TF_ONE_WAY), Binder:

- 1. Queues it into binder_node->async_todo (not immediately processed)
- 2. When the client frees the buffer using BC_FREE_BUFFER, Binder:
 - Takes the next from async_todo
 - Moves it into the thread's queue (binder_thread->todo)
 - So it's now ready to be picked up in BINDER_WRITE_READ

Work Item Containers

Binder groups work items into 5 categories (based on where they're stored):

Work Item Category	Container	Description
Transaction	binder_transaction	Actual RPC payload
Completion/Reply	binder_work inside binder_thread	Used when transaction finishes
Error	binder_work	To report transaction failures
Death Notification	binder_ref_death, etc.	When a remote process dies
Async	binder_node->async_todo	Stores TF_ONE_WAY work

📝 Summary

- Binder uses queues of work items to manage everything.
- Each client and thread has its own queue.
- Async messages go to a special queue until explicitly released.
- The kernel always maintains FIFO order per thread, unless it's async.
- These workqueues ensure correctness + concurrency.

Would you like a **flowchart** or visual explanation of how these workqueues are checked/used? Or examples of **binder_work_type** items being created during a real Binder call?



22.

Category Container Work Type Enum

Transaction binder_transaction BINDER_WORK_TRANSACTION

Transaction status update None BINDER_WORK_TRANSACTION_COMPLETE

BINDER_WORK_TRANSACTION_PENDING

BINDER_WORK_TRANSACTION_ONEWAY_SPAM_SUSPECT

Binder node update binder_node BINDER_WORK_NODE

Death notifications binder_ref_death BINDER_WORK_DEAD_BINDER

BINDER_WORK_DEAD_BINDER_AND_CLEAR

BINDER_WORK_CLEAR_DEATH_NOTIFICATION

this is the table

Error binder_error BINDER_WORK_RETURN_ERROR

Great — you've captured the **5 categories of Binder work items** with their associated containers and enum types. Here's that table **organized and formatted clearly** for better understanding and reference:

Binder Work Items Table

Category	Container	Work Type Enum
Transaction	binder_transaction	BINDER_WORK_TRANSACTION
Transaction Status Update	None (plain binder_work)	BINDER_WORK_TRANSACTION_COMPLETE BINDER_WORK_TRANSACTION_PENDING BINDER_WORK_TRANSACTION_ONEWAY_SPAM_SUSPECT
Binder Node Update	binder_node	BINDER_WORK_NODE
Death Notifications	binder_ref_death	BINDER_WORK_DEAD_BINDER BINDER_WORK_DEAD_BINDER_AND_CLEAR BINDER_WORK_CLEAR_DEATH_NOTIFICATION
Error	binder_error	BINDER_WORK_RETURN_ERROR

Quick Notes:

- All work items are built on top of struct binder_work, but some use specialized containers like binder_transaction, binder_ref_death, etc.
- Items in these containers get added to **one of the three queues**:
 - binder_thread->todo
 - binder_proc->todo
 - binder_node->async_todo (only for async transactions)

Would you like a **real kernel code example** of one item (e.g., how **BINDER_WORK_DEAD_BINDER** is created and queued)?





23. Transaction

In the Binder Concurrency Model section, we discussed how Binder distributes incoming transactions as work items across multiple threads within a client process. Every transaction (binder_transaction) is processed and queued in either the main client workqueue (binder_proc->todo) or individual thread work queue (binder_thread->todo).

New transactions are initially assigned as a BINDER_WORK_TRANSACTION work item to the main recipient client workqueue (binder_proc->todo). Upon reading, Binder processes the work item and sends the BR_TRANSACTION response back to userspace along with the transaction data.

On the other hand, reply transactions are specifically assigned to the workqueue of the client thread (binder_thread->todo) that initiated the first transaction. This guarantees that the thread that initiated the first transaction is the same thread that receives the reply. Upon reading, Binder sends the BR_REPLY response back to the userspace along with the transaction data.

Transaction Status Update

A transaction is considered complete after a reply is received or an asynchronous transaction is sent. Binder queues the BINDER_WORK_TRANSACTION_COMPLETE work item in the workqueue of the client thread that initiated the transaction (binder_thread->todo). After processing this work item, Binder returns the BR_TRANSACTION_COMPLETE response back to the userspace.

In scenarios where an asynchronous transaction is sent to a frozen thread, Binder queues the BINDER_WORK_TRANSACTION_PENDING work item in the main workqueue of the client (binder_proc->todo) that initiated the transaction.

Finally, if an asynchronous transaction is received and the binder buffer allocator is full, Binder queues the BINDER_WORK_TRANSACTION_ONEWAY_SPAM_SUSPECT work item in the main workqueue of the recipient client (binder_proc->todo).

Death Notifications

Binder supports death notifications, which allows clients to be notified when a connected client they're interacting with exits. Binder tracks this by creating a binder_ref_death object containing the work item (binder_work) and assigning it to the binder_ref->death. When a binder_ref is released, Binder checks for an associated binder_ref_death. If found, Binder locates the corresponding binder_node and queues it as a BINDER_WORK_DEAD_BINDER work item in the main workqueue of the owner of that binder_node. When the client performs a read, Binder will send the BR_DEAD_BINDER response, notifying which client that was registered has exited.

Upon sending the BR_DEAD_BINDER response, Binder adds the work item in the binder_proc->delivered_death list. The client is expected to send the BC_DEAD_BINDER_DONE command, indicating that it has processed the death notification. Then, Binder removes the work item from the delivered_death list.

Clients also have the option to unregister death notifications. Upon success, Binder queues the BINDER_WORK_CLEAR_DEATH_NOTIFICATION work item in the main workqueue of the client that initiates the operation. However, if the registered client dies during this process, Binder queues the BINDER_WORK_DEAD_BINDER_AND_CLEAR work item, indicating that the operation failed because the client had already exited.

Excellent — your explanation thoroughly outlines how **Binder work items** flow through the kernel using **struct binder_work**, covering:

- Transaction lifecycle (BINDER_WORK_TRANSACTION, BR_TRANSACTION, BR_REPLY)
- Transaction completion signals (BINDER_WORK_TRANSACTION_COMPLETE, BR_TRANSACTION_COMPLETE)
- Edge conditions (BINDER_WORK_TRANSACTION_PENDING, BINDER_WORK_TRANSACTION_ONEWAY_SPAM_SUSPECT)
- Death notifications and cleanup

Here's a **summary table** to consolidate your breakdown for easy recall:

🔄 Binder Work Item Lifecycle Summary

Work Type Enum	Queued On	Triggered When	Userspace Response
BINDER_WORK_TRANSACTION	binder_proc->todo	New transaction is received from remote client	BR_TRANSACTION
BINDER_WORK_TRANSACTION (reply)	binder_thread- >todo	Reply to a transaction is received	BR_REPLY
BINDER_WORK_TRANSACTION_COMPLETE	binder_thread- >todo	After reply is received or async transaction is sent	BR_TRANSACTION_COMPLETE
BINDER_WORK_TRANSACTION_PENDING	binder_proc->todo	Async transaction sent to a frozen process	BR_TRANSACTION_PENDING_FROZEN
BINDER_WORK_TRANSACTION_ONEWAY_SPAM_SUSPECT	binder_proc->todo	Async sent but buffer allocator full (spam	BR_ONEWAY_SPAM_SUSPECT



Work Type Enum	Queued On	Triggered When	Userspace Response
		suspect)	
BINDER_WORK_DEAD_BINDER	binder_proc->todo	Referenced remote process dies (death recipient registered)	BR_DEAD_BINDER
BINDER_WORK_DEAD_BINDER_AND_CLEAR	binder_proc->todo	Client dies during unregistering death notification	BR_DEAD_BINDER
BINDER_WORK_CLEAR_DEATH_NOTIFICATION	binder_proc->todo	Client requests to unregister death notification	No direct response
BINDER_WORK_RETURN_ERROR	binder_proc->todo	Error occurs in transaction (e.g., failed target, invalid data)	BR_ERROR

Key Details:

- Asynchronous transaction queuing happens in binder_node->async_todo first, not directly to thread or process workqueues.
- Reply routing guarantees that the initiator thread receives the reply, ensuring stack continuity.
- Death-related work is delivered **only if the client has registered for it** via **binder_link_to_death()**.
- Work items always go through binder_work, even if embedded in larger objects (binder_transaction, binder_ref_death, etc).

Let me know if you'd like a flow diagram, kernel path walkthrough, or a real example like what happens during binder_transaction() in the kernel.



24. Binder Node

The BINDER_WORK_NODE work item provides updates to the client about the presence or absence of strong or weak references of a binder_node. Depending on who initiated the operation, Binder assigns the binder_node->work as a BINDER_WORK_NODE work item to either the main client workqueue or a client thread workqueue.

For example, if a client sends a BINDER_TYPE_BINDER to another client, which results in the creation of a binder_ref and an increase in the strong reference of the binder_node, Binder then assigns the work item to the workqueue of the client thread that sends it. Meanwhile, if another client acquires a strong reference on its binder_ref, leading to an increase in the strong reference of the binder_node owned by another client, Binder assigns the work item to the main workqueue of the other client.

Binder informs the userspace changes the presence or absence of strong or weak references only once. Binder uses the has strong ref and has_weak_ref fields within the binder_node to monitor the changes. When Binder processes the BINDER_WORK_NODE work item, it updates these fields and returns one of four responses based on the changes:

```
BR_INCREFS: has_weak_ref transitions from zero to one
BR_ACQUIRE: has_strong_ref transitions from zero to one
BR_RELEASE: has_strong_ref transitions from one to zero
BR_DECREFS: has_weak_ref transitions from one to zero
static int binder_thread_read(...)
{
    case BINDER_WORK_NODE: {
        // Save the previous values
        has_strong_ref = node->has_strong_ref;
        has_weak_ref = node->has_weak_ref;
        // Update the presence of strong and weak references
        if (weak && !has_weak_ref) {
             node->has weak ref = 1;
        ... }
        if (strong && !has_strong_ref) {
             node->has_strong_ref = 1;
        ... }
        if (!strong && has_strong_ref)
             node->has_strong_ref = 0;
        if (!weak && has_weak_ref)
             node->has_weak_ref = 0;
        // Check for any changes and return approriate responses
        if (weak && !has_weak_ref)
             ret = binder_put_node_cmd(..., BR_INCREFS, "BR_INCREFS");
        if (!ret && strong && !has_strong_ref)
             ret = binder_put_node_cmd(..., BR_ACQUIRE, "BR_ACQUIRE");
        if (!ret && !strong && has_strong_ref)
             ret = binder_put_node_cmd(..., BR_RELEASE, "BR_RELEASE");
        if (!ret && !weak && has_weak_ref)
             ret = binder_put_node_cmd(..., BR_DECREFS, "BR_DECREFS");
Error
When certain operations either complete or fail, Binder queues the BINDER_WORK_RETURN_ERROR work item into the workqueue of the client
```

You've explained the Binder Node work item (BINDER_WORK_NODE) and Error handling (BINDER_WORK_RETURN_ERROR) very clearly. Here's a consolidated summary with diagrams and notes to reinforce your points:

thread that initiated it. Binder processes this work item and returns either the BR_OK or BR_ERROR response back to userspace.

Binder Node Work Item (BINDER_WORK_NODE)

Notifies clients when the strong or weak reference count on a binder_node changes from or to zero.

When it's queued:



- When reference count changes on a binder_node
- Queued to:
 - binder_thread->todo: if change was caused by this client thread
 - binder_proc->todo: if change was caused externally (from another client)

Reference change tracking fields:

```
struct binder_node {
   int has_strong_ref; // 0 or 1
   int has_weak_ref; // 0 or 1
};
```

Userspace notifications:

Transition	Userspace Response
has_weak_ref: 0 → 1	BR_INCREFS
$\textbf{has_strong_ref:} \ 0 \rightarrow 1$	BR_ACQUIRE
$\textbf{has_strong_ref:} \ 1 \rightarrow 0$	BR_RELEASE
has_weak_ref: 1 → 0	BR_DECREFS

Note: Each of these is reported **once**, only when transitioning across the zero threshold.

🔁 Example Flow: Binder Reference Propagation

Let's say:

- 1. Process A sends a BINDER TYPE BINDER object to B
- 2. This creates a binder_ref in B, referencing a binder_node owned by A
- 3. This causes:
 - has_strong_ref on A's binder_node to go $0 \rightarrow 1$
 - A BINDER_WORK_NODE is queued to A's main workqueue
 - A receives BR_ACQUIRE

Later, when ${\bf B}$ drops the ref and the count goes to 0:

• A receives BR_RELEASE

X BINDER_WORK_RETURN_ERROR (Error Work Items)

Purpose

To notify userspace about completion or failure of a binder operation (e.g., reply not deliverable, dead target, or malformed transaction).

When it's queued:

- · Sent to the thread that initiated the action
- Queued to: binder_thread->todo

Userspace responses:

Condition	Userspace Response
Operation succeeded	BR_0K
Operation failed (e.g., no target, invalid handle)	BR_ERROR

This helps the originating thread know the result of its Binder operation at the kernel level.

Summary Table (for Quick Review)

Work Type	Queued On	Trigger	Userspace Response
BINDER_WORK_NODE	Thread or main queue	Ref count change on binder_node	BR_INCREFS, BR_ACQUIRE, BR_RELEASE, BR_DECREFS
BINDER_WORK_RETURN_ERROR	binder_thread->todo	Operation fails or completes	BR_OK, BR_ERROR



Let me know if you'd like a **diagram** showing reference propagation and transitions or how these link to death notification and GC.





25. Dploaded image

Binder Buffer Allocator

Initialization

Binder implements a memory allocator to store incoming transaction data, which we will call the binder buffer allocator. Every client binder_proc owns a binder buffer allocator binder_alloc which allocates memory for incoming transaction data.

During initialization, a client must create a memory map for the Binder device file descriptor as follows:

```
#define BINDER_VM_SIZE 4 * 1024 * 1024
```

int binder_fd = open("/dev/binder", O_RDWR | O_CLOEXEC);

void *map = mmap(nullptr, BINDER_VM_SIZE, PROT_READ, MAP_PRIVATE, binder_fd, 0);

The mmap syscall will call binder_mmap to reserve a virtual memory area and map it to the userspace. Binder defers the allocation of physical backing pages to store incoming transaction data until needed (lazy allocation).

Great — you've covered the **Binder Buffer Allocator** setup and initialization process accurately. Here's a clean summary and explanation of the image and concept you described:

Binder Buffer Allocator Overview

Each client process in the Binder IPC system owns a memory allocator (binder_alloc) used to store incoming transaction data (like marshaled objects, file descriptors, etc.).

X Initialization Process

1. User space code calls mmap() on /dev/binder:

```
#define BINDER_VM_SIZE (4 * 1024 * 1024) // 4MB
int binder_fd = open("/dev/binder", 0_RDWR | 0_CLOEXEC);
void *map = mmap(nullptr, BINDER_VM_SIZE, PROT_READ, MAP_PRIVATE, binder_fd, 0);
```

- 2. This triggers the **Binder driver's binder_mmap()** in the kernel:
 - Reserves a virtual memory area of size BINDER_VM_SIZE
 - No actual physical memory is allocated yet (lazy allocation)
- 3. Binder allocates the pages only when needed, for example:
 - When receiving large binder_transaction payloads

What's Shown in the Diagram

- The gray block labeled BINDER_VM_SIZE represents the mapped virtual memory region in client A's userspace.
- The pink arrow labeled "Virtual Memory Mapping" shows how kernel pages are mapped back to userspace.
- The bottom right block shows:
 - binder_proc: Each process has one
 - binder_alloc: Allocator associated with the process

Key Points

Component	Purpose	
binder_proc	Per-process structure managing IPC state	
binder_alloc	Handles memory allocation for incoming data	
BINDER_VM_SIZE	Maximum memory that can be mapped for transaction data (typically 4 MB)	
Lazy Allocation	Physical memory is not allocated during mmap () — only on actual use	



Let me know if you'd like a deep dive into allocation strategy, slab reuse, or memory reclamation (BC_FREE_BUFFER) in the Binder allocator!



26. confusing explain in simple words

Sure! Let's break it down **super simple**, step by step:

ia What is Binder Buffer Allocator?

When apps on Android send messages to each other using **Binder**, the kernel needs a place to **store the message data** (like strings, numbers, files, etc.).

This "place" is called the **Binder Buffer Allocator** — it's like a **mailbox** for each app.

What Happens When an App Starts Using Binder?

1. The app opens /dev/binder, which is like telling the OS:

"Hey, I want to send or receive messages using Binder."

2. The app maps some memory using mmap() (this means:

"Reserve me 4 MB of memory to use as a mailbox.")

- This memory is called **BINDER_VM_SIZE** (usually 4 MB).
- It sits in the app's virtual memory space (the app sees it but it's not filled yet).
- 3. Inside the kernel, Binder keeps track of:
 - Who the app is (binder_proc)
 - The app's memory mailbox (binder_alloc)

Does Binder Fill That Memory Immediately?



Binder $\operatorname{doesn't}$ give real memory pages right away — it waits until needed.

This is called lazy allocation.

🥊 Real-Life Analogy:

Imagine you rent a 4 MB storage locker but only get charged **when you actually put stuff in it**. Binder does the same — it gives your app a 4 MB slot, but fills it **only when a message comes**.

✓ Summary:

Step	What Happens	
1	App opens /dev/binder	
2	App asks for memory with mmap()	
3	OS reserves 4 MB space in app memory	
4	Binder only fills it when a message arrives	

Let me know if you want this explained with a picture or animation too!



27. Binder relies on the integrity of the transaction data in the allocator's memory for cleanup. If the active transaction data is corrupted, it could lead to memory corruptions and even code execution in the kernel as demonstrated in the CVE-2020-0041 and CVE-2023-20938 writeups. As a result, Binder only allows users to create a read-only memory map (PROT_READ) and prevents them from modifying its access permission later.

You're asking about why Binder uses read-only memory mappings, and here's the explanation in very simple terms:

♦ The Problem: Data Corruption Can Be Dangerous

Binder stores message data in a special shared memory area (the allocator memory).

If a malicious or buggy app were allowed to change that memory after the kernel starts using it, it could:

- Corrupt important internal data structures.
- Crash the system (kernel panic).
- Even take control of the kernel (security attack), like in:
 - CVE-2020-0041
 - CVE-2023-20938

The Solution: Make It Read-Only

To protect itself, Binder says:

"I'll let you read this memory, but you are **not allowed to write to it**."

That's done by mapping the memory as:

PROT_READ // Read-only access

Also, the kernel blocks any attempts to change the access later with tricks like mprotect() or remapping.

Why This Works

- Apps can **see** what's in the shared memory (to know what's being sent/received).
- But they can't change it, which means:
 - No accidental corruption
 - No sneaky hacks
 - No kernel crashes

✓ Summary

? What?	☑ Why?
Memory is mapped read-only	To stop apps from corrupting Binder's data
Writes are blocked entirely	Protect the kernel from bugs and attacks
Based on past CVEs	Binder learned from real-world attacks

Let me know if you'd like a visual for this too!





28. Best-Fit Allocation

The binder buffer allocator implements the best-fit allocation strategy with the kernel's red-black tree data structure (rb_tree). The binder buffer allocator starts with a single binder_buffer, which takes up the whole buffer space and is labeled as unused.

Let's break down Best-Fit Allocation in Binder in simple words:

What is Binder Buffer Allocator?

When an app sends data using Binder, the **Binder driver** needs to temporarily store that data. To do this, it uses a special memory region called the **Binder Buffer**.

6 What is "Best-Fit Allocation"?

Imagine you have a **notebook** with free and used sections.

You want to write a new note and are looking for a **blank space** just big enough for your note—not too big, not too small.

That's **best-fit**: it finds the smallest empty slot that **best fits** the data you want to store.

How does Binder implement Best-Fit?

- 1. Binder tracks **free memory chunks** using a **red-black tree** a special tree structure that makes searching fast.
- 2. When data arrives:
 - It looks through the tree for the **smallest free space** that's big enough.
 - It picks the **best match** (smallest possible chunk that fits the data).
 - This helps reduce memory waste (called fragmentation).

📠 Example

Suppose you have 3 free chunks:

Chunk Size	Used?
64 KB	X Free
128 KB	X Free
256 KB	X Free

If you need 100 KB:

- Binder won't pick 256 KB (too big).
- It will choose 128 KB the smallest chunk that fits the request.

It Starts with One Big Chunk

When the buffer is initialized:

- It's just one big empty block (binder_buffer)
- As transactions are sent and memory is used:
 - Big block gets **split** into smaller blocks
 - Freed blocks go back into the red-black tree

🖈 Summary

Term	Meaning in Simple Words
Best-Fit Allocation	Choose the smallest space that fits the data
Red-Black Tree (rb_tree)	Fast data structure to track free space



Term	Meaning in Simple Words
binder_buffer	A block of memory in Binder's pool

Let me know if you'd like a visual diagram for this concept!



29. When sending a transaction to a client, Binder first allocates a binder_transaction object to store information about the transaction. Then, the binder buffer allocator allocates a binder_buffer object to own a chunk of memory in the memory map and assign it to the binder_transaction.

Sure! Here's a simple explanation of what happens when Binder sends a transaction to a client:

Step-by-Step: How Binder Sends Data

Let's say **Process A** wants to send a message (transaction) to **Process B** using Binder.

Step 1: Allocate binder_transaction

- Binder creates a binder_transaction structure in the kernel.
- Think of it like a **container** that stores metadata about the transaction:
 - · Who is sending?
 - · Who is receiving?
 - What data is being sent?

Step 2: Allocate Memory with binder_buffer

- Binder now needs a place to store the actual data (the message).
- It uses its binder buffer allocator to:
 - Find a free chunk of memory in the memory-mapped region.
 - Allocate that chunk using a binder_buffer object.

Step 3: Link the Two Together

- The allocated memory (binder_buffer) is attached to the transaction container (binder_transaction).
- Now, the transaction has:
 - Metadata (who, what, where) → binder_transaction
 - Actual data (the message) → binder_buffer

Then What?

- Binder queues this transaction to the receiver's workqueue.
- The receiving process reads the message from the **mapped memory** (read-only).
- After it's done, Binder can free the memory back to the pool.

😍 Visual Summary

This structure ensures:

- Memory is safely and efficiently used.
- The kernel can track what memory belongs to which transaction.

Let me know if you want a diagram to visualize this flow!





30. Dploaded image

When sending a transaction to a client, Binder first allocates a binder_transaction object to store information about the transaction. Then, the binder buffer allocator allocates a binder_buffer object to own a chunk of memory in the memory map and assign it to the binder_transaction.

Great — you're looking at how Binder manages memory during a transaction. Let me explain this diagram and the concept in very simple terms.

What's Going On?

When Binder sends a message (called a transaction) from one process to another, it does two things internally:

1. binder_transaction (the container)

This is a **structure** created in the **kernel** that holds metadata:

- Who is sending the message?
- Who will receive it?
- · How large is the data?
- · Which buffer holds the message?

It's like a "cover page" on a document — contains all the important info but not the actual content.

2. binder_buffer (the memory)

This is the actual **chunk of memory** used to store the message (transaction data).

Binder uses the memory it mapped earlier (mmap) and cuts out a piece using a binder_buffer structure. This memory contains:

- The message data
- The **offsets** (for Binder object references)

The binder_buffer is then linked to the binder_transaction so the kernel knows which memory goes with which message.

Diagram Breakdown

Top Half (Boxes & Arrows):

- binder_proc (the client process)
- owns binder_alloc (the memory allocator),
- which gives memory to binder_buffer.
- The binder_buffer is linked to a binder_transaction.

This happens for each transaction, so you see multiple transactions and buffers.

Bottom Half (Memory Layout):

Represents the actual memory mapped area:

css

[buffer][offsets][buffer][offsets] ... [unused space]

Each binder_buffer holds:

- data: what the sender wants to transmit
- offsets: references to Binder objects (e.g., file descriptors, handles)

The rest of the space is marked as unused, ready for future allocations.



Summary

Part	Meaning
binder_transaction	Info about the message (who, what, size)
binder_buffer	Actual memory storing the data
binder_alloc	The manager that gives out chunks of memory
offsets	Special pointers to Binder objects
unused	Free space for next messages

Let me know if you'd like me to label or annotate this diagram visually for better understanding!



31. confused with the offset here explain in simple

Great question — let's break down what "offsets" mean in Binder transactions using a simple example and analogy.

What is an "offset" in Binder?

In Binder, **offsets** are like **sticky notes** that mark where special objects (like Binder handles, file descriptors) are placed **inside the buffer**. They help the Binder driver and receiver **know which part of the message contains a special Binder object**, not just raw bytes.

• Imagine this:

Suppose Process B sends this message to Process A:

```
struct {
  int x = 42;
  sp<IMyService> myService;
  int y = 99;
};

// just data
// Binder object
// Binder object
// more data

// more data
```

Now Binder will:

- 1. Pack all this into a **buffer** (binary memory).
- 2. Recognize that myService is a Binder object, not just normal data.
- 3. Write the full struct into the buffer like this:

```
css
[ 42 ][ HANDLE_of_myService ][ 99 ]
```

Why we need offsets:

Binder doesn't automatically know where the Binder object is inside the buffer, so it uses a second list called offsets to say:

"Hey! At byte offset 4 (i.e., second element), there's a Binder object!"

This **offset list** is sent **along with the buffer**.

So in the diagram:

Buffer:

```
kotlin
buffer: [ raw data | raw data | Binder object | raw data ]
```

Offsets:

```
vbnet

offsets: [location of Binder object inside buffer]
```

Together, they help Binder:

- Know where the real objects are,
- Treat them specially (e.g., reference counting, death notification),
- And serialize/deserialize them properly.



🔚 Summary (in plain words)

Term	Meaning
Buffer	The whole message (includes integers, strings, binder handles, etc.)
Offset	Points to the exact byte position in the buffer where a Binder object (like a service) is stored
Why needed?	To tell Binder which parts of the message are just data and which are special Binder objects

 $Let \ me \ know \ if \ you'd \ like \ me \ to \ draw \ or \ visualize \ this \ with \ real \ numbers \ or \ bytes \ -- \ that \ can \ make \ it \ even \ clearer.$



32. Dploaded image

Allocate a Buffer

When a client (Client A) sends a transaction with data, Binder allocates a binder_buffer from the target client's (Client B) binder buffer allocator and copies the data into it. The target client receives the transaction and reads the data from the memory map.

This image perfectly demonstrates how **Binder buffer allocation and object offsets** work when **Client A sends a transaction to Client B**. Let me walk you through it **step-by-step in simple words**, especially focusing on the **offsets** part.

1. Client A sends a transaction

- ioctl(fd, BINDER_WRITE_READ, ...) is called by Client A.
- This includes a BC_TRANSACTION command and a structure called binder_transaction_data.
- Inside that structure:
 - buffer holds the actual data: it may include primitive values, strings, or Binder objects like flat_binder_object.
 - offsets is a list of byte positions that point to special Binder objects inside the buffer.

Example:

```
buffer = [ flat_binder_object | opaque data | object 2 | object 3 | ... ]
offsets = [ θ, 12, 16, ... ] // "Hey, there's a special object at byte θ, 12, 16..."
```

2. Binder kernel copies the data

- Binder allocates a new binder_buffer for Client B from its memory map (which was mmap'd earlier).
- It then **copies the buffer and offsets** from Client A into Client B's mmap'd space.
- This copied data lives in Client B's memory, and is read-only mapped into user space (for safety).

So:

- The buffer is the raw data.
- _ The offsets help Binder identify which parts of that data are actual Binder objects (so it can handle them correctly).

3. Client B reads the transaction

- Client B calls ioctl(fd, BINDER WRITE READ, ...) to read.
- Kernel gives it a BR_TRANSACTION response.
- The binder_transaction_data now contains pointers to the buffer and offsets inside Client B's memory space.

So Client B can:

- Access the raw message.
- Know where the Binder handles (or file descriptors, etc.) are inside the message.

6 Why "offsets" matter:

Think of the message like a box of mixed items. Offsets are like labels on the box:

- "This item is special (Binder object). Handle it differently."
- Without these labels, Binder wouldn't know what's just data and what's a handle or remote reference.

✓ Summary:



Component	Description	
buffer	Raw data (including Binder objects)	
offsets	Byte positions that say: "this part is a Binder object"	
Why needed?	So Binder and receiver can parse and interpret the message correctly	
mmap	Memory shared between user and kernel for efficient transfer	

Let me know if you'd like a breakdown of how flat_binder_object works or what happens if the object is a file descriptor!



33. explain the image in detail

Absolutely! Let's break down the **image** step-by-step in a clear and detailed way. This is about how **Binder IPC** (Inter-Process Communication) passes data between two processes using **shared memory** and **Binder buffers**.

ℯ Context of the Diagram

The image describes what happens when **Client A sends a transaction to Client B** using Binder IPC. The transaction data is passed through kernel space using a special memory-mapped buffer.

STEP 1: Client A Sends a Transaction

```
ioctl(fd, BINDER_WRITE_READ, &bwr);
```

- Client A is invoking ioctl() to send a Binder transaction.
- bwr contains a write_buffer that includes the BC_TRANSACTION command.
- This command carries a structure: struct binder_transaction_data.
- What's inside binder_transaction_data?
- **buffer**: Pointer to actual transaction data (e.g., strings, objects).
- offsets: Array of byte positions within the buffer where special Binder objects are located (e.g., handles, file descriptors).

These offsets help Binder kernel recognize what parts of the buffer require special handling.

STEP 2: Binder Kernel Processes the Transaction

- What happens in kernel space:
 - Kernel allocates memory for **Client B** using its binder allocator (binder_alloc).
- A new binder_buffer is created in Client B's mapped memory region.
- The kernel:
- 1. Copies the buffer from Client A into Client B's mapped region.
- 2. Copies the offsets array into the corresponding location.
- 3. Tracks this whole transaction using a ${\tt binder_transaction}$ object.

🔄 Visual Data Flow:

- Green region (top half): Represents Client A's buffer and offsets.
- Red arrows: Kernel copies the buffer and offsets into Client B's memory.
- Yellow regions (bottom half): Now show these copied buffers inside Client B's user-mapped memory.

This transfer is completely invisible to userspace; Binder handles this behind the scenes using virtual memory mapping.

Memory Layout Breakdown

```
struct binder_transaction_data {
  void* buffer; <-- points to copied data in receiver's mmap space</pre>
```



```
void* offsets; <-- points to copied offsets in receiver's mmap space
}</pre>
```

Inside memory (simplified):

```
buffer: [ flat_binder_object | opaque data | object 2 | object 3 ... ]
offsets: [ 0 , 12 , 16 , ... ]

points to these Binder objects inside buffer
```

This tells Binder:

- At byte 0, there's a flat_binder_object
- At byte 12, there's another object
- etc.

STEP 3: Client B Reads the Transaction

• Client B calls:

```
ioctl(fd, BINDER_WRITE_READ, &bwr);
```

- Kernel replies with a **BR_TRANSACTION** command, including a pointer to the copied:
 - buffer (transaction data)
 - offsets (locations of special objects)

Now, Client B can access:

- Data content (read_buffer)
- Information on where the Binder handles or special objects are located (via offsets)

Summary: Purpose of Everything in the Image

Component	Purpose
write_buffer	What Client A sends initially
binder_transaction_data	Contains the buffer + offsets metadata
buffer	Holds the actual data (some may be Binder objects)
offsets	Byte positions that indicate special Binder objects inside buffer
binder_proc	Per-client Binder structure in kernel
binder_alloc	Memory allocator for that process
binder_buffer	Represents a chunk of memory used in the transaction
Virtual Memory Mapping	Allows kernel to share memory safely with user apps

Final Notes

• Why use offsets?

Because Binder needs to safely and correctly interpret special objects (e.g., handles, file descriptors) passed between processes.

• Why memory mapped?

To avoid expensive copy_to_user() and copy_from_user() operations, and allow efficient zero-copy communication.

Let me know if you'd like a simplified diagram or if you want to explore what flat_binder_object contains or how this is handled when you pass a file descriptor or callback!



34. Dploaded image

Free a Buffer

To free a transaction and its data, a client sends a BC_FREE_BUFFER message with the start address of the transaction data. Binder then frees the binder_transaction and sets the free field of the binder_buffer. If adjacent memory is also freed, the binder buffer allocator merges the two binder_buffer into one.

Let's break down this image in a **simple, step-by-step** way. The diagram shows **how a Binder transaction's memory is freed** and **how the kernel reclaims and merges that memory**.

What's This About?

This diagram explains what happens when a client frees a binder transaction after reading/using it. The Binder driver cleans up the memory that was allocated for the transaction.

STEP 1: Client A Frees a Transaction

ioctl(fd, BINDER_WRITE_READ, &bwr);

• Inside bwr.write_buffer, the command is:

срр

срр

BC_FREE_BUFFER

- This tells the kernel: "I'm done with this buffer, free it."
- It also passes a void pointer* to the memory region that was used (address of the buffer).
- Why?

Client A had received transaction data. After processing, it must explicitly tell Binder to free that memory.

- What Happens in the Kernel:
 - Binder marks that buffer as unused.
 - In the diagram:
 - The **buffer + offsets** are now colored gray → showing they are freed.
 - The red outline around them emphasizes which block is being deallocated.

STEP 2: Binder Merges Adjacent Free Memory

After marking that buffer as free, Binder tries to merge adjacent freed blocks to reduce fragmentation (like a memory defragmenter).

Why merge?

It reduces wasted space and allows future larger allocations.

- Merge Logic:
- Binder uses binder_alloc to manage all allocated blocks (binder_buffer).
- If the just-freed block is next to another free block, Binder merges them into one bigger binder_buffer.
- Visual Flow (bottom diagram):

- $\bullet \ \ binder_proc \to \text{OWNS} \to binder_alloc$
- binder_alloc manages many binder_buffer blocks.
- A binder_transaction refers to a binder_buffer.
- $\bullet\,$ The red ${\tt binder_transaction}$ and ${\tt binder_buffer}$ are being deleted.
- Then Binder merges the freed memory with the neighboring binder_buffer, creating a larger free chunk.

Summary of Key Concepts

Concept	Meaning
BC_FREE_BUFFER	Tells Binder to free memory used by a transaction
binder_buffer	Represents a memory block used in a transaction
binder_alloc	Binder's custom memory allocator
Merge adjacent buffers	Helps prevent fragmentation and supports best-fit allocation strategy
Red/gray blocks	Indicate freed memory
Pink arrows	Show virtual memory mapping from kernel to userspace

🔁 Real World Analogy

Imagine you rented 2 adjacent rooms in a hotel. When you're done and leave, the hotel merges them back into one large room, so it's easier to book next time someone wants a big space. This is what Binder does with memory blocks.

Let me know if you want to walk through the code path in the kernel (binder_free_buf(), binder_alloc_free()), or how it uses the red-black tree to track free blocks!



35. Zero Out Transaction Data

The binder buffer allocator does not zero out the transaction data after freeing the transaction. A client has read access to the memory map, so it can still read the transaction data after freeing it (BC_FREE_BUFFER). To zero out the transaction data after free, the sender must explicitly set the TF_CLEAR_BUF flag in the binder_transaction_data when sending the BC_TRANSACTION command.

For stub and proxy code generated from the AIDL, developers can annotate the interface with @SensitiveData to explicitly set the TF_CLEAR_BUF flag in all outgoing transactions. This prevents sensitive data in the transaction from remaining in memory after free. For example, the IKeyMintOperation.aidl AIDL interface used by Keymint is annotated with @SensitiveData.

@SensitiveData interface IKeyMintOperation $\{ \dots \}$

Let's break this concept down in very simple terms:



What is the Problem?

When a client frees a binder transaction using BC_FREE_BUFFER, the memory is marked as free by the Binder driver, but...

Interior The actual data in that memory is not cleared (zeroed out).

So even though the memory is no longer "in use," the **client can still read it** from userspace because the memory was only marked as free, not erased.

This could lead to a security risk if the freed memory contained sensitive information like:

- passwords
- · cryptographic keys
- health records
- messages

How to Fix This?

When sending a transaction (BC TRANSACTION), the sender can tell Binder to zero out (wipe) the memory after it's freed by setting a flag called:

C
TF_CLEAR_BUF

This ensures that when the buffer is freed, the data is wiped (set to zero) in memory.

March How Developers Can Use This Easily

When using AIDL (Android Interface Definition Language), developers usually don't write binder_transaction_data by hand.

To automate the setting of the TF_CLEAR_BUF flag, you can annotate the AIDL interface with:

```
@SensitiveData
interface MySecretInterface { ... }
```

This automatically:

- Tells the Binder framework to set TF_CLEAR_BUF for all transactions via this interface.
- Ensures **sensitive data is erased** from memory after the transaction is processed.

Real Example:



```
aidl
@SensitiveData
interface IKeyMintOperation {
       void begin();
void update();
void finish();
}
```

- IKeyMintOperation is used in Android's cryptographic framework (KeyMint).
- Its transactions may carry secret keys.
- Marking it with <code>@SensitiveData</code> ensures memory is **cleaned up** safely after use.

TL;DR

Concept	Purpose
BC_FREE_BUFFER	Frees the buffer, but does not zero it out
TF_CLEAR_BUF	Tells Binder to wipe data before freeing
@SensitiveData	AIDL annotation to automatically set TF_CLEAR_BUF
Why?	Prevents data leaks and memory snooping after free

Let me know if you want a diagram or kernel code explanation of how ${\tt TF_CLEAR_BUF}$ is handled!





36. Binder Transaction Stacks

As we discussed in Binder Concurrency Model, a single-threaded client cannot retrieve the next incoming transaction until it has responded to the current one. On the caller side, a single-threaded client cannot initiate a new RPC (BC_TRANSACTION) until it receives a reply (BR_REPLY) to the previous RPC. To maintain these orders, Binder tracks every incoming and outgoing transaction between two different threads on a transaction stack. The purpose of transaction stacks is different from the Binder Workqueues whose purpose is to support concurrency among multiple threads in a client.

Note: Every transaction is only associated with one sender thread and one receiver thread during its lifetime, regardless of whether the client is multithreaded or not.

Let's break this down simply.

What Are Binder Transaction Stacks?

Binder Transaction Stacks are used to:

- Track and maintain order of ongoing transactions (calls & replies),
- For each thread, whether it is a sender or a receiver.

Why Are They Needed?

Because of synchronous behavior:

- A thread can't **start a new transaction** until it gets a **reply** to the previous one.
- A thread can't handle a new incoming transaction until it finishes responding to the current one.

This means:

- Caller thread is blocked until it gets BR_REPLY.
- Callee thread is blocked until it finishes processing the BR_TRANSACTION.

Key Concept:

Every **transaction** involves exactly:

- One sender thread (caller)
- One receiver thread (callee)

Binder keeps a stack per thread to enforce this 1:1 relationship and preserve the call/return order.

🚛 Analogy:

Think of each thread having a stack of tasks like this:

Caller Thread Stack:

```
vbnet

Call 1 (waiting for reply)

→ Call 2 (can't start yet)
```

Callee Thread Stack:

```
vbnet
Handle Call 1 (must finish reply)
```

Until Call 1 is done, you can't move forward.

Difference from Binder Workqueues

Binder Workqueues	Binder Transaction Stacks
For concurrency (multithreaded apps)	For strict call-return order
Manages list of work items	Tracks call stack per thread
Used to deliver transactions	Used to enforce that each thread handles one at a time

Why Is This Important?

Without transaction stacks:

- Threads could initiate or handle multiple transactions at once,
- Which would break ordering,
- And lead to bugs or undefined behavior.

Even in Multi-threaded Clients?

Yes, each transaction is bound to a single sender and receiver thread, even in a multithreaded process.

So each thread has its **own** stack tracking the **exact call/response sequence** it's involved in.

Would you like a diagram showing how the caller/callee stacks grow and shrink as transactions happen?





37. Dploaded image

A Chain Request with Multiple Clients

It is common to have multiple clients working with each other to serve a RPC request. The diagram below shows an example of a RPC originating from A that involves multiple single-threaded clients.

Great — let me walk you through this image step-by-step in **simple words**, showing how **Binder transaction stacks** handle a chain of RPCs (Remote Procedure Calls) across multiple **single-threaded clients**: $A \rightarrow B \rightarrow C \rightarrow D$.

Scenario Overview

- A calls B
- B calls C
- C calls D
- D needs to ask B something before replying to C

Each client is single-threaded, so they must complete a current transaction before starting or handling another one.

🧵 What's Happening in the Diagram

\blacksquare A \rightarrow B

- Client A starts a transaction to client B.
- B is now **blocked**, processing this request.
- On B's thread stack:
 - ← transaction from A

2 B → C

- To serve A, B sends a **new transaction** to C.
- Now C is busy processing B's request.
- On C's stack:
 - ← transaction from B
- On B's stack:
 - ← transaction from A → transaction to C

3 C → D

- Similarly, C sends a transaction to D.
- D starts processing.
- On D's stack:
 - \leftarrow transaction from C
- On C's stack:
 - ← from B → transaction to D

$\boxed{4} \quad \bullet \quad D \rightarrow B$

- Now D can't finish its reply to C yet.
- It needs more data from B, so it sends another transaction to B.

Important!

This works only because:

- B has multiple threads OR
- The Binder kernel uses transaction stack tracking to allow nested transactions like this without deadlock.

5 B Replies to D

- B responds to D.
- D now has everything it needs.

D Replies to C

• D finishes its part and replies to C.

C Replies to B

• C is done, so it sends a reply back to B.

B Replies to A

• Finally, B can now respond back to A.

Stack-Like Execution

This chain looks like a call stack:

```
less
A \rightarrow B \rightarrow C \rightarrow D
\uparrow \qquad | \qquad |
| \leftarrow B \text{ (needed info)}
```

And replies go in reverse:

```
css
← A ← B ← C ← D
```

Key Takeaways

- Each transaction is **tracked** in a thread-specific **Binder transaction stack**.
- A thread can only send one outgoing synchronous transaction at a time.
- A thread must wait for a reply before continuing.
- Binder ensures this nested request chain doesn't deadlock by maintaining transaction stack logic.

Would you like a simplified version of this scenario visualized like function calls (stack view)?



38. It is a chain of transactions in the following order:

Binder allows a client to handle multiple pending transactions at the same time. For example, client B has two pending transactions at one point, one coming from A and another coming from D. However, the client can only respond with BR_REPLY to those pending transactions in the last-infirst-out (LIFO) order. In addition, when one of the clients in the chain dies, Binder ensures proper error handling by delivering errors back to every involved client in the correct order.

Exactly! You're describing how **Binder's transaction stack** works with **LIFO (Last-In-First-Out)** ordering — just like a function call stack in programming. Let's simplify and summarize this whole flow:

$\label{eq:constrain}$ Transaction Chain: $A \to B \to C \to D \to B$

+ Transaction Stack Growth (LIFO style)

Every time a transaction is sent, it's **pushed** onto the receiver's stack.

Here's how the stack evolves:

- 1. $\mathbf{A} \rightarrow \mathbf{B}$
 - B gets a transaction from A
 - Stack: [A → B]
- 2. $\mathbf{B} \rightarrow \mathbf{C}$
 - C gets a transaction from B
 - Stack: [A → B → C]
- 3. $\mathbf{C} \rightarrow \mathbf{D}$
 - D gets a transaction from C
 - Stack: [A → B → C → D]
- 4. **D** → **B**
 - B gets a **second transaction**, this time from D
 - Stack: $[A \rightarrow B, D \rightarrow B]$

Now B has 2 active transactions

- One from A
- One from D

binder allows this — B can handle both transactions.

🧵 Important Rule: LIFO Reply Order

When replying using ${f BR_REPLY}$, Binder enforces:

- ✓ Last-In-First-Out (LIFO)
 - B must reply to D first
 - Only after that can it reply to A

So reply flow is:

```
B (reply to D)
D (reply to C)
C (reply to B)
```

X What if a client dies?

Let's say **C crashes** or exits unexpectedly.

Binder will:

- Automatically unwind the stack
- Return BR_DEAD_REPLY or BR_FAILED_REPLY back to B
- Then back to A

Ensuring that **every caller** knows something went wrong.

☑ Summary (in simple terms):

Concept	Explanation
LIFO replies	Reply must follow the reverse order of transaction calls (like call stacks)
Multiple pending calls	A client can receive multiple calls, but replies go in stack order
Crash handling	If one link in the chain fails, Binder sends errors up the stack

Would you like a visualization of this LIFO stack behavior or crash case?



39. Two Stack Layouts

Binder puts every transaction on two different stacks, which we will call the chain transaction stack and the thread transaction stack.

Let's have an overview of the functions each stack serves:

Chain transaction stack

The order of transactions of a chain request.

Binder traverses it to clean up the chain request when one of the clients exits early.

Thread transaction stack

The order of transactions that is sent or received by a client

Binder traverses it to clean up and release transactions, which a client participated in before exit.

Binder implements these two stacks as two linked lists with the following fields in binder_transaction:

```
struct binder_transaction {
...
    struct binder_transaction *from_parent;
    struct binder_transaction *to_parent;
...
    struct binder_thread *from;
    struct binder_thread *to_thread;
...
}
```

The binder_thread stores a pointer to the top element of its thread transaction stack in the transaction_stack field. This top element represents the last transaction that the thread sent or received.

```
struct binder_thread {
...
     struct binder_transaction *transaction_stack
...
}
```

Push a Transaction

When a client initiates a transaction (BC_TRANSACTION), Binder pushes the transaction onto the sender's thread transaction stack. This is achieved by setting the from_parent field of the new transaction (binder_transaction) to point to the current top of the sender's stack (transaction_stack). Then, the top of the stack is updated to point to the new transaction (binder_transaction).

```
binder_transaction t;
binder_thread sender;
...
t->from_parent = sender->transaction_stack;
sender->transaction_stack = t;
```

When a client reads a transaction, Binder pushes the transaction onto the receiver's thread transaction stack. This is achieved by setting the to_parent field of the new transaction (binder_transaction) to point to the current top of the sender's stack (transaction_stack). Then, the top of the stack is updated to point to the new transaction (binder_transaction).

```
binder_transaction t;
binder_thread receiver;
...
t->to_parent = receiver->transaction_stack;
receiver->transaction_stack = t;
```

Consequently, the chain transaction stack is formed by linking transactions through their from_parent fields, creating a chain of requests.

Pop a Transaction

Assuming everything is in order, when a client sends a reply (BC_REPLY), Binder pops the current top transaction of the sender's thread transaction stack. This is achieved by updating the top of the stack to point to the to_parent of the current top transaction. The popped transaction will be the one the sender had received and needs to reply to.

```
static void binder_transaction(..., struct binder_thread *thread, ...) {
...
    struct binder_transaction *in_reply_to = NULL;
...
    if (reply) {
        in_reply_to = thread->transaction_stack;
...
```



```
thread->transaction_stack = in_reply_to->to_parent;
...
}
When a client with a pending incoming transaction fails or crashes, Binder cancels the pending request by popping the current top transaction from the sender's thread transaction stack. The popped transaction will be the one the sender had sent, but the client failed to reply to. To notify the sender of the failure, Binder queues a BINDER_WORK_RETURN_ERROR work item to the sender's client thread. Later, when the sender tries to read a reply, Binder processes the work item and returns either BR_DEAD_REPLY or BR_FAILED_REPLY according to the cause of the failure.

static void binder_pop_transaction_ilocked(struct binder_thread *target_thread, ...)
{
...
    target_thread->transaction_stack =
        target_thread->transaction_stack->from_parent;
...
}
When a client with a pending incoming transaction fails to reply or crashes, Binder cancels the pending request by popping the current top
```

transaction from the sender's thread transaction stack. The popped transaction will be the one the sender had sent, but the client failed to reply to. To notify the sender of the failure, Binder queues a BINDER_WORK_RETURN_ERROR work item to the sender's client thread. Later, when the sender tries to read a reply, Binder processes the work item and returns either BR_DEAD_REPLY or BR_FAILED_REPLY according to the cause of the failure.

Great! Let's break this all down in simple, clear terms, with the core idea being:

Binder uses two stacks per transaction to keep track of both the chain of RPCs and individual thread activity.

Why Two Stacks?

- 1. Chain Transaction Stack (from parent)
 - Tracks who called whom in a chain of transactions.
 - Helps clean up the full RPC chain if any client in the middle crashes or exits early.
 - Think of it like the **global call path** across clients.
- 2. Thread Transaction Stack (to_parent)
- Tracks all transactions handled by a single thread.
- Helps Binder release memory and clean up properly when a thread exits.
- Think of it like a per-thread call stack.

How Are They Built?

🚣 When a client sends a transaction:

- A new binder_transaction object is created.
- It's pushed onto the sender's thread transaction stack via from_parent.

```
t->from_parent = sender->transaction_stack;
sender->transaction_stack = t;
```

When another client receives that transaction:

• It's pushed onto the receiver's thread transaction stack via to_parent.

```
t->to_parent = receiver->transaction_stack;
receiver->transaction_stack = t;
```

This way, one transaction ends up in two stacks:

- One tracking the call chain
- One tracking the thread-local activity

Popping a Transaction (Reply or Crash)

✓ When replying (BC_REPLY)

Binder pops the transaction from the **receiver's thread stack**:

```
c
thread->transaction_stack = in_reply_to->to_parent;
```

X When a client crashes

Binder pops the transaction from the **sender's thread stack**:

```
thread->transaction_stack = thread->transaction_stack->from_parent;
```

Then it sends:

- BR_DEAD_REPLY if the receiver thread died
- BR_FAILED_REPLY if there was an error

Think of it Like This

Example:

Let's say:

```
CSS

A calls B
B calls C
C calls D
```

A single transaction flows across:

```
css A \rightarrow B \rightarrow C \rightarrow D
```

Binder maintains:

- \P A **chain stack**: $A \rightarrow B \rightarrow C \rightarrow D$ (linked via **from_parent**)
- **I** A **thread stack** for each thread (linked via **to_parent**)

If **C crashes**, Binder will:

- Walk the **chain** back to A using **from_parent**
- Clean up each thread's transaction stack using to_parent
- Notify A and B with proper errors (BR_DEAD_REPLY)

Summary Table

Stack Type	Field Name	Purpose
Chain Transaction Stack	from_parent	Tracks caller-to-callee path across clients
Thread Transaction Stack	to_parent	Tracks per-thread transactions
Reply Cleanup	to_parent	Pop when replying



Stack Type	Field Name	Purpose
Crash Cleanup	from_parent	Pop when client crashes before replying

Would you like a visual diagram to help make this even clearer?



40. →

Chain Transaction Stack`from_parent`Tracks **caller-to-callee** path across clientsThread Transaction Stack`to_parent`Tracks **per-thread transactions**Reply Cleanup`to_parent`Pop when **replying**Crash Cleanup`from_parent`Pop when **client crashes before replying** explain in simple words

Absolutely! Let's explain it in **very simple words**, like a real-world conversation.

Imagine a chain of people passing messages

Let's say:

- Person A asks Person B a question.
- Then **B** asks **C** for help.
- Then C asks D.

This is a chain of questions:

 $A \rightarrow B \rightarrow C \rightarrow D$

1. Chain Transaction Stack (from_parent)

- Think of this like a message chain across people.
- It remembers who started the request and who's waiting for a reply.
- So if **D crashes**, Binder knows:
 - "D was called by C"
 - "C was called by B"
 - "B was called by A"
- It uses this to tell everyone: "Sorry, your message didn't make it all the way."

2. Thread Transaction Stack (to_parent)

- Each person (thread) has their own personal task list.
- It remembers:
 - "This person is working on this request right now."
 - So they can't take a new one until they finish the current one.
- When the person finishes (sends reply), Binder **removes** it from their list.

3. What Happens When Things End?

When a person replies:

• Binder removes the request from their own task list (to_parent stack).

X If a person crashes:

- Binder follows the message chain (from_parent) to let others know.
- It sends back: "The last person didn't respond here's an error."

🖈 Simple Summary



 ₩hat	It Does	★ When Used
from_parent	Remembers who asked whom	Used when a client crashes
to_parent	Remembers what each thread is working on	Used when replying

Would you like me to draw this in a diagram for you as well?



41. → to_parent confusing

Got it! Let's break down to_parent in the simplest way possible.

What is to_parent?

Every thread (like person or worker) can be handling **only one task at a time** in Binder.

When a thread **receives** a new task (transaction), Binder puts that task on a **stack** for the thread.

Each task remembers the task that came before it using to_parent.

Visual Example

Imagine a stack of books:

```
arduino

Top: Task 3 ← most recent
Task 2

Bottom: Task 1 ← first
```

Each task points to the one **below it** using to_parent.

So:

- Task 3 → to_parent → Task 2
- $\bullet \ \ \, \text{Task 2} \rightarrow \textbf{to_parent} \rightarrow \text{Task 1}$

Why do we need this?

This helps Binder:

- Know what task the thread is currently working on (top of the stack).
- Clean up tasks one by one (like popping books off a stack).
- Enforce order: You must reply to the top task before moving to the next.

✓ When is to_parent used?

- When a thread **gets a transaction**, it's **pushed** on top of its thread stack.
- When the thread sends a reply, that task is popped off, and Binder looks at to_parent to move back down the stack.

In one line:

to_parent is like a "previous task" pointer — it tells Binder what transaction the thread was handling before the current one.

Let me know if you'd like a picture — that helps a lot too!



42. Dploaded image

Chain Transaction Stack

The chain transaction stack tracks the order of transactions in a chain, which originates from the first request.

Let's reuse the example above involving four transactions among A, B, C and D. Before B responds D, the chain transaction stack will look as follows:

Great! Let's break down the chain transaction stack in this image in very simple words.

What is the image showing?

This image shows 4 transactions happening between 4 clients:

- $A \rightarrow B$
- $\bullet \quad B \to C$
- $C \rightarrow D$
- $D \rightarrow B$

Each transaction is saved as a binder_transaction object.

Binder keeps track of these transactions using two pointers:

- $from_parent \rightarrow the previous transaction in the chain$
- to_parent → previous transaction on this thread (receiver side)

What is a chain transaction stack?

It's a **linked list** using the **from_parent** pointer that tracks the entire flow of requests in a chain.

Let's walk through the stack step by step using the image:

Transaction 1:

- A sends to B
- from = A, to_thread = B
- This is the **first transaction**, so:
 - from_parent = NULL (no previous request)
 - to_parent = NULL (B's thread is handling nothing else)

Transaction 2:

- B sends to C
- from = B, to_thread = C
- It's part of the same chain, so:
 - from_parent points to Transaction 1 (A→B)
 - to_parent = NULL (C is idle)

Transaction 3:

- · C sends to D
- from = C, to_thread = D
- Again, it's part of the chain, so:
 - from_parent points to Transaction 2 (B→C)

• to_parent = NULL

Transaction 4:

- D sends back to B
- from = D, to_thread = B
- Continues the chain:
 - from_parent points to Transaction 3 (C→D)
 - to_parent = NULL (this is the new work for B)

Chain View (from last to first):

```
D→B

↑
C→D

↑
B→C

↑
A→B
```

All connected through the from_parent field.

★ Why is this useful?

- If one client dies (say, D crashes), Binder uses this chain to clean up and send error replies in the correct order back to A.
- Helps **track responsibility** who requested what, in a multi-step RPC.

Let me know if you want a visual or simplified version of this in your own words!



43. Binder can traverse the chain transaction stack, by following the from_parent field of any transaction, to find the previous transaction and the first transaction in the chain.

Suppose client B exits before responding to the last transaction sent by D. During cleanup, Binder traverses the chain transaction stack starting from the top transaction on B's transaction_stack to look for its previous client in the chain. Then, it sends a BR_DEAD_REPLY to notify the client that there is a failed reply. In our case, Binder sends BR_DEAD_REPLY to D, which is the previous client before B in the chain.

```
A -> B -> C -> D -> B
```

Binder calls binder_send_failed_reply to traverse the chain transaction stack and sends an error_code (e.g BR_DEAD_REPLY) to the previous client in the chain.

Let's break this down in **very simple terms** using your chain:

```
css A \rightarrow B \rightarrow C \rightarrow D \rightarrow B
```

What happened?

- Client **D** made a request to **B**.
- But now B has crashed or exited before replying.

Now Binder has to clean up this situation.

What does Binder do?

Binder wants to **notify the previous client (D)** that:

"Hey, your reply from B is not coming — B is dead."

How does Binder figure out who to notify?

It uses the chain transaction stack — which is a linked list of requests — to go backwards in the chain using from_parent.

Here's what it does:

- 1. It starts from the **last transaction** (D \rightarrow B).
- 2. It looks at from parent to find the previous transaction ($C \rightarrow D$), and from that it finds out that **D** made the request.
- 3. Binder says, "Ah! D is waiting for a reply from B."
- 4. Binder sends a BR_DEAD_REPLY to D a signal that the reply won't come.

∦ What does the code do?



```
c
while (1) {
   target_thread = binder_get_txn_from_and_acq_inner(t);
```

• It tries to get the **thread** (like D) that sent the transaction t (the last one).

```
if (target_thread) {
    // Send BR_DEAD_REPLY to D
    return;
}
```

• If found, send the error (e.g. BR_DEAD_REPLY) to that thread and stop.

```
c
next = t->from_parent;
```

• If not found, keep going **backward** in the chain using **from_parent**.

₩hat does this ensure?

If **any client in a chain crashes**, Binder can:

- Walk **backward** through the chain.
- Inform every caller that something failed.
- In the correct order.

Would you like me to draw a simple box-and-arrow diagram to show this?



44. Duploaded image

Thread Transaction Stack

The thread transaction stack tracks the order of active transactions that a client has sent and received.

Following the previous example, the thread transaction stack of each client will look as follows:

This image shows how **Binder tracks active transactions** per client using a structure called the **Thread Transaction Stack** — let me explain this in simple terms using what's shown.

The Problem Binder Solves

Each app (A, B, C, D) is sending and receiving Binder transactions. Binder must keep track of:

- What each thread is currently doing.
- What it needs to reply to.
- What it needs to clean up if it crashes.

🤪 Thread Transaction Stack: Simple Idea

Each binder_thread (in apps A, B, C, D) has a stack called transaction_stack. It tracks:

- What transactions the thread is currently handling (both sent and received).
- The stack grows when the thread receives or sends a new transaction.
- It shrinks (pops) when it replies or crashes.

🚻 Breakdown of the Image:

Let's look at each app/thread one by one.

Client A:

- Has only 1 transaction on its stack.
- This transaction was sent from $A \rightarrow B$.

makefile

from: A
to_thread: B

So A is waiting for a reply from B.

Client B:

• B is very busy. It has **3 transactions** on its stack, in LIFO (Last-In-First-Out) order.

From top (last pushed) to bottom (first pushed):

1. From D to B

- \rightarrow B is now replying to D
- \rightarrow This is the top of the stack.

2. From B to C

→ B earlier sent a request to C (to get help before replying to A)

3. From A to B

→ Original transaction from A.

P B must **reply in reverse order** (top to bottom):

- First reply to D
- Then wait for reply from C
- Then finally reply to A

Client C:

• 2 transactions:

1. From C to D

 \rightarrow C sent a request to D

2. From B to C

 \rightarrow C received a transaction from B

Client D:

• 2 transactions:

1. From D to B

 \rightarrow D sent request to B

2. From C to D

 \rightarrow D received request from C

Why is this useful?

- This helps **Binder enforce ordering**: A client cannot reply out of order.
- If any client crashes, Binder can walk this stack to:
 - Clean up the transaction.
 - Inform the previous sender (with BR_DEAD_REPLY).

Summary

Thread	Transaction Stack (Top to Bottom)	
A	Sent to B	
В	From D \rightarrow From B to C \rightarrow From A	
С	Sent to D \rightarrow From B	
D	Sent to B \rightarrow From C	

Would you like a **simplified cartoon diagram** showing this flow with arrows and stacks?



45. Binder utilizes the from parent and to parent fields along with from and to thread to traverse the thread transaction stack of each client thread. By checking if from or to_thread points to the target client thread, it follows either the from_parent or to_parent field to the next transaction in the stack.

For example, starting from B's transaction_stack, Binder checks whether the from or to_thread points to B and follows either the from_parent or to_parent to the next transaction.

The first transaction from the top has to_thread pointing to B, so Binder follows to_parent to the next transaction.

The second transaction has from pointing to B, so Binder follows the from_parent to the next transaction.

When a client thread exits, Binder must remove every reference to that thread within all ongoing transactions. The binder_thread_release, which is responsible for releasing the client thread, handles that cleanup. It traverses the thread transaction stack to remove every reference to the client (binder_proc) and client thread (binder_thread).

```
static int binder_thread_release(struct binder_proc *proc,
                   struct binder_thread *thread)
{
    while (t) {
         if (t->to_thread == thread) {
             t->to_proc = NULL;
             t->to_thread = NULL;
             t = t->to_parent;
         } else if (t->from == thread) {
             t->from = NULL;
             t = t->from_parent;
}
```

Let's break this down into **very simple words** with a clear example:

What's the goal?

When a client thread (like B) exits (due to crash or normal exit), Binder must:

- 1. Clean up all transactions that this thread was part of (either sender or receiver).
- 2. Remove all references to this thread from those transactions.

🧱 How is this cleanup done?

Each binder transaction keeps track of:

- Who sent it (from)
- Who received it (to_thread)
- Links to other transactions:
 - from_parent (next one below in sender's stack)
 - to_parent (next one below in receiver's stack)

How does Binder walk the stack?

- 1. Start from the top of the thread's stack: transaction stack in binder thread.
- 2. Check:
 - Did this transaction get sent to this thread? → use to_parent to move down.

- Did this transaction get sent **from** this thread? → use **from_parent** to move down.
- 3. Keep walking until there's nothing left.

What cleanup does Binder do?

For every transaction where the thread was involved:

```
if (t->to_thread == thread) {
    t->to_proc = NULL;
    t->to_thread = NULL;
    t = t->to_parent;
} else if (t->from == thread) {
    t->from = NULL;
    t = t->from_parent;
}
```

This removes the thread reference so:

- The memory is safe to free.
- Other clients don't use an invalid pointer.
- The system avoids leaks or crashes.

Example (thread B exiting)

Suppose B has these on its transaction stack:

What happens when B exits?

Binder goes:

- 1. Transaction1: to_thread == $B \rightarrow clear to_thread$, go to to_parent.
- 2. Transaction2: from $== B \rightarrow clear from, go to from_parent.$
- 3. Transaction3: $to_thread == B \rightarrow clear to_thread$, go to to_parent .

Done.

In Summary

- Binder tracks who sent and who received every transaction.
- When a thread exits, Binder:
 - Traverses its transaction stack.
 - Cleans out all references to that thread.
- This prevents use-after-free bugs and crashes in the kernel.

Let me know if you'd like a diagram showing this cleanup visually — happy to draw it!

Great — let's explain to_thread, from, from_parent, and to_parent in very simple words, like you're learning Binder for the first time.

💡 Think of a binder transaction like a message envelope being passed between clients (like A, B, C, D).

Each binder_transaction stores 4 key pieces of info to track how the message is flowing:

1. \bigcirc from \rightarrow Who sent the message?

This points to the sender's thread.

"This transaction was created by thread A (from = A)"

2. Pto_thread → Who is receiving the message?

This points to the receiver's thread.

This message is going to thread B (to_thread = B)"

3. ☐ from_parent → What was the sender doing before this?

This points to the **previous transaction** that the sender thread was involved in.

🚛 "I sent this message while still waiting for a reply to an earlier message — track it with from_parent."

So you can walk back in history of what this thread **sent**.

4. ☐ to_parent → What was the receiver doing before this?

This points to the **previous transaction** that the receiver thread was working on.

"This receiver is already handling another message — track it with to_parent."

So you can walk back in history of what this thread received.

Example:

Let's say:

- A sends a message to B → Transaction1
- B sends a message to C → Transaction2

Now:

Field	Meaning
from	A (for Transaction1), B (for T2)
to_thread	B (for Transaction1), C (for T2)
from_parent	points to previous send txn (T1)
to_parent	points to previous recv txn (T1)

Why we need these:

- So Binder can walk back and clean up when someone crashes.
- So Binder can **track stack of messages**: like $A \rightarrow B \rightarrow C \rightarrow D...$
- · So replies are matched with correct requests.

Let me know if you want this explained with a small drawing!



46. still confusing

No problem — let me now break this down like a story, step by step using super simple language.

What is a Binder Transaction?

Imagine **A** is sending a message (like a letter) to **B**. Binder wraps this letter inside a binder_transaction object.

This transaction stores:

- Who sent the message? from
- Who should receive the message? to_thread
- What message came before it? from_parent or to_parent (like a chain of letters)

Let's build a real story:

Step 1: A sends message to B

```
plaintext

Transaction T1:
   from = A
   to_thread = B
```

B is now working on this message. But B hasn't replied yet.

Step 2: B sends message to C (without replying to A)

```
plaintext

Transaction T2:
    from = B
    to_thread = C
    from_parent = T1 (because B sent this while handling T1)
```

So now B's stack looks like:

```
Top -> T2 (sent to C)

T1 (received from A)
```

Step 3: C sends message to D (same thing)

```
plaintext

Transaction T3:
    from = C
    to_thread = D
    from_parent = T2
```

Now C's stack is:

```
CSS

Top -> T3 (sent to D)

T2
```

Step 4: D sends message to B!

```
plaintext

Transaction T4:
    from = D
    to_thread = B
    from_parent = T3
```

Now B has a second message:

o So What Are These Fields?

Field	What it Means	Example (in T4)
from	Who sent it	D
to_thread	Who receives	В
from_parent	Last message this sender sent	Т3
to_parent	Last message this receiver got	T1

Why all this?

Binder uses this info to:

- Track message chains like: $\mathbf{A} \to \mathbf{B} \to \mathbf{C} \to \mathbf{D} \to \mathbf{B}$
- Clean up if something goes wrong (e.g., if C crashes)
- Maintain correct reply order

What happens when B crashes?

Binder looks at B's transaction stack:

```
CSS

Top \rightarrow T4 (D \rightarrow B)

1
T1 (A \rightarrow B)
```

ightarrow It sees the latest transaction is from ${f D}
ightarrow$ sends ${f BR_DEAD_REPLY}$ to ${f D}$ to say "B is gone".

Let me know if you'd like this as a **diagram**, it'll make things even easier.





47. Exploring Binder with libdevbinder

We would like to conclude this blog with a quick overview of the libdevbinder project we briefly mentioned in the introduction. As you might have noticed based on the information provided above Binder kernel module is a very complex target for analysis. In order to fully understand semantics of the exposed Binder kernel API to the user-space code via ioctls one would need to study the implementation of libbinder - library which sits on top of the Binder kernel module and provides a higher-level Binder IPC interface to the Android Framework. The libbinder itself consists of multiple files written in C++ & Rust and might be challenging to comprehend for the audience with no prior knowledge in this area.

Thus, to facilitate the Binder research and make understanding Binder concepts easier we developed a tiny and simple library – libdevbinder – which serves as an example on how two endpoints running in user-space could communicate with each other over the Binder. This library provides necessary minimalistic implementation sufficient to send a Binder transaction across the IPC interface.

As an example, libdevbinder additionally provides two small programs client and server where client sends user-provided data via Binder transaction to the server which prints the received data to stdout.

These programs are expected to run on top of a vanilla Linux kernel built with Binder driver enabled config (e.g. in QEMU) – not in an Android environment. Main reason for that is that the server program registers itself with the Binder driver as the context manager. There can only be one context manager per binder device node, which very likely is already claimed by the ServiceManager process on Android.

To send the transaction we would use client program which takes as input a string and sends it to the server:

./client "Hello world!"

We hope that these tiny examples remove the layer of ambiguity and complexity over the Binder kernel ioctl interface and make researching Binder easier and more convenient.

Great! Let's break this down in very simple terms:



What's This About?

This section introduces libdevbinder, a simple project created to help you learn and experiment with Binder IPC in Linux.

🔔 Why Do We Need libdevbinder?

The Android Binder system is complex:

- Kernel part: written in C
- User-space part: libbinder written in C++ and Rust
- Requires knowledge of ioctls, kernel modules, threads, transactions...

If you're just starting or want to experiment, it's **too heavy** and tied to Android.



libdevbinder = Minimal Binder IPC for Learning

To make it easier to understand:

- They built a small library: libdevbinder
- It lets two user-space programs talk over Binder without Android

How Does It Work?

They give you two example programs:

1. server

- Starts and waits for messages
- It registers itself as a **context manager** (a special role in Binder)
- When it receives a message, it prints it out



2. client

• Sends a **string** to the server

You run:

bash

./client "Hello world!"

The server prints:

bash

Received: Hello world!

Simple!

Why Run Outside Android?

On Android:

- The context manager is already taken by ServiceManager
- So you can't just register your own server

Instead, they run this example:

- On a regular Linux kernel
- With Binder driver enabled
- e.g., in a **QEMU virtual machine**

6 Final Goal?

- Help researchers and developers:
 - Understand how Binder transactions work under the hood
 - Try out ideas with less complexity
 - Avoid needing full Android or Java stack

TL;DR (Summary)

Feature	Description
libdevbinder	Tiny C library to try Binder easily
Works on	Linux with Binder driver (e.g. QEMU)
Programs provided	client and server
Does what?	Client sends text, server receives and prints
Why not Android?	Android already uses the context manager
Purpose	Learn Binder ioctl system with minimal setup

Would you like me to help you set up this libdevbinder example on Linux/QEMU? Or go deeper into how client/server works internally?