

Rajalakshmi Engineering College

Name: Bebin Y
Email: 240801040@rajalakshmi.edu.in
Roll no: 240801040
Phone: 750858599
Branch: REC
Department: I ECE FA
Batch: 2028
Degree: B.E - ECE

Scan to verify results



NeoColab_REC_CS23231_DATA STRUCTURES

REC_DS using C_Week 7_COD_Question 3

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

In a messaging application, users maintain a contact list with names and corresponding phone numbers. Develop a program to manage this contact list using a dictionary implemented with hashing.

The program allows users to add contacts, delete contacts, and check if a specific contact exists. Additionally, it provides an option to print the contact list in the order of insertion.

Input Format

The first line consists of an integer n , representing the number of contact pairs to be inserted.

Each of the next n lines consists of two strings separated by a space: the name of the contact (key) and the corresponding phone number (value).

The last line contains a string *k*, representing the contact to be checked or removed.

Output Format

If the given contact exists in the dictionary:

1. The first line prints "The given key is removed!" after removing it.
2. The next *n* - 1 lines print the updated contact list in the format: "Key: X; Value: Y" where X represents the contact's name and Y represents the phone number.

If the given contact does not exist in the dictionary:

1. The first line prints "The given key is not found!".
2. The next *n* lines print the original contact list in the format: "Key: X; Value: Y" where X represents the contact's name and Y represents the phone number.

Refer to the sample outputs for the formatting specifications.

Sample Test Case

Input: 3

Alice 1234567890

Bob 9876543210

Charlie 4567890123

Bob

Output: The given key is removed!

Key: Alice; Value: 1234567890

Key: Charlie; Value: 4567890123

Answer

```
// You are using GCC
```

```
#include <stdio.h>
```

```
#include <stdlib.h>
```

```
#include <string.h>
```

```
#define INITIAL_CAPACITY 10
```

```
typedef struct {
    char key[50];
    char value[50];
} KeyValuePair;
```

```
typedef struct {
    KeyValuePair *pairs;
    int size;
    int capacity;
} Dictionary;
```

```
void initDictionary(Dictionary *dict) {
    dict->size = 0;
    dict->capacity = INITIAL_CAPACITY;
    dict->pairs = (KeyValuePair *)malloc(dict->capacity * sizeof(KeyValuePair));
}
```

```
int hash(const char *key) {
    int hash = 0;
    for (int i = 0; key[i] != '\0'; i++) {
        hash += key[i];
    }
    return hash;
}
```

```
void insertKeyValuePair(Dictionary *dict, const char *key, const char *value) {
    if (dict->size == dict->capacity) {
        dict->capacity *= 2;
        dict->pairs = (KeyValuePair *)realloc(dict->pairs, dict->capacity *
sizeof(KeyValuePair));
    }
    strcpy(dict->pairs[dict->size].key, key);
    strcpy(dict->pairs[dict->size].value, value);
    dict->size++;
}
```

```
int doesKeyExist(Dictionary *dict, const char *key) {
    for (int i = 0; i < dict->size; i++) {
        if (strcmp(dict->pairs[i].key, key) == 0) {
            return i;
        }
    }
}
```

```

    }
    return -1;
}

void removeKeyValuePair(Dictionary *dict, const char *key) {
    int index = doesKeyExist(dict, key);
    if (index != -1) {
        for (int i = index; i < dict->size - 1; i++) {
            strcpy(dict->pairs[i].key, dict->pairs[i + 1].key);
            strcpy(dict->pairs[i].value, dict->pairs[i + 1].value);
        }
        dict->size--;
        printf("The given key is removed!\n");
    }
}

void printDictionary(Dictionary *dict) {
    for (int i = 0; i < dict->size; i++) {
        printf("Key: %s; Value: %s\n", dict->pairs[i].key, dict->pairs[i].value);
    }
}

int main() {
    Dictionary dict;
    initDictionary(&dict);
    int numPairs;
    scanf("%d", &numPairs);
    char key[50], value[50];
    for (int i = 0; i < numPairs; i++) {
        scanf("%s %s", key, value);
        insertKeyValuePair(&dict, key, value);
    }
    scanf("%s", key);
    if (doesKeyExist(&dict, key) != -1) {
        removeKeyValuePair(&dict, key);
        printDictionary(&dict);
    } else {
        printf("The given key is not found!\n");
        printDictionary(&dict);
    }
    free(dict.pairs);
    return 0;
}

```

}

Status : Correct

Marks : 10/10