# Master in Artificial Intelligence

Introduction

General methodology

Mention detection

ML-based coreference prediction

Hand-crafted rules

References

# Introduction to Human Language Technologies 10. Coreference resolution





- 1 Introduction
  - Goal and motivation
  - Background
- 2 General methodology
- 3 Mention detection
- 4 ML-based coreference prediction
  - Mention-Pair model
  - Mention-ranking models
  - Entity-Mention model
- 5 Hand-crafted rules
- 6 References

#### Introduction

General methodology

Mention detection

ML-based coreference prediction

Hand-crafted rules

- Introduction
- General methodology
- Mention detection
- ML-based coreference prediction
- Hand-crafted rules
- References

- 1 Introduction
  - Goal and motivation
  - Background
- 2 General methodology
- 3 Mention detection
- 4 ML-based coreference prediction
  - Mention-Pair model
  - Mention-ranking models
  - Entity-Mention model
- 5 Hand-crafted rules
- 6 References

# The goal of coreference resolution

Introduction

Goal and motivation

General methodology Mention detection

ML-based coreference prediction

Hand-crafted rules

References

# Determining which mentions in a discourse refer to the same real world entity, property or situation. Example:

FC Barcelona president Joan Laporta has warned Chelsea off star strike Lionel Messi.

This warning has generated discouragement in Chelsea.

Aware of Chelsea owner Roman Abramovich's interest in the young Argentine, Laporta said last night: " I will answer as always. Messi is not for sale and we do not want to let him go."

# The goal of coreference resolution

Introduction

Goal and motivation

General methodology

Mention detection

ML-based coreference prediction

Hand-crafted rules

References

Determining which mentions in a discourse refer to the same real-world entity, property or situation.

Example:

FC Barcelona president Joan Laporta has warned Chelsea off star strike Lionel Messi.

This warning has generated dicouragement in Chelsea.

Aware of Chelsea owner Roman Abramovich's interest in the young Argentine Laporta said last night: "I

will answer as always, Messi is not for sale and we do not want to let him go."

# The goal of coreference resolution

Introduction

Goal and motivation

General methodology Mention detection

ML-based coreference prediction

Hand-crafted rules

References

Determining which mentions in a discourse refer to the same real world entity, property or situation.

Example:

FC Barcelona president Joan Laporta has warned Chelsea off star strike Lionel Messi

This warning has generated discouragement in Chelsea.

Aware of Chelsea owner Roman Abramovich's interest in the young Argentine, Laporta said last night: " I will answer as always, Messi is not for sale and we do not want to let him go."

# Identity noun-phrase coreference resolution

Introduction

Goal and motivation

General methodology

Mention detection

ML-based coreference prediction

Hand-crafted rules

References

- Most commonly investigated type of coreference.
- Determining which noun-phrases in a discourse refer to the same real-word entity

Ex:  $[Messi]_1$  is not for sale. We do not want to let  $[him]_1$  go.

Ex:  $[The \ car]_1$  hit a tree.  $[The \ vehicle]_1$  was found one day later.

Ex: [Bruce Springsteen]<sub>1</sub> will play in Barcelona. [The Boss]<sub>1</sub> is well liked in that place.

We will focus on identity noun-phrase coreference resolution. (For simplicity, we will refer to it simply as *coreference resolution*).

#### Motivation

Introduction

Goal and motivation

General methodology Mention

Mention detection

ML-based coreference prediction

Hand-crafted rules

References

#### Coreference resolution is involved in may NLP applications

- Reading machine: required to full understanding text
- Information extraction

Ex: Extract organizations in which a person has worked.

Automatic summarization

Ex: Find relevant sentences related to a particular person.

Question Answering:

Ex: Answer factual questions such as *Where has Mary Doe been working?* 

She worked at UPC. ... Mrs. Doe moved to IBM in 1976

- Introduction
  Background
- General methodology
- Mention detection
- ML-based coreference prediction
- Hand-crafted rules
- References

- Introduction
  - Goal and motivation
  - Background
- 2 General methodology
- 3 Mention detection
- 4 ML-based coreference prediction
  - Mention-Pair model
  - Mention-ranking models
  - Entity-Mention model
- 5 Hand-crafted rules
- 6 References

# Types of referent

Introduction Background

General methodology

Mention detection

ML-based coreference prediction

Hand-crafted rules

References

#### Referring expressions:

world knowledge can be necessary for the resolution

Ex: Laporta, the president, FC Barcelona president Joan Laporta

Ex: Lionel Messi, the young Argentine

#### Pronouns:

linguistic information can be useful for the resolution (number, genre, grammatical constraints)

Ex: Laporta said: "I will answer"

Ex: the president said: "I will answer"

# Coreferent, Anaphor, Cataphor

#### Orthogonal concepts

- Coreferent: two mentions refer to the same world entity
- Anaphora: a mention (anaphor) refers to a preceding mention (antecedent) and the interpretation of the anaphor depends on the antecedent.

John Smith had been writting for months. He ended up sleeping on the bed.

Cataphora: the antecedent occurs after the anaphor (cataphor)

He had been writting for months. John Smith ended up sleeping on the bed.

Anaphor is more frequently used than cataphor

Introduction Background

General methodology Mention

ML-based coreference prediction

Hand-crafted rules

# Coreference vs Anaphora

#### Anaphora resolution is different from coreference resolution

	Example	Anaphora	Coreference
	$[John]_1$ wrote $[his]_1$ book.	X	Х
	[Steve Jobs] <sub>2</sub> set up Apple in 1976.	Х	Х
	[The genius] $_2$ died in 2011.		
	$[The man]_3$ wrote $[his]_3$ book.	X	X
(1)	[Every dog] <sub>3</sub> has [its] <sub>3</sub> day.	X	
(2)	The boy entered [the room] <sub>4</sub> .	X	
	The $[door]_4$ closed automatically.		
(3)	[Apple] <sub>5</sub> launched the iphoneX today.		X
	[Apple] <sub>5</sub> has already won 100 millions.		

- (1) Not a real world entity a quantified concept
- (2) Not the same entity
- (3) They don't need each other to be interpreted

Introduction Background

General methodology Mention

detection ML-based


coreference prediction

Hand-crafted rules

- Introduction
- General methodology
- Mention detection
- ML-based coreference prediction
- Hand-crafted rules
- References

- 1 Introduction
  - Goal and motivation
  - Background
- 2 General methodology
- 3 Mention detection
- 4 ML-based coreference prediction
  - Mention-Pair model
  - Mention-ranking models
  - Entity-Mention model
- 5 Hand-crafted rules
- 6 References

# General methodology of a coreference solver



Introduction

General

methodology

Mention

ML-based coreference prediction

Hand-crafted rules

References

#### Mention detection:

- Detects the boundaries of the mentions in the input text.
- $\mathbf{m} = (m_1, m_2, \dots, m_n)$  ordered as found in the document.

#### Coreference prediction:

- find the coreference chains.
- Heuristic-driven approaches: based on the centering theory of the discourse [Grosz et al., 83, 95]. See details in [Walker et al., 98].
- ML-based approaches
- Hand-crafted rules

- Introduction
- General methodology
- Mention detection
- ML-based coreference prediction
- Hand-crafted rules
- References

- 1 Introduction
  - Goal and motivation
  - Background
- 2 General methodology
- 3 Mention detection
- 4 ML-based coreference prediction
  - Mention-Pair model
  - Mention-ranking models
  - Entity-Mention model
- 5 Hand-crafted rules
- 6 References

#### Mention detection

Introduction

General methodology

Mention detection

ML-based coreference prediction

Hand-crafted rules

- Preprocess: POS-tagging, NERC and parsing (constituent parsing or dependence parsing).
- Recursiverly visiting the parse tree, accept the following as mention
  - Pronouns (filter out pleonastic pronouns, e.g., It is raining)
  - Proper names
  - Maximal noun-phrase projections
  - Coordinated noun phrases

# **Examples**

Examples of maximal NP projections with constituent parses:

Introduction


General methodology


Mention detection

ML-based coreference prediction

Hand-crafted rules

References





Drop out NPs sharing the same head. (head: essentially, right-most noun in first sub-constituent)

- Introduction
- General methodology
- Mention detection
- ML-based coreference prediction
- Hand-crafted rules
- References

- 1 Introduction
  - Goal and motivation
  - Background
- 2 General methodology
- 3 Mention detection
- 4 ML-based coreference prediction
  - Mention-Pair model
  - Mention-ranking models
  - Entity-Mention model
- 5 Hand-crafted rules
- 6 References

- Introduction
- General methodology
- Mention detection
- ML-based coreference prediction

Mention-Pair model

Hand-crafted rules

- 1 Introduction
  - Goal and motivation
  - Background
- 2 General methodology
- 3 Mention detection
- 4 ML-based coreference prediction
  - Mention-Pair model
  - Mention-ranking models
  - Entity-Mention model
- 5 Hand-crafted rules
- 6 References

#### Mention-Pair model

- **E**xamples:  $(m_i, m_i)$  classified as CO/NC.
- Two steps:
  - 1 Learn a classifier of mention pairs. Ex:
    - Decision Trees [McCarthy & Lehnert, 95], [Soon et al., 01]
    - Rule induction (RIPPER) [Ng & Cardie, 02]
    - Maximum Entropy [Denis & Baldrige, 07], [Ji et al., 05]
    - SVMs [Yang et al., 06]
  - 2 Generate chains. Ex:
    - Closest-first strategy [Soon et al., 01]
    - Best-first strategy [Ng & Cardie, 02][Bengtson & Roth, 08]
    - Clustering [Klenner & Ailloud 2008]...
    - Global optimization (ILP) [Klenner, 07][Finkel & Manning, 08]
    - Graph partitioning [McCallum & Wellner,05][Nicolae & Nicolae, 06][Sapena et al, 10]...

Introduction

General methodology

Mention detection

ML-based coreference prediction

Mention-Pair model

Hand-crafted rules

# 1) Learn a mention-pair classifier

Creating training examples from anotated corpus:

- **■** [Soon et al, 01]
  - the classifier is biased to select the closest antecedent
  - $lackbox{e}^+ \Longrightarrow (m_i, m_j)$  Anaphor  $m_j$  and closest antecedent  $m_i$
  - $e^- \Longrightarrow \forall k : i < k < j : (m_k, m_j)$
- [Ng & Cardie,02]
  - the classifier is biased to select the best antecedent
  - $e^+$   $\Longrightarrow$   $(m_i, m_j)$  Anaphor  $m_j$  and closest antecedent  $m_i$  but for non-pronominal anaphor  $m_j$  select the closest non-pronominal antecedent  $m_i$
  - $e^- \Longrightarrow \forall k : i < k < j : (m_k, m_j)$  where  $m_k$  is not in the same chain that  $m_j$

Introduction

General methodology

Mention detection ML-based

coreference prediction Mention-Pair model

mencion i un mode

Hand-crafted rules

#### Exercise

Introduction

General methodology

Mention detection

ML-based coreference prediction

Mention-Pair model

Hand-crafted rules

References

Identify all the mentions for identity noun-phrase coreference resolution in the following text:

Mr. Smith was traveling when Lara came back home. He had never been far from his wife. Mrs. Smith closed the door and went to bed thinking of John.

2 Extract all positive and negative examples of coreferent mention pairs for closest-first and for best-first strategies.

# 1) Learn a mention-pair classifier

# Examples of feature functions for mention pair $(m_i, m_j)$ :

Introduction

General methodology

Mention detection

ML-based coreference prediction


Mention-Pair model

Hand-crafted rules

T	F+	Description	
Туре	Feature	Description	
Structural	DIST_SEN_k	distance in sentences is k: y,n	
	DIST_SEN_>2	distance in sentences greater than 2: y,n	
	DIST_MEN_k	distance in mentions is k: y,n	
	DIST_MEN_>2	distance in mentions greater than 2: y,n	
	APPOSITIVE	One mention in apposition with the other: y,n	
Lexical	STR_MATCH	String matching: y,n	
	ALIAS	One mention is an alias of the other: y,n,u	
Morphological	NUMBER	The number of both mentions match: y,n,u	
	GENDER	The gender of both mentions match: y,n,u	
Syntactic	DEF_NP	$m_i$ is a definitive NP: y,n	
	DEM_NP	$m_i$ is a demonstrative NP: y,n	
Semantic	SEMCLASS	Semantic class match: y,n,u	
	ANIMACY	Animacy of both mentions match: y,n	

# 2) Generate chains

### Closest-first strategy [Soon et al., 01]



- for a given  $m_j$ , select as antecedent the closest preceding  $m_k$  from the +pairs provided by a binary mention-pair classifier
- if a probabilistic classifier is used then define a threshold above which a pair is considered coreferent

Introduction

General methodology


Mention detection ML-based

coreference prediction Mention-Pair model

Hand-crafted rules

# 2) Generate chains

Best-first strategy [Ng & Cardie, 02][Bengtson & Roth, 08]



- for a given  $m_j$ , select as antecedent the most probable precedent  $m_k$  from the +pairs achieved by a probabilistic mention-pair classifier
- aims to improve the Precision of closest-first strategy by taking profit of the probabilities of the +pairs

#### Introduction

General methodology

Mention detection ML-based

coreference prediction Mention-Pair model

Wention-Fair model

Hand-crafted rules

#### Exercise

Introduction

General methodology

Mention detection

ML-based coreference prediction

Mention-Pair model

Hand-crafted rules

References

Assume we have already learned a mention-pair classifier. Consider m1, ..., m9 as the ordered sequence of mentions in a text. Given the following probabilities for the mention pairs:

$$P(CO| < m1, m7 >) = 0.8;$$
  $P(CO| < m2, m7 >) = 0.6;$   $P(CO| < m3, m7 >) = 0.4;$   $P(CO| < m4, m7 >) = 0.5;$   $P(CO| < m5, m7 >) = 0.7;$   $P(CO| < m6, m7 >) = 0.6;$   $P(CO| < m7, m8 >) = 0.9;$   $P(CO| < m7, m9 >) = 0.5;$ 

provide the m7 antecedent that results from applying:

- Closest-first strategy
- 2 Best-first strategy

assuming a coreference threshold of 0.6.

# Drawbacks of the Mention-Pair model

Introduction

General methodology

Mention detection


ML-based coreference prediction

Mention-Pair model

Hand-crafted rules

References

#### Lack of information.



# Drawbacks of the Mention-Pair model

Introduction

General methodology

Mention detection


ML-based coreference prediction

Mention-Pair model


Hand-crafted rules

References

#### Lack of information.



#### Contradictions in classification.



# Drawbacks of the Mention-Pair model

Introduction

General methodology

Mention detection


ML-based coreference prediction

Mention-Pair model


Hand-crafted rules

References

Lack of information.



Contradictions in classification.




Mention-ranking models and Entity-mention model are different perspectives to deal with the problem.

- Introduction
- General methodology
- Mention detection
- ML-based coreference prediction
- Mention-ranking models
- Hand-crafted rules
- References

- 1 Introduction
  - Goal and motivation
  - Background
- 2 General methodology
- 3 Mention detection
- 4 ML-based coreference prediction
  - Mention-Pair model
  - Mention-ranking models
  - Entity-Mention model
- 5 Hand-crafted rules
- 6 References

# Mention-ranking models

**Mention-pair models** take profit of independent mention pair decisions between  $m_i$  and each possible antecedent.



**Mention-ranking models** take profit of decisions between  $m_j$  and all its possible antecedents.

The mention-pair classifier is replaced by a ranker.

For a given  $m_j$ , provide a ranking of the set of possible antecedents

Introduction

General methodology

Mention detection ML-based

coreference prediction Mention-ranking

Hand-crafted

# Mention-ranking models

Introduction

General methodology

Mention detection

ML-based coreference prediction

models

Hand-crafted

References

Ex: rankers [Denis and Baldrige, 08]

- Learn a ranker from examples
- Example =  $(m_i, \alpha_i, A_i)$ , where  $\alpha_i$  is the first antecedent of  $m_i$  (the non-pronominal one if  $m_i$  is non-pronominal) and  $A_i$  is the set of non-antecedents in a context of 2 sentences around  $\alpha_i$
- Exponential model:

$$P(\alpha_i|m_i) = \frac{\exp \sum_k \lambda_k f_k(m_i, \alpha_i)}{\sum_{m_s \in A_i \cup \{\alpha_i\}} \exp \sum_k \lambda_k f_k(m_i, m_s)}$$

■ Resolution:  $\alpha_i$  is any potential antecedent of  $m_i$ .

# Mention-ranking models

Introduction

General methodology

Mention detection

ML-based coreference prediction

Mention-ranking models

Hand-crafted rules

References

- Pros: take profit of decisions involving all the candidate antecedents.
- Cons: always pick an antecedent from the candidates, although the mention in course is not anaphoric.


(a classifier of anaphoricity improves the results)

- Introduction
- General methodology
- Mention detection
- ML-based coreference prediction Entity-Mention model
- Hand-crafted rules
- References

- 1 Introduction
  - Goal and motivation
  - Background
- 2 General methodology
- 3 Mention detection
- 4 ML-based coreference prediction
  - Mention-Pair model
  - Mention-ranking models
  - Entity-Mention model
- 5 Hand-crafted rules
- 6 References

# **Entity-Mention model**

- The classifier classifies a partial entity and a mention (or two partial entities in some approaches)
- Entities characterization:
  - Partial entity: a set of mentions considered coreferent during the resolution
  - Each partial entity is represented as the set of features of its mentions.
  - Each partial entity has its representative mention



Introduction

General methodology

Mention detection

ML-based coreference prediction Entity-Mention model

Hand-crafted

- Introduction
- General methodology
- Mention detection
- ML-based coreference prediction
- Hand-crafted rules
- References

- 1 Introduction
  - Goal and motivation
  - Background
- 2 General methodology
- 3 Mention detection
- 4 ML-based coreference prediction
  - Mention-Pair model
  - Mention-ranking models
  - Entity-Mention model
- 5 Hand-crafted rules
- 6 References

# Stanford Easy-first approach

Introduction

General methodology

Mention detection

ML-based coreference prediction

Hand-crafted rules

References

- Exact string match
- Relaxed string match

Ex: "Clinton", "Clinton, whose term ends in January"

- Precise constructs (appositives, predicate nominatives, ...)

  Ex: "[Donald Trump] is [the president of the USA]"
- 4 Strict head matching: (entity-mention model)

Ex: { "the Florida Supreme Court" }, "the Florida court"

**5** Strict head matching – Variant 1:

Ex: {"American President Clinton", "Clinton"}, "President Clinton"

6 Strict head matching – Variant 2:

Ex: {"an organization of journalists", "The Gridiron Club"}, "The Gridiron Club at Greenbrier Hotel"

Proper head noun matching Ex: "southern Lebanon". "Lebanon"

8 Relaxed Head Matching (entity-mention model)

Ex:  $\{$ "the judge", "Circuit Judge N. Sanders Sauls" $\}$ , "Sanders"

9 Pronouns

- Introduction
- General methodology
- Mention detection
- ML-based coreference prediction
- Hand-crafted rules
- References

- 1 Introduction
  - Goal and motivation
  - Background
- 2 General methodology
- 3 Mention detection
- 4 ML-based coreference prediction
  - Mention-Pair model
  - Mention-ranking models
  - Entity-Mention model
- 5 Hand-crafted rules
- 6 References

#### References

Introduction

General methodology

Mention detection

ML-based coreference prediction

Hand-crafted rules

- B.J. Grosz, A.K. Joshi and S. Weinstein, Providing a unified account of definite noun phrases in discourse. Proceedings of ACL, 1983.
- B.J. Grosz, A.K. Joshi and S. Weinstein, Centering: A framework for modeling the local coherence of discourse. Computational Linguistics, 21(2), 1995.
- M. Walker, A. Joshi, and E. Prince, editors. 1998. Centering theory in discourse. Oxford University Press
- W.M. Soon, H.T. Ng and D.C.Y. Lim, A machine learning approach to coreference resolution of noun phrases.
   Computational Linguistics, 27(4), 2001
- V. Ng and C. Cardie, Improving machine learning approaches to coreference resolution. Proceedings of ACL, 2002

#### References

Introduction

General methodology

Mention detection

ML-based coreference prediction

Hand-crafted rules

- C. Nicolae and A. Nicolae, Best Cut: A graph algorithm for coreference resolution. Proceedings of EMNLP, 2006.
- V. Ng, Supervised noun phrase coreference research: The First Fifteen Years. Proceedings of ACL, 2010.
- E. Sapena, L. Padró and J. Turmo. 2010. A global relaxation labeling. Proceedings of COLING 2010