

GSE iOS — programme workspace

What this is. The native iOS client for Galaxy Sports Edge, built on top of [Beexly/Sports](#).

What it is not. It is not deployed, not built, and not run. See “Honest status” below — that section is the most important one in this file.

Layout

PLAN.md	the plan of action, and the constraints it works under
app/	the Expo SDK 57 / React Native 0.86 iOS app
preview/	design review harness (HTML mirror – the app has no simulator here)
server-patches/	PR-ready routes the repo does not have yet
docs/store/SUBMISSION.md	App Store Connect packet: metadata, privacy, review notes
docs/product/	X community strategy
research/round-01-*.md	10 reference repositories, with the lesson each one changed
reports/01-review-and-audit.md	the review pass: defects, doctrine audit, upstream findings
x-transport/	OAuth 1.0a signer + tests (the X bot's missing transport)
sports-meta/	a sparse checkout of Beexly/Sports, used as the source of truth

Start here

If you want to...	Read
understand what was built and what is unverified	<code>reports/01-review-and-audit.md</code> §1–2
know what is broken upstream in the Sports repo	<code>reports/01-review-and-audit.md</code> §4
ship it	<code>docs/store/SUBMISSION.md</code> §9
run the checks	<code>sh app/scripts/verify.sh</code>
see the screens	open <code>preview/screens.html</code>
work on the X account	<code>docs/product/x-community-strategy.md</code>

Honest status

Area	State
App source	Complete and lint-clean — 41 files, 0 invariant violations
Pure logic	Tested — 105 passing assertions
Core typecheck (13 pure files)	Passing — 0 diagnostics
Full typecheck	UNRELIABLE — NOT COUNTED AS A GATE. It completed three times earlier in the session (0 diagnostics) and later was killed on <i>every</i> attempt, including a two-file project. A killed run exits 0 with empty output. <code>scripts/typecheck.js</code> prints its own summary line so a killed run is distinguishable from a clean one; last completed run predates the <code>live-activity</code> module.
App build / run	NEVER EXECUTED. No Xcode, no simulator.
Server patches	Written, never run.
Store submission	Packet complete, not submitted. Needs the owner's App Store Connect API key.
X transport	Signer verified (18 tests incl. the RFC 5849 vector); sender not written.

The single next action: run `npx expo start --ios` on a Mac, then `tsc --noEmit`. The type layer has NOT been verified on a reliable host, so expect a handful of errors in the same class as the four that were caught before the compiler degraded (listed in the audit).

The three constraints everything bends around

1. **The server is the only enforcer.** `app/src/lib/entitlements.ts` is presentational — it picks labels for redacted fields and nothing else. There is a test asserting it imports no components and holds no state, because the failure mode is a client that “unlocks” data the server already sent (CLAUDE.md rule 3).

2. **Confidence is a score, not a probability.** Measured 2026-09-13: the 80+ band claimed 0.8663 and realized 0.5191 ($z = -10.7$). It renders `72/100`. A linter rule fails the build on any attempt to render it with a percent sign.
 3. **A check is not trusted until it can demonstrate it fails.** The typechecker silently passed for an hour while it was actually being killed by the host. Only the two checks with a positive control are treated as gates: the linter (which self-tests all 9 rules against synthetic violations on every run) and the test suite (which asserts real values). The typecheck is reported but never counted.
-

Reproducing the verification

```
cd app
sh scripts/verify.sh          # lint self-test, lint, tests, then a best-
                              effort typecheck
sh scripts/verify.sh quick    # skip the typecheck attempt
```

Environment requirements for the good path (see the script header for why):

```
export UV_THREADPOOL_SIZE=2    # or tsc aborts with a libuv assertion
node --test --test-concurrency=1 # parallel test processes SIGSEGV on this
host
```

Dependencies the toolchain needs (already installed on this host)

TypeScript and the SDK 57 type set live outside the project, because `npm install react-native` fails here (npm's rename-over-directory path leaves an empty `node_modules`).

<code>/opt/gsetools/node_modules/typescript</code>	<code>6.0.3</code>
<code>/opt/gstypes/node_modules/</code>	the full SDK 57 type surface
<code>/opt/gstypes/fetch.sh <pkg> <ver></code>	tarball fetcher that bypasses
npm's rename	
<code>/node_modules -> /opt/gstypes/node_modules</code>	root symlink (symlinks are
blocked under <code>/var/minis</code>)	

To typecheck on a normal machine, `npm install` in `app/` and use `tsc --noEmit` directly.