

Dependency Grammar

Introduction

Christopher Manning

Dependency Grammar and Dependency Structure

Dependency syntax postulates that syntactic structure consists of lexical items linked by binary asymmetric relations ("arrows") called **dependencies**

Christopher Manning

Dependency Grammar and Dependency Structure

Dependency syntax postulates that syntactic structure consists of lexical items linked by binary asymmetric relations ("arrows") called **dependencies**

The arrows are commonly **typed** with the name of grammatical relations (subject, prepositional object, apposition, etc.)

Christopher Manning

Dependency Grammar and Dependency Structure

Dependency syntax postulates that syntactic structure consists of lexical items linked by binary asymmetric relations ("arrows") called dependencies

The arrow connects a **head** (governor, superior, regent) with a **dependent** (modifier, inferior, subordinate)

Usually, dependencies form a tree (connected, acyclic, single-head)

Christopher Manning

Dependency Grammar and Dependency Structure

ROOT Discussion of the outstanding issues was completed .

- Some people draw the arrows one way; some the other way!
 - Tesnière had them point from head to dependent...
- Usually add a fake ROOT so every word is a dependent of precisely 1 other node

Christopher Manning

Dependency Grammar/Parsing History

- The idea of dependency structure goes back a long way
 - To Pāṇini's grammar (c. 5th century BCE)
 - Basic approach of 1st millennium Arabic grammarians
- Constituency is a new-fangled invention
 - 20th century invention (R.S. Wells, 1947)
- Modern dependency work often linked to work of L. Tesnière (1959)
 - Was dominant approach in "East" (Russia, China, ...)
 - Good for free-er word order languages
- Among the earliest kinds of parsers in NLP, even in the US:
 - David Hays, one of the founders of U.S. computational linguistics, built early (first?) dependency parser (Hays 1962)

Relationship between phrase structure and dependency structure

- A dependency grammar has a notion of a head. Officially, CFGs don't.
- But modern linguistic theory and all modern statistical parsers (Charniak, Collins, Stanford, ...) do, via hand-written phrasal "head rules":
 - The head of a Noun Phrase is a noun/number/adj/...
 - The head of a Verb Phrase is a verb/modal/...
- The head rules can be used to extract a dependency parse from a CFG parse


The closure of dependencies give constituency from a dependency tree

But the dependents of a word must be at the same level (i.e., "flat") – there can be no VP!

```

graph TD
    swalked --> NP_Sue[NP Sue]
    swalked --> VP_walked[VP walked]
    NP_Sue --> NNP_Sue[NNP Sue]
    VP_walked --> VBD_walked[VBD walked]
    VP_walked --> PP_into[PP into]
    VBD_walked --> Sue1[Sue]
    VBD_walked --> walked[walked]
    PP_into --> P_into[P into]
    PP_into --> NP_store[NP store]
    P_into --> into[into]
    NP_store --> DT_the[DT the]
    NP_store --> NN_store[NN store]
    DT_the --> the[the]
    NN_store --> store[store]
  
```


Christopher Manning



Dependency Conditioning Preferences

What are the sources of information for dependency parsing?

1. Bilexical affinities [issues → the] is plausible
2. Dependency distance mostly with nearby words
3. Intervening material
Dependencies rarely span intervening verbs or punctuation
4. Valency of heads
How many dependents on which side are usual for a head?



ROOT Discussion of the outstanding issues was completed .


Dependency Parsing

- A sentence is parsed by choosing for each word what other word (including ROOT) that it is a dependent of.
- Usually some constraints:
 - Only one word is a dependent of ROOT
 - Don't want cycles $A \rightarrow B, B \rightarrow A$
- This makes the dependencies a tree
- Final issue is whether arrows can cross (non-projective) or not

ROOT I 'll give a talk tomorrow on bootstrapping

11

Christopher Manning



Methods of Dependency Parsing

1. Dynamic programming (like in the CKY algorithm)

You can do it similarly to lexicalized PCFG parsing: an $O(n^3)$ algorithm
Eisner (1996) gives a clever algorithm that reduces the complexity to $O(n^3)$, by producing parse items with heads at the ends rather than in the middle

2. Graph algorithms

You create a Minimum Spanning Tree for a sentence
McDonald et al.'s (2005) MSTParser scores dependencies independently using a ML classifier (he uses MIRA, for online learning, but it could be something else)


3. Constraint Satisfaction

Edges are eliminated that don't satisfy hard constraints. Karlsson (1990), etc.

4. "Deterministic parsing"


Greedy choice of attachments guided by good machine learning classifiers
MaltParser (Nivre et al. 2008)


[illegible]




Probabilistic dependency grammar: generative model

1. Start with left wall \$
2. Generate root w_0
3. Generate left children $w_{-1}, w_{-2}, \dots, w_{-\ell}$ from the FSA λ_{w_0}
4. Generate right children w_1, w_2, \dots, w_r from the FSA ρ_{w_0}
5. Recurse on each w_i for i in $\{-\ell, \dots, -1, 1, \dots, r\}$, sampling α (steps 2-4)
6. Return $\alpha_{-\ell} \dots \alpha_{-1} w_0 \alpha_1 \dots \alpha_r$







Christopher Manning



Dependency Grammar Cubic Recognition/Parsing (Eisner & Satta, 1999)

- **Triangles:** span over words, where tall side of triangle is the head, other side is dependent, and no non-head words expecting more dependents
- **Trapezoids:** span over words, where larger side is head, smaller side is dependent, and smaller side is still looking for dependents on its side of the trapezoid






Christopher Manning


Cubic Recognition/Parsing (Eisner & Satta, 1999)

$O(n)$
combinations


goal




$O(n^2)$
combinations



$O(n^3)$
combinations




Gives $O(n^3)$ dependency grammar parsing




McDonald et al. (2005 ACL)

Online Large-Margin Training of Dependency Parsers

- One of two best-known recent dependency parsers
- Score of a dependency tree = sum of scores of dependencies
- Scores are independent of other dependencies
- If scores are available, parsing can be solved as a minimum spanning tree problem
 - Chiu-Liu-Edmonds algorithm
 - One then needs a score for dependencies




Christopher Manning



McDonald et al. (2005 ACL):
Online Large-Margin Training of Dependency Parsers


- Edge scoring is via a discriminative classifier
 - Can condition on rich features in that context
 - Each dependency is a linear function of features times weights
- Feature weights were learned by MIRA, an online large-margin algorithm
 - But you could use an SVM, maxent, or a perceptron
- Features cover:
 - Head and dependent word and POS separately
 - Head and dependent word and POS bigram features
 - Words between head and dependent
 - Length and direction of dependency



Greedy Transition-Based Parsing

MaltParser


Christopher Manning



MaltParser
[Nivre et al. 2008]

- A simple form of greedy discriminative dependency parser
- The parser does a sequence of bottom up actions
 - Roughly like “shift” or “reduce” in a shift-reduce parser, but the “reduce” actions are specialized to create dependencies with head on left or right
- The parser has:
 - a stack σ , written with top to the right
 - which starts with the ROOT symbol
 - a buffer β , written with top to the left
 - which starts with the input sentence
 - a set of dependency arcs A
 - which starts off empty
 - a set of actions

Christopher Manning



Basic transition-based dependency parser

Start: $\sigma = [\text{ROOT}]$, $\beta = w_1, \dots, w_n$, $A = \emptyset$


- Shift $\sigma, w_i | \beta, A \rightarrow \sigma, w_i, \beta, A$
- Left-Arc $\sigma | w_i, w_j | \beta, A \rightarrow \sigma, w_j | \beta, A \cup \{r(w_i, w_j)\}$
- Right-Arc $\sigma | w_i, w_j | \beta, A \rightarrow \sigma, w_i | \beta, A \cup \{r(w_i, w_j)\}$

Finish: $\beta = \emptyset$

Notes:

- Unlike the regular presentation of the CFG reduce step, dependencies combine one thing from each of stack and buffer

Christopher Manning



Actions (“arc-eager” dependency parser)


Start: $\sigma = [\text{ROOT}]$, $\beta = w_1, \dots, w_n$, $A = \emptyset$

- Left-Arc $\sigma | w_i, w_j | \beta, A \rightarrow \sigma, w_j | \beta, A \cup \{r(w_i, w_j)\}$
Precondition: $r'(w_i, w_j) \in A$, $w_i \neq \text{ROOT}$
- Right-Arc $\sigma | w_i, w_j | \beta, A \rightarrow \sigma | w_i | w_j, \beta, A \cup \{r(w_i, w_j)\}$
- Reduce $\sigma | w_i, \beta, A \rightarrow \sigma, \beta, A$
Precondition: $r'(w_i, w_i) \in A$
- Shift $\sigma, w_i | \beta, A \rightarrow \sigma | w_i, \beta, A$

Finish: $\beta = \emptyset$

This is the common “arc-eager” variant: a head can immediately take a right dependent, before *its* dependents are found

Christopher Manning




Example

1. Left-Arc	$\sigma w_i, w_j \beta, A \rightarrow \sigma, w_j \beta, A \cup \{r(w_i, w_j)\}$	Precondition: $(w_i, r', w_j) \in A$, $w_i \neq \text{ROOT}$
2. Right-Arc	$\sigma w_i, w_j \beta, A \rightarrow \sigma w_i w_j, \beta, A \cup \{r(w_i, w_j)\}$	
3. Reduce	$\sigma w_i, \beta, A \rightarrow \sigma, \beta, A$	Precondition: $(w_i, r', w_i) \in A$
4. Shift	$\sigma, w_i \beta, A \rightarrow \sigma w_i, \beta, A$	

Happy children like to play with their friends .

	[ROOT]	[Happy, children, ...]	\emptyset
Shift	[ROOT, Happy]	[children, like, ...]	\emptyset
LA _{amod}	[ROOT]	[children, like, ...]	$\{\text{amod}(\text{children}, \text{happy})\} = A_1$
Shift	[ROOT, children]	[like, to, ...]	A_1
LA _{subj}	[ROOT]	[like, to, ...]	$A_1 \cup \{\text{nsbj}(\text{like}, \text{children})\} = A_2$
RA _{root}	[ROOT, like]	[to, play, ...]	$A_2 \cup \{\text{root}(\text{ROOT}, \text{like})\} = A_3$
Shift	[ROOT, like, to]	[play, with, ...]	A_3
LA _{aux}	[ROOT, like]	[play, with, ...]	$A_3 \cup \{\text{aux}(\text{play}, \text{to})\} = A_4$
RA _{xcomp}	[ROOT, like, play]	[with their, ...]	$A_4 \cup \{\text{xcomp}(\text{like}, \text{play})\} = A_5$

Christopher Manning

 **Example**

Happy children like to play with their friends .

RA_{xcomp} [ROOT, like, play] [with their, ...] $A_4 \cup \{xcomp(like, play) = A_5\}$
 RA_{prep} [ROOT, like, play, with] [their, friends, ...] $A_5 \cup \{prep(play, with) = A_6\}$
Shift [ROOT, like, play, with, their] [friends, .] A_6
 LA_{poss} [ROOT, like, play, with] [friends, .] $A_6 \cup \{poss(friends, their) = A_7\}$
 RA_{pobj} [ROOT, like, play, with, friends] [.] $A_7 \cup \{pobj(with, friends) = A_8\}$
Reduce [ROOT, like, play, with] [.] A_8
Reduce [ROOT, like, play] [.] A_8
Reduce [ROOT, like] [.] A_8
 RA_{punc} [ROOT, like, .] [] $A_8 \cup \{punc(like, .) = A_9\}$

You terminate as soon as the buffer is empty. Dependencies = A_9

Example

1. Left-Arc: $\sigma[w_i, w_j] \beta, A \rightarrow \sigma, w_j | \beta, A \cup \{r(w_i, w_j)\}$
Precondition: $(w_i, r', w_j) \in A, w_i \neq ROOT$
2. Right-Arc: $\sigma[w_i, w_j] \beta, A \rightarrow \sigma | w_i | w_j, \beta, A \cup \{r(w_i, w_j)\}$
3. Reduce: $\sigma[w_i, \beta], A \rightarrow \sigma, \beta, A$
Precondition: $(w_i, r', w_j) \in A$
4. Shift: $\sigma, w_i | \beta, A \rightarrow \sigma | w_i, \beta, A$

$\left[\text{_ROOT_} \right]_S \left\{ \text{Red figures on the screen indicated falling stocks} \right\}_Q$

28 Dependency Parsing (Prashanth Mannem) October 21, 2013

Example

1. Left-Arc: $\sigma[w_i, w_j] \beta, A \rightarrow \sigma, w_j | \beta, A \cup \{r(w_i, w_j)\}$
Precondition: $(w_i, r', w_j) \in A, w_i \neq ROOT$
2. Right-Arc: $\sigma[w_i, w_j] \beta, A \rightarrow \sigma | w_i | w_j, \beta, A \cup \{r(w_i, w_j)\}$
3. Reduce: $\sigma[w_i, \beta], A \rightarrow \sigma, \beta, A$
Precondition: $(w_i, r', w_j) \in A$
4. Shift: $\sigma, w_i | \beta, A \rightarrow \sigma | w_i, \beta, A$

$\left[\text{_ROOT_} \text{Red} \right]_S \left\{ \text{figures on the screen indicated falling stocks} \right\}_Q$

Shift

29 Dependency Parsing (P. Mannem) October 21, 2013

Example

1. Left-Arc: $\sigma[w_i, w_j] \beta, A \rightarrow \sigma, w_j | \beta, A \cup \{r(w_i, w_j)\}$
Precondition: $(w_i, r', w_j) \in A, w_i \neq ROOT$
2. Right-Arc: $\sigma[w_i, w_j] \beta, A \rightarrow \sigma | w_i | w_j, \beta, A \cup \{r(w_i, w_j)\}$
3. Reduce: $\sigma[w_i, \beta], A \rightarrow \sigma, \beta, A$
Precondition: $(w_i, r', w_j) \in A$
4. Shift: $\sigma, w_i | \beta, A \rightarrow \sigma | w_i, \beta, A$

$\left[\text{_ROOT_} \right]_S \text{Red} \left\{ \text{figures on the screen indicated falling stocks} \right\}_Q$

Left-arc

30 Dependency Parsing (P. Mannem) October 21, 2013

Example

1. Left-Arc: $\sigma[w_i, w_j] \beta, A \rightarrow \sigma, w_j | \beta, A \cup \{r(w_i, w_j)\}$
Precondition: $(w_i, r', w_j) \in A, w_i \neq ROOT$
2. Right-Arc: $\sigma[w_i, w_j] \beta, A \rightarrow \sigma | w_i | w_j, \beta, A \cup \{r(w_i, w_j)\}$
3. Reduce: $\sigma[w_i, \beta], A \rightarrow \sigma, \beta, A$
Precondition: $(w_i, r', w_j) \in A$
4. Shift: $\sigma, w_i | \beta, A \rightarrow \sigma | w_i, \beta, A$

$\left[\text{_ROOT_} \text{Red figures} \right]_S \left\{ \text{on the screen indicated falling stocks} \right\}_Q$

Shift

31 Dependency Parsing (P. Mannem) October 21, 2013

Example

1. Left-Arc: $\sigma[w_i, w_j] \beta, A \rightarrow \sigma, w_j | \beta, A \cup \{r(w_i, w_j)\}$
Precondition: $(w_i, r', w_j) \in A, w_i \neq ROOT$
2. Right-Arc: $\sigma[w_i, w_j] \beta, A \rightarrow \sigma | w_i | w_j, \beta, A \cup \{r(w_i, w_j)\}$
3. Reduce: $\sigma[w_i, \beta], A \rightarrow \sigma, \beta, A$
Precondition: $(w_i, r', w_j) \in A$
4. Shift: $\sigma, w_i | \beta, A \rightarrow \sigma | w_i, \beta, A$

$\left[\text{_ROOT_} \text{Red figures on} \right]_S \left\{ \text{the screen indicated falling stocks} \right\}_Q$

Right-arc

32 Dependency Parsing (P. Mannem) October 21, 2013

Example

1. Left-Arc, $\sigma[w_i, w_j] \beta, A \rightarrow \sigma, w_j \beta, A \cup \{r(w_i, w_j)\}$
Precondition: $(w_i, r', w_j) \in A, w_i \neq \text{ROOT}$
2. Right-Arc, $\sigma[w_i, w_j] \beta, A \rightarrow \sigma[w_i] w_j \beta, A \cup \{r(w_i, w_j)\}$
3. Reduce, $\sigma[w_i, \beta, A \rightarrow \sigma, \beta, A$
Precondition: $(w_i, r', w_j) \in A$
4. Shift, $\sigma, w_j \beta, A \rightarrow \sigma[w_j] \beta, A$

$\left[\text{_ROOT_} \text{Red figures on the} \right]_S \left[\text{screen indicated falling stocks} \right]_Q$

Shift

► 33 Dependency Parsing (P. Mannem) October 21, 2013

Example

1. Left-Arc, $\sigma[w_i, w_j] \beta, A \rightarrow \sigma, w_j \beta, A \cup \{r(w_i, w_j)\}$
Precondition: $(w_i, r', w_j) \in A, w_i \neq \text{ROOT}$
2. Right-Arc, $\sigma[w_i, w_j] \beta, A \rightarrow \sigma[w_i] w_j \beta, A \cup \{r(w_i, w_j)\}$
3. Reduce, $\sigma[w_i, \beta, A \rightarrow \sigma, \beta, A$
Precondition: $(w_i, r', w_j) \in A$
4. Shift, $\sigma, w_j \beta, A \rightarrow \sigma[w_j] \beta, A$

$\left[\text{_ROOT_} \text{Red figures on} \right]_S \left[\text{the screen indicated falling stocks} \right]_Q$

Left-arc

► 34 Dependency Parsing (P. Mannem) October 21, 2013

Example

1. Left-Arc, $\sigma[w_i, w_j] \beta, A \rightarrow \sigma, w_j \beta, A \cup \{r(w_i, w_j)\}$
Precondition: $(w_i, r', w_j) \in A, w_i \neq \text{ROOT}$
2. Right-Arc, $\sigma[w_i, w_j] \beta, A \rightarrow \sigma[w_i] w_j \beta, A \cup \{r(w_i, w_j)\}$
3. Reduce, $\sigma[w_i, \beta, A \rightarrow \sigma, \beta, A$
Precondition: $(w_i, r', w_j) \in A$
4. Shift, $\sigma, w_j \beta, A \rightarrow \sigma[w_j] \beta, A$

$\left[\text{_ROOT_} \text{Red figures on the screen} \right]_S \left[\text{indicated falling stocks} \right]_Q$

Right-arc

► 35 Dependency Parsing (P. Mannem) October 21, 2013

Example

1. Left-Arc, $\sigma[w_i, w_j] \beta, A \rightarrow \sigma, w_j \beta, A \cup \{r(w_i, w_j)\}$
Precondition: $(w_i, r', w_j) \in A, w_i \neq \text{ROOT}$
2. Right-Arc, $\sigma[w_i, w_j] \beta, A \rightarrow \sigma[w_i] w_j \beta, A \cup \{r(w_i, w_j)\}$
3. Reduce, $\sigma[w_i, \beta, A \rightarrow \sigma, \beta, A$
Precondition: $(w_i, r', w_j) \in A$
4. Shift, $\sigma, w_j \beta, A \rightarrow \sigma[w_j] \beta, A$

$\left[\text{_ROOT_} \text{Red figures on the screen} \right]_S \left[\text{indicated falling stocks} \right]_Q$

Reduce

► 36 Dependency Parsing (P. Mannem) October 21, 2013

Example

1. Left-Arc, $\sigma[w_i, w_j] \beta, A \rightarrow \sigma, w_j \beta, A \cup \{r(w_i, w_j)\}$
Precondition: $(w_i, r', w_j) \in A, w_i \neq \text{ROOT}$
2. Right-Arc, $\sigma[w_i, w_j] \beta, A \rightarrow \sigma[w_i] w_j \beta, A \cup \{r(w_i, w_j)\}$
3. Reduce, $\sigma[w_i, \beta, A \rightarrow \sigma, \beta, A$
Precondition: $(w_i, r', w_j) \in A$
4. Shift, $\sigma, w_j \beta, A \rightarrow \sigma[w_j] \beta, A$

$\left[\text{_ROOT_} \text{Red figures} \right]_S \left[\text{on the screen indicated falling stocks} \right]_Q$

Reduce

► 37 Dependency Parsing (P. Mannem) October 21, 2013

Example

1. Left-Arc, $\sigma[w_i, w_j] \beta, A \rightarrow \sigma, w_j \beta, A \cup \{r(w_i, w_j)\}$
Precondition: $(w_i, r', w_j) \in A, w_i \neq \text{ROOT}$
2. Right-Arc, $\sigma[w_i, w_j] \beta, A \rightarrow \sigma[w_i] w_j \beta, A \cup \{r(w_i, w_j)\}$
3. Reduce, $\sigma[w_i, \beta, A \rightarrow \sigma, \beta, A$
Precondition: $(w_i, r', w_j) \in A$
4. Shift, $\sigma, w_j \beta, A \rightarrow \sigma[w_j] \beta, A$

$\left[\text{_ROOT_} \right]_S \left[\text{Red figures on the screen indicated falling stocks} \right]_Q$

Left-arc

► 38 Dependency Parsing (P. Mannem) October 21, 2013

Example

1. Left-Arc, $\sigma[w_i, w_j] \beta, A \rightarrow \sigma, w_j \beta, A \cup \{r(w_i, w_j)\}$
Precondition: $(w_i, r', w_j) \in A, w_i \neq \text{ROOT}$
2. Right-Arc, $\sigma[w_i, w_j] \beta, A \rightarrow \sigma[w_i] w_j \beta, A \cup \{r(w_i, w_j)\}$
3. Reduce, $\sigma[w_i] \beta, A \rightarrow \sigma, \beta, A$
Precondition: $(w_i, r', w_j) \in A$
4. Shift, $\sigma, w_j \beta, A \rightarrow \sigma[w_j] \beta, A$

Right-arc

► 39 Dependency Parsing (P. Mannem) October 21, 2013

Example

1. Left-Arc, $\sigma[w_i, w_j] \beta, A \rightarrow \sigma, w_j \beta, A \cup \{r(w_i, w_j)\}$
Precondition: $(w_i, r', w_j) \in A, w_i \neq \text{ROOT}$
2. Right-Arc, $\sigma[w_i, w_j] \beta, A \rightarrow \sigma[w_i] w_j \beta, A \cup \{r(w_i, w_j)\}$
3. Reduce, $\sigma[w_i] \beta, A \rightarrow \sigma, \beta, A$
Precondition: $(w_i, r', w_j) \in A$
4. Shift, $\sigma, w_j \beta, A \rightarrow \sigma[w_j] \beta, A$

Shift

► 40 Dependency Parsing (P. Mannem) October 21, 2013

Example

1. Left-Arc, $\sigma[w_i, w_j] \beta, A \rightarrow \sigma, w_j \beta, A \cup \{r(w_i, w_j)\}$
Precondition: $(w_i, r', w_j) \in A, w_i \neq \text{ROOT}$
2. Right-Arc, $\sigma[w_i, w_j] \beta, A \rightarrow \sigma[w_i] w_j \beta, A \cup \{r(w_i, w_j)\}$
3. Reduce, $\sigma[w_i] \beta, A \rightarrow \sigma, \beta, A$
Precondition: $(w_i, r', w_j) \in A$
4. Shift, $\sigma, w_j \beta, A \rightarrow \sigma[w_j] \beta, A$

Left-arc

► 41 Dependency Parsing (P. Mannem) October 21, 2013

Example

1. Left-Arc, $\sigma[w_i, w_j] \beta, A \rightarrow \sigma, w_j \beta, A \cup \{r(w_i, w_j)\}$
Precondition: $(w_i, r', w_j) \in A, w_i \neq \text{ROOT}$
2. Right-Arc, $\sigma[w_i, w_j] \beta, A \rightarrow \sigma[w_i] w_j \beta, A \cup \{r(w_i, w_j)\}$
3. Reduce, $\sigma[w_i] \beta, A \rightarrow \sigma, \beta, A$
Precondition: $(w_i, r', w_j) \in A$
4. Shift, $\sigma, w_j \beta, A \rightarrow \sigma[w_j] \beta, A$

Right-arc

► 42 Dependency Parsing (P. Mannem) October 21, 2013

Example

1. Left-Arc, $\sigma[w_i, w_j] \beta, A \rightarrow \sigma, w_j \beta, A \cup \{r(w_i, w_j)\}$
Precondition: $(w_i, r', w_j) \in A, w_i \neq \text{ROOT}$
2. Right-Arc, $\sigma[w_i, w_j] \beta, A \rightarrow \sigma[w_i] w_j \beta, A \cup \{r(w_i, w_j)\}$
3. Reduce, $\sigma[w_i] \beta, A \rightarrow \sigma, \beta, A$
Precondition: $(w_i, r', w_j) \in A$
4. Shift, $\sigma, w_j \beta, A \rightarrow \sigma[w_j] \beta, A$

Reduce


► 43 Dependency Parsing (P. Mannem) October 21, 2013

Example

1. Left-Arc, $\sigma[w_i, w_j] \beta, A \rightarrow \sigma, w_j \beta, A \cup \{r(w_i, w_j)\}$
Precondition: $(w_i, r', w_j) \in A, w_i \neq \text{ROOT}$
2. Right-Arc, $\sigma[w_i, w_j] \beta, A \rightarrow \sigma[w_i] w_j \beta, A \cup \{r(w_i, w_j)\}$
3. Reduce, $\sigma[w_i] \beta, A \rightarrow \sigma, \beta, A$
Precondition: $(w_i, r', w_j) \in A$
4. Shift, $\sigma, w_j \beta, A \rightarrow \sigma[w_j] \beta, A$

Reduce

► 44 Dependency Parsing (P. Mannem) October 21, 2013




Christopher Manning

MaltParser


[Nivre et al. 2008]

- We have left to explain how we choose the next action
- Each action is predicted by a discriminative classifier (often SVM, can be perceptron, maxent classifier) over each legal move
 - Max of 4 untyped choices, max of $|R| \times 2 + 2$ when typed
 - Features: top of stack word, POS; first in buffer word, POS; etc.
- There is NO search (in the simplest and usual form)
 - But you could do some kind of beam search if you wish
- It provides **VERY** fast time parsing
- The model's accuracy is *slightly* below the best Lexicalized PCFGs (evaluated on dependencies), but
- It provides close to state of the art parsing performance



Christopher Manning

Evaluation of Dependency Parsing: (labeled) dependency accuracy




$$\text{Acc} = \frac{\# \text{ correct deps}}{\# \text{ of deps}}$$

UAS = 4 / 5 = 80%

LAS = 2 / 5 = 40%

Gold	
1	2
2	0
3	5
4	5
5	2

Parsed	
1	2
2	0
3	4
4	5
5	2




Representative performance numbers

- The CoNLL-X (2006) shared task provides evaluation numbers for various dependency parsing approaches over 13 languages
 - MALT: LAS scores from 65–92%, depending greatly on language/treebank
- Here we give a few UAS for English to allow some comparison to constituency parsing


Parser	UAS%
Sagae and Lavie (2006) ensemble of dependency parsers	92.7
Charniak (2000) <i>generative, constituency, as dependencies</i>	92.2
Collins (1999) <i>generative, constituency, as dependencies</i>	91.7
McDonald and Pereira (2005) – MST graph-based dependency	91.5
Yamada and Matsumoto (2003) – transition-based dependency	90.4

Christopher Manning




Projectivity

- Dependencies from a CFG tree using heads, must be **projective**
 - There must not be any crossing dependency arcs when the words are laid out in their linear order, with all arcs above the words.
- But dependency theory normally does allow non-projective structures to account for displaced constituents
 - You can't easily get the semantics of certain constructions right without these nonprojective dependencies



Who did Bill buy the coffee from yesterday ?

Christopher Manning



Handling non-projectivity

- The arc-eager algorithm we presented only builds projective dependency trees
- Possible directions to head:
 1. Just declare defeat on nonprojective arcs
 2. Use a dependency formalism which only admits projective representations (a CFG doesn't represent such structures...)
 3. Use a postprocessor to a projective dependency parsing algorithm to identify and resolve nonprojective links
 4. Add extra types of transitions that can model at least most non-projective structures
 5. Move to a parsing mechanism that does not use or require any constraints on projectivity (e.g., the graph-based MSTParser)

Christopher Manning

Dependency paths identify relations like protein interaction

[Erkan et al. EMNLP 07, Fundel et al. 2007]

KaiC ←_{nsbj} interacts _{prep_with}→ SasA
 KaiC ←_{nsbj} interacts _{prep_with}→ SasA _{conj_and}→ KaiA
 KaiC ←_{nsbj} interacts _{prep_with}→ SasA _{conj_and}→ KaiB

Christopher Manning

Stanford Dependencies

[de Marneffe et al. LREC 2006]

- The basic dependency representation is projective
- It can be generated by postprocessing headed phrase structure parses (Penn Treebank syntax)
- It can also be generated directly by dependency parsers, such as MaltParser, or the Easy-First Parser

Christopher Manning


Graph modification to facilitate semantic analysis

Bell, based in LA, makes and distributes electronic and computer products.

Christopher Manning

Graph modification to facilitate semantic analysis

Bell, based in LA, makes and distributes electronic and computer products.



Christopher Manning

56