


Dependency Grammar


Introduction

Christopher Manning




Dependency Grammar and Dependency Structure

Dependency syntax postulates that syntactic structure consists of relations between lexical items, normally binary asymmetric relations ("arrows") called **dependencies**




Christopher Manning




Dependency Grammar and Dependency Structure

Dependency syntax postulates that syntactic structure consists of relations between lexical items, normally binary asymmetric relations ("arrows") called **dependencies**

The arrows are commonly **typed** with the name of grammatical relations (subject, prepositional object, apposition, etc.)



Christopher Manning




Dependency Grammar and Dependency Structure


Dependency syntax postulates that syntactic structure consists of relations between lexical items, normally binary asymmetric relations ("arrows") called **dependencies**

The arrow connects a **head** (governor, superior, regent) with a **dependent** (modifier, inferior, subordinate)


Usually, dependencies form a tree (connected, acyclic, single-head)



Christopher Manning




Dependency Grammar and Dependency Structure



ROOT Discussion of the outstanding issues was completed .

- Some people draw the arrows one way; some the other way!
 - Tesnière had them point from head to dependent...
- Usually add a fake ROOT so every word is a dependent of precisely 1 other node

Christopher Manning



Dependency Grammar/Parsing History

- The idea of dependency structure goes back a long way
 - To Pāṇini's grammar (c. 5th century BCE)
 - Basic approach of 1st millennium Arabic grammarians
- Constituency is a new-fangled invention
 - 20th century invention (R.S. Wells, 1947)
- Modern dependency work often linked to work of L. Tesnière (1959)
 - Was dominant approach in "East" (Russia, China, ...)
 - Good for free-er word order languages
- Among the earliest kinds of parsers in NLP, even in the US:
 - David Hays, one of the founders of U.S. computational linguistics, built early (first?) dependency parser (Hays 1962)


Relationship between phrase structure and dependency structure

- A dependency grammar has a notion of a head. Officially, CFGs don't.
- But modern linguistic theory and all modern statistical parsers (Charniak, Collins, Stanford, ...) do, via hand-written phrasal "head rules":
 - The head of a Noun Phrase is a noun/number/adj/...
 - The head of a Verb Phrase is a verb/modal/...
- The head rules can be used to extract a dependency parse from a CFG parse

The closure of dependencies give constituency from a dependency tree

But the dependents of a word must be at the same level (i.e., "flat") – there can be no VP!


```
graph TD
    swalked --> NPSue[NP Sue]
    swalked --> VPwalked[VP walked]
    NPSue --> NNP[Sue]
    VPwalked --> VBDwalked[VBD walked]
    VPwalked --> PPinto[PP into]
    VBDwalked --> ISue[I Sue]
    VBDwalked --> Iwalked[I walked]
    PPinto --> Pinto[P into]
    PPinto --> NPstore[NP store]
    Pinto --> Iinto[I into]
    NPstore --> DTthe[DT the]
    NPstore --> NNstore[NN store]
    DTthe --> Ithe[I the]
    NNstore --> Istore[I store]
```



Dependency Conditioning Preferences

What are the sources of information for dependency parsing?

1. Bilexical affinities [issues → the] is plausible
2. Dependency distance mostly with nearby words
3. Intervening material
Dependencies rarely span intervening verbs or punctuation
4. Valency of heads
How many dependents on which side are usual for a head?



ROOT Discussion of the outstanding issues was completed .


Christopher Manning

Dependency Parsing

- A sentence is parsed by choosing for each word what other word (including ROOT) that it is a dependent of.
- Usually some constraints:
 - Only one word is a dependent of ROOT
 - Don't want cycles $A \rightarrow B, B \rightarrow A$
- This makes the dependencies a tree
- Final issue is whether arrows can cross (non-projective) or not

The diagram shows a dependency parse tree for the sentence "I'll give a talk tomorrow on bootstrapping". The root node is "ROOT", which has a single child "I". "I" has a child "ll", which in turn has a child "give". "give" has two children: "a" and "talk". "talk" has a child "tomorrow". "tomorrow" has a child "on", which finally has a child "bootstrapping". The arrows represent the dependency edges, showing a hierarchical tree structure where each word (except the root) has exactly one parent.

9



Christopher Manning

Stanford University
Natural Language Processing

Methods of Dependency Parsing

- Dynamic programming (like in the CKY algorithm)**

You can do it similarly to lexicalized PCFG parsing: an $O(n^3)$ algorithm

Eisner (1996) gives a clever algorithm that reduces the complexity to $O(n^3)$, by producing parse items with heads at the ends rather than in the middle
- Graph algorithms**

You create a Minimum Spanning Tree for a sentence


McDonald et al.'s (2005) MSTParser scores dependencies independently using a ML classifier (he uses MIRA, for online learning, but it can be something else)
- Constraint Satisfaction**

Edges are eliminated that don't satisfy hard constraints. Karlsson (1990), etc.
- "Deterministic parsing"**

Greedy choice of attachments guided by good machine learning classifiers


MaltParser (Nivre et al. 2008)







Christopher Manning




Probabilistic dependency grammar: generative model

1. Start with left wall \$
2. Generate root w_0
3. Generate left children $w_{-1}, w_{-2}, \dots, w_{-\ell}$ from the FSA λ_{w_0}
4. Generate right children w_1, w_2, \dots, w_r from the FSA ρ_{w_0}
5. Recurse on each w_i for i in $\{-\ell, \dots, -1, 1, \dots, r\}$, sampling α (steps 2-4)
6. Return $\alpha_{-\ell} \dots \alpha_{-1} w_0 \alpha_1 \dots \alpha_r$








Christopher Manning


McDonald et al. (2005 ACL):

Online Large-Margin Training of Dependency Parsers

- Edge scoring is via a discriminative classifier
 - Can condition on rich features in that context
 - Each dependency is a linear function of features times weights
- Feature weights were learned by MIRA, an online large-margin algorithm
 - But you could use an SVM, maxent, or a perceptron
- Features cover:
 - Head and dependent word and POS separately
 - Head and dependent word and POS bigram features
 - Words between head and dependent
 - Length and direction of dependency



MaltParser
[Nivre et al. 2008]



- A simple form of greedy discriminative dependency parser
- The parser does a sequence of bottom up actions
 - Roughly like “shift” or “reduce” in a shift-reduce parser, but the “reduce” actions are specialized to create dependencies with head on left or right
- The parser has:
 - a stack σ , written with top to the right
 - which starts with the ROOT symbol
 - a buffer β , written with top to the left
 - which starts with the input sentence
 - a set of dependency arcs A
 - which starts off empty
 - a set of actions

Christopher Manning

Basic transition-based dependency parser


Start: $\sigma = [\text{ROOT}]$, $\beta = w_1, \dots, w_n$, $A = \varnothing$

1. Shift $\sigma, w_i | \beta, A \rightarrow \sigma | w_i, \beta, A$
2. Left-Arc_c $\sigma | w_i, w_j | \beta, A \rightarrow \sigma, w_i | \beta, A \cup \{r(w_i, w_j)\}$
3. Right-Arc_c $\sigma | w_i, w_j | \beta, A \rightarrow \sigma, w_i | \beta, A \cup \{r(w_i, w_j)\}$

Finish: $\beta = \varnothing$

Notes:

- Unlike the regular presentation of the CFG reduce step, dependencies combine one thing from each of stack and buffer



Christophorus Manning

Dependency Parsing


Actions (“arc-eager” dependency parser)

Start: $\sigma = [\text{ROOT}], \beta = w_1, \dots, w_n, A = \varnothing$

1. Left-Arc_r $\sigma | w_i, w_j | \beta, A \rightarrow \sigma, w_j | \beta, A \cup \{r(w_i, w_j)\}$
 Precondition: $r'(w_i, w_j) \notin A, w_i \neq \text{ROOT}$
2. Right-Arc_r $\sigma | w_i, w_j | \beta, A \rightarrow \sigma | w_i, w_j, \beta, A \cup \{r(w_i, w_j)\}$
3. Reduce $\sigma | w_i, \beta, A \rightarrow \sigma, \beta, A$
 Precondition: $r'(w_i, w_i) \in A$
4. Shift $\sigma, w_i | \beta, A \rightarrow \sigma | w_i, \beta, A$

Finish: $\beta = \varnothing$

This is the common “arc-eager” variant: a head can immediately take a right dependent, before *its* dependents are found




Christopher Manning

Example

Happy children like to play with their friends .

	<ol style="list-style-type: none"> 1. Left-Arc: $\alpha[w, w] \beta, A \Rightarrow \alpha, w] \beta, A U \{r(w, w)\}$ Precondition: $\{w, r', w\} \in A, w, \# \text{ ROOT}$ 2. Right-Arc: $\alpha, w] \beta, A \Rightarrow \alpha[w] \beta, A U \{r(w, w)\}$ 3. Reduce: $\alpha[w, \beta, A] \Rightarrow \alpha, \beta, A$ Precondition: $\{w, r', w\} \in A$ 4. Shift: $\alpha, w] \beta, A \Rightarrow \alpha, w] \beta, A$ 		
Shift	[ROOT]	[Happy, children, ...]	\varnothing
Shift	[ROOT, Happy]	[children, like, ...]	\varnothing
LA_{amod}	[ROOT]	[children, like, ...]	$A_1 \{ \text{amod}(\text{children}, \text{happy}) \} = A_1$
Shift	[ROOT, children]	[like, to, ...]	A_1
LA_{nsubj}	[ROOT]	[like, to, ...]	$A_1 \cup \{ \text{nsubj}(\text{like}, \text{children}) \} = A_2$
RA_{root}	[ROOT, like]	[to, play, ...]	$A_2 \cup \{ \text{root}(\text{ROOT}, \text{like}) \} = A_3$
Shift	[ROOT, like, to]	[play, with, ...]	A_3
LA_{aux}	[ROOT, like]	[play, with, ...]	$A_3 \cup \{ \text{aux}(\text{play}, \text{to}) \} = A_4$
RA_{xcomp}	[ROOT, like, play]	[with their, ...]	$A_4 \cup \{ \text{xcomp}(\text{like}, \text{play}) \} = A_5$

Christopher Manning

 **Example**

1. Left-Arc, $\sigma | w_p, w_j | \beta, A \rightarrow \sigma, w_j | \beta, A \cup \{r(w_p, w_j)\}$
Precondition: $(w_p, r', w_j) \in A, w_j \neq \text{ROOT}$
2. Right-Arc, $\sigma | w_p, w_j | \beta, A \rightarrow \sigma | w_p | w_j, \beta, A \cup \{r(w_p, w_j)\}$
3. Reduce, $\sigma | w_p, \beta, A \rightarrow \sigma, \beta, A$
Precondition: $(w_p, r', w_j) \in A$
4. Shift, $\sigma, w_j | \beta, A \rightarrow \sigma | w_p, \beta, A$

Happy children like to play with their friends .

RA_{xcomp} [ROOT, like, play] [with their, ...] $A_4 \cup \{xcomp(like, play) = A_5\}$
 RA_{prep} [ROOT, like, play, with] [their, friends, ...] $A_5 \cup \{prep(play, with) = A_6\}$
Shift [ROOT, like, play, with, their] [friends, .] A_6
 LA_{poss} [ROOT, like, play, with] [friends, .] $A_6 \cup \{poss(friends, their) = A_7\}$
 RA_{pobj} [ROOT, like, play, with, friends] [.] $A_7 \cup \{pobj(with, friends) = A_8\}$
Reduce [ROOT, like, play, with] [.] A_8
Reduce [ROOT, like, play] [.] A_8
Reduce [ROOT, like] [.] A_8
 RA_{punc} [ROOT, like, .] [] $A_8 \cup \{punc(like, .) = A_9\}$

You terminate as soon as the buffer is empty. Dependencies = A_9

Example

1. Left-Arc, $\sigma | w_p, w_j | \beta, A \rightarrow \sigma, w_j | \beta, A \cup \{r(w_p, w_j)\}$
Precondition: $(w_p, r', w_j) \in A, w_j \neq \text{ROOT}$
2. Right-Arc, $\sigma | w_p, w_j | \beta, A \rightarrow \sigma | w_p | w_j, \beta, A \cup \{r(w_p, w_j)\}$
3. Reduce, $\sigma | w_p, \beta, A \rightarrow \sigma, \beta, A$
Precondition: $(w_p, r', w_j) \in A$
4. Shift, $\sigma, w_j | \beta, A \rightarrow \sigma | w_p, \beta, A$

$\left[\text{_ROOT_} \right]_S \left\{ \text{Red figures on the screen indicated falling stocks} \right\}_Q$

► 26 Dependency Parsing (Prashanth Mannem) October 20, 2014

Example

1. Left-Arc, $\sigma | w_p, w_j | \beta, A \rightarrow \sigma, w_j | \beta, A \cup \{r(w_p, w_j)\}$
Precondition: $(w_p, r', w_j) \in A, w_j \neq \text{ROOT}$
2. Right-Arc, $\sigma | w_p, w_j | \beta, A \rightarrow \sigma | w_p | w_j, \beta, A \cup \{r(w_p, w_j)\}$
3. Reduce, $\sigma | w_p, \beta, A \rightarrow \sigma, \beta, A$
Precondition: $(w_p, r', w_j) \in A$
4. Shift, $\sigma, w_j | \beta, A \rightarrow \sigma | w_p, \beta, A$

$\left[\text{_ROOT_} \text{Red} \right]_S \left\{ \text{figures on the screen indicated falling stocks} \right\}_Q$

Shift

► 27 Dependency Parsing (P. Mannem) October 20, 2014

Example

1. Left-Arc, $\sigma | w_p, w_j | \beta, A \rightarrow \sigma, w_j | \beta, A \cup \{r(w_p, w_j)\}$
Precondition: $(w_p, r', w_j) \in A, w_j \neq \text{ROOT}$
2. Right-Arc, $\sigma | w_p, w_j | \beta, A \rightarrow \sigma | w_p | w_j, \beta, A \cup \{r(w_p, w_j)\}$
3. Reduce, $\sigma | w_p, \beta, A \rightarrow \sigma, \beta, A$
Precondition: $(w_p, r', w_j) \in A$
4. Shift, $\sigma, w_j | \beta, A \rightarrow \sigma | w_p, \beta, A$

$\left[\text{_ROOT_} \right]_S \text{Red} \left\{ \text{figures on the screen indicated falling stocks} \right\}_Q$

Left-arc

► 28 Dependency Parsing (P. Mannem) October 20, 2014

Example

1. Left-Arc, $\sigma | w_p, w_j | \beta, A \rightarrow \sigma, w_j | \beta, A \cup \{r(w_p, w_j)\}$
Precondition: $(w_p, r', w_j) \in A, w_j \neq \text{ROOT}$
2. Right-Arc, $\sigma | w_p, w_j | \beta, A \rightarrow \sigma | w_p | w_j, \beta, A \cup \{r(w_p, w_j)\}$
3. Reduce, $\sigma | w_p, \beta, A \rightarrow \sigma, \beta, A$
Precondition: $(w_p, r', w_j) \in A$
4. Shift, $\sigma, w_j | \beta, A \rightarrow \sigma | w_p, \beta, A$

$\left[\text{_ROOT_} \text{Red figures} \right]_S \left\{ \text{on the screen indicated falling stocks} \right\}_Q$

Shift

► 29 Dependency Parsing (P. Mannem) October 20, 2014

Example

1. Left-Arc, $\sigma | w_p, w_j | \beta, A \rightarrow \sigma, w_j | \beta, A \cup \{r(w_p, w_j)\}$
Precondition: $(w_p, r', w_j) \in A, w_j \neq \text{ROOT}$
2. Right-Arc, $\sigma | w_p, w_j | \beta, A \rightarrow \sigma | w_p | w_j, \beta, A \cup \{r(w_p, w_j)\}$
3. Reduce, $\sigma | w_p, \beta, A \rightarrow \sigma, \beta, A$
Precondition: $(w_p, r', w_j) \in A$
4. Shift, $\sigma, w_j | \beta, A \rightarrow \sigma | w_p, \beta, A$

$\left[\text{_ROOT_} \text{Red figures on} \right]_S \left\{ \text{the screen indicated falling stocks} \right\}_Q$

Right-arc

► 30 Dependency Parsing (P. Mannem) October 20, 2014

Example

1. Left-Arc: $\sigma[w_i, w_j] \beta, A \rightarrow \sigma, w_j \beta, A \cup \{r(w_i, w_j)\}$
Precondition: $(w_i, r', w_j) \in A, w_i \neq \text{ROOT}$
2. Right-Arc: $\sigma[w_i, w_j] \beta, A \rightarrow \sigma[w_i] w_j \beta, A \cup \{r(w_i, w_j)\}$
3. Reduce: $\sigma[w_i, \beta, A \rightarrow \sigma, \beta, A$
Precondition: $(w_i, r', w_j) \in A$
4. Shift: $\sigma, w_i \beta, A \rightarrow \sigma[w_i] \beta, A$

$(_ \text{ROOT_} \text{Red figures on the})_S (\text{screen indicated falling stocks})_Q$

Shift

► 31 Dependency Parsing (P. Mannem) October 20, 2014

Example

1. Left-Arc: $\sigma[w_i, w_j] \beta, A \rightarrow \sigma, w_j \beta, A \cup \{r(w_i, w_j)\}$
Precondition: $(w_i, r', w_j) \in A, w_i \neq \text{ROOT}$
2. Right-Arc: $\sigma[w_i, w_j] \beta, A \rightarrow \sigma[w_i] w_j \beta, A \cup \{r(w_i, w_j)\}$
3. Reduce: $\sigma[w_i, \beta, A \rightarrow \sigma, \beta, A$
Precondition: $(w_i, r', w_j) \in A$
4. Shift: $\sigma, w_i \beta, A \rightarrow \sigma[w_i] \beta, A$

$(_ \text{ROOT_} \text{Red figures on the})_S (\text{screen indicated falling stocks})_Q$

Left-arc

► 32 Dependency Parsing (P. Mannem) October 20, 2014

Example

1. Left-Arc: $\sigma[w_i, w_j] \beta, A \rightarrow \sigma, w_j \beta, A \cup \{r(w_i, w_j)\}$
Precondition: $(w_i, r', w_j) \in A, w_i \neq \text{ROOT}$
2. Right-Arc: $\sigma[w_i, w_j] \beta, A \rightarrow \sigma[w_i] w_j \beta, A \cup \{r(w_i, w_j)\}$
3. Reduce: $\sigma[w_i, \beta, A \rightarrow \sigma, \beta, A$
Precondition: $(w_i, r', w_j) \in A$
4. Shift: $\sigma, w_i \beta, A \rightarrow \sigma[w_i] \beta, A$

$(_ \text{ROOT_} \text{Red figures on the screen})_S (\text{indicated falling stocks})_Q$

Right-arc

► 33 Dependency Parsing (P. Mannem) October 20, 2014

Example

1. Left-Arc: $\sigma[w_i, w_j] \beta, A \rightarrow \sigma, w_j \beta, A \cup \{r(w_i, w_j)\}$
Precondition: $(w_i, r', w_j) \in A, w_i \neq \text{ROOT}$
2. Right-Arc: $\sigma[w_i, w_j] \beta, A \rightarrow \sigma[w_i] w_j \beta, A \cup \{r(w_i, w_j)\}$
3. Reduce: $\sigma[w_i, \beta, A \rightarrow \sigma, \beta, A$
Precondition: $(w_i, r', w_j) \in A$
4. Shift: $\sigma, w_i \beta, A \rightarrow \sigma[w_i] \beta, A$

$(_ \text{ROOT_} \text{Red figures on the screen})_S (\text{indicated falling stocks})_Q$

Reduce

► 34 Dependency Parsing (P. Mannem) October 20, 2014

Example

1. Left-Arc: $\sigma[w_i, w_j] \beta, A \rightarrow \sigma, w_j \beta, A \cup \{r(w_i, w_j)\}$
Precondition: $(w_i, r', w_j) \in A, w_i \neq \text{ROOT}$
2. Right-Arc: $\sigma[w_i, w_j] \beta, A \rightarrow \sigma[w_i] w_j \beta, A \cup \{r(w_i, w_j)\}$
3. Reduce: $\sigma[w_i, \beta, A \rightarrow \sigma, \beta, A$
Precondition: $(w_i, r', w_j) \in A$
4. Shift: $\sigma, w_i \beta, A \rightarrow \sigma[w_i] \beta, A$

$(_ \text{ROOT_} \text{Red figures})_S (\text{on the screen indicated falling stocks})_Q$

Reduce

► 35 Dependency Parsing (P. Mannem) October 20, 2014

Example

1. Left-Arc: $\sigma[w_i, w_j] \beta, A \rightarrow \sigma, w_j \beta, A \cup \{r(w_i, w_j)\}$
Precondition: $(w_i, r', w_j) \in A, w_i \neq \text{ROOT}$
2. Right-Arc: $\sigma[w_i, w_j] \beta, A \rightarrow \sigma[w_i] w_j \beta, A \cup \{r(w_i, w_j)\}$
3. Reduce: $\sigma[w_i, \beta, A \rightarrow \sigma, \beta, A$
Precondition: $(w_i, r', w_j) \in A$
4. Shift: $\sigma, w_i \beta, A \rightarrow \sigma[w_i] \beta, A$

$(_ \text{ROOT_})_S (\text{Red figures on the screen indicated falling stocks})_Q$

Left-arc

► 36 Dependency Parsing (P. Mannem) October 20, 2014

Example

1. Left-Arc, $\sigma[w_i, w_j] \beta, A \rightarrow \sigma, w_j \beta, A \cup \{r(w_i, w_j)\}$
Precondition: $(w_i, r', w_j) \in A, w_i \neq \text{ROOT}$
2. Right-Arc, $\sigma[w_i, w_j] \beta, A \rightarrow \sigma[w_i] w_j \beta, A \cup \{r(w_i, w_j)\}$
3. Reduce, $\sigma[w_i, \beta, A \rightarrow \sigma, \beta, A$
Precondition: $(w_i, r', w_j) \in A$
4. Shift, $\sigma, w_j \beta, A \rightarrow \sigma[w_j] \beta, A$

Right-arc

► 37 Dependency Parsing (P. Mannem) October 20, 2014

Example

1. Left-Arc, $\sigma[w_i, w_j] \beta, A \rightarrow \sigma, w_j \beta, A \cup \{r(w_i, w_j)\}$
Precondition: $(w_i, r', w_j) \in A, w_i \neq \text{ROOT}$
2. Right-Arc, $\sigma[w_i, w_j] \beta, A \rightarrow \sigma[w_i] w_j \beta, A \cup \{r(w_i, w_j)\}$
3. Reduce, $\sigma[w_i, \beta, A \rightarrow \sigma, \beta, A$
Precondition: $(w_i, r', w_j) \in A$
4. Shift, $\sigma, w_j \beta, A \rightarrow \sigma[w_j] \beta, A$

Shift

► 38 Dependency Parsing (P. Mannem) October 20, 2014

Example

1. Left-Arc, $\sigma[w_i, w_j] \beta, A \rightarrow \sigma, w_j \beta, A \cup \{r(w_i, w_j)\}$
Precondition: $(w_i, r', w_j) \in A, w_i \neq \text{ROOT}$
2. Right-Arc, $\sigma[w_i, w_j] \beta, A \rightarrow \sigma[w_i] w_j \beta, A \cup \{r(w_i, w_j)\}$
3. Reduce, $\sigma[w_i, \beta, A \rightarrow \sigma, \beta, A$
Precondition: $(w_i, r', w_j) \in A$
4. Shift, $\sigma, w_j \beta, A \rightarrow \sigma[w_j] \beta, A$

Left-arc

► 39 Dependency Parsing (P. Mannem) October 20, 2014

Example

1. Left-Arc, $\sigma[w_i, w_j] \beta, A \rightarrow \sigma, w_j \beta, A \cup \{r(w_i, w_j)\}$
Precondition: $(w_i, r', w_j) \in A, w_i \neq \text{ROOT}$
2. Right-Arc, $\sigma[w_i, w_j] \beta, A \rightarrow \sigma[w_i] w_j \beta, A \cup \{r(w_i, w_j)\}$
3. Reduce, $\sigma[w_i, \beta, A \rightarrow \sigma, \beta, A$
Precondition: $(w_i, r', w_j) \in A$
4. Shift, $\sigma, w_j \beta, A \rightarrow \sigma[w_j] \beta, A$

Right-arc

► 40 Dependency Parsing (P. Mannem) October 20, 2014

Example

1. Left-Arc, $\sigma[w_i, w_j] \beta, A \rightarrow \sigma, w_j \beta, A \cup \{r(w_i, w_j)\}$
Precondition: $(w_i, r', w_j) \in A, w_i \neq \text{ROOT}$
2. Right-Arc, $\sigma[w_i, w_j] \beta, A \rightarrow \sigma[w_i] w_j \beta, A \cup \{r(w_i, w_j)\}$
3. Reduce, $\sigma[w_i, \beta, A \rightarrow \sigma, \beta, A$
Precondition: $(w_i, r', w_j) \in A$
4. Shift, $\sigma, w_j \beta, A \rightarrow \sigma[w_j] \beta, A$

Reduce

► 41 Dependency Parsing (P. Mannem) October 20, 2014


Example

1. Left-Arc, $\sigma[w_i, w_j] \beta, A \rightarrow \sigma, w_j \beta, A \cup \{r(w_i, w_j)\}$
Precondition: $(w_i, r', w_j) \in A, w_i \neq \text{ROOT}$
2. Right-Arc, $\sigma[w_i, w_j] \beta, A \rightarrow \sigma[w_i] w_j \beta, A \cup \{r(w_i, w_j)\}$
3. Reduce, $\sigma[w_i, \beta, A \rightarrow \sigma, \beta, A$
Precondition: $(w_i, r', w_j) \in A$
4. Shift, $\sigma, w_j \beta, A \rightarrow \sigma[w_j] \beta, A$

Reduce


► 42 Dependency Parsing (P. Mannem) October 20, 2014

Christopher Manning

 **MaltParser**
[Nivre et al. 2008]


- We have left to explain how we choose the next action
- Each action is predicted by a discriminative classifier (often SVM, can be perceptron, maxent classifier) over each legal move
 - Max of 4 untyped choices, max of $|R| \times 2 + 2$ when typed
 - Features: top of stack word, POS; first in buffer word, POS; etc.
- There is **NO** search (in the simplest and usual form)
 - But you could do some kind of beam search if you wish
- It provides **VERY** fast linear time parsing
- The model's accuracy is *slightly* below the best Lexicalized PCFGs (evaluated on dependencies), but
- It provides close to state of the art parsing performance

Christopher Manning

 **Evaluation of Dependency Parsing:**
(labeled) dependency accuracy


Acc = $\frac{\# \text{ correct deps}}{\# \text{ of deps}}$

UAS = $4 / 5 = 80\%$
LAS = $2 / 5 = 40\%$



Gold			Parsed		
1	2	She	1	2	She
2	0	saw	2	0	saw
3	5	the	3	4	the
4	5	video	4	5	video
5	2	lecture	5	2	lecture


Christopher Manning

 **Representative performance numbers**


- The CoNLL-X (2006) shared task provides evaluation numbers for various dependency parsing approaches over 13 languages
 - MALT: LAS scores from 65–92%, depending greatly on language/treebank
- Here we give a few UAS numbers for English to allow some comparison to constituency parsing

Parser	UAS%
Sagae and Lavie (2006) ensemble of dependency parsers	92.7
Charniak (2000) generative, constituency, as dependencies	92.2
Collins (1999) generative, constituency, as dependencies	91.7
McDonald and Pereira (2005) – MST graph-based dependency	91.5
Yamada and Matsumoto (2003) – transition-based dependency	90.4


Christopher Manning

 **Projectivity**

- Dependencies from a CFG tree using heads, must be **projective**
 - There must not be any crossing dependency arcs when the words are laid out in their linear order, with all arcs above the words.
- But dependency theory normally does allow non-projective structures to account for displaced constituents
 - You can't easily get the semantics of certain constructions right without these nonprojective dependencies




Christopher Manning

 **Handling non-projectivity**

- The arc-eager algorithm we presented only builds projective dependency trees
- Possible directions to head:
 - Just declare defeat on nonprojective arcs
 - Use a dependency formalism which only admits projective representations (a CFG doesn't represent such structures...)
 - Use a postprocessor to a projective dependency parsing algorithm to identify and resolve nonprojective links
 - Add extra types of transitions that can model at least most non-projective structures
 - Move to a parsing mechanism that does not use or require any constraints on projectivity (e.g., the graph-based MSTParser)

Dependencies encode relational structure

Relation Extraction with Stanford Dependencies



Christopher Manning

Dependency paths identify relations like protein interaction

[Erkan et al. EMNLP 07, Fundel et al. 2007]


KaiC ←*nsbj* interacts *prep_with*→ SasA
 KaiC ←*nsbj* interacts *prep_with*→ SasA *conj_and*→ KaiA
 KaiC ←*nsbj* interacts *prep_with*→ SasA *conj_and*→ KaiB

Christopher Manning

Stanford Dependencies

[de Marneffe et al. LREC 2006]

- The basic dependency representation is projective
- It can be generated by postprocessing headed phrase structure parses (Penn Treebank syntax)
- It is generated directly by dependency parsers, such as MaltParser, or the Easy-First Parser



Christopher Manning

Graph modification to facilitate semantic analysis

Bell, based in LA, makes and distributes electronic and computer products.

Christopher Manning

Graph modification to facilitate semantic analysis

Bell, based in LA, makes and distributes electronic and computer products.

Christopher Manning

54