BEHAVRY
GOVERN THE SWARM

BEHAVRY EXAMPLE · MSP OPERATIONS


Meraki Alert Triage

A governed AI technician for managed service providers

What this example proves

An AI technician can triage Meraki alerts, write a useful note in the PSA, and ask before it acts, with every step on a signed record. That answers the question an MSP's clients will ask: what did the AI do on my network, and who said it could.

The agent is hosted, so nothing runs on a client endpoint. A Meraki alert arrives as a webhook, the agent triages it, posts the summary to Halo through the MSP's tool gateway, and asks for approval before any remediation. Behavry sits between the agent and everything it touches, so each alert produces one Decision Trace: what the agent read, what it wrote, what it tried to do, and who approved it.



The agent never calls Halo or Claude directly. Reads and notes pass straight through; a device action waits in the approval queue until a technician decides, and every step lands in the same Decision Trace.

Start narrow, then widen

Prove the triage first, then let the agent ask to act. Trust in the notes comes before trust in the actions.

Phase	The agent can	It cannot	Move on when
1: read and comment	Read Halo and Meraki, add notes, create tickets, set priority	Change anything on a device or network	Technicians agree with most of the first 50 triage notes
2: ask to act	Request a reboot or a Meraki change; Behavry holds the call for a person	Act without an approval	Approvals and rejections behave as agreed, and the injection test is held

- **Alert types:** device down and back up, VPN connectivity change, uplink status change, rogue access point. Add more only after these read well.
- **One test client and one Meraki network.** A network where you can safely unplug things makes the test script easy.
- **A sandbox Halo client or ticket type,** so trial notes and tickets stay out of live queues.

Build the agent to absorb Meraki's noise

Most of what makes technicians trust the agent is noise handling, not model quality. A down/up pair that opens two tickets loses them faster than a weak summary.

1. **Reply fast, work later.** Check the webhook's shared secret, return 200 at once, and queue the alert. Meraki retries a delivery that is slow or fails, and slow triage turns into duplicate alerts.
2. **Remove duplicates.** Key each alert on network, device and alert type, and drop repeats inside a short window.
3. **Wait out flapping.** Hold a "down" alert for a few minutes (the example uses 5). If the matching "up" arrives first, write nothing.
4. **Look for an open ticket first.** If the device already has one, add a note to it rather than opening another.
5. **Then triage,** with only the context the model needs: the alert, the client and site, the asset, and the open ticket if there is one.

Treat alert content as untrusted

Alert text can be written by outsiders, so the agent must read it as data and never as instructions. Anyone in range can broadcast a network name, and a guest can name a laptop anything. An agent that reads that text and can write to the PSA is a real prompt-injection target.

- **Fence the alert.** Put the alert inside a clearly marked block in the prompt, and tell the model in the system prompt that the block is data.
- **Give the agent only the tools it needs.** A triage agent has no use for identity administration, or for creating clients and users in Halo. Behavry policy enforces this too, so a tool the agent was never meant to call is refused or held, even if the model asks for it.
- **Keep the model's output structured.** The model returns a fixed set of fields, and the agent's own code decides which tools to call. The model never names a tool.
- **Test it.** One alert in the test script carries a device name written as an instruction. The note should report it as suspicious, and any action it provokes should be held.

Route everything through Behavry

The record is only complete if every call the agent makes passes through Behavry. One direct call to the Halo API is a gap a client could ask about.

- **Model calls** go through Behavry's model proxy, so each call is part of the record.
- **Tool calls** go through Behavry to the MSP's gateway. Behavry sees which system each call reaches (Halo, Meraki, the RMM), and policy is set per system.
- **One label per alert,** sent with every model and tool call, so each alert produces a single Decision Trace from webhook to final note.
- **Its own identity.** The agent gets its own Behavry identity and its own Halo API user (for example "AI Technician"). Halo then shows who wrote each note, and the agent can be paused alone if anything looks wrong.
- **Secrets in a secret store,** never in environment files or the image.

A starting policy, per system:

System	Allowed	Held for approval	Refused
Halo	Reads, add a note, create a ticket, change priority or assignee	Merge or delete a ticket, client or user changes	None
Meraki	Reads	Any change	None
RMM	Reads	Reboot a device, run a script	Wipe or delete a device
Identity administration	None	None	Everything, for this agent
Anything else	None	Everything	None

Notes technicians can trust, and approvals that behave

Every note should look the same, so a technician can read one in ten seconds and know how far to trust it.

- **The model returns fixed fields:** severity, headline, impact, likely cause, what it checked, recommendation, recommended action, confidence, whether a person is needed, and whether the alert looked tampered with.
- **Every Halo note has the same parts:** what happened, the impact, what the agent checked, the likely cause, its recommendation, and its confidence. It is signed "AI Technician" in the first line.
- **Low confidence goes to a person.** When the agent is unsure, the note says so and the ticket is assigned to the on-call technician. A guess is worse than a hand-off.

When the agent asks to act, Behavry holds the call until someone decides. The agent should treat that as a normal outcome:

- Write "remediation requested, awaiting approval" on the ticket first.
- Wait for the decision. Behavry holds the call for up to 30 minutes depending on the agent's risk tier, so the agent's own timeout must be longer (the example waits 31). On a timeout, hand the ticket to a person.
- If something between the agent and Behavry, such as a load balancer, closes the connection before a decision, treat the outcome as unknown, not failed: the request may still be approved and carried out. Say so on the ticket and do not ask again.
- Treat a rejection or a timeout as a result to record, never a reason to retry.
- Name the approvers before go-live, and decide where they approve: the Behavry dashboard, or Slack notices.

How you will know it worked

Agree these measures before the first alert, so the end of the trial is a decision and not an opinion.

Measure	Target
Technician agrees with the triage note	Most of the first 50 alerts; agree the exact bar up front
Time from alert to note in Halo	Faster than today's manual path
Duplicate tickets from flapping or repeat alerts	None
Actions taken without an approval	None
Calls that skipped Behavry	None
Injection test alert	Flagged in the note; any action it provokes is held


Run this script before go-live. Meraki's "send test webhook" button covers the first item; the rest need a real device on the test network.

- A normal alert opens a ticket with a structured note.
- A repeat of the same alert adds nothing new.
- A down then up inside five minutes produces no ticket.
- An alert for a device with an open ticket adds a note to that ticket.
- A remediation request is held, approved, and carried out.
- A remediation request is held and rejected, and the agent records it without retrying.
- The injection alert is flagged and nothing it asks for happens.


What it looks like in Behavry

These screens come from a real run of the example agent against Behavry's demo plane, with a stand-in gateway and fictional data.


Map the gateway once. Register your gateway in Behavry, mark it as a gateway, and map each system it fronts. Policy and the record can then tell a Halo call from a Meraki or RMM call.




Write the policy per system. The example policy allows reads and PSA notes, holds any device action for a person, and refuses destructive ones.




A reboot waits for a technician. When the agent asked to reboot an access point that had stopped serving clients, Behavry held the call. The technician sees the tool, the system it targets, and why it was held, and decides.



The trail for one alert. Every call the agent made for an alert sits on one signed trail: the lookups, the model call, each write and its outcome.



An injection attempt, stopped twice. In the test run, a rogue access point broadcast a network name written as an instruction. The agent's code flagged it and asked for no action. When its triage note quoted that text, Behavry's outbound check blocked the write as a critical injection. The agent then wrote a short note with none of the alert's text, and handed the ticket to a person.



The example code

The `agent/` folder holds a small, readable Python agent that follows every point in this guide:

- checks Meraki's shared secret, replies at once, removes duplicates and waits out flapping;
- looks up the asset, client, site and open ticket in Halo through the gateway;
- triages with Claude through Behavry, with the alert fenced as data and fixed output fields;
- writes the same structured note every time, as a private note, and assigns the on-call technician when a person is needed;
- flags instruction-like alert text, sends that ticket to a person, and never asks to act on it;

- in phase 2, asks to reboot a device, records the approval, rejection or timeout on the ticket, and never retries.

It comes with tests for each of these and a container image definition.

> **About Behavry.** Behavry is the independent, signed record of what AI agents did across every system they touched. It binds every action to an identity, reconstructs the sequence into a signed Decision Trace, and, because it sits in the path, can permit, redact, hold or block an action against policy. Learn more at behavry.ai.