



# 杭州电子科技大学

**HANGZHOU DIANZI UNIVERSITY** Online Judge

Online Judge	Online Exercise	Online Teaching	Online Contests	Exercise Author
F.A.Q Hand In Hand Online Acmers Forum   Discuss Statistical Charts	Problem Archive Realtime Judge Status Authors Ranklist	C/C++/Java Exams ACM Steps Go to Job Contest LiveCast ICPC@China	<b>Best Coder</b> <small>beta</small> VIP   STD Contests Virtual Contests DIY   Web-DIY <small>beta</small> Recent Contests	 用QQ帐号登录 Author ID Password <a href="#">Register new ID</a>

如何参加“HDOJ暑期多校联合训练”? 请加QQ群837241962咨询~

## Tempter of the Bone

Time Limit: 2000/1000 MS (Java/Others)    Memory Limit: 65536/32768 K (Java/Others)  
Total Submission(s): 164335    Accepted Submission(s): 43576

### Problem Description

The doggie found a bone in an ancient maze, which fascinated him a lot. However, when he picked it up, the maze began to shake, and the doggie could feel the ground sinking. He realized that the bone was a trap, and he tried desperately to get out of this maze.

The maze was a rectangle with sizes N by M. There was a door in the maze. At the beginning, the door was closed and it would open at the T-th second for a short period of time (less than 1 second). Therefore the doggie had to arrive at the door on exactly the T-th second. In every second, he could move one block to one of the upper, lower, left and right neighboring blocks. Once he entered a block, the ground of this block would start to sink and disappear in the next second. He could not stay at one block for more than one second, nor could he move into a visited block. Can the poor doggie survive? Please help him.

The input consists of multiple test cases. The first line of each test case contains three integers N, M, and T ( $1 < N, M < 7$ ;  $0 < T < 50$ ), which denote the sizes of the maze and the time at which the door will open, respectively. The next N lines give the maze layout, with each line containing M characters. A character is one of the following:

- 'X': a block of wall, which the doggie cannot enter;
- 'S': the start point of the doggie;
- 'D': the Door; or
- ': an empty block.

The input is terminated with three 0's. This test case is not to be processed.

### Output

For each test case, print in one line "YES" if the doggie can survive, or "NO" otherwise.

### Sample Input

```
4 4 5
S.X.
..X.
..XD
....
3 4 5
S.X.
..X.
...D
0 0 0
```

### Sample Output

```
NO
YES
```

### Author

ZHANG, Zheng

Source

ZJCPC2004

Recommend

JGShining

[Statistic](#) | [Submit](#) | [Discuss](#) | [Note](#)

[Home](#) | [Top](#)

Hangzhou Dianzi University Online Judge 3.0  
Copyright © 2005-2019 [HDU ACM Team](#). All Rights Reserved.  
[Designer & Developer](#) : [Wang Rongtao](#) [LinLe](#) [GaoJie](#) [GanLu](#)  
Total 0.000000(s) query 1, Server time : 2019-07-17 19:15:37, Gzip disabled

[Administration](#)