



Online Judge	Online Exercise	Online Teaching	Online Contests	Exercise Author
F.A.Q Hand In Hand Online Acmers Forum Discuss Statistical Charts	Problem Archive Realtime Judge Status Authors Ranklist	C/C++/Java Exams ACM Steps Go to Job Contest LiveCast ICPC@China	Best Coder <small>beta</small> VIP STD Contests Virtual Contests DIY Web-DIY <small>beta</small> Recent Contests	 Author ID Password Register new ID

如何参加“HDOJ暑期多校联合训练”? 请加QQ群837241962咨询~

Legal or Not

Time Limit: 2000/1000 MS (Java/Others) Memory Limit: 32768/32768 K (Java/Others)
Total Submission(s): 13045 Accepted Submission(s): 6129

Problem Description

ACM-DIY is a large QQ group where many excellent acmers get together. It is so harmonious that just like a big family. Every day, many "holy cows" like HH, hh, AC, ZT, lcc, BF, Qinz and so on chat on-line to exchange their ideas. When someone has questions, many warm-hearted cows like Lost will come to help. Then the one being helped will call Lost "master", and Lost will have a nice "prentice". By and by, there are many pairs of "master and prentice". But then problem occurs: there are too many masters and too many prentices, how can we know whether it is legal or not?

We all know a master can have many prentices and a prentice may have a lot of masters too, it's legal. Nevertheless, some cows are not so honest, they hold illegal relationship. Take HH and 3xian for instant, HH is 3xian's master and, at the same time, 3xian is HH's master, which is quite illegal! To avoid this, please help us to judge whether their relationship is legal or not.

Please note that the "master and prentice" relation is transitive. It means that if A is B's master and B is C's master, then A is C's master.

Input

The input consists of several test cases. For each case, the first line contains two integers, N (members to be tested) and M (relationships to be tested) ($2 \leq N, M \leq 100$). Then M lines follow, each contains a pair of (x, y) which means x is y's master and y is x's prentice. The input is terminated by N = 0. TO MAKE IT SIMPLE, we give every one a number (0, 1, 2, ..., N-1). We use their numbers instead of their names.

Output

For each test case, print in one line the judgement of the messy relationship.
If it is legal, output "YES", otherwise "NO".

Sample Input

```
3 2
0 1
1 2
2 2
0 1
1 0
0 0
```

Sample Output

```
YES
NO
```

Author

QiuQiu@NJFU

Source

HDOJ Monthly Contest – 2010.03.06

Recommend

lcy

[Statistic](#) | [Submit](#) | [Discuss](#) | [Note](#)

[Home](#) | [Top](#)

Hangzhou Dianzi University Online Judge 3.0
Copyright © 2005-2019 HDU ACM Team. All Rights Reserved.
[Designer & Developer](#) : [Wang Rongtao](#) [LinLe](#) [GaoJie](#) [GanLu](#)
Total 0.000000(s) query 1, Server time : 2019-07-17 19:49:40, Gzip enabled

[Administration](#)