

# Application of graph matching in Computer Vision

## Master Seminar

Ekaterina Tikhoncheva

University of Heidelberg  
Faculty of Mathematics and Computer Science  
Computer Vision group  
at  
Heidelberg Collaboratory for Image Processing

November 2015


# Agenda

- 1 Graph matching
  - Introduction
  - Graph matching
  - Exact graph matching
  - Inexact graph matching
- 2 Two level graph matching framework (2LevelGM)
- 3 Evaluation
  - Synthetic data
  - Real data
- 4 Conclusions

# Attributed undirected graph I

Attributed undirected graph  $G = (V,$


- set of nodes  $V = \{v_i\}_{i=1}^n$



# Attributed undirected graph II

Attributed undirected graph  $G = (V, E,$


- set of nodes  $V = \{v_i\}_{i=1}^n$
- set of edges  $E \subseteq \{\{u, v\} | u, v \in V\}$



# Attributed undirected graph


Attributed undirected graph  $G = (V, E, D)$

- set of nodes  $V = \{v_i\}_{i=1}^n$
- set of edges  $E \subseteq \{\{u, v\} | u, v \in V\}$
- node attributes  $D = \{d_i\}_{i=1}^n, D \subset \mathbb{R}^r$




# Graph matching

Let us consider two undirected attributed graphs  $G^I = (V^I, E^I, D^I)$  and  $G^J = (V^J, E^J, D^J)$ :




# Graph matching



A matching function between  $G^I$  and  $G^J$  is a mapping  
$$m: V^I \rightarrow V^J$$

# Graph matching




A matching function between  $G^I$  and  $G^J$  is a mapping

$$m: V^I \rightarrow V^J$$

not unique!



# Graph matching




A matching function between  $G^I$  and  $G^J$  is a mapping  
$$m : V^I \rightarrow V^J$$

Define a function  $S(G^I, G^J, m)$  to measure the quality of matching  $m$  that fulfills some constraints

$\Rightarrow$  **Graph matching problem** between  $G^I$  and  $G^J$

$$m = \operatorname{argmax}_{\hat{m}} S(G^I, G^J, \hat{m})$$

# Graph matching in computer vision



- image matching
- shape matching
- object detection
- object tracking
- ...

# Graph matching

A matching function between  $G^I$  and  $G^J$  is a mapping

$$m : V^I \rightarrow V^J$$

Graph matching problem between  $G^I$  and  $G^J$

$$m = \underset{\hat{m}}{\operatorname{argmax}} S(G^I, G^J, \hat{m})$$


Depending on the required properties of a matching one distinguishes

- exact graph matching
- inexact graph matching


# Exact graph matching I

Edge preserving mapping  $m: \{v_i, v_{i'}\} \in E^I \Rightarrow \{m(v), m(v_{i'})\} \in E^J$


- mapping  $m$  is bijective  $\rightarrow$  graph isomorphism (GI)



- mapping  $m$  is injective  $\rightarrow$  graph monomorphism



- mapping  $m$  is total  $\rightarrow$  graph homomorphism




NP complete (except GI) [Garey and Johnson, 1979]

# Exact graph matching II

Exact graph matching:

- too strict
- cannot handle object deformation
- time/memory consuming



# Inexact graph matching I

Introduce similarity measure between nodes/edges in the graphs

$$m = \underset{\hat{m}}{\operatorname{argmax}} S(G^I, G^J, \hat{m})$$

$$S(G^I, G^J, m) = \sum_{\substack{m(v_i)=v_j \\ m(v'_i)=v'_j}} s_E(e_{ii'}, e_{jj'}) + \sum_{m(v_i)=v_j} s_V(v_i, v_j)$$

- second-order (edge) similarity  $s_E(e_{ii'}, e_{jj'})$ ,  $e_{ii'} \in E^I, e_{jj'} \in E^J$
- first-order (node) similarity  $s_V(v_i, v_j)$ ,  $v_i \in V^I, v_j \in V^J$
- assignment matrix  $X \in \{0, 1\}^{n_1 \times n_2}$ ,  $X_{ij} = 1 \iff m(v_i) = v_j$   
vector form  $x = \operatorname{vec}(X)$

# Inexact graph matching II

The most common problem formulation:

Quadratic Assignment Problem (NP complete) [Burkard et al., 1998]

$$x^* = \arg \max \sum_{\substack{x_{ij}=1 \\ x_{i'l'}=1}} s_E(e_{ii'}, e_{jj'}) + \sum_{x_{ij}=1} s_V(v_i, v_j)$$

$$s.t. \begin{cases} x \in \{0, 1\}^{n_1 n_2} \\ \sum_{i=1}^{n_1} x_{ij} \leq 1 \\ \sum_{j=1}^{n_2} x_{ij} \leq 1 \end{cases}$$

Using matrix notation :  $\arg \max_x x^T S x$ ,  $S$  is a similarity (or affinity) matrix

# Inexact graph matching III

## Solution techniques [Conte et al., 2004]

- discrete optimization
  - tree search [Bunke and Allermann, 1983, Shapiro and Haralick, 1981, Tsai and Fu, 1979, Wang et al., 1995]
  - simulated annealing [Hérault et al., 1990]
- continuous optimization
  - constraint relaxation [Gold and Rangarajan, 1996, Leordeanu et al., 2009, Lu et al., 2012, Vogelstein et al., 2011/14, Zaslavskiy et al., 2009]
  - spectral methods [Leordeanu and Hebert, 2005, Umeyam, 1988]
  - probabilistic frameworks [Armiti and Gertz, 2014, Kittler and Hancock, 1989, Luo and Hancock, 2001, Sanromà et al., 2012]
  - clustering [Carcassoni and Hancock, 2003, Cho et al., 2009, Qiu and Hancock, 2006, Lyzinski et al., 2011/14]



## Drawback of the existing algorithms

- most of the algorithms are developed for matching relatively small graphs ( $\sim 150$  nodes)
- scale badly due to the polynomial increase of time and storage demand
- algorithms for the big graphs use another formulation of the graph matching optimization problem

$$x^* = \operatorname{argmin}_x \|A^I - XA^JX^T\|^2 + \|D^I - XD^J\|_2^2$$

# Aim of the master's thesis

- a novel framework that should help to extend the usability of existing graph matching algorithms to bigger graphs
- a variant of the well-known divide and conquer paradigm: subdividing initial problem into a set of smaller problems, which can be easily handled with existing algorithms
- iterative algorithm that allows to improve initial subdivision into subproblems

# Complexity reduction

$$x^* = \arg \max x^T S x$$
$$\text{s.t. } \begin{cases} x \in \{0, 1\}^{n_1 n_2} \\ \sum_{i=1}^{n_1} x_{ij} \leq 1 \\ \sum_{j=1}^{n_2} x_{ij} \leq 1 \end{cases}$$

- set of candidate correspondences [Cho and Lee, 2012]
- sparse affinity matrix
- subdivide problem into a set of smaller subproblems

# Complexity reduction

$$x^* = \arg \max x^T S x$$
$$\text{s.t. } \begin{cases} x \in \{0, 1\}^{n_1 n_2} \\ \sum_{i=1}^{n_1} x_{ij} \leq 1 \\ \sum_{j=1}^{n_2} x_{ij} \leq 1 \end{cases}$$

- set of candidate correspondences [Cho and Lee, 2012]
- sparse affinity matrix
- subdivide problem into a set of smaller subproblems ←

## Complexity reduction


$$x^* = \arg \max x^T S x$$
$$\text{s.t. } \begin{cases} x \in \{0, 1\}^{n_1 n_2} \\ \sum_{i=1}^{n_1} x_{ij} \leq 1 \\ \sum_{j=1}^{n_2} x_{ij} \leq 1 \end{cases}$$

- set of candidate correspondences [Cho and Lee, 2012]
- sparse affinity matrix
- subdivide problem into a set of smaller subproblems ←  
Similar works:
  - semisupervised case [Lyzinski et al., 2011/14]
  - another objective function [Lyzinski et al., 2011/14, Carcassoni and Hancock, 2003, Qiu and Hancock, 2006]
  - special kind of subproblem [Qiu and Hancock, 2006, Nie et al., 2015]

# Two level graph matching framework

Lower level: initial graphs  $G^I$ ,  $G^J$

Higher level: simplified graphs (anchor graphs  $A^I$ ,  $A^J$ )



## Anchor graph construction

Goal:  $G^l = (V^l, E^l, D^l) \rightarrow A^l = (V^{la}, E^{la}, U^{la})$

Equivalent: partitioning of  $G^l \supset (G_1^l \cup \dots \cup G_{|V^{la}|}^l)$

Done by:

- grid with  $r$  rows and  $c$  columns
- graph coarsening algorithms: Heavy Edge Matching (HEM) and Light Edge Matching (LEM)

# Anchor graph and subgraph matching

Goal: find correspondences between two anchor graphs

$A^I = (V^{Ia}, E^{Ia}, U^{Ia})$  and  $A^J = (V^{Ja}, E^{Ja}, U^{Ja})$


- edge similarity: compare length of the edges between anchors
- node similarity:
  - score of the matching of  $G_k^I$  and  $G_p^J$
  - define anchor attributes based on the  $D^I, D^J$  and/or on the geometry of  $G^I, G^J$

Match anchor graphs and subgraph using some existing algorithm (e.g. RRWM [Cho et al., 2010])



## Graph partition update

- 1 estimate an affine transformation between matched subgraphs (point set registration problem)
- 2 let nodes "vote" to which subgraphs they should belong to




# Evaluation

Two ways of evaluation have been used


- synthetic data
- real data

# Synthetic data I












Performance of the 2LevelGM with non-attributed anchor graphs

# Synthetic data II






Performance of the 2LevelGM with attributed anchor graphs

# Synthetic data III




Comparison of 2LevelGM, GLAG and PATH on bigger graphs

# Image affine transformation I




Evaluation of 2LevelGM on the synthetic image dataset

## Image affine transformation II




Iteration 1




Accuracy

Iteration 2




Matching score

Iteration 3




Gap between current and optimal solutions


# House data set




Evaluation of 2LevelGM on the CMU House sequence: not extrapolated solution



accuracy 11.63%



accuracy 100%



Evaluation of 2LevelGM on the CMU House sequence: extrapolated solution



# Conclusions

The developed algorithm

- solves inexact graph matching problem
- is fast
- allows application of existing algorithms to bigger graphs
- shows very good results for (sub)graph isomorphism problems
- handles reasonably the affine deformations in graph structure

It has following properties:

- it is sensible to non-affine deformations in graph structure
- it's complexity depends on the number of iterations and on the size of the anchor graphs and subgraphs
- anchor attributes for anchor graph matching are preferred

## Future work

- more sophisticated graph partitioning techniques
- improvement of anchor attributes
- further improvement of the update rule
- probabilistic matching framework
- hierarchical method

The end

Thank you for your attention!



## References I

- Ayser Armiti and Michael Gertz. Geometric graph matching and similarity: A probabilistic approach. In *Proceedings of the 26th International Conference on Scientific and Statistical Database Management, SSDBM '14*, pages 27:1–27:12, New York, NY, USA, 2014. ACM. URL <http://doi.acm.org/10.1145/2618243.2618259>.
- H. Bunke and G. Allermann. Inexact graph matching for structural pattern recognition. *Pattern Recognition Letters*, 1(4):245–253, 1983.
- R. E. Burkard, E. Çela, P. M. Pardalos, and L. Pitsoulis. The quadratic assignment problem. In P. M. Pardalos and D.-Z Du, editors, *Handbook of Combinatorial Optimization*, pages 241–338. Kluwer Academic Publisher, 1998.

## References II

- Marco Carcassoni and Edwin R. Hancock. Correspondence matching with modal clusters. *IEEE Trans. Pattern Anal. Mach. Intell.*, 25(12):1609–1615, 2003.
- Minsu Cho and Kyoung Mu Lee. Progressive graph matching: Making a move of graphs via probabilistic voting. In *The IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, CVPR '12. IEEE Computer Society, 2012.
- Minsu Cho, Jungmin Lee, and Kyoung Mu Lee. Feature Correspondence and Deformable Object Matching via Agglomerative Correspondence Clustering. In *The IEEE International Conference on Computer Vision (ICCV)*, 2009.
- Minsu Cho, Jungmin Lee, and Kyoung Mu Lee. Reweighted Random Walks for Graph Matching. *ECCV*, 2010.

## References III

- Minsu Cho, Karteek Alahari, and Jean Ponce. Learning Graphs to Match. In *Proceedings of the IEEE International Conference on Computer Vision*, 2013.
- D. Conte, P. Foggia, C. Sansone, and M. Vento. Thirty Years of Graph Matching in Pattern Recognition. *International Journal of Pattern Recognition and Artificial Intelligence*, 18(03):265–298, 2004.
- Michael R. Garey and David S. Johnson. *Computers and Intractability: A Guide to the Theory of NP-Completeness*. W. H. Freeman & Co., 1979.
- S. Gold and Anand Rangarajan. A Graduated assignment algorithm for graph matching. In *IEEE Transactions on Pattern Analysis and Machine Intelligence*, volume 18, pages 377–388, 1996.

## References IV

- L. Héroult, R. Horaud, F. Veillon, and J. Niez. Symbolic image matching by simulated annealing. In *Proceedings of the British Machine Vision Conference*, pages 319–324, 1990.
- J. Kittler and E. R. Hancock. International journal of pattern recognition and artificial intelligence. *IEEE Trans. Pattern Anal. Mach. Intell.*, 3(1):29–51, 1989.
- Marius Leordeanu and Martial Hebert. A spectral technique for correspondence problems using pairwise constraints. In *ICCV*, 2005.
- Marius Leordeanu, Martial Hebert, Rahul Sukthankar, and Martial Herbert. An Integer Projected Fixed Point Method for Graph Matching and MAP Inference. In *NIPS*, 2009.



## References V

- Yao Lu, Kaizhu Huang, and Cheng-Lin Liu. A fast projected fixed-point algorithm for large graph matching, 2012. Available at <http://arxiv.org/abs/1207.1114v3>, last access on 17/10/2015.
- Bin Luo and Edwin R. Hancock. Structural graph matching using the EM algorithm and singular value decomposition. *IEEE Trans. Pattern Anal. Mach. Intell.*, 23(10):1120–1136, 2001.
- Vince Lyzinski, Daniel L Sussman, Donniell E Fishkind, Henry Pao, Li Chen, Joshua T Vogelstein, Youngser Park, and Carey E Priebe. Spectral Clustering for Divide-and-Conquer Graph Matching. 2011/14. Available at <http://arxiv.org/abs/1310.1297v5>, last access on 17/10/2015.

## References VI

- Wei-Zhi Nie, An-An Liu, Zan Gao, and Yu-Ting Su. Clique-graph Matching by Preserving Global & Local Structure. In *The IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 2015.
- Huaijun Qiu and Edwin R. Hancock. Graph matching and clustering using spectral partitions. *Pattern Recognition*, 39(1): 22–34, 2006.
- Gerard Sanromà, René Alquézar, and Francesc Serratosa. A new graph matching method for point-set correspondence using the EM algorithm and Softassign. *Computer Vision and Image Understanding*, 116:292–304, 2012.

## References VII

- L. G. Shapiro and R. M. Haralick. Structural descriptions and inexact matching. *IEEE transactions on pattern analysis and machine intelligence*, 3(5):504–519, 1981.
- Wen-Hsiang Tsai and King-Sun Fu. Error-Correcting Isomorphisms of Attributed Relational Graphs for Pattern Analysis. *IEEE Transactions on Systems, Man, and Cybernetics*, 9(12):757–768, 1979.
- Shinji Umeyam. An Eigendecomposition Approach to Weighted Graph Matching Problems. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 10, 1988.

## References VIII

- J. T. Vogelstein, J. M. Conroy, L. J. Podrazik, S. G. Kratzer, E. T. Harley, D. E. Fishkind, R. J. Vogelstein, and C. E. Priebe. Large (Brain) Graph Matching via Fast Approximate Quadratic Programming, 2011/14. Available at <http://arxiv.org/abs/1112.5507v5>, last access on 17/10/2015.
- Jason T.L. Wang, Kaizhong Zhang, and Gung-Wei Chirn. Algorithms for approximate graph matching. *Information Sciences*, 82(1-2):45–74, 1995. URL <http://www.sciencedirect.com/science/article/pii/002002559400057I>.

## References IX

Mikhail Zaslavskiy, Francis Bach, and Jean-Philippe Vert. A Path Following Algorithm for the Graph Matching Problem. *Pattern Analysis and Machine Intelligence, IEEE Transactions on*, 31 (12):2227–2242, 2009.