

Acero dúctil RDM 2019 - sección COL75X75FC28MPa

Project ID: Modelos_constitutivos

Case ID: COL75X75FC28MPa

Material: ductile_reinforcing_steel

Behavior: monotonic

Model ID: Mon_RDM2019

Source JSON: C:\Users\LENOVO\Documents\Proyectos python\StructureLab_PBD_RC\configs\stage_02\ductile_reinforcing_steel\monotonic\Mon_RDM2019.json

Response metrics

Point count: 1203

Strain range: -0.1141 to 0.1141

Stress range [MPa]: -469.44635705937594 to 659.74

Reversals: 0

Failed points: 0

Calculated parameters

fy_mpa: 470.3

fu_mpa: 659.74

epsilon_y: 0.0024

epsilon_sh: 0.0138

epsilon_su: 0.1141

parameter_p: 3.087

elastic_modulus_mpa: 195958.33333333334

special_case_parameter_p: 1.0

Barras de borde en flexion

effective_restrained_bars: 5

tie_stiffness_N_per_mm: 30835.690193062394

equivalent_stiffness_ratio: 0.24878601889233665

buckling_intervals: 2

unsupported_length_mm: 200.0

L_over_D: 8.998875140607424

rb: 19.51532172688238

eps_i: 0.02427542406760927

f_i_mpa: 400.3405557508032

eps_ii: 0.04981277612485804

compression_ultimate_stress_mpa: 174.2792443611055

Barras interiores en compresion axial

effective_restrained_bars: 10

tie_stiffness_N_per_mm: 15417.845096531197

equivalent_stiffness_ratio: 0.12439300944616832

buckling_intervals: 3

unsupported_length_mm: 300.0

L_over_D: 13.498312710911135

rb: 29.272982590323565

eps_i: 0.0168

f_i_mpa: 293.2140176286254

eps_ii: 0.03550384973178559

compression_ultimate_stress_mpa: 94.06

Warnings

None.

Acero dúctil RDM 2019 - sección COL75X75FC28MPa

Monotónico | Acero de refuerzo dúctil | Mon_RDM2019 | Flexión: $n = 2$, $L/D = 8.999$ | Compresión axial: $n = 3$, $L/D = 13.498$ | Puntos notables

