

Acero ductil RDM 2019 - L/D calculado igual a 5

Project ID: default

Case ID: rdm_2019_Id5

Material: ductile_reinforcing_steel

Behavior: monotonic

Model ID: Mon_RDM2019

Source JSON: D:\Users\byomayusa\Documents\GitHub\StructureLab_PBD_RC\configs\stage_02\ductile_reinforcing_steel\monotonic\Mon_RDM2019.json

Response metrics

Point count: 801

Strain range: -0.1 to 0.1

Stress range [MPa]: -537.7690778920974 to 630.0

Reversals: 0

Failed points: 0

Calculated parameters

buckling_calculation_mode: rectangular_transverse_restraint

buckling_restraint_case: bending

epsilon_y: 0.0021

tie_area_mm2: 78.53981633974483

longitudinal_bar_inertia_mm4: 7853.981633974483

reduced_flexural_rigidity_N_mm2: 804793631.2008746

effective_restrained_bars: 2

bar_normalized_stiffness_N_per_mm: 78394.21608523135

tie_stiffness_N_per_mm: 78539.81633974484

equivalent_stiffness_ratio: 1.0018572831234793

buckling_intervals: 1

unsupported_length_mm: 100.0

s_over_db: 5.0

L_over_D: 5.0

rb: 10.2469507659596

buckling_active: True

residual_stress_mpa: 84.0

Warnings

None.

Acero ductil RDM 2019 - L/D calculado igual a 5

monotonic | ductile_reinforcing_steel | Mon_RDM2019

