




ASSOCIATION RULE MINING

BEIYU LIN



FREQUENT ITEMSET GENERATION


- Brute-force approach:
 - Each itemset in the lattice is a **candidate** frequent itemset
 - Count the support of each candidate by scanning the database



- Match each transaction against every candidate
- Complexity $\sim O(NMw) \Rightarrow$ **Expensive since $M = 2^d$!!!**

FREQUENT ITEMSET GENERATION STRATEGIES

- Reduce the **number of candidates** (M)
 - Complete search: $M=2^d$
 - Use pruning techniques to reduce M
- Reduce the **number of transactions** (N)
 - Reduce size of N as the size of itemset increases
 - Used by DHP and vertical-based mining algorithms
- Reduce the **number of comparisons** (NM)
 - Use efficient data structures to store the candidates or transactions
 - No need to match every candidate against every transaction



Given a transaction {B, M, D, C}, find all possible subset with size 3 from this transaction.

REDUCING NUMBER OF CANDIDATES

- **Apriori principle:**
 - If an itemset is frequent, then all of its subsets must also be frequent
- Apriori principle holds due to the following property of the support measure:

$$\forall X, Y : (X \subseteq Y) \Rightarrow s(X) \geq s(Y)$$

- Support of an itemset never exceeds the support of its subsets
- This is known as the **anti-monotone** property of support

$$s = \frac{\sigma}{\text{total } T}$$

$$X = \{M, B\}$$

$$Y = \{D\}$$

$$X \rightarrow Y$$

$$X \cup Y = \{M, B, D\}$$

TID	Items
1	Bread, Milk
2	Bread, Diaper, Beer, Eggs
3	Milk, Diaper, Beer, Coke
4	Bread, Milk, Diaper, Beer
5	Bread, Milk, Diaper, Coke

Support (fraction)


$$s(\{\text{Milk, Bread, Diaper}\}) = 2/5 = \frac{\# \text{ itemsets}}{\text{total \# of transaction}} = \frac{2}{5}$$

Support count: # of the itemsets that show in the transaction = 2

$$\text{Confidence} = \frac{\# X \cup Y}{\# X} = \frac{2}{3}$$

SUPPORT COUNTING OF CANDIDATE ITEMSETS

- To reduce number of comparisons, store the candidate itemsets in a hash structure / hash function
- Instead of matching each transaction against every candidate, match it against candidates contained in the hashed buckets



N.M

SUPPORT COUNTING: AN EXAMPLE



Suppose you have 15 candidate itemsets of length 3:

{1 4 5}, {1 2 4}, {4 5 7}, {1 2 5}, {4 5 8}, {1 5 9}, {1 3 6}, {2 3 4}, {5 6 7}, {3 4 5}, {3 5 6}, {3 5 7}, {6 8 9}, {3 6 7}, {3 6 8}

Reduce N from Apriori Alg


How many of these itemsets are supported by transaction (1,2,3,5,6)?

itemsets pruned



$$C_r^n = C_3^5 = \frac{n!}{r!(n-r)!}$$

$$= \frac{5!}{3!2!} = \frac{5 \times 4 \times 3 \times 2 \times 1}{3 \times 2 \times 1 \times 2 \times 1} = \frac{20}{2} = 10$$



SUPPORT COUNTING:AN EXAMPLE

Suppose you have 15 candidate itemsets of length 3:


→ Reduce W from Apriori Alg

$\{1\ 4\ 5\}, \{1\ 2\ 4\}, \{4\ 5\ 7\}, \{1\ 2\ 5\}, \{4\ 5\ 8\}, \{1\ 5\ 9\}, \{1\ 3\ 6\}, \{2\ 3\ 4\}, \{5\ 6\ 7\}, \{3\ 4\ 5\}, \{3\ 5\ 6\}, \{3\ 5\ 7\}, \{6\ 8\ 9\}, \{3\ 6\ 7\}, \{3\ 6\ 8\}$


How to find all the subsets with k items from an itemset?

Given an itemset $\{1,2,3,5,6\} \Leftrightarrow$ one transaction, we want to reduce NM


How many of these itemsets are supported by transaction (1,2,3,5,6)?



$$C_r^n = C_3^5 = \frac{n!}{r!(n-r)!}$$



$$= \frac{5!}{3! 2!} = \frac{5 \times 4 \times 3 \times 2 \times 1}{3 \times 2 \times 1 \cdot 2 \times 1} = \frac{20}{2} = 10$$



$$15 \times 10 = 150$$



SUPPORT COUNTING USING A HASH TREE

Suppose you have 15 candidate itemsets of length 3:


{1 4 5}, {1 2 4}, {4 5 7}, {1 2 5}, {4 5 8}, {1 5 9}, {1 3 6}, {2 3 4}, {5 6 7}, {3 4 5}, {3 5 6}, {3 5 7}, {6 8 9}, {3 6 7}, {3 6 8}

You need:


- Hash function
- Max leaf size: max number of itemsets stored in a leaf node (if number of candidate itemsets exceeds max leaf size, split the node)




SUPPORT COUNTING USING A HASH TREE




SUPPORT COUNTING USING A HASH TREE




SUPPORT COUNTING USING A HASH TREE



SUPPORT COUNTING USING A HASH TREE



SUPPORT COUNTING USING A HASH TREE



SUPPORT COUNTING USING A HASH TREE

