

Comparing dates with a function

```
Date appt, today;  
appt.yr = 2010;  
appt.mon = 4;  
appt.day = 10;  
today.yr = 2010;  
today.mon = 4;  
today.day = 14;  
  
if( before( appt, today ) )  
    cout << "You missed it!" << endl;
```

- Function compares two objects: `appt` and `today`
 - The function takes `appt` and `today` as parameters
 - The function will return true if `appt` is before `today`

Comparing dates with a function

- Function definition
 - Takes 2 dates, a and b
 - Returns true if a is before b

Handwritten examples of dates in YYYY-MM-DD format:

2009
april 2009-4-10
Today 2010-4-14

```
bool before( Date a, Date b )
{
    if( (a.yr < b.yr) ||
        (a.yr == b.yr && a.mon < b.mon) ||
        (a.yr == b.yr && a.mon == b.mon && a.day < b.day) )
        return true;
    else
        return false;
}
```

Comparing dates with a method

```
Date appt, today;  
appt.yr = 2010;  
appt.mon = 4;  
appt.day = 10;  
today.yr = 2010;  
today.mon = 4;  
today.day = 14;  
  
if( appt.Before( today ) )  
    cout << "You missed it!" << endl;
```

- Method compares two objects: `appt` and `today`
 - The method is called on `appt`
 - The method takes `today` as a parameter
 - The method will return true if `appt` is before `today`

Comparing dates with a method

- Declare the method in the Date class
 - This method takes a single argument of type Date

```
class Date
{
public:
    int day, mon, yr;
    void Print();
    bool Before( Date other );
};
```

Comparing dates with a method

```
class Date
{
public:
    int day, mon, yr;
    void Print();
    bool Before( Date other );
};
```

- Method definition

```
bool Date::Before( Date other )
{
    if( (yr < other.yr) ||
        (yr == other.yr && mon < other.mon) ||
        (yr == other.yr && mon == other.mon && day < other.day) )
        return true;
    else
        return false;
}
```

Comparing dates with a method

- Comparing the object called on with the object passed in
 - `yr` is in the object called on
 - `other.yr` is in the object passed in

```
bool Date::Before( Date other )
{
    if( (yr < other.yr) ||
        (yr == other.yr && mon < other.mon) ||
        (yr == other.yr && mon == other.mon && day < other.day) )
        return true;
    else
        return false;
}
```

Exercise



1. Define a Rectangle class with:
 - Data members height and width (doubles) $A = h \times w;$
 - A method set_size that takes values from the keyboard for height and width
 - A method area that returns the area (double)
2. Define the set_size and area methods
3. Use the Rectangle class to:
 - Declare a Rectangle object
 - Call set_size to set the size of the Rectangle to width 10 and height 3
 - Print the area of the Rectangle
 - Call set_size to change the size of the Rectangle to width 15 and height 7
 - Print the area of the Rectangle again