



Hierarchical Clustering

Hierarchical Clustering

- Produces a set of nested clusters organized as a hierarchical tree
- Can be visualized as a dendrogram
 - A tree like diagram that records the sequences of merges or splits



Strengths of Hierarchical Clustering



- Does not have to assume any particular number of clusters
 - Any desired number of clusters can be obtained by 'cutting' the dendrogram at the proper level
- The dendrogram may correspond to meaningful taxonomies

Hierarchical Clustering

- Two main types of hierarchical clustering
 - Agglomerative:
 - Start with the points as individual clusters
 - At each step, merge the closest pair of clusters until only one cluster (or k clusters) left
 - Divisive:
 - Start with one, all-inclusive cluster
 - At each step, split a cluster until each cluster contains a point (or there are k clusters)
- Traditional hierarchical algorithms use a similarity or distance matrix
 - Merge or split one cluster at a time

MST: Divisive Hierarchical Clustering

- Build MST (Minimum Spanning Tree)
 - Start with a tree that consists of any point
 - In successive steps, look for the closest pair of points (p, q) such that one point (p) is in the current tree but the other (q) is not



MST: Divisive Hierarchical Clustering

- Use MST for constructing hierarchy of clusters


Algorithm 7.5 MST Divisive Hierarchical Clustering Algorithm

- 1: Compute a minimum spanning tree for the proximity graph.
 - 2: **repeat**
 - 3: Create a new cluster by breaking the link corresponding to the largest distance (smallest similarity).
 - 4: **until** Only singleton clusters remain
-

Agglomerative Clustering Algorithm

- More popular hierarchical clustering technique
- Basic algorithm is straightforward
 1. Compute the proximity matrix
 2. Let each data point be a cluster
 3. **Repeat**
 4. Merge the two closest clusters
 5. Update the proximity matrix
 6. **Until** only a single cluster remains
- Key operation is the computation of the proximity of two clusters
 - Different approaches to defining the distance between clusters distinguish the different algorithms

How to Define Inter-Cluster Proximity




- MIN
- MAX
- Group Average
- Distance Between Centroids
- Other methods driven by an objective function
 - Ward's Method uses squared error

	p1	p2	p3	p4	p5	...
p1						
p2						
p3						
p4						
p5						
.						
.						
.						

Proximity Matrix

How to Define Inter-Cluster Proximity




- MIN
- MAX
- Group Average
- Distance Between Centroids
- Other methods driven by an objective function
 - Ward's Method uses squared error

	p1	p2	p3	p4	p5	...
p1						
p2						
p3						
p4						
p5						
.						
.						
.						

Proximity Matrix

How to Define Inter-Cluster Proximity




- MIN
- MAX
- Group Average
- Distance Between Centroids
- Other methods driven by an objective function
 - Ward's Method uses squared error

	p1	p2	p3	p4	p5	...
p1						
p2						
p3						
p4						
p5						
.						
.						
.						

Proximity Matrix

How to Define Inter-Cluster Proximity




- MIN
- MAX
- **Group Average**
- Distance Between Centroids
- Other methods driven by an objective function
 - Ward's Method uses squared error

	p1	p2	p3	p4	p5	...
p1						
p2						
p3						
p4						
p5						
.						
.						
.						

Proximity Matrix

How to Define Inter-Cluster Proximity




- MIN
- MAX
- Group Average
- Distance Between Centroids
- Other methods driven by an objective function
 - Ward's Method uses changes in SSE

	p1	p2	p3	p4	p5	...
p1						
p2						
p3						
p4						
p5						
.						
.						
.						

Proximity Matrix

MIN


- Proximity of two clusters is based on the two closest points in the different clusters
 - Determined by one pair of points
- Example:




Distance Matrix:

	p1	p2	p3	p4	p5	p6
p1	0.00	0.24	0.22	0.37	0.34	0.23
p2	0.24	0.00	0.15	0.20	0.14	0.25
p3	0.22	0.15	0.00	0.15	0.28	0.11
p4	0.37	0.20	0.15	0.00	0.29	0.22
p5	0.34	0.14	0.28	0.29	0.00	0.39
p6	0.23	0.25	0.11	0.22	0.39	0.00

Hierarchical Clustering: MIN




Nested Clusters




Dendrogram

Strength of MIN




Original Points



Six Clusters


- Can handle non-elliptical shapes

Limitations of MIN




Original Points

- Sensitive to noise




Two Clusters



Three Clusters

MAX


- Similarity of two clusters is based on the two most distant points in the different clusters
 - Determined by all pairs of points in the two clusters




Distance Matrix:

	p1	p2	p3	p4	p5	p6
p1	0.00	0.24	0.22	0.37	0.34	0.23
p2	0.24	0.00	0.15	0.20	0.14	0.25
p3	0.22	0.15	0.00	0.15	0.28	0.11
p4	0.37	0.20	0.15	0.00	0.29	0.22
p5	0.34	0.14	0.28	0.29	0.00	0.39
p6	0.23	0.25	0.11	0.22	0.39	0.00

Hierarchical Clustering: MAX




Nested Clusters




Dendrogram

Strength of MAX




- Less susceptible to noise

Limitations of MAX ✖



Original Points



Two Clusters


- Tends to break large clusters

Group Average

- Proximity of two clusters is the average of pairwise proximity between points in the two clusters.

$$\text{proximity}(\text{Cluster}_i, \text{Cluster}_j) = \frac{\sum_{\substack{p_i \in \text{Cluster}_i \\ p_j \in \text{Cluster}_j}} \text{proximity}(p_i, p_j)}{|\text{Cluster}_i| \times |\text{Cluster}_j|}$$


- Need to use average connectivity for scalability since total proximity favors large clusters




Distance Matrix:

	p1	p2	p3	p4	p5	p6
p1	0.00	0.24	0.22	0.37	0.34	0.23
p2	0.24	0.00	0.15	0.20	0.14	0.25
p3	0.22	0.15	0.00	0.15	0.28	0.11
p4	0.37	0.20	0.15	0.00	0.29	0.22
p5	0.34	0.14	0.28	0.29	0.00	0.39
p6	0.23	0.25	0.11	0.22	0.39	0.00

Hierarchical Clustering: Group Average





Nested Clusters





Dendrogram


Hierarchical Clustering: Group Average

- Compromise between MIN and MAX
- Strengths 
 - Less susceptible to noise
- Limitations 
 - Biased towards globular clusters


Centroid Methods

- Similarity of two clusters is based on proximity between centroids of clusters
- Less susceptible to noise 
- Biased towards globular clusters 

Hierarchical Clustering: Centroid





Nested Clusters



Dendrogram




Inversion

- Two clusters that are merged may be more similar than the pair of clusters that were merged in a previous step



Centroid vs Group Average


X	Y
0.9	0.4
0.7	0.9
0.15	0.05
0.4	0.35
0.9	0.8
0.9	0




Cluster Similarity: Ward's Method

- Proximity of two clusters is based on the increase in squared error when two clusters are merged
 - Similar to group average if distance between points is distance squared
- Less susceptible to noise
- Biased towards globular clusters

Hierarchical Clustering: Ward's Method






Nested Clusters




Dendrogram

Hierarchical Clustering: Comparison



Ward's Method



Lance-Williams Formula

- Proximity between clusters Q and R, where R is formed by merging clusters A and B

$$p(R, Q) = \alpha_A p(A, Q) + \alpha_B p(B, Q) + \beta p(A, B) + \gamma |p(A, Q) - p(B, Q)|$$

Clustering Method	α_A	α_B	β	γ
MIN	1/2	1/2	0	-1/2
MAX	1/2	1/2	0	1/2
Group Average	$\frac{m_A}{m_A+m_B}$	$\frac{m_B}{m_A+m_B}$	0	0
Centroid	$\frac{m_A}{m_A+m_B}$	$\frac{m_B}{m_A+m_B}$	$\frac{-m_A m_B}{(m_A+m_B)^2}$	0
Ward's	$\frac{m_A+m_Q}{m_A+m_B+m_Q}$	$\frac{m_B+m_Q}{m_A+m_B+m_Q}$	$\frac{-m_Q}{m_A+m_B+m_Q}$	0

- m_i is size of cluster i, $p(i,j)$ is proximity of clusters i & j

Hierarchical Clustering: Problems and Limitations



- Once a decision is made to combine two clusters, it cannot be undone
- No global objective function is directly minimized
- Different schemes have problems with one or more of the following:
 - Sensitivity to noise
 - Difficulty handling different sized clusters and convex shapes
 - Breaking large clusters