

Compatibility between tuple and tuple-like objects

Document #: P2165R0
Date: 2020-06-29
Project: Programming Language C++
Audience: LEWG
Reply-to: Corentin Jabot <corentin.jabot@gmail.com>

Abstract

We propose to make tuples of 2 elements and pairs comparable. We extend comparison and assignment between tuple and any object following the tuple protocol.

Tony tables

Before	After
<pre>constexpr std::pair p {1, 3.0}; constexpr std::tuple t {1.0, 3}; static_assert(std::tuple(p) == t); static_assert(std::tuple(p) <=> t == 0);</pre>	<pre>constexpr std::pair p {1, 3.0}; constexpr std::tuple t {1.0, 3}; static_assert(p == t); static_assert(p <=> t == 0);</pre>

Motivation

pairs are platonic tuples of 2 elements. pair and tuple share most of their interface.

Notably, a tuple can be constructed and assigned from a pair. However, tuple and pair are not comparable. This proposal fixes that.

This makes tuple more consistent (assignment and comparison usually form a pair, at least in regular-ish types), and makes the library ever so slightly less surprising.

Following that reasoning, we can extend support for these operations to any tuple-like object, aka object following the tuple protocol.

Design

We introduce an exposition only concept tuple-like which can then be used in the definition of tuples comparison and assignment operators.

A type satisfies tuple-like if it implements the tuple protocol (std::get, std::tuple_element, std::tuple_size)

That same concept can be used in [ranges] to simplify the specification. pair is not modified as to not introduce dependencies between <pair> and <tuple>

Questions For LEWG

Should tuple-like and pair-like be named concepts (as opposition to exposition only) ?

Future work

Tuple comparison operators are good candidates for hidden friends.

Wording

❖ Header <tuple> synopsis

[tuple.syn]

[...]

```
template<class T, class... Types>
constexpr const T& get(const tuple<Types...>& t) noexcept;
template<class T, class... Types>
constexpr const T&& get(const tuple<Types...>&& t) noexcept;
```

```
template <typename T, std::size_t N>    // exposition only
constexpr bool is_tuple_element = requires (T t) {
    typename tuple_element_t<N-1, remove_const_t<T>>;
    { get<N-1>(t) } -> convertible_to<tuple_element_t<N-1, T>&>;
} && is_tuple_element<T, N-1>;
```

```
template <typename T>
constexpr bool is_tuple_element<T, 0> = true;
```

```
template <typename T>
concept tuple-like // exposition only
    = !is_reference_v<T> && requires {
    typename tuple_size<T>::type;
    same_as<decltype(tuple_size_v<T>), size_t>;
} && is_tuple_element<T, tuple_size_v<T>>;
```

```
template <typename T>
concept pair-like // exposition only
    = tuple-like<T> && std::tuple_size_v<T> == 2;
```

```

// [tuple.rel], relational operators
template<class... TTypes, class... UTypes>
constexpr bool operator==(const tuple<TTypes...>&, const tuple tuple-like<UTypes...>&);
template<class... TTypes, class... UTypes>

constexpr common_comparison_category_t<synth-three-way-result<TTypes, UTypes>...>
operator<=(const tuple<TTypes...>&, const tuple tuple-like<UTypes...>&);

// [tuple.traits], allocator-related traits
template<class... Types, class Alloc>
struct uses_allocator<tuple<Types...>, Alloc>;

}

namespace std {
template<class... Types>
class tuple {
public:
    // ??, tuple construction
    constexpr explicit(see below) tuple();
    constexpr explicit(see below) tuple(const Types&...);
    // only if sizeof...(Types) >= 1
    template<class... UTypes>
    constexpr explicit(see below) tuple(UTypes&&...);
    // only if sizeof...(Types) >= 1

    tuple(const tuple&) = default;
    tuple(tuple&&) = default;

    template<class... UTypes>
    constexpr explicit(see below) tuple(const tuple tuple-like<UTypes...>&);
    template<class... UTypes>
    constexpr explicit(see below) tuple(tuple tuple-like<UTypes...>&&);

    template<class U1, class U2>
    constexpr explicit(see below)
    tuple(const pair<U1, U2>&); // only if sizeof...(Types) == 2
    template<class U1, class U2>
    constexpr explicit(see below)
    tuple(pair<U1, U2>&&); // only if sizeof...(Types) == 2

    // allocator-extended constructors
    template<class Alloc>
    constexpr explicit(see below)
    tuple(allocator_arg_t, const Alloc& a);
    template<class Alloc>
    constexpr explicit(see below)
    tuple(allocator_arg_t, const Alloc& a, const Types&...);
    template<class Alloc, class... UTypes>
    constexpr explicit(see below)
    tuple(allocator_arg_t, const Alloc& a, UTypes&&...);

```

```

template<class Alloc>
constexpr tuple(allocator_arg_t, const Alloc& a, const tuple&);
template<class Alloc>
constexpr tuple(allocator_arg_t, const Alloc& a, tuple&&);
template<class Alloc, class... UTypes>
constexpr explicit(see below)
tuple(allocator_arg_t, const Alloc& a, const tuple tuple-like<UTypes...>&);
template<class Alloc, class... UTypes>
constexpr explicit(see below)
tuple(allocator_arg_t, const Alloc& a, tuple tuple-like<UTypes...>&&);

template<class Alloc, class U1, class U2>
constexpr explicit(see below)
tuple(allocator_arg_t, const Alloc& a, const pair<U1, U2>&);
template<class Alloc, class U1, class U2>
constexpr explicit(see below)
tuple(allocator_arg_t, const Alloc& a, pair<U1, U2>&&);

// ??, tuple assignment
constexpr tuple& operator=(const tuple&);
constexpr tuple& operator=(tuple&&) noexcept(see below);

template<class... UTypes>
constexpr tuple& operator=(const tuple tuple-like<<UTypes...>&);
template<class... UTypes>
constexpr tuple& operator=(tuple tuple-like<<UTypes...>&&);

template<class U1, class U2>
constexpr tuple& operator=(const pair<U1, U2>&);
// only if sizeof...(Types) == 2
template<class U1, class U2>
constexpr tuple& operator=(pair<U1, U2>&&);
// only if sizeof...(Types) == 2

// ??, tuple swap
constexpr void swap(tuple&) noexcept(see below);
};

template<class... UTypes>
tuple(UTypes...) -> tuple<UTypes...>;
template<class T1, class T2 class... UTypes>
tuple(pair<T1, T2> tuple-like<UTypes...>) -> tuple<T1, T2 UTypes...>;
template<class Alloc, class... UTypes>
tuple(allocator_arg_t, Alloc, UTypes...) -> tuple<UTypes...>;
template<class Alloc, class T1, class T2>
tuple(allocator_arg_t, Alloc, pair<T1, T2>) -> tuple<T1, T2>;
template<class Alloc, class... UTypes>
tuple(allocator_arg_t, Alloc, tuple tuple-like<UTypes...>) -> tuple<UTypes...>;
}

```



Construction

[tuple.cnstr]

[...]

```
template<class... UTypes>
constexpr explicit(see below) tuple(const tuple-like<UTypes...>& u);
```

Constraints:

- sizeof...(Types) equals sizeof...(UTypes) and
- is_constructible_v< T_i , const U_i > is true for all i , and
- either sizeof...(Types) is not 1, or (when Types... expands to T and UTypes... expands to U) is_convertible_v<const tuple<U>&, T>, is_constructible_v<T, const tuple<U>&>, and is_same_v<T, U> are all false.

Effects: Initializes each element of *this with the corresponding element of u.

Remarks: The expression inside explicit is equivalent to:

```
!conjunction_v<is_convertible<const UTypes&, Types>...>
```

```
template<class... UTypes>
constexpr explicit(see below) tuple(tuple-like<UTypes...>&& u);
```

Constraints:

- sizeof...(Types) equals sizeof...(UTypes), and
- is_constructible_v< T_i , U_i > is true for all i , and
- either sizeof...(Types) is not 1, or (when Types... expands to T and UTypes... expands to U) is_convertible_v<tuple<U>, T>, is_constructible_v<T, tuple<U>>, and is_same_v<T, U> are all false.

Effects: For all i , initializes the i^{th} element of *this with std::forward< U_i >(get< i >(u)).

Remarks: The expression inside explicit is equivalent to:

```
!conjunction_v<is_convertible<UTypes, Types>...>
```

```
template<class U1, class U2> constexpr explicit(see below) tuple(const pair<U1, U2>& u);
```

Constraints:

- sizeof...(Types) is 2,
- is_constructible_v< T_0 , const U1&> is true, and
- is_constructible_v< T_1 , const U2&> is true.

Effects: Initializes the first element with u.first and the second element with u.second.

The expression inside explicit is equivalent to:

```
!is_convertible_v<const U1&, T0> || !is_convertible_v<const U2&, T1>
```

```
template<class U1, class U2> constexpr explicit(see below) tuple(pair<U1, U2>&& u);
```

Constraints:

- sizeof...(Types) is 2,
- is_constructible_v<T₀, U1> is true, and
- is_constructible_v<T₁, U2> is true.

Effects: Initializes the first element with `std::forward<U1>(u.first)` and the second element with `std::forward<U2>(u.second)`.

The expression inside `explicit` is equivalent to:

```
!is_convertible_v<U1, T0> || !is_convertible_v<U2, T1>
```

```
template<class Alloc>
constexpr explicit(see below)
tuple(allocator_arg_t, const Alloc& a);
template<class Alloc>
constexpr explicit(see below)
tuple(allocator_arg_t, const Alloc& a, const Types&...);
template<class Alloc, class... UTypes>
constexpr explicit(see below)
tuple(allocator_arg_t, const Alloc& a, UTypes&&...);
template<class Alloc>
constexpr tuple(allocator_arg_t, const Alloc& a, const tuple&);
template<class Alloc>
constexpr tuple(allocator_arg_t, const Alloc& a, tuple&&);
template<class Alloc, class... UTypes>
constexpr explicit(see below)
tuple(allocator_arg_t, const Alloc& a, const tuple tuple-like<UTypes...>&);
template<class Alloc, class... UTypes>
constexpr explicit(see below)
tuple(allocator_arg_t, const Alloc& a, tuple tuple-like<UTypes...>&&);
```

```
template<class Alloc, class U1, class U2>
constexpr explicit(see below)
tuple(allocator_arg_t, const Alloc& a, const pair<U1, U2>&);
template<class Alloc, class U1, class U2>
constexpr explicit(see below)
tuple(allocator_arg_t, const Alloc& a, pair<U1, U2>&&);
```

Expects: Alloc meets the *Cpp17Allocator* requirements ().

Effects: Equivalent to the preceding constructors except that each element is constructed with `uses-allocator` construction.

◆ Assignment

[tuple.assign]

For each tuple assignment operator, an exception is thrown only if the assignment of one of the types in Types throws an exception. In the function descriptions that follow, let i be in the range $[0, \text{sizeof} \dots (\text{Types}))$ in order, T_i be the i^{th} type in Types, and U_i be the i^{th} type in a template parameter pack named UTypes, where indexing is zero-based.

```
constexpr tuple& operator=(const tuple& u);
```

Effects: Assigns each element of u to the corresponding element of $*this$.

Remarks: This operator is defined as deleted unless `is_copy_assignable_v< T_i >` is true for all i .

Returns: $*this$.

```
constexpr tuple& operator=(tuple&& u) noexcept(see below);
```

Constraints: `is_move_assignable_v< T_i >` is true for all i .

Effects: For all i , assigns `std::forward< T_i >(get< i >(u))` to `get< i >(*this)`.

Remarks: The expression inside `noexcept` is equivalent to the logical AND of the following expressions:

```
is_nothrow_move_assignable_v< $T_i$ >
```

where T_i is the i^{th} type in Types.

Returns: $*this$.

```
template<class... UTypes> constexpr tuple& operator=(const tuple tuple-like<UTypes...>& u);
```

Constraints:

- `sizeof... (Types)` equals `sizeof... (UTypes)` and
- `is_assignable_v< T_i &, const U_i &>` is true for all i .

Effects: Assigns each element of u to the corresponding element of $*this$.

Returns: $*this$.

```
template<class... UTypes> constexpr tuple& operator=(tuple tuple-like<UTypes...>&& u);
```

Constraints:

- `sizeof... (Types)` equals `sizeof... (UTypes)` and
- `is_assignable_v< T_i &, U_i >` is true for all i .

Effects: For all i , assigns `std::forward< U_i >(get< i >(u))` to `get< i >(*this)`.

Returns: $*this$.

```
template<class U1, class U2> constexpr tuple& operator=(const pair<U1, U2>& u);
```

Constraints:

- `sizeof...(Types)` is 2 and
- `is_assignable_v<T0&, const U1&>` is true, and
- `is_assignable_v<T1&, const U2&>` is true.

Effects: Assigns `u.first` to the first element of `*this` and `u.second` to the second element of `*this`.

Returns: `*this`.

```
template<class U1, class U2> constexpr tuple& operator=(pair<U1, U2>&& u);
```

Constraints:

- `sizeof...(Types)` is 2 and
- `is_assignable_v<T0&, U1>` is true, and
- `is_assignable_v<T1&, U2>` is true.

Effects: Assigns `std::forward<U1>(u.first)` to the first element of `*this` and `std::forward<U2>(u.second)` to the second element of `*this`.

Returns: `*this`.



Relational operators

[tuple.rel]

```
template<class... TTypes, class... UTypes>
constexpr bool operator==(const tuple<TTypes...>& t, tuple<UTypes...>& u);
```

Mandates: For all i , where $0 \leq i < \text{sizeof}...(TTypes)$, `geti(t) == geti(u)` is a valid expression returning a type that is convertible to `bool`. `sizeof...(TTypes)` equals `sizeof...(UTypes)`.

Returns: true if `geti(t) == geti(u)` for all i , otherwise false. For any two zero-length tuples `e` and `f`, `e == f` returns true.

Effects: The elementary comparisons are performed in order from the zeroth index upwards. No comparisons or element accesses are performed after the first equality comparison that evaluates to false.

```
template<class... TTypes, class... UTypes>
constexpr common_comparison_category_t<synth-three-way-result<TTypes, UTypes>...>
operator<=>(const tuple<TTypes...>& t, const tuple<UTypes...>& u);
```

Effects: Performs a lexicographical comparison between `t` and `u`. For any two zero-length tuples `t` and `u`, `t <=> u` returns `strong_ordering::equal`. Otherwise, equivalent to:

```
if (auto c = synth-three-way(get<0>(t), get<0>(u)); c != 0) return c;
return ttail <=> utail;
```


where r_{tail} for some tuple r is a tuple containing all but the first element of r .

[*Note:* The above definition does not require t_{tail} (or u_{tail}) to be constructed. It may not even be possible, as t and u are not required to be copy constructible. Also, all comparison functions are short circuited; they do not perform element accesses beyond what is required to determine the result of the comparison. — *end note*]



Range utilities

[range.utility]



Sub-ranges

[range.subrange]

The subrange class template combines together an iterator and a sentinel into a single object that models the view concept. Additionally, it models the sized_range concept when the final template parameter is subrange_kind::sized.

```
namespace std::ranges {
    template<class From, class To>
    concept convertible-to-non-slicing =                // exposition only
        convertible_to<From, To> &&
        !(is_pointer_v<decay_t<From>> &&
         is_pointer_v<decay_t<To>> &&
         not-same-as<remove_pointer_t<decay_t<From>>, remove_pointer_t<decay_t<To>>>);

    template<class T>
    concept pair-like =                                // exposition only
        !is_reference_v<T> && requires(T t) {
            typename tuple_size<T>::type;                // ensures tuple_size<T> is complete
            requires derived_from<tuple_size<T>, integral_constant<size_t, 2>>;
            typename tuple_element_t<0, remove_const_t<T>>;
            typename tuple_element_t<1, remove_const_t<T>>;
            { get<0>(t) } -> convertible_to<const tuple_element_t<0, T>&>;
            { get<1>(t) } -> convertible_to<const tuple_element_t<1, T>&>;
        };

    template<class T, class U, class V>
    concept pair-like-convertible-from =                // exposition only
        !range<T> && pair-like<T> &&
        constructible_from<T, U, V> &&
        convertible-to-non-slicing<U, tuple_element_t<0, T>> &&
        convertible_to<V, tuple_element_t<1, T>>;
}
```



Elements view

[range.elements]



Class template elements_view

[range.elements.view]

```
namespace std::ranges {
```

```

template<class T, size_t N>
concept has-tuple-element = // exposition only
tuple-like<T> && tuple_size_v<T> < N;
requires(T t){
-typename tuple_size<T>::type;
-requires N < tuple_size_v<T>;
-typename tuple_element_t<N, T>;
-{ get<N>(t) }-> convertible_to<const tuple_element_t<N, T>&>;
};

```

Acknowledgments

References

[N4861] Richard Smith *Working Draft, Standard for Programming Language C++*
<https://wg21.link/N4861>