

# Universal Template Parameters

Document #: D1985R1  
Date: 2020-02-08  
Project: Programming Language C++  
Evolution Working Group Incubator  
Reply-to: Mateusz Pusz ([Epam Systems](https://.epam.com))  
<[mateusz.pusz@gmail.com](mailto:mateusz.pusz@gmail.com)>  
Gašper Ažman  
<[gasper.azman@gmail.com](mailto:gasper.azman@gmail.com)>

## Contents

<b>1</b>	<b>Introduction</b>	<b>1</b>
<b>2</b>	<b>Change Log</b>	<b>2</b>
2.1	R0 -> R1 . . . . .	2
<b>3</b>	<b>Motivation</b>	<b>2</b>
<b>4</b>	<b>Proposed Solution</b>	<b>2</b>
4.1	Mechanism . . . . .	2
4.1.1	Specializing class templates on parameter kind . . . . .	2
4.1.2	Eager or late checking? . . . . .	3
4.1.3	Template-template parameter binding . . . . .	4
4.2	Clarifying examples . . . . .	4
4.2.1	Single parameter examples . . . . .	4
4.2.2	Pack Expansion Example . . . . .	4
4.2.3	Example of parsing ambiguity (if late check, not proposed) . . . . .	5
<b>5</b>	<b>Example Applications</b>	<b>5</b>
5.1	Enabling higher order metafunctions . . . . .	5
5.2	Making dependent <code>static_assert(false)</code> work . . . . .	5
5.3	Checking whether a type is an instantiation of a given template . . . . .	6
5.4	Universal alias as a library . . . . .	7
5.5	Integration with reflection . . . . .	7
5.6	Library fundamentals II TS detection idiom . . . . .	7
<b>6</b>	<b>Other Considered Syntaxes</b>	<b>7</b>
6.1	. and ... instead of <code>template auto</code> and <code>template auto ...</code> . . . . .	7
<b>7</b>	<b>Acknowledgements</b>	<b>8</b>
<b>8</b>	<b>References</b>	<b>8</b>

## 1 Introduction

We propose a universal template parameter. This would allow for a generic `apply` and other higher-order template metafunctions, as well as certain type traits.

## 2 Change Log

### 2.1 R0 -> R1

- Greatly expanded the number of examples based on feedback from the BSI panel.
- Clarified that we are proposing eager checking

## 3 Motivation

Imagine trying to write a metafunction for `apply`. While `apply` is very simple, a metafunction like `bind` or `curry` runs into the same problems; for demonstration, `apply` is clearest.

It works for pure types in C++20:

```
template <template <class...> class F, typename... Args>
using apply = F<Args...>;

template <typename X>
class G { using type = X; };

static_assert(std::is_same<apply<G, int>, G<int>>{}>); // OK
```

As soon as `G` tries to take any kind of NTTP (non-type template parameter) or a template-template parameter, `apply` becomes impossible to write; we need to provide analogous parameter kinds for every possible combination of parameters:

```
template <template <class> class F>
using H = F<int>;
apply<H, G> // error, can't pass H as arg1 of apply, and G as arg2
```

## 4 Proposed Solution

Introduce a way to specify a truly universal template parameter that can bind to anything usable as a template argument.

Let's spell it `template auto`. The syntax is the best we could come up with; but there are plenty of unexplored ways of spelling such a template parameter.

As an example, let's implement `apply` from above:

```
template <template <template auto...> class F, template auto... Args>
using apply = F<Args...>;

apply<G, int>; // OK, G<int>
apply<H, G>;  // OK, G<int>
```

### 4.1 Mechanism

#### 4.1.1 Specializing class templates on parameter kind

The new universal template parameter introduces similar generalizations as the `auto` universal NTTP did; in order to make it possible to pattern-match on the parameter, class templates need to be able to be specialized on the kind of parameter as well:

```
template <template auto>
struct X;
```

```

template <typename T>
struct X<T> {
    // T is a type
    using type = T;
};

template <auto val>
struct X<val> : std::integral_constant<decltype(val), val> {
    // val is an NTTP
};

template <template <class> F>
struct X<F> {
    // F is a unary metafunction
    template <typename T>
    using func = F<T>;
};

```

This alone allows building enough traits to connect the new feature to the rest of the language with library facilities, and rounds out template parameters as just another form of a compile-time parameter.

#### 4.1.2 Eager or late checking?

There exists a choice in whether we check the usage of a universal template parameter eagerly or late. Consider:

```

template <template auto Arg>
struct Y {
    using type = Arg; // can only alias a type
    // Q: late (on Y<1>) or early (on parse) error?
};

```

We could either:

- Eagerly check this and hard-error on parsing the template.
- Late-check and hard-error only if Y is *instantiated* with anything but a type.

This paper **proposes eager checking**, thus allowing the utterance of a universal template parameter only in:

- *template-parameter-list* as the declaration of such a parameter
- *template-argument-list* as the usage of such a parameter. It must bind exactly to a declared `template auto` template parameter.

This avoids any parsing issues by being conservative. We can always extend the grammar to allow usage in more contexts later.

Examples that inform the following reasoning:

```

template <template auto Arg>
void f() {
    using type = Arg<int>; // error, not valid for types and values
    using value = Arg.foo(); // error, not valid for types and class templates
    auto x = Arg::member; // error, not valid for class templates and values
};

```

We avoid ambiguity by allowing the use of the universal template parameter solely in ways that are valid for any kind of thing (value, type, or class template) it may represent. It just so happens that the only such use is passing it as an argument to a template and wait for something else to pattern-match it out.

### 4.1.3 Template-template parameter binding

We have to consider the two phases of class template (and template alias) usage: parsing, and substitution.

Let's take `apply` again:

```
template <template <template auto...> class F, template auto... Args>
using apply = F<Args...>;
```

This *parses*, because `F` is *declared* as a class template parameter taking a pack of `template auto`, while `Args` is being expanded into a place that takes `template auto` parameters.

When we pass a metafunction such a `is_same` as `F`:

```
using result = apply<std::is_same, int, 1>; // error
```

everything is known, so the compiler is free to check dependent expansions at instantiation time.

## 4.2 Clarifying examples

### 4.2.1 Single parameter examples

```
template <int> struct takes_int {};
template <typename T> using takes_type = T;
template <template auto> struct takes_anything {};
template <template <class> class F> struct takes_metafunc {};

template <template <template auto> class F, template auto Arg>
struct fwd {
    using type = F<Arg>; // ok, passed to template auto parameter
}; // ok, correct definition

void f() {
    fwd<takes_int, 1>{}; // ok; type = takes_int<1>
    fwd<takes_int, int>{}; // error, takes_int<int> invalid
    fwd<takes_type, int>{}; // ok; type = takes_type<int>
    fwd<takes_anything, int>{}; // ok; type = takes_anything<int>
    fwd<takes_anything, 1>{}; // ok; type = takes_anything<1>
    fwd<takes_metafunc, takes_int>; // ok; type = takes_metafunc<takes_int>
    fwd<takes_metafunc, takes_metafunc>{}; // error (1)
}
```

(1): `takes_metafunc` is not a metafunction on a *type*, so `takes_metafunc<takes_metafunc>` is invalid (true as of C++98).

### 4.2.2 Pack Expansion Example

It is interesting to think about what happens if one expands a non-homogeneous pack of these. The result should not be surprising:

```
template <template auto X, template auto Y>
struct is_same : std::false_type {};
template <typename auto V>
struct is_same<V, V> : std::true_type {};

template <template auto V, template auto ... Args>
struct count : std::integral_constant<
    size_t,
```

```
(is_same<Args>::value + ...) > {};
```

```
constexpr size_t ints = count<int, 1, 2, int, is_same>::value; // ok, ints = 2
```

### 4.2.3 Example of parsing ambiguity (if late check, not proposed)

The reason for eager checking is that not doing that could introduce parsing ambiguities. Example courtesy of [P0945R0], and adapted:

```
template<template auto A>
struct X {
    void f() { A * a; }
};
```

The issue is that we do not know how to parse `f()`, since `A * a;` is either a declaration or a multiplication. Original example from [???]:

```
template<typename T> struct X {
    using A = T::something; // P0945R0 proposed universal alias
    void f() { A * a; }
};
```

## 5 Example Applications

This feature is very much needed in very many places. This section lists examples of usage.

### 5.1 Enabling higher order metafunctions

This was the introductory example. Please refer to the [Proposed Solution](#).

Further example: `curry`:

```
template <typename <template auto...> class F,
         template auto ... Args1>
struct curry {
    template <template auto... Args2>
    using func = F<Args1..., Args2...>;
};
```

### 5.2 Making dependent `static_assert(false)` work

Dependent static assert idea is described in [P1936R0] and [P1830R1]. In the former the author writes:

Another parallel paper [P1830R1] that tries to solve this problem on the library level is submitted. Unfortunately, **it cannot fulfill all use-case since it is hard to impossible to support all combinations of template template parameters in the dependent scope.**

The above papers are rendered superfluous with the introduction of this feature. Observe:

```
// stdlib
template<bool value, template auto Args...>
inline constexpr bool dependent_bool = value;
template<template auto... Args>
inline constexpr bool dependent_false = dependent_bool<false, Args...>;

// user code
```

```
template<template <class> class Arg>
struct my_struct {
    // no type template parameter available to make a dependent context
    static_assert(dependent_false<Arg>, "forbidden instantiation.");
};
```

### 5.3 Checking whether a type is an instantiation of a given template

When writing template libraries, it is useful to check whether a given type is an instantiation of a given template. When our templates mix types and NTTPs, this trait is currently impossible to write in general. However, with the universal template parameter, we can write a concept for that easily as follows.

```
// is_instantiation_of
template<typename T, template<template auto...> class Type>
inline constexpr bool is_instantiation_impl = false;

template<template auto... Params, template<template auto...> class Type>
inline constexpr bool is_instantiation_impl<Type<Params...>, Type> = true;

template<typename T, template<template auto...> class Type>
concept is_instantiation_of = is_instantiation_impl<T, Type>;
```

With the above we are able to easily constrain various utilities taking class templates:

```
template <auto N, auto D>
struct ratio {
    static constexpr decltype(N) n = N;
    static constexpr decltype(D) d = D;
};

template<is_instantiation_of<ratio> R1, is_instantiation_of<ratio> R2>
using ratio_mul = simplify<ratio<
    R1::n * R2::n,
    R1::d * R2::d
>>;
```

or create named concepts for them:

```
template<typename T>
concept is_ratio = is_instantiation_of<ratio>;

template<is_ratio R1, is_ratio R2>
using ratio_mul = simplify<ratio<
    R1::n * R2::n,
    R1::d * R2::d
>>;
```

This concept can then be easily used everywhere:

```
template <is_instantiation_of<std::vector> V>
void f(V& v) {
    // valid for any vector
}
```

## 5.4 Universal alias as a library

While this paper does not try to relitigate Richard Smith’s [P0945R0], it does provide a solution to aliasing anything as a library facility, without running into the problem that [P0945R0] ran into.

Observe:

```
template <template auto Arg>
struct alias /* undefined on purpose */;

template <typename T>
struct alias<T> { using value = T; }

template <auto V>
struct alias<T> : std::integral_constant<decltype(V), V> {};

template <template <template auto...> class Arg>
using alias<Arg> {
    template <template auto...> using value = Arg;
};
```

We can then use alias when we *know* what it holds:

```
template <template auto Arg>
struct Z {
    using type = alias<Arg>;
    // existing rules work
    using value = typename type::value; // dependent
}; // ok, parses

Z<int> z1; // ok, decltype(z1)::value = int
Z<1> z; // error, alias<1>::value is not a type
```

## 5.5 Integration with reflection

The authors expect that code using reflection will have a need for this facility. We should not reach for code-generation when templates will do, and so being able to pattern-match on the result of the reflection expression might be a very simple way of going from the consteval + injection world back to template matching.

The examples in this section are pending discussion with reflection authors.

Importantly, the authors do not see how one could write `is_instantiation_of` with the current reflection facilities, because one would have no way to pattern-match. This is, however, also pending discussion with the authors of reflection.

## 5.6 Library fundamentals II TS detection idiom

TODO. Concievably simplifies the implementation and makes it far more general.

# 6 Other Considered Syntaxes

In addition to the syntax presented in the paper, we have considered the following syntax options:

### 6.1 . and ... instead of template auto and template auto ...

```
template<template<...> class F, . x, . y, . z>
using apply3 = F<x, y, z>;
```

The reason we discarded this one is that it is very terse for something that should not be commonly used, and as such uses up valuable real-estate.

## 7 Acknowledgements

Special thanks and recognition goes to [Epam Systems](#) for supporting Mateusz's membership in the ISO C++ Committee and the production of this proposal.

Gašper would likewise like to thank his employer, Citadel Securities Europe, LLC, for supporting his attendance in committee meetings.

A big thanks also to the members of the BSI C++ panel for their review and commentary.

## 8 References

- [P0945R0] Richard Smith. 2018. Generalizing alias declarations.  
<https://wg21.link/p0945r0>
- [P1830R1] Ruslan Arutyunyan. 2019. std::dependent\_false.  
<https://wg21.link/p1830r1>
- [P1936R0] Ruslan Arutyunyan. 2019. Dependent Static Assertion.  
<https://wg21.link/p1936r0>